

Measurement Results

No.1-1635/20-01-05_Annex_MR

Test logging

This document is electronically signed and valid without handwritten signature.
For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:

Michael Dorongovski
Lab Manager
Radio Communications

Table of Content

EUT Information	3
FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4	4
FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4	6
FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4 (2475MHz)	8
FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4 (2480MHz)	10
FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4	12
FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4	16
FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 (2475MHz)	20
FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 (2480MHz)	24
FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4	28
FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4	31
FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 (2475MHz)	34
FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 (2480MHz)	37
FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4	40
FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4	42
FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4 (2475MHz)	44
FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4 (2480MHz)	46
FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4	48
FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4	51
FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 (2475MHz)	54
FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 (2480MHz)	57

EUT Information

EUT DEFINITION	
Manufacturer	Panasonic Industrial Devices Europe GmbH
Type	PAN1780
Serial Number	ES 3
Setup Number	1.0
Version SW	NI
Version FW	NI
Version HW	NI
Comment 1	
Comment 2	
Temperature [°C] Min	-40
Temperature [°C] Nom	20
Temperature [°C] Max	85
Voltage [V] Min	3.3
Voltage [V] Nom	3.3
Voltage [V] Max	3.3

FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4

Test References

TC Start	13.12.2021 13:59:40
Ambit Temp [°C] Humidity [rel%]	23.9 31
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2405 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	7.13	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.13 10.6 20
Start [MHz] Stop [MHz]	2402.600 2407.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1544	kHz	PASS



FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4

Test References

TC Start	13.12.2021 14:34:00
Ambit Temp [°C] Humidity [rel%]	23.7 32
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2440 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.96	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.96 10.6 20
Start [MHz] Stop [MHz]	2437.600 2442.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1540	kHz	PASS



FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4 (2475MHz)

Test References	
TC Start	14.01.2022 10:31:24
Ambit Temp [°C] Humidity [rel%]	22.5 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Add. Information	Power Setting 2475 MHz: 8dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2475 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.33	dBm	INFO
Ref. Frequency	---	---	2474.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.33 11.14 20
Start [MHz] Stop [MHz]	2472.600 2477.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1553	kHz	PASS



FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4 (2480MHz)

Test References	
TC Start	14.01.2022 11:13:18
Ambit Temp [°C] Humidity [rel%]	22.7 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	99
TC Version	0.0.1
My Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Add. Information	Power Setting 2480 MHz: 0dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2480 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	-0.75	dBm	INFO
Ref. Frequency	---	---	2480.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	4.25 11.15 10
Start [MHz] Stop [MHz]	2477.600 2482.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	1556	kHz	PASS



FCC Part 15.247 Bandwidth 6dB DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

Test References

TC Start	13.12.2021 14:00:57
Ambit Temp [°C] Humidity [rel%]	23.9 31
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2405 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	7.09	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.09 10.6 20
Start [MHz] Stop [MHz]	2402.600 2407.400
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2254.815	kHz	INFO
T1 99%	2400.000000	---	2403.8894	MHz	PASS
T2 99%	---	2483.500000	2406.1442	MHz	PASS

Plot: Bandwidth only



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 99PCT


Plot: Bandwidth within Band



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4


RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2497	kHz	INFO
T1 20dB	2400.000000	---	2403.7832	MHz	PASS
T2 20dB	---	2483.500000	2406.2806	MHz	PASS

Plot: Bandwidth only



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 20dB

Plot: Bandwidth within Band



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

Test References

TC Start	13.12.2021 14:35:18
Ambit Temp [°C] Humidity [rel%]	23.7 32
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2440 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.95	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.95 10.6 20
Start [MHz] Stop [MHz]	2437.600 2442.400
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2256.254	kHz	INFO
T1 99%	2400.000000	---	2438.8851	MHz	PASS
T2 99%	---	2483.500000	2441.1413	MHz	PASS

Plot: Bandwidth only




FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 99PCT

Plot: Bandwidth within Band




RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2534	kHz	INFO
T1 20dB	2400.000000	---	2438.7462	MHz	PASS
T2 20dB	---	2483.500000	2441.2806	MHz	PASS

Plot: Bandwidth only



Plot: Bandwidth within Band



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

General verdict	PASS
-----------------	------

FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 (2475MHz)

Test References	
TC Start	14.01.2022 10:32:45
Ambit Temp [°C] Humidity [rel%]	22.5 25
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Add. Information	Power Setting 2475 MHz: 8dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2475 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.31	dBm	INFO
Ref. Frequency	---	---	2474.500	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.31 11.14 20
Start [MHz] Stop [MHz]	2472.600 2477.400
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2262.974	kHz	INFO
T1 99%	2400.000000	---	2473.8827	MHz	PASS
T2 99%	---	2483.500000	2476.1456	MHz	PASS

Plot: Bandwidth only



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 99PCT


Plot: Bandwidth within Band



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4


RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2540	kHz	INFO
T1 20dB	2400.000000	---	2473.7462	MHz	PASS
T2 20dB	---	2483.500000	2476.2864	MHz	PASS

Plot: Bandwidth only



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 20dB

Plot: Bandwidth within Band



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

General verdict	PASS
-----------------	------

FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 (2480MHz)

Test References

TC Start	14.01.2022 11:14:38
Ambit Temp [°C] Humidity [rel%]	22.7 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	
TC Version	0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Add. Information	Power Setting 2480 MHz: 0dBm

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2480 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	-0.81	dBm	INFO
Ref. Frequency	---	---	2479.500	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	4.19 11.15 10
Start [MHz] Stop [MHz]	2477.600 2482.400
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	2259.614	kHz	INFO
T1 99%	2400.000000	---	2478.8899	MHz	PASS
T2 99%	---	2483.500000	2481.1495	MHz	PASS

Plot: Bandwidth only



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 99PCT

Plot: Bandwidth within Band




FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	2533	kHz	INFO
T1 20dB	2400.000000	---	2478.7534	MHz	PASS
T2 20dB	---	2483.500000	2481.2864	MHz	PASS

Plot: Bandwidth only



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4 20dB

Plot: Bandwidth within Band



FCC Part 15.247 Bandwidth 99PCT-20dB ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4

Test References	
TC Start	13.12.2021 13:58:36
Ambit Temp [°C] Humidity [rel%]	23.9 31
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS4 - Generic 2G4
Add. Information	

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2405 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	7.08	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.08 10.6 20
Start [MHz] Stop [MHz]	2402.600 2407.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

DTS Bandwidth

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1544	kHz	INFO




FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 DTS BW

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.08 10.6 25
Start [MHz] Stop [MHz]	2402.600 2407.400
RBW [MHz] VBW [MHz]	3.000000 10.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	6.88	dBm	PASS
Peak Power	---	1000	4.875285	mW	PASS
Frequency at Peak	---	---	2404.568	MHz	INFO



FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4

Test References	
TC Start	13.12.2021 14:32:56
Ambit Temp [°C] Humidity [rel%]	23.7 32
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS4 - Generic 2G4
Add. Information	

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2440 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	7.00	dBm	INFO
Ref. Frequency	---	---	2440.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.00 10.6 20
Start [MHz] Stop [MHz]	2437.600 2442.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

DTS Bandwidth

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1539	kHz	INFO




FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 DTS BW

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.00 10.6 25
Start [MHz] Stop [MHz]	2437.600 2442.400
RBW [MHz] VBW [MHz]	3.000000 10.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	6.82	dBm	PASS
Peak Power	---	1000	4.808393	mW	PASS
Frequency at Peak	---	---	2440.489	MHz	INFO



FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 (2475MHz)

Test References	
TC Start	14.01.2022 10:30:29
Ambit Temp [°C] Humidity [rel%]	22.5 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS4 - Generic 2G4
Add. Information	Power Setting 2475 MHz: 8dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2475 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.28	dBm	INFO
Ref. Frequency	---	---	2474.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.28 11.14 20
Start [MHz] Stop [MHz]	2472.600 2477.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

DTS Bandwidth

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1554	kHz	INFO




FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 DTS BW

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.28 11.14 25
Start [MHz] Stop [MHz]	2472.600 2477.400
RBW [MHz] VBW [MHz]	3.000000 10.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	6.19	dBm	PASS
Peak Power	---	1000	4.159106	mW	PASS
Frequency at Peak	---	---	2474.554	MHz	INFO



FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 (2480MHz)

Test References	
TC Start	14.01.2022 11:12:25
Ambit Temp [°C] Humidity [rel%]	22.6 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
TC Version	0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS4 - Generic 2G4
Add. Information	Power Setting 2480 MHz: 0dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2480 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	-0.84	dBm	INFO
Ref. Frequency	---	---	2480.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	4.16 11.15 10
Start [MHz] Stop [MHz]	2477.600 2482.400
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE

DTS Bandwidth

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	1556	kHz	INFO




FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4 DTS BW

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.16 11.15 15
Start [MHz] Stop [MHz]	2477.600 2482.400
RBW [MHz] VBW [MHz]	3.000000 10.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	-0.94	dBm	PASS
Peak Power	---	1000	0.805378	mW	PASS
Frequency at Peak	---	---	2480.518	MHz	INFO



FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4

Test References	
TC Start	13.12.2021 14:00:13
Ambit Temp [°C] Humidity [rel%]	23.9 31
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2405 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	7.11	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.11 10.6 20
Start [MHz] Stop [MHz]	2403.200 2406.800
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-6.2	dBm/3KHz	PASS



FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4

Test References	
TC Start	13.12.2021 14:34:34
Ambit Temp [°C] Humidity [rel%]	23.7 32
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2440 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.95	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.95 10.6 20
Start [MHz] Stop [MHz]	2438.200 2441.800
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-8.18	dBm/3KHz	PASS



FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4 (2475MHz)

Test References	
TC Start	14.01.2022 10:32:00
Ambit Temp [°C] Humidity [rel%]	22.5 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - Generic 2G4
Add. Information	Power Setting 2475 MHz: 8dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2475 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.29	dBm	INFO
Ref. Frequency	---	---	2474.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.29 11.14 20
Start [MHz] Stop [MHz]	2473.200 2476.800
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-7.19	dBm/3KHz	PASS



FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4 (2480MHz)

Test References	
TC Start	14.01.2022 11:13:53
Ambit Temp [°C] Humidity [rel%]	22.7 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
TC Version	0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - Generic 2G4
Add. Information	Power Setting 2480 MHz: 0dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2480 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	-0.81	dBm	INFO
Ref. Frequency	---	---	2480.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	4.19 11.15 10
Start [MHz] Stop [MHz]	2478.200 2481.800
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-14.18	dBm/3KHz	PASS



FCC Part 15.247 Peak Power Spectral Density DTS ~ Generic 2G4

General verdict

PASS

FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4

Test References	
TC Start	13.12.2021 14:01:51
Ambit Temp [°C] Humidity [rel%]	23.9 31
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2405 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	7.09	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	7.09 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2405.00 MHz	---	---	2.76	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 19352.333 MHz	0	---	28.58	dB	INFO



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2405



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2405

General verdict

PASS

FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4

Test References	
TC Start	13.12.2021 14:36:13
Ambit Temp [°C] Humidity [rel%]	23.7 31
System Version	3.0.3.2
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Add. Information	

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	0.5
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,3.8.13	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2440 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.96	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.96 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2440.17 MHz	---	---	2.84	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 6849.833 MHz	0	---	28.57	dB	INFO



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2440



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2440

General verdict

PASS

FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 (2475MHz)

Test References	
TC Start	14.01.2022 10:33:43
Ambit Temp [°C] Humidity [rel%]	22.5 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Add. Information	Power Setting 2475 MHz: 8dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2475 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.29	dBm	INFO
Ref. Frequency	---	---	2475.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.29 0 25
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2474.83 MHz	---	---	2.00	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 6998.167 MHz	0	---	27.34	dB	INFO



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2475



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2475

General verdict

PASS

FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 (2480MHz)

Test References	
TC Start	14.01.2022 11:15:35
Ambit Temp [°C] Humidity [rel%]	22.7 24
System Version	3.0.3.7
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
TC Version	0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Add. Information	Power Setting 2480 MHz: 0dBm

EUT Common settings 2G4	
Hopping supported	No
Burst length [ms]	10
Nominal Bandwidth [MHz]	2.4
User Interaction	No

Test Parameter	
Technology to test	Generic 2G4
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment	
Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70	
Signaling unit,Rohde&Schwarz,CMW,1201.0002k75/102550,4.0.20	
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI	

Test at TX 2480 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	-0.81	dBm	INFO
Ref. Frequency	---	---	2479.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-0.81 0 15
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2480.00 MHz	---	---	-4.71	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2484 MHz	0	---	21.6	dB	INFO



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2480



FCC Part 15.247 TX Spurious Conducted ~ Generic 2G4 2480

General verdict	PASS
-----------------	------

- END OF DOCUMENT -