

Project No: TM-2202000442P
Report No.: TMWK2202000746KS

FCC ID: 2APJ4-SNM900

Page: 1 / 31
Rev.: 01

SAR TEST REPORT

FCC 47 CFR § 2.1093
IEEE Std 1528-2013

for
Tablet

Model: M276FQC

Prepared for:

FLYTECH Technology Co., Ltd.
No. 168, Sing-Ai Rd., Neihu District 11494, Taipei City, Taiwan

Prepared by

Compliance Certification Services Inc.
Wugu Lab.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)
Issue Date: May 20, 2022

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2202000746KS

Page: 2 / 31
Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Revised By
00	May 11, 2022	Initial Issue	Doris Chu
01	May 20, 2022	See the following Note Rev. (01)	Doris Chu

Rev. (01)



1. FCC ID 2APJ4-SLM758 revised to 2APJ4-SNM900 in page 1.

Table of Contents

1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES	5
3	DEVICE UNDER TEST (DUT) INFORMATION	6
	3.1 DUT DESCRIPTION	6
	3.2 WIRELESS TECHNOLOGIES	7
4	SAR MEASUREMENT SYSTEM	8
	4.1 SYSTEM COMPONENTS.....	9
	4.2 SAR SCAN PROCEDURES.....	12
5	MEASUREMENT UNCERTAINTY.....	14
6	RF EXPOSURE CONDITIONS (TEST CONFIGURATIONS).....	15
	6.1 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	15
7	DIELECTRIC PROPERTY MEASUREMENTS & SYSTEM CHECK	16
	7.1 DIELECTRIC PROPERTY MEASUREMENTS.....	16
	7.2 SYSTEM CHECK.....	19
8	CONDUCTED OUTPUT POWER MEASUREMENTS.....	21
	8.1 WI-FI 2.4GHZ (DTS BAND)	21
	8.2 WI-FI 5GHZ (U-NII BANDS).....	22
	8.3 BLUETOOTH.	23
9	MEASURED AND REPORTED (SCALED) SAR RESULTS.....	25
	9.1 WI-FI (DTS BAND).....	25
	9.2 WI-FI (U-NII BAND).....	25
	9.3 BLUETOOTH	25
10	SAR MEASUREMENT VARIABILITY	26
11	SIMULTANEOUS TRANSMISSION SAR ANALYSIS	27
	11.1 SUM OF THE SAR FOR WI-FI & BT	29
12	EQUIPMENT LIST & CALIBRATION STATUS.....	30
13	FACILITIES.....	31
14	APPENDIXES	31

Report No.: TMWK2202000746KS

1 Attestation of Test Results

Applicant Name	FLYTECH Technology Co., Ltd.		
Model Name	M276FQC		
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013		
Exposure Category	SAR Limits (W/Kg)		
	Peak spatial-average (1g of tissue)	Extremities (hands, wrists, ankles, etc.) (10g of tissue)	
General population	1.6	4	
RF Exposure Conditions	Equipment Class - Highest Reported SAR (W/kg)		
	DTS	NII	DSS
Body	1.377	0.383	0.057
Simultaneous TX	1.481		
Receive EUT Date:	February 25, 2022		
Date Tested	March 6 ~ 8, 2022		
Test Results	Pass		
<p>Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.</p>			
Approved & Released By:		Tested by:	
			
Kevin Tsai Deputy Manager Compliance Certification Services Inc.		Sky Zhou Asst. Section Manager Compliance Certification Services Inc.	



Report No.: TMWK2202000746KS

Page: 5 / 31
Rev.: 01

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures:

- 248227 D01 802.11 Wi-Fi SAR v02r02
- 447498 D01 General RF Exposure Guidance v07
- 616217 D04 SAR for laptop and tablets v01r02
- 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- 865664 D02 RF Exposure Reporting v01r02

In addition to the above, the following information was used:

- TCB workshop October, 2016; Page 7, RF Exposure Procedures (Bluetooth Duty Factor)

3 Device Under Test (DUT) Information

3.1 DUT Description

Applicant Name	FLYTECH Technology Co., Ltd.
Applicant Address	No. 168, Sing-Ai Rd., Neihu District 11494, Taipei City, Taiwan
Manufacturer Name	FLYTECH Technology Co., Ltd.
Manufacturer Address	No. 168, Sing-Ai Rd., Neihu District 11494, Taipei City, Taiwan
Product	Tablet
Trade Name	FLYTECH
Model No.	M276FQC
Device Dimension	Overall (Length x Width): 275 mm x 179 mm Overall Diagonal: 326 mm Display Diagonal: 296 mm
Back Cover	<input type="checkbox"/> Normal Battery Cover <input type="checkbox"/> Normal Battery Cover with NFC <input type="checkbox"/> Wireless Charger Battery Cover <input type="checkbox"/> Wireless Charger Battery Cover with NFC <input checked="" type="checkbox"/> The Back Cover is not removable.
Battery Options	<input checked="" type="checkbox"/> Standard – Lithium-ion battery, Rating 3.85Vdc, 28.69Wh <input type="checkbox"/> Extended (large capacity) <input type="checkbox"/> The rechargeable battery is not user accessible.
Hardware Version	V1.0
Software Version	Android 9
Sample Stage	PVT

Report No.: TMWK2202000746KS


3.2 Wireless Technologies

Wireless technologies	Frequency bands	Peak Antenna Gain (dBi)	Operating mode	Duty Cycle used for SAR testing
Wi-Fi	2.4 GHz ¹	2.9	802.11b	97.67% (802.11b)
			802.11g	87.32% (802.11g/n 20MHz BW)
	5 GHz ¹	4.5	802.11n (HT20)	86.51% (802.11n 40MHz BW)
			802.11n (HT40)	
		802.11a		87.21% (802.11a)
		802.11n (HT20)		86.57% (802.11n 20MHz BW)
		802.11n (HT40)		86.57% (802.11n 40MHz BW)
		Does this device support bands 5.60 ~ 5.65 GHz? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
		Does this device support Band gap channel? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Bluetooth	2.4 GHz	2.9	LE	62.4%
Antenna Specification	Brand Name	ARISTOTLE ENTERPRISES		
	Type	PIFA Antenna		
	Parts Number	RFA-25-AP866L-4B-210		

Notes:

1. The sample selected for test was prototype that representative to production product and was provided by manufacturer
2. Variant information between/among model numbers / trademarks is provided by the applicant, test results of this report are applicable to the sample EUT received of main test model name.
3. Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received
4. The device turns off U-NII-2A,U-NII-2C and U-NII-3.
5. The device turns off BR,EDR.




4 SAR Measurement System







The DASY5 system for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7 or Windows XP.
- DASY software version: NEO52 D10.3 S14.6.13.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

4.1 System Components

DASY5 Measurement Server	
	<p>The DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE4 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.</p> <p>The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.</p>
	<p>The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server.</p> <p>Calibration: No calibration required.</p>
Data Acquisition Electronics (DAE)	
	<p>The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MΩ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.</p>

EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements	
	<p>Construction: Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p> <p>Calibration: Basic Broad Band Calibration in air: 10-3000 MHz. Conversion Factors (CF) for HSL 900 and HSL 1800 CF-Calibration for other liquids and frequencies upon request.</p> <p>Frequency: 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)</p> <p>Directivity: ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in HSL (rotation normal to probe axis)</p> <p>Dynamic Range: 10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μW/g)</p>
	<p>Dimensions: Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1 mm</p> <p>Application: High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.</p>
SAM Phantom	
	<p>Construction: The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE1528: 2013. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.</p> <p>Shell Thickness: 2 ± 0.2 mm</p> <p>Filling Volume: Approx. 25 liters</p> <p>Dimensions: Height: 810mm; Length: 1000mm; Width: 500mm</p>
ELI Phantom	
	<p>Construction: Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEEE1528: 2013 and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles</p> <p>Shell Thickness: 2.0 ± 0.2 mm (sagging: <1%)</p> <p>Filling Volume: Approx. 25 liters</p> <p>Dimensions: Major ellipse axis: 600 mm Minor axis: 400 mm 500mm</p>

Report No.: TMWK2202000746KS

Device Holder for SAM Twin Phantom	
	<p>Construction: In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).</p>
System Validation Kits for SAM Phantom	
	<p>Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.</p> <p>Frequency: 2450, 5300, 5600, 5800 MHz</p> <p>Return loss: > 20 dB at specified validation position</p> <p>Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz)</p> <p>Dimensions: D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm</p>
System Validation Kits for ELI phantom	
	<p>Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.</p> <p>Frequency: 2450, 5300, 5600, 5800 MHz</p> <p>Return loss: > 20 dB at specified validation position</p> <p>Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz)</p> <p>Dimensions: D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm</p>

4.2 SAR Scan Procedures

Step 1: Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE1528 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

- Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm	$3 - 4$ GHz: ≤ 5 mm $4 - 6$ GHz: ≤ 4 mm
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Maximum zoom scan volume	x, y, z	≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm	

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction



Report No.: TMWK2202000746KS

Page: 14 / 31
Rev.: 01

5 Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE1528: 2013 is not required in SAR reports submitted for equipment approval.

Therefore, the measurement uncertainty is not required.

6 RF Exposure Conditions (Test Configurations)

Refer to Appendixes 1 for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

6.1 Standalone SAR Test Exclusion Considerations

Since the Dedicated Host Approach is applied, the SAR-based exemption in Appendix B of KDB 447498 is applied together with KDB 616217 § 4.3 to determine the minimum test separation distance:

- When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.

SAR Test Exclusion Calculations for $1.5 \text{ GHz} \leq f \leq 6 \text{ GHz}$

Tx Interface	Frequency (GHz)	Output Power		Separation Distances (cm)					P_{in} (mW)					Exemption result				
		dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
WiFi 2.4GHz	2.462	16.50	45	1.1	2.045	6.035	15.185	19.357	12	40	313	1812	2875	-MEASURE-	-MEASURE-	-EXEMPT-	-EXEMPT-	-EXEMPT-
WiFi 5.2GHz	5.24	14.00	25	1.1	2.045	19.357	15.185	6.035	8	27	2860	1732	257	-MEASURE-	-EXEMPT-	-EXEMPT-	-EXEMPT-	-EXEMPT-
Bluetooth	2.48	3.00	2	1.1	2.045	6.035	15.185	19.357	12	40	312	1811	2875	-EXEMPT-	-EXEMPT-	-EXEMPT-	-EXEMPT-	-EXEMPT-

Required Test Configurations

The table below identifies the standalone test configurations required for this device according to the findings in Section 6.1:

Test Configurations	Rear	Edge1	Edge2	Edge3	Edge4
$1.5\text{GHz} \leq f \leq 6\text{GHz}$					
WiFi 2.4GHz	Yes	Yes	No	No	No
WiFi 5.2GHz	Yes	No	No	No	No
Bluetooth	Yes	Yes	No	No	No

Note(s):

Yes = Testing is required.

No = Testing is not required.

7 Dielectric Property Measurements & System Check

7.1 Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

The dielectric constant (ϵ_r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to be within $\pm 5\%$ of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEEE Std 1528-2013, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ϵ_r and σ may be relaxed to $\pm 10\%$. This is limited to frequencies ≤ 3 GHz.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Report No.: TMWK2202000746KS

Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99+% Pure Sodium Chloride Sugar: 98+% Pure Sucrose
 Water: De-ionized, 16 MΩ⁺ resistivity HEC: Hydroxy thyl Cellulose
 DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]
 Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

Dielectric Property Measurements Results:

Date	Tissue Type	Frequency (MHz)	Relative Permittivity (ϵ_r)			Conductivity (σ)		
			Measured	Target	Delta (%)	Measured	Target	Delta (%)
2022/3/8	Head	2400	39.75	39.30	1.15	1.81	1.76	3.19
		2450	39.49	39.20	0.74	1.88	1.80	4.44
		2480	39.37	39.16	0.54	1.92	1.83	4.91
2022/3/6	Head	5150	35.14	36.05	-2.52	4.53	4.61	-1.65
		5200	34.86	36.00	-3.17	4.61	4.66	-0.99
		5350	34.54	35.85	-3.65	4.76	4.81	-1.06

7.2 System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ± 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube
- Distance between probe sensors and phantom surface was set to 2 mm.
- The dipole input power (forward power) was 250 mW (below 2GHz) and 100 mW
- The results are normalized to 1 W input power.

Report No.: TMWK2202000746KS

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within $\pm 10\%$ of the manufacturer calibrated dipole SAR target. Refer to Appendix 2 for the SAR System Check Plots.

Date	Tissue Type	Dipole S/N	Input Power (mW)	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Delta 1g ± 10 (%)	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Delta 10g ± 10 (%)	Plot No.
2022/3/8	Head	D2450V2-727	250	12.60	53.90	50.4	-6.49	6.06	25.10	24.24	-3.43	1
2022/3/6	Head	D5GHzV2-1040-5200	100	7.41	76.90	74.1	-3.64	2.14	21.80	21.4	-1.83	2

Report No.: TMWK2202000746KS

8 Conducted Output Power Measurements

8.1 Wi-Fi 2.4GHz (DTS Band)

The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures.

SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11g/n/ac/ax mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band. Additional output power measurements were not deemed necessary.

SAR testing is not required for OFDM mode(s) when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Measured Results

Band	Mode	Data Rate	Ch #	Freq. (MHz)	Meas. Avg Pwr (dBm)	Tune-up Limit (dBm)	SAR Test (Yes/No)
2.4GHz (DTS)	802.11b	1 Mbps	1	2412	16.23	16.5	Yes
			6	2437	14.93		
			11	2462	15.89		
	802.11g	6 Mbps	1	2412	15.28	15.5	No
			6	2437	14.04		
			11	2462	15.12		
	802.11n (HT20)	MCS0	1	2412	13.42	14.0	No
			6	2437	12.28		
			11	2462	13.49		
	802.11n (HT40)	MCS0	3	2422	13.79	14.5	No
			6	2437	13.12		
			9	2452	14.16		

Report No.: TMWK2202000746KS

8.2 Wi-Fi 5GHz (U-NII Bands)

The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures.

When the same transmission mode configurations have the same maximum output power on the same channel for the 802.11 a/g/n/ac modes, the channel in the lower order/sequence 802.11 mode (i.e. a, g, n then ac) is selected.

SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band. Additional output power measurements were not deemed necessary.

Measured Results

Band	Mode	Data Rate	Ch #	Freq. (MHz)	Meas. Avg Pwr (dBm)	Tune-up Limit (dBm)	SAR Test (Yes/No)
5.2GHz (U-NII 1)	802.11a	6 Mbps	36	5180	13.92	14.0	Yes
			40	5200	13.48		
			44	5220	13.96		
			48	5240	13.37		
	802.11n (HT20)	MCS0	36	5180	12.93	13.0	No
			40	5200	12.56		
			44	5220	12.98		
			48	5240	12.43		
	802.11n (HT40)	MCS0	38	5190	11.28	11.5	No
			46	5230	11.11		

Report No.: TMWK2202000746KS

8.3 Bluetooth.

Maximum tune-up tolerance limit is 3 dBm. This power level qualifies for exclusion of SAR testing.

Max. RF Output Power	Antenna Gain	2.9 dBi	Frequency	At separation distance of	Exemption Limits (mW)	Result
	(dBm)	(mW)				
Conducted	3.00	2.00	2450 MHz	10 mm	10	Estimate SAR
E.I.R.P	5.90	3.89				

Average Power Measured Results


Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Meas. Avg Pwr (dBm)	Meas. Avg Pwr (mW)	Tune-up Limit (dBm)	SAR Test (Yes/No)
2.4	LE, GFSK	1 Mbps	0	2402	1.89	1.55	3.0	No
			19	2440	1.92	1.56		
			39	2480	1.97	1.57		

Duty Factor Measured Results

Mode	Type	T on (ms)	Period (ms)	Duty Cycle	Crest Factor (1/duty cycle)
GFSK	DH5	0.39	0.625	62.40%	1.60

Duty Cycle plots

GFSK



Report No.: TMWK2202000746KS

9 Measured and Reported (Scaled) SAR Results

9.1 Wi-Fi (DTS Band)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Duty Cycle	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up Limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Body	802.11b	0	Rear	1	2412	97.67%	16.5	16.23	1.020	1.111	0.399	0.435	
			Rear	6	2437	97.67%	16.5	14.93	0.937	1.377	0.370	0.544	1
			Rear	11	2462	97.67%	16.5	15.89	0.958	1.129	0.379	0.447	
			Edge 1	1	2412	97.67%	16.5	16.23	0.048	0.053	0.022	0.023	

9.2 Wi-Fi (U-NII Band)

Frequency Band	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Duty Cycle	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up Limit	Meas.	Meas.	Scaled	Meas.	Scaled	
5.2GHz (U-NII 1)	802.11a	0	Rear	44	5220	87.21%	14.0	13.96	0.331	0.383	0.101	0.117	2

9.3 Bluetooth

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Duty Cycle	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up Limit	Meas.	Meas.	Scaled	Meas.	Scaled	
Body	LE_GFSK 1M	0	Rear	39	2480	62.40%	3.0	1.97	0.028	0.057	0.010	0.020	3
			Edge 1	39	2480	62.40%	3.0	1.97	0.000	0.000	0.001	0.002	

Report No.: TMWK2202000746KS

10 SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is <0.8 or 2 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.8 or 2 W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg (~ 10% from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first, or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

WiFi 2.4GHz

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Duty Cycle	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio	Delta Target $\leq 5\%$
							Original	Repeated		
Body	802.11b	0	Rear	1	2412	97.67%	1.020	1.030	1.01	1%

Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is < 1.20 .

11 Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance provides two procedures for determining simultaneous transmission SAR test exclusion: Sum of SAR and SAR to Peak Location Ratio (SPLSR)

Sum of SAR

To qualify for simultaneous transmission SAR test exclusion based upon Sum of SAR the sum of the reported standalone SARs for all simultaneously transmitting antennas shall be below the applicable standalone SAR limit. If the sum of the SARs is above the applicable limit then simultaneous transmission SAR test exclusion may still apply if the requirements of the SAR to Peak Location Ratio (SPLSR) evaluation are met.

SAR to Peak Location Ratio (SPLSR)

KDB 447498 D01 General RF Exposure Guidance explains how to calculate the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i$$

Where:

SAR₁ is the highest measured or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest measured or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

R_i is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$

In order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i \leq 0.04$$

When an individual antenna transmits at on two bands simultaneously, the sum of the highest reported SAR for the frequency bands should be used to determine SAR₁.or SAR₂. When SPLSR is necessary, the smallest distance between the peak SAR locations for the antenna pair with respect to the peaks from each antenna should be used.

The antennas in all antenna pairs that do not qualify for simultaneous transmission SAR test exclusion must be tested for SAR compliance, according to the enlarged zoom scan and volume scan post-processing procedures in KDB Publication 865664 D01

Simultaneous Transmission Condition

RF Exposure Condition	Item	Capable Transmit Configurations		
Standalone	1	DTS	+	BT
	2	U-NII	+	BT
Notes:				
1. Wi-Fi 2.4GHz & Wi-Fi 5GHz cannot transmit simultaneously.				

Report No.: TMWK2202000746KS

Estimated SAR for Simultaneous Transmission SAR Analysis Considerations for SAR estimation

1. When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
2. Please refer to Estimated SAR Tables to see which test positions are inherently compliant as they consist of only estimated SAR values for all applicable transmitters and consequently will always have sum of SAR values < 1.2 W/kg. Simultaneous transmission SAR analysis was therefore not performed for these test positions.
3. Refer to Appendix C of KDB 447498 D01 and multiply the corresponding ratio by the 1-g SAR limit of 1.6 W/kg SAR.

Estimated SAR for $1.5 \text{ GHz} \leq f \leq 6 \text{ GHz}$

Tx Interface	Frequency (GHz)	Output Power		Separation Distances (cm)					P _{EM} (mW)					Exemption result				
		dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
WiFi 2.4GHz	2.462	16.50	45	1.1	2.045	6.035	15.185	19.357	12	40	313	1812	2875	-MEASURE-	-MEASURE-	0.230	0.040	0.025
WiFi 5.2GHz	5.24	14.00	25	1.1	2.045	19.357	15.185	6.035	8	27	2860	1732	257	-MEASURE-	1.481	0.014	0.023	0.156
Bluetooth	2.462	3.00	2	1.1	2.045	6.035	15.185	19.357	12	40	312	1811	2875	0.267	0.080	0.010	0.002	0.001

11.1 Sum of the SAR for Wi-Fi & BT

Test Position	Standalone SAR (W/kg)			Σ 10-g SAR (W/kg)	
	DTS	U-NII	BT	DTS + BT	U-NII + BT
	①	②	③	① + ③	② + ③
Rear	1.377	0.383	0.057	1.434	0.440
Edge 1	0.053	1.481	0.000	0.053	1.481

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

Report No.: TMWK2202000746KS

12 Equipment List & Calibration Status

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements				
Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	SPEAG	DAKS_VNA R140	0140417	2023/1/24
Dielectric Assessment Kit	SPEAG	DAKS-3.5	1001	2023/1/26
Thermometer	TES	TES-1306	210801061	2022/10/21

System Check				
Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Signal Generator	Agilent	N5181A	MY50144143	2022/5/13
Power Meter	Agilent	E4417A	MY52240003	2022/10/26
Power Sensor	Agilent	E9301H	MY52200004	2022/10/24
Power Sensor	Agilent	E9301H	MY51470002	2022/3/22
Dual Directional Coupler	Agilent	772D	MY46151242	2022/9/10
Amplifier	EMCI	ZVE-8G	S1900977	N/A
Data Acquisition Electronic	SPEAG	DAE4	1260	2022/9/19
Dosimetric E-Field Probe	SPEAG	EX3DV4	3665	2022/8/24
System Validation Dipole	SPEAG	D2450V2	727	2022/4/13
System Validation Dipole	SPEAG	D5GHzV2	1040	2022/6/3
Humidity/Temp meter	TECPEL	DTM-303A	TP130074	2022/4/26
Thermometer	TES	TES-1306	210801061	2022/10/21

Software Version
DASY NEO52 D10.3 S14.6.13
SEMCAD-X-PostPro



Report No.: TMWK2202000746KS

Page: 31 / 31
Rev.: 01

13 Facilities

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

14 Appendixes

Exhibit	Content
1	SAR Setup Photos
2	SAR System Check Plots
3	Highest SAR Test Plots
4	SAR DAE and Probe Calibration Certificates
5	SAR Dipole Calibration Certificates

END OF REPORT