



Certificate No.: 3745.01



China

FCC - TEST REPORT

Report Number : **709502102970-00** Date of Issue: September 2, 2021

Model : BP3L

Product Type : Bluetooth LE module

Applicant : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun
Road, Hangzhou, Zhejiang China

Manufacturer : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun
Road, Hangzhou, Zhejiang China

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including Appendices : 43

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test	4
4	Summary of Test Standards.....	5
5	Summary of Test Results.....	6
6	General Remarks	7
7	Test Setups	8
8	Systems test configuration.....	11
9	Technical Requirement	12
9.1	Conducted Emission	12
9.2	Conducted peak output power.....	15
9.3	6dB bandwidth	18
9.4	Power spectral density.....	21
9.5	Spurious RF conducted emissions	24
9.6	Band edge	31
9.7	Spurious radiated emissions for transmitter	34
10	Test Equipment List.....	40
11	System Measurement Uncertainty	41
12	Photographs of Test Set-ups	42
13	Photographs of EUT	43



China

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Test Firm FCC
Registration
Number: 820234

Test Firm IC
Registration
Number: 25988

Telephone: +86 21 6141 0123
Fax: +86 21 6140 8600



3 Description of the Equipment under Test

Description of the Equipment Under Test

Product: Bluetooth LE module

Model no.: BP3L

FCC ID: 2ANDL-BP3L

Options and accessories: NA

Rating: 1.8V-3.6V DC

RF Transmission Frequency: 2402~2480 MHz (LE 5.1)

No. of Operated Channel: 40

Modulation: GFSK

Antenna Type: Onboard PCB antenna

Antenna Gain: 1.09dBi

Description of the EUT: The Equipment Under Test (EUT) is a Bluetooth LE module which support 1Mbps and 2Mbps data rate. We tested it and listed the worst data in this report.

Test sample no.: SHA-591520-2

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2020 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	12-14	Site 1	☒	☐	☐
§15.247 (b) (1)	Conducted peak output power	15-17	Site 1	☒	☐	☐
§15.247(a)(1)	20dB bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Dwell Time	---	---	☐	☐	☒
§15.247(a)(2)	6dB bandwidth	18-20	Site 1	☒	☐	☐
§15.247(e)	Power spectral density	21-23	Site 1	☒	☐	☐
§15.247(d)	Spurious RF conducted emissions	24-30	Site 1	☒	☐	☐
§15.247(d)	Band edge	31-33	Site 1	☒	☐	☐
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	34-39	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an on board PCB antenna, which gain is 1.09dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ANDL-BP3L, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: August 24, 2021

Testing Start Date: August 26, 2021

Testing End Date: August 30, 2021

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:




Hui TONG
Review Engineer

Jiaxi XU
Project Engineer

Guo Chengjie
Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 40GHz Test Setup:



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09

Test software: PhyPlusKit

The system was configured to channel 0, 19, and 39 for the test.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : Bluetooth LE module
 M/N : BP3L
 Operating Condition : Mode 1: Tx_2402MHz for BLE, the data rate is 2Mbps.
 Test Specification : L-line
 Comment : AC 120V/60Hz (powered by notebook)




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.163500	---	31.42	55.28	23.86	1000.0	9.000	L1	19.5
0.172500	48.42	---	64.84	16.42	1000.0	9.000	L1	19.5
0.555000	---	27.55	46.00	18.45	1000.0	9.000	L1	19.5
0.555000	34.80	---	56.00	21.20	1000.0	9.000	L1	19.5
2.121000	---	25.99	46.00	20.01	1000.0	9.000	L1	19.5
2.121000	30.80	---	56.00	25.20	1000.0	9.000	L1	19.5
2.476500	---	27.92	46.00	18.08	1000.0	9.000	L1	19.5
2.728500	31.31	---	56.00	24.69	1000.0	9.000	L1	19.5
5.419500	27.56	---	60.00	32.44	1000.0	9.000	L1	19.6
5.419500	---	22.18	50.00	27.82	1000.0	9.000	L1	19.6
17.200500	---	30.67	50.00	19.33	1000.0	9.000	L1	19.8
17.227500	36.78	---	60.00	23.22	1000.0	9.000	L1	19.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

Product Type : Bluetooth LE module
 M/N : BP3L
 Operating Condition : Mode 1: Tx_2402MHz for BLE, the data rate is 2Mbps.
 Test Specification : N-line
 Comment : AC 120V/60Hz (powered by notebook)



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.163500	---	29.91	55.28	25.37	1000.0	9.000	N	19.5
0.163500	52.15	---	65.28	13.13	1000.0	9.000	N	19.5
0.541500	---	27.36	46.00	18.64	1000.0	9.000	N	19.5
0.546000	35.77	---	56.00	20.23	1000.0	9.000	N	19.5
1.783500	24.94	---	56.00	31.06	1000.0	9.000	N	19.5
2.107500	---	21.80	46.00	24.20	1000.0	9.000	N	19.5
2.985000	31.85	---	56.00	24.15	1000.0	9.000	N	19.5
3.534000	---	26.83	46.00	19.17	1000.0	9.000	N	19.5
5.550000	31.04	---	60.00	28.96	1000.0	9.000	N	19.6
11.539500	---	23.89	50.00	26.11	1000.0	9.000	N	19.7
17.241000	37.36	---	60.00	22.64	1000.0	9.000	N	19.8
17.344500	---	31.13	50.00	18.87	1000.0	9.000	N	19.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a power meter to measure the conducted peak output power.

Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

Test result as below table


Frequency MHz	Conducted Peak Output Power dBm	Data transmission rate	Result
Low channel 2402MHz	7.51	1Mbps	Pass
Middle channel 2440MHz	7.10	1Mbps	Pass
High channel 2480MHz	6.51	1Mbps	Pass

Frequency MHz	Conducted Peak Output Power dBm	Data transmission rate	Result
Low channel 2402MHz	7.56	2Mbps	Pass
Middle channel 2440MHz	7.13	2Mbps	Pass
High channel 2480MHz	6.54	2Mbps	Pass


Peak output power (1Mbps)

Channel 0 (2402MHz)

Channel 19 (2440MHz)



Date: 30 AUG 2021 11:11:02



Date: 30 AUG 2021 11:12:58

Channel 39 (2480MHz)





Date: 30 AUG 2021 11:16:09


Peak output power (2 Mbps)

Channel 0 (2402MHz)

Channel 19 (2440MHz)



Channel 39 (2480MHz)



9.3 6dB bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]

≥ 500

Test result

Frequency	6dB bandwidth	Data transmission rate	Result
MHz	MHz		
Top channel 2402MHz	0.804	1Mbps	Pass
Middle channel 2440MHz	0.830	1Mbps	Pass
Bottom channel 2480MHz	0.836	1Mbps	Pass


Frequency	6dB bandwidth	Data transmission rate	Result
MHz	MHz		
Top channel 2402MHz	1.387	2Mbps	Pass
Middle channel 2440MHz	1.402	2Mbps	Pass
Bottom channel 2480MHz	1.400	2Mbps	Pass



China


6dB Bandwidth

1Mbps
2402




Date: 30 AUG 2021 11:10:41

2440



Date: 30 AUG 2021 11:12:36

2480






Date: 30 AUG 2021 11:15:47



2Mbps

China



9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit


Limit [dBm/3kHz]

≤ 8


Test result

Frequency MHz	Power spectral density dBm/3KHz	Data transmission rate	Result
Top channel 2402MHz	-9.41	1Mbps	Pass
Middle channel 2440MHz	-9.71	1Mbps	Pass
Bottom channel 2480MHz	-9.96	1Mbps	Pass


Frequency MHz	Power spectral density dBm/3KHz	Data transmission rate	Result
Top channel 2402MHz	-13.73	2Mbps	Pass
Middle channel 2440MHz	-14.35	2Mbps	Pass
Bottom channel 2480MHz	-14.64	2Mbps	Pass

Power spectral density**PK PSD (1Mbps)****Channel 0 (2402MHz)**

Date: 30 AUG 2021 11:11:09

Channel 19 (2440MHz)

Date: 30 AUG 2021 11:13:04


Channel 39 (2480MHz)

Date: 30 AUG 2021 11:16:15

PK PSD (2Mbps)


Channel 0 (2402MHz)

China




Date: 30 AUG 2021 11:20:10

Channel 19 (2440MHz)



Date: 30 AUG 2021 11:22:13

Channel 39 (2480MHz)



Date: 30 AUG 2021 11:24:03


9.5 Spurious RF conducted emissions

Test Method


1. Establish a reference level by using the following procedure:
 - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
 - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
 - a. Set the center frequency and span to encompass frequency range to be measured.
 - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20

Spurious RF conducted emissions**Out-of-Band Emissions for 1Mbps
Channel 0 (2402MHz)****Reference point**


Date: 30.AUG.2021 11:11:25

Spurious Emission (30MHz – 1GHz)

Date: 30.AUG.2021 11:11:29

Spurious Emission (1GHz – 5GHz)

Date: 30.AUG.2021 11:11:42

Spurious Emission (5GHz – 26.5GHz)

Date: 30.AUG.2021 11:12:13


Out-of-Band Emissions for 1Mbps Channel 19 (2440MHz)

Reference point




Date: 30.AUG.2021 11:13:10

Spurious Emission (30MHz – 1GHz)




Date: 30.AUG.2021 11:13:14

Spurious Emission (1GHz – 5GHz)



Date: 30.AUG.2021 11:13:27

Spurious Emission (5GHz – 26.5GHz)



Date: 30.AUG.2021 11:13:58

Out-of-Band Emissions for 1Mbps


Channel 39 (2480MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 30.AUG.2021 11:16:31




Date: 30.AUG.2021 11:16:36

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)



Date: 30.AUG.2021 11:16:48




Date: 30.AUG.2021 11:17:19

Out-of-Band Emissions for 2Mbps


Channel 0 (2402MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 30.AUG.2021 11:20:27




Date: 30.AUG.2021 11:20:31

Spurious Emission (1GHz – 5GHz)

Spurious Emission (5GHz – 26.5GHz)




Date: 30.AUG.2021 11:20:43



Date: 30.AUG.2021 11:21:14


Out-of-Band Emissions for 2Mbps Channel 19 (2440MHz)

Reference point




Date: 30.AUG.2021 11:22:19

Spurious Emission (30MHz – 1GHz)




Date: 30.AUG.2021 11:22:24

Spurious Emission (1GHz –5GHz)



Date: 30.AUG.2021 11:22:36


Spurious Emission (5GHz –26.5GHz)



Date: 30.AUG.2021 11:23:07


Out-of-Band Emissions for 2Mbps Channel 39 (2480MHz)

Reference point




Date: 30 AUG 2021 11:24:19

Spurious Emission (30MHz – 1GHz)




Date: 30 AUG 2021 11:24:23

Spurious Emission (1GHz – 5GHz)



Date: 30 AUG 2021 11:24:35

Spurious Emission (5GHz – 26.5GHz)



Date: 30 AUG 2021 11:25:07

9.6 Band edge


Test Method

- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

Limit

According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.

Test result







China

2Mbps

2402



2480



9.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) $VBW \geq [3 \times RBW]$.
- c) Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq RBW / 2$.
Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBuV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Pre-scan with three orthogonal axis and worst case as X axis. The only worse case test result is listed in the report.

Test result

Test mode: GFSK (1Mbps)					
Channel 0 (2402MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2386.9	48.39	74.00	25.61	Peak	Horizontal
4804.0	46.57	74.00	27.43	Peak	Horizontal
2385.9	45.38	74.00	28.62	Peak	Vertical
4804.0	47.53	74.00	26.47	Peak	Vertical

Test mode: GFSK (1Mbps)					
Channel 19 (2440MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4880.0	45.73	74.00	28.27	Peak	Horizontal
4879.0	45.37	74.00	28.63	Peak	Vertical

Test mode: GFSK (1Mbps)					
Channel 39 (2480MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.7	51.03	74.00	22.97	Peak	Horizontal
2495.9	50.05	74.00	23.95	Peak	Horizontal
4959.8	44.80	74.00	29.20	Peak	Horizontal
2483.8	50.61	74.00	23.39	Peak	Vertical
2495.9	48.03	74.00	25.97	Peak	Vertical
4959.3	45.93	74.00	28.07	Peak	Vertical

Test mode: GFSK (2Mbps)					
Channel 0 (2402MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2386.7	47.68	74.00	26.32	Peak	Horizontal
4805.1	47.54	74.00	26.46	Peak	Horizontal
2386.4	45.52	74.00	28.48	Peak	Vertical
4803.4	44.08	74.00	29.92	Peak	Vertical

Test mode: GFSK (2Mbps)					
Channel 19 (2440MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4879.4	45.93	74.00	28.07	Peak	Horizontal
2662.6	47.87	74.00	26.13	Peak	Vertical
4881.1	45.34	74.00	28.66	Peak	Vertical

Test mode: GFSK (2Mbps)					
Channel 39 (2480MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2484.9	49.77	74.00	24.23	Peak	Horizontal
2495.8	49.26	74.00	24.74	Peak	Horizontal
4961.5	46.13	74.00	27.87	Peak	Horizontal
2483.9	49.61	74.00	24.39	Peak	Vertical
2495.6	47.95	74.00	26.05	Peak	Vertical
4958.7	44.46	74.00	29.54	Peak	Vertical


Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

The worst case of Radiated Emission below 1GHz:

Site: 3 meter chamber	Time: 2021/08/27 - 13:11
Limit: FCC_Part15.209_RE(3m)_ClassB	Engineer: Guo Chengjie
Probe: VULB9168	Polarity: Horizontal
EUT: Wi-Fi and Bluetooth Module, Model no: BP3L	Power: DC 3.3V by debug board for EUT, AC 120V,60Hz for notebook
Note: Transmit by at channel 2402MHz and the data rate is 2Mbps.	
Note: Pre-scan with three orthogonal axis and worst case as X axis	

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
168.000000	28.8	1000.0	120.000	100.4	H	200.0	14.9	14.7	43.5
192.000000	30.4	1000.0	120.000	100.4	H	159.0	12.1	13.1	43.5
223.960000	31.0	1000.0	120.000	100.4	H	239.0	12.7	15.0	46.0
287.960000	32.4	1000.0	120.000	100.4	H	285.0	14.7	13.6	46.0
336.000000	32.3	1000.0	120.000	100.4	H	327.0	16.0	13.7	46.0
455.960000	33.7	1000.0	120.000	100.4	H	108.0	18.6	12.3	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

The worst case of Radiated Emission below 1GHz:

Site: 3 meter chamber	Time: 2021/08/27 - 13:36
Limit: FCC_Part15.209_RE(3m)_ClassB	Engineer: Guo Chengjie
Probe: VULB9168	Polarity: Vertical
EUT: Wi-Fi and Bluetooth Module, Model no: BP3L	Power: DC 3.3V by debug board for EUT, AC 120V,60Hz for notebook
Note: Transmit by at channel 2402MHz and the data rate is 2Mbps.	
Note: Pre-scan with three orthogonal axis and worst case as X axis	

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
119.960000	28.1	1000.0	120.000	100.4	V	313.0	13.5	15.5	43.5
168.000000	29.2	1000.0	120.000	100.4	V	133.0	14.9	14.3	43.5
360.000000	30.2	1000.0	120.000	100.4	V	154.0	16.5	15.8	46.0
455.960000	33.5	1000.0	120.000	100.4	V	165.0	18.6	12.5	46.0
504.000000	33.1	1000.0	120.000	100.4	V	22.0	19.6	12.9	46.0
903.040000	39.7	1000.0	120.000	100.4	V	164.0	25.9	6.3	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

10 Test Equipment List

List of Test Instruments

Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2021-8-2	2022-8-1
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2019-3-16	2022-3-15
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-3-15	2024-3-14
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2021-8-2	2022-8-1
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2021-5-21	2022-5-20
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2020-9-23	2021-9-22
	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2021-8-2	2022-8-1
	LISN	Rohde & Schwarz	ENV216	101924	2021-8-2	2022-8-1

Measurement Software Information

Test Item	Software	Manufacturer	Version
C	Bluetooth and WiFi Test System	Shenzhen JS tonscond co.,ltd	2.6.77.0518
RE	EMC 32	Rohde & Schwarz	V9.15.00
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, $\pm 3.16\text{dB}$
Radiated Disturbance	30MHz to 1GHz, $\pm 5.03\text{dB}$ (Horizontal) $\pm 5.12\text{dB}$ (Vertical) 1GHz to 18GHz, $\pm 5.49\text{dB}$ 18GHz to 40GHz, $\pm 5.63\text{dB}$
Carrier power conducted measurement	50MHz~18GHz, $\pm 1.238\text{dB}$
Spurious Emission Conducted Measurement	9kHz ~40GHz, $\pm 1.224\text{dB}$



12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

THE END