

POWER DENSITY ESTIMATIONS BASED ON POWER OUTPUT, ANTENNA GAIN, AND DISTANCE FROM ANTENNA

$$(P G) / (4 R^2 \pi) = S$$

| | | | | | |
|---------------|------------|---|---|--|-----------------------------|
| where: | S = | maximum power density (mW/cm ²) | transmitter operating variables: | ↓ must be blank if dB values are entered ↓ | |
| | P = | power input to the antenna ----->> | = | 13.5 | (dBm) - or - (mW) |
| | G = | gain of the antenna - worst case ----->> | = | 1.2 | (dBi) - or - (numeric gain) |
| | R = | distance to the center of the radiation of the antenna -->> | = | 20 | (cm) |

$$(P \quad G) / (4 * R^2 * \pi) = S \quad (mW/cm^2)$$

$$\left(\frac{22.3872114}{(mw)} \quad \frac{1.31826}{(gain)} \right) / \left(4 * \frac{20}{(cm)}^2 * \pi \right) = S \quad (mW/cm^2)$$

$$\left(29.51209227 \right) / \left(4 * 400 * \pi \right) = S \quad (mW/cm^2)$$

$$\left(29.51209227 \right) / \left(5026.548246 \right) = 0.005871 \quad (mW/cm^2)$$

Power Density Based on 20 separation distance (cm)

| | |
|------|------------------------|
| 920 | Frequency (MHz) |
| 13.5 | Power to Antenna (dBm) |
| 1.2 | Antenna gain (dBi) |

FCC

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

0.005871
 Power Density (mW/cm²)

| Canada | FCC | Limit (mW/cm ²) |
|---------|---------|-----------------------------|
| 0.27606 | 0.60800 | Limit (mW/cm ²) |
| 0.27018 | 0.60213 | Margin |
| 0.02127 | 0.00966 | MPE Ratio |

(General Population)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | *900/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | | | f/300 | 6 |
| 1,500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | *180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | | | f/1500 | 30 |
| 1,500-100,000 | | | 1.0 | 30 |

Device FCC ID XQC-GDZW7LR
 Date 5/1/2023
 Prepared By Kyle F.

Canada

| Frequency Range (MHz) | Electric Field (V/m rms) | Magnetic Field (A/m rms) | Power Density (W/m ²) | Reference Period (minutes) |
|--|---------------------------|--|-----------------------------------|----------------------------|
| 0.003-10 ²¹ | 83 | 90 | - | Instantaneous* |
| 0.1-10 | - | 0.73/ f | - | 6** |
| 1.1-10 | 87/ f ^{0.5} | - | - | 6** |
| 10-20 | 27.46 | 0.0728 | 2 | 6 |
| 20-48 | 58.07/ f ^{0.25} | 0.1540/ f ^{0.25} | 8.944/ f ^{0.5} | 6 |
| 48-300 | 22.06 | 0.05852 | 1.291 | 6 |
| 300-6000 | 3.142 f ^{0.3417} | 0.008335 f ^{0.3417} | 0.02619f ^{0.6834} | 6 |
| 6000-15000 | 61.4 | 0.163 | 10 | 6 |
| 15000-150000 | 61.4 | 0.163 | 10 | 616000/ f ^{1.2} |
| 150000-300000 | 0.158 f ^{0.5} | 4.21 x 10 ⁻⁴ f ^{0.5} | 6.67 x 10 ⁻⁵ f | 616000/ f ^{1.2} |
| Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR). | | | | |