

## FCC Part 15, Subpart B, Class B

## TEST REPORT

ARTIKA FOR LIVING INC.

Glitzer 1-LED integrated Pendant Light

Test Model: PDT-1GL

Additional Model No.: PDT-1GL-XXXXXX ("XXXXXX" can be A to Z and/or  
0 to 9 and/or blank (commercial code))

Prepared for : ARTIKA FOR LIVING INC.  
Address : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park  
Shajing Street, Baoan District, Shenzhen, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 24, 2021  
Number of tested samples : 1  
Sample No. : 210323067A  
Serial number : Prototype  
Date of Test : March 24, 2021~ March 30, 2021  
Date of Report : March 30, 2021



## FCC TEST REPORT

### FCC Part 15, Subpart B, Class B

**Report Reference No. .... : LCS210323067AE**

Date Of Issue ..... : March 30, 2021

**Testing Laboratory Name .... : Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address ..... : 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China

Testing Location/ Procedure... : Full application of Harmonised standards ■  
Partial application of Harmonised standards □  
Other standard testing method □**Applicant's Name..... : ARTIKA FOR LIVING INC.**

Address ..... : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5

**Test Specification**Standard ..... : FCC 47 CFR Part 15 Subpart B, Class B,  
ANSI C63.4 -2014

Test Report Form No..... : LCSEMC-1.0

TRF Originator ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

**SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description..... : Glitzer 1-LED integrated Pendant Light**

Test Model ..... : PDT-1GL

Trade Mark ..... : Artika


Ratings ..... : Input: AC 100-135V, 50/60Hz, 0.4A Max

**Result ..... : Positive****Compiled by:**

Jin Wang/ File administrator

**Supervised by:**

Linda He/ Technique principal

**Approved by:**

Gavin Liang/ Manager

**FCC -- TEST REPORT****Test Report No. : LCS210323067AE**March 30, 2021

Date of issue

Test Model ..... : PDT-1GL

EUT..... : Glitzer 1-LED integrated Pendant Light

**Applicant..... : ARTIKA FOR LIVING INC.**

Address..... : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5

Telephone..... : /

Fax..... : /

**Manufacturer..... : ZHONGSHAN C5 LIGHTING CO. LTD**Address..... : 1# Henglong Road, Tongyi Industrial Area, Cao San,  
Guzhen, Zhongshan, Guangdong, China.

Telephone..... : /

Fax..... : /

**Factory..... : ZHONGSHAN C5 LIGHTING CO. LTD**Address..... : 1# Henglong Road, Tongyi Industrial Area, Cao San,  
Guzhen, Zhongshan, Guangdong, China.

Telephone..... : /

Fax..... : /

**Test Result** according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

Revision	Issue Date	Revisions	Revised By
000	March 30, 2021	Initial Issue	Gavin Liang

## TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. Description of Device (EUT) .....	7
2.2. Support Equipment List.....	8
2.3. Description of Test Facility .....	8
2.4. Statement of the Measurement Uncertainty .....	8
2.5. Measurement Uncertainty.....	8
2.6. Test Sample.....	9
<b>3. TEST RESULTS .....</b>	<b>10</b>
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT .....	10
3.2. Radiated emission Measurement .....	14
<b>4. PHOTOGRAPH .....</b>	<b>18</b>
<b>5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>	<b>19</b>

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC Part 15, Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
Radiated disturbance	FCC Part 15, Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
N/A is an abbreviation for Not Applicable.			

**Test mode:**

Mode	Lighting	Record
------	----------	--------

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT : Glitzer 1-LED integrated Pendant Light

Trade Mark : Artika

Test Model : PDT-1GL

Additional Models : PDT-1GL-XXXXXX ("XXXXXX" can be A to Z and/or 0 to 9 and/or blank (commercial code))

Models Declaration : PCB board, structure and internal of these model(s) are same, So no additional models were tested.

Power Supply : Input: AC 100-135V, 50/60Hz, 0.4A Max

Highest internal frequency :  $F_x \leq 108 \text{ MHz}$

Highest internal frequency ( $F_x$ )	Highest measured frequency
$F_x \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} < F_x \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} < F_x \leq 1 \text{ GHz}$	5 GHz
$F_x > 1 \text{ GHz}$	$5 \times F_x$ up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers,  $F_x$  is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.  
Where  $F_x$  is unknown, the radiated emission measurements shall be performed up to 6 GHz.

## 2.2. Support Equipment List

Name	Manufacturers	M/N	S/N
--	--	--	--

## 2.3. Description of Test Facility

Site Description

EMC Lab.

: NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

## 2.4. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 2.5. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucisp)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	$\pm 2.63$ dB $\pm 2.35$ dB	$\pm 3.8$ dB $\pm 3.4$ dB
Radiated Emission	Level accuracy (30MHz to 1000MHz)	$\pm 3.48$ dB	$\pm 5.3$ dB
Radiated Emission	Level accuracy (above 1000MHz)	$\pm 3.90$ dB	$\pm 5.2$ dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.



## 2.6. Test Sample

The application provides 1 sample to meet requirement;

Sample Number	Description
Sample (210323067A)	Normal sample – Intermittent transmit

### 3. TEST RESULTS


#### 3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

##### 3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	Farad	EZ	/	N/A	N/A
2	EMI Test Receiver	R&S	ESPI	101840	2020-06-22	2021-06-21
3	Artificial Mains	R&S	ENV216	101288	2020-06-22	2021-06-21
4	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2020-06-22	2021-06-21
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2020-10-20	2021-10-19

##### 3.1.2. Block Diagram of Test Setup



##### 3.1.3. Test Standard

###### Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB $\mu$ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

##### 3.1.4. EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

### 3.1.5. Operating Condition of EUT

3.1.5.1. Setup the EUT as shown on Section 3.1.2

3.1.5.2. Turn on the power of all equipments.

3.1.5.3. Let the EUT work in measuring Lighting and measure it.

### 3.1.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.


The frequency range from 150kHz to 30MHz is investigated

### 3.1.7. Test Results

**PASS.**


The test result please refer to the next page.

<b>Test Model</b>	PDT-1GL	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.3°C, 53.7% RH	<b>Test Engineer</b>	Jay Li
<b>Pol</b>	Line	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	39.42	21.15	60.57	66.00	-5.43	QP
2	0.1516	24.08	21.14	45.22	55.91	-10.69	AVG
3	0.2086	31.46	20.75	52.21	63.26	-11.05	QP
4	0.2106	14.52	20.73	35.25	53.18	-17.93	AVG
5	0.4336	25.75	21.09	46.84	57.18	-10.34	QP
6	0.4381	9.52	21.10	30.62	47.10	-16.48	AVG
7	0.7891	24.94	20.35	45.29	56.00	-10.71	QP
8	0.8026	7.64	20.34	27.98	46.00	-18.02	AVG
9	6.1801	33.87	19.54	53.41	60.00	-6.59	QP
10	6.2206	18.21	19.54	37.75	50.00	-12.25	AVG
11	24.3961	33.09	20.24	53.33	60.00	-6.67	QP
12	24.5626	18.82	20.24	39.06	50.00	-10.94	AVG

<b>Test Model</b>	PDT-1GL	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.3℃, 53.7% RH	<b>Test Engineer</b>	Jay Li
<b>Pol</b>	Neutral	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	39.42	21.15	60.57	66.00	-5.43	QP
2	0.1532	21.51	21.13	42.64	55.82	-13.18	AVG
3	0.1726	34.89	21.00	55.89	64.83	-8.94	QP
4	0.1749	12.52	20.98	33.50	54.72	-21.22	AVG
5	0.7216	25.75	20.45	46.20	56.00	-9.80	QP
6	0.7306	9.92	20.43	30.35	46.00	-15.65	AVG
7	2.0266	27.59	19.41	47.00	56.00	-9.00	QP
8	2.0851	11.40	19.41	30.81	46.00	-15.19	AVG
9	6.1801	32.37	19.54	51.91	60.00	-8.09	QP
10	6.2206	16.71	19.54	36.25	50.00	-13.75	AVG
11	24.3961	30.09	20.24	50.33	60.00	-9.67	QP
12	24.6661	16.08	20.24	36.32	50.00	-13.68	AVG

Note: Result = Reading + Correct, Margin = Result – Limit.


## 3.2. Radiated emission Measurement

### 3.2.1. Test Equipment

The following test equipment are used during the radiated emission measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2018-07-26	2021-07-25
3	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2018-07-02	2021-07-01
4	EMI Test Receiver	R&S	ESR 7	101181	2020-06-22	2021-06-21
5	Broadband Preamplifier	/	BP-01M18G	P190501	2020-06-22	2021-06-21
6	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	/	2020-06-22	2021-06-21

### 3.2.2. Block Diagram of Test Setup



### 3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54

Remark: (1) Emission level  $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$   
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for Radiated Emission Above 1GHz

Frequency (MHz)	Distance (Meters)	Peak Limit ( $\text{dB}\mu\text{V/m}$ )	Average Limit ( $\text{dB}\mu\text{V/m}$ )
Above 1000	3	74	54

\*\*\*Note: The lower limit applies at the transition frequency.

### 3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Lighting and measure it.

### 3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.


The bandwidth of the EMI test receiver is set at 120kHz, 300kHz.  
 The frequency range from 30MHz to 1000MHz is checked.

### 3.2.7. Radiated Emission Noise Measurement Result

**PASS.**

The scanning waveforms please refer to the next page.

<b>Test Model</b>	PDT-1GL	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	22.4°C, 53.2% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Jay Li	<b>Test Voltage</b>	AC 120V/60Hz



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	34.52	43.60	0.41	12.30	26.35	40.00	-13.65	QP
2	56.79	41.46	0.47	12.90	24.80	40.00	-15.20	QP
3	85.60	50.84	0.47	10.50	31.71	40.00	-8.29	QP
4	120.70	49.50	0.70	10.37	30.40	43.50	-13.10	QP
5	145.35	50.06	0.77	8.23	28.82	43.50	-14.68	QP
6	313.28	43.91	1.09	13.24	27.69	46.00	-18.31	QP


Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported



<b>Test Model</b>	PDT-1GL	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	22.4°C, 53.2% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Jay Li	<b>Test Voltage</b>	AC 120V/60Hz



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	54.64	36.42	0.46	13.04	19.90	40.00	-20.10	QP
2	83.23	38.47	0.54	9.68	18.59	40.00	-21.41	QP
3	115.32	42.70	0.68	11.31	24.54	43.50	-18.96	QP
4	146.89	45.73	0.77	8.24	24.50	43.50	-19.00	QP
5	222.17	44.51	0.95	11.30	26.37	46.00	-19.63	QP
6	313.28	46.25	1.09	13.24	30.03	46.00	-15.97	QP

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

#### 4. PHOTOGRAPH



Photo of Power Line Conducted Measurement




Photo of Radiated Measurement

## 5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT




Fig. 1




Fig. 2






Fig. 3



Fig. 4




Fig. 5



Fig. 6





Fig. 7




Fig. 8



Fig. 9



Fig. 10

-----THE END OF TEST REPORT-----