

# RF Exposure Evaluation Report

**Product** : TRAIL CAMERAS  
**Trade mark** : BROWNING  
**Model/Type reference** : BTC-PSMHDS  
**Serial Number** : N/A  
**Report Number** : EED32Q82106801  
**FCC ID** : 2ALGTBTC-PSMHDS  
**Date of Issue** : Feb. 11, 2025  
**Test Standards** : 47 CFR Part 1.1307  
47 CFR Part 1.1310  
47 CFR Part 2.1091(mobile devices)  
47 CFR Part 2.1093(portable devices)  
KDB 447498 D04 Interim General RF  
Exposure Guidance v01  
**Test result** : PASS

Prepared for:

**Prometheus Group LLC**  
**2 Perimeter Park S, suite 305E, Birmingham, Alabama 35243 USA**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

Compiled by:

*Frazer Li*

Frazer Li

Reviewed by:

*Tom Chen*

Tom Chen

Approved by:

*Aaron Ma*

Aaron Ma

Date:

Feb. 11, 2025



Check No.:6455181224

1 Version

| Version No. | Date          | Description |
|-------------|---------------|-------------|
| 00          | Feb. 11, 2025 | Original    |
|             |               |             |
|             |               |             |

2 Contents

|                                                       | Page |
|-------------------------------------------------------|------|
| 1 VERSION .....                                       | 2    |
| 2 CONTENTS .....                                      | 3    |
| 3 GENERAL INFORMATION .....                           | 4    |
| 3.1 CLIENT INFORMATION .....                          | 4    |
| 3.2 GENERAL DESCRIPTION OF EUT .....                  | 4    |
| 3.3 TEST LOCATION .....                               | 5    |
| 3.4 DEVIATION FROM STANDARDS .....                    | 5    |
| 3.5 ABNORMALITIES FROM STANDARD CONDITIONS .....      | 5    |
| 3.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER ..... | 5    |
| 4 SAR EVALUATION .....                                | 6    |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....          | 6    |
| 4.1.1 Limits .....                                    | 6    |
| 4.1.2 Test Procedure .....                            | 6    |
| 4.1.3 EUT RF Exposure Evaluation .....                | 7    |

### 3 General Information

#### 3.1 Client Information

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| Applicant:               | Prometheus Group LLC                                                           |
| Address of Applicant:    | 2 Perimeter Park S, suite 305E, Birmingham, Alabama 35243 USA                  |
| Manufacturer:            | Hooray Innovation Limited                                                      |
| Address of Manufacturer: | Flat 1, 4/F, Wah Wai Centre, 38-42 Au Pui Wan Street, Fotan, Shatin, Hong Kong |
| Factory:                 | Hooray Innovation Limited                                                      |
| Address of Factory:      | Flat 1, 4/F, Wah Wai Centre, 38-42 Au Pui Wan Street, Fotan, Shatin, Hong Kong |

#### 3.2 General Description of EUT

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Product Name:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | TRAIL CAMERAS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                       |
| Model No.:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | BTC-PSMHDS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                       |
| Trade Mark:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | BROWNING                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                       |
| Product Type:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location                                                                                                                                                                                                                                                                                                                                                                                               |                                                                       |
| Frequency Band:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | LTE Cat 1bits Band 2:UL:1850-1910MHz,DL:1930-1990MHz;<br>LTE Cat 1bits Band 4:UL:1710-1755MHz,DL:2110-2155MHz;<br>LTE Cat 1bits Band 5:UL:824-849MHz,DL: 869-894MHz;<br>LTE Cat 1bits Band 12:UL:699-716MHz,DL:729-746MHz;<br>LTE Cat 1bits Band 13:UL:777-787MHz,DL:746-756MHz;<br>LTE Cat 1bits Band 14:UL:788-798MHz,DL:758-768MHz;<br>LTE Cat 1bits Band 17:UL:704-716MHz,DL:734-746MHz;<br>LTE Cat 1bits Band 25:UL:1850-1915MHz,DL:1930-1995MHz;<br>LTE Cat 1bits Band 66:UL:1710-1780MHz,DL:2110-2200MHz; |                                                                       |
| Modulation Type:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | QPSK,16QAM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                       |
| Antenna Type:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Dipole antenna                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                       |
| Antenna Gain:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | LTE Cat 1bits Band 2: 2.2dBi;<br>LTE Cat 1bits Band 4: 2.2dBi;<br>LTE Cat 1bits Band 5: 6.1dBi;<br>LTE Cat 1bits Band 12: 6.1dBi;<br>LTE Cat 1bits Band 13: 6.1dBi;<br>LTE Cat 1bits Band 14: 6.1dBi;<br>LTE Cat 1bits Band 17: 6.1dBi;<br>LTE Cat 1bits Band 25: 2.2dBi;<br>LTE Cat 1bits Band 66: 2.2dBi;                                                                                                                                                                                                      |                                                                       |
| Power Supply:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Adapter:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Model:KPH-040012<br>Input:100-240V~50/60Hz,1.5A<br>Output:12.0V,3.33A |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Battery:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | DC 3.7V,2600mAh,9.62Wh                                                |
| Sample Received Date:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Dec. 18, 2024                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                       |
| Sample tested Date:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Dec. 24, 2024 to Dec. 25, 2024                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                       |
| Remark:<br>This test report (Ref. No.: EED32Q82107102) is only valid with the original test report (Ref. No.: EED32Q82106802).Review this report and original report, this report just change the Model No.,Trade Mark and Color of product,all of the test data comes from the original test report (Ref. No.: EED32Q82106802).<br>Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                       |

### 3.3 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

### 3.4 Deviation from Standards

None.

### 3.5 Abnormalities from Standard Conditions

None.

### 3.6 Other Information Requested by the Customer

None.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## 4.1.3 EUT RF Exposure Evaluation

For Stand alone:

| Frequency (MHz) | Estimation distance (cm) | Max. Conducted Output power (dBm) | Antenna Gain (dBi) | ERP (dBm) | ERP (mW) | Limit (mW) | Result |
|-----------------|--------------------------|-----------------------------------|--------------------|-----------|----------|------------|--------|
| 711             | 20                       | 24                                | 6.1                | 27.95     | 623.7348 | 1450.44    | Pass   |

**Note:**

- ① EIRP=conducted power+antenna gain;
- ②  $ERP=EIRP-2.15$ ;
- ③  $EIRP(dBm) = \text{Field strength of the fundamental signal}(dBuV/m@3m) - 95.23$ ;
- ④  $ERP(mW) = 10^{(ERP(dBm)/10)}$ ;
- ⑤ The estimation distance is 20cm;
- ⑥ The test data please refer to the report of EED32Q82107101 and only the worst case data was recorded in the report.

## Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full.

\*\*\* End of Report \*\*\*