

LEDVANCE LLC

MPE ASSESSMENT REPORT

Report Type:

FCC MPE assessment report

Model:

EVC48ALVL2C1, EVC48ALVL2C1WH,
EVC48ALVL2C1GY

REPORT NUMBER:

230402534SHA-002

ISSUE DATE:

June 26, 2023

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



Applicant: LEDVANCE LLC
181 Ballardvale Street, Suite 203, Wilmington, MA 01887, USA

Manufacturer: Longhorn Intelligent Tech Co.,Ltd
Longhorn Hi-Tech Estate, Gongyeyuan Road, Dalang Street, Longhua New District, Shenzhen Guangdong, China

Factory: Longhorn Intelligent Tech Co.,Ltd
3rd to 5th floors, 5th Plant, Zhonghai Science and Technology (Huizhou) Park, Western Zone, Dayawan, Huizhou City, Guangdong, China

FCC ID: 2AKGT-78134

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

REVIEWED BY:



Project Engineer
Sky Yang

Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
230402534SHA-002	Rev. 01	Initial issue of report	June 26, 2023

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	EV Charger
Type/Model:	EVC48ALVL2C1, EVC48ALVL2C1WH, EVC48ALVL2C1GY
Description of EUT:	The EUT is electric vehicle AC charger with RFID, WIFI and LTE function. The wireless module FCC ID is XMR201909EC25AFX and 2AHMR-BW16. The wireless module IC is 10224A-2019EC25AFX and 23236-BW16. All models are electrically identical except the appearance color.
Rating:	Input/Output: 208/240VAC, 50/60Hz, Max 48A, Max 11.5kW
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	-
Hardware Version:	-
Serial numbers:	0230116-24-001
Sample received date:	January 29, 2023
Date of test:	January 30, 2023 ~ February 17, 2023

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna gain:	PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

TEST REPORT

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = P / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

R = distance (cm)

As we can see from the test report 230402534SHA-001:

$$62.25\text{dBuV/m}@3\text{m}, @20\text{cm}=@3\text{m}+40\log(3/0.2)=109.29\text{dBuV/m}=0.29\text{V/m}<60.77.$$

The power for WIFI module refers to certificate of FCC ID: 2AHMR-BW16

The power for LTE module refers to certificate of FCC ID: XMR201909EC25AFX

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency Range (MHz)	EIRP		Antenna Gain (dBi)	R (cm)	S (mW/cm ²)	Limits (mW/cm ²)
	(dBm)	(mW)				
WIFI 5G	18	63.10	2	20	0.0126	1
WIFI 2.4G	20	100.00	2	20	0.0199	1
WCDMA Band II	28.9	776.25	3.9	20	0.154	1
WCDMA Band IV	28.9	776.25	3.9	20	0.154	1
WCDMA Band V	28.9	776.25	3.9	20	0.154	0.55
LTE Band 2	28.9	776.25	3.9	20	0.154	1
LTE Band 4	28.9	776.25	3.9	20	0.154	1
LTE Band 5	28.9	776.25	3.9	20	0.154	0.55
LTE Band 12	28.9	776.25	3.9	20	0.154	0.47
LTE Band 13	28.9	776.25	3.9	20	0.154	0.52
LTE Band 14	28.9	776.25	3.9	20	0.154	0.53
LTE Band66	28.9	776.25	3.9	20	0.154	1
LTE Band 71	28.9	776.25	3.9	20	0.154	0.45

Note: 1 mW/cm² from 1.310 Table 1.

RFID, WIFI and LTE can transmit simultaneously, so the maximum rate of MPE is,
 $0.29/60.77+0.0199/1+0.154/0.45=0.367 < 1.0.$

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

*****END*****