



FCC RF Test Report

For

Bytech NY Inc.

Test Standards:	<u>Part 15C Subpart C §15.247</u>
Product Name:	<u>TWS STICK iPX4 TCH XT-49</u>
Tested Model:	<u>HM-AU-BE-209 XT-49</u>
FCC ID:	<u>2AHN6-AUBE209</u>
Classification	<u>(DTS) Digital Transmission System</u>
Report No.:	<u>EC2010033RF01</u>
Tested Date:	<u>2020-10-29 to 2020-11-13</u>
Issued Date:	<u>2020-11-13</u>
Prepared By:	<u></u> Jerry Wang / Engineer
Approved By:	<u></u> Tiny Yang / RF Manager

Hunan Ecloud Testing Technology Co., Ltd.

Building A1, Changsha E Center, No. 18 Xiangtai Avenue, Liuyang Economic and
Technological Development Zone, Hunan, P.R.C

Tel.: +86-731-89634887 Fax.: +86-731-89634887

www.hn-ecloud.com

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Hunan Ecloud Testing Technology Co., Ltd., the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2020.11.13	Valid	Original Report

TABLE OF CONTENTS

1. TEST LABORATORY	5
1.1 Test facility	5
2. GENERAL DESCRIPTION.....	6
2.1 Applicant	6
2.2 Manufacturer	6
2.3 General Description Of EUT	6
2.4 Modification of EUT	7
2.5 Applicable Standards	7
3. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
3.1 Descriptions of Test Mode	8
3.2 Test Mode	8
3.3 Support Equipment	9
3.4 Test Setup	9
3.5 Measurement Results Explanation Example	12
4. TEST RESULT	13
4.1 6dB and 99% Bandwidth Measurement	13
4.2 Peak Output Power Measurement	14
4.3 Power Spectral Density Measurement	15
4.4 Conducted Band Edges and Spurious Emission Measurement	16
4.5 Radiated Band Edges and Spurious Emission Measurement	17
4.6 AC Conducted Emission Measurement.....	47
4.7 Antenna Requirements	50
5. LIST OF MEASURING EQUIPMENT	51
6. UNCERTAINTY OF EVALUATION.....	53
APPENDIX A: DTS BANDWIDTH	54
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	57
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	60
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	63
APPENDIX E: BAND EDGE MEASUREMENTS	66
APPENDIX F: CONDUCTED SPURIOUS EMISSION	68
APPENDIX G: SETUP PHOTOGRAPHS	74

Summary of Test RESULT

FCC Rule	Description	Limit	Result	Remark
15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
-	99% Bandwidth	-	Pass	-
15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.15 dB at 9920 MHz
15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 19.76 dB at 0.155 MHz
15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1. Test Laboratory

1.1 Test facility

CNAS (accreditation number:L11138)

Hunan Ecloud Testing Technology Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number:CN1244 , Test Firm Registration

Number:793308)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

ISED(CAB identifier: CN0012, ISED# :24347)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the Wireless Device Testing Laboratories list of innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

A2LA (Certificate Number:4895.01)

Hunan Ecloud Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

2. General Description

2.1 Applicant

Bytech NY Inc.
2585 West 13th Street Brooklyn NY 11223 USA

2.2 Manufacturer

Bytech NY Inc.
2585 West 13th Street Brooklyn NY 11223 USA

2.3 General Description Of EUT

Product	TWS STICK IPX4 TCH XT-49
Model No.	HM-AU-BE-209 XT-49
Additional No.	NA
Difference Description	NA
FCC ID	2AHN6-AUBE209
Power Supply	5Vdc for Charging stand 3.7Vdc Li-ion Battery for EUT
Modulation Technology	BLE
Modulation Type	GFSK
Operating Frequency	2402MHz~2480MHz
Number Of Channel	40
Max. Output Power	-4.29 dBm (0.0004 W)
Antenna Type	Ceramics Antenna with 1.24dBi gain
HW Version	TWS-AC6936D V1.2-20201023
SW Version	N/A
I/O Ports	Refer to user's manual

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.4 Modification of EUT

No modifications are made to the EUT during all test items.

2.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦

Remark:

1. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3. Test Configuration of Equipment Under Test

3.1 Descriptions of Test Mode

The transmitter has a maximum peak conducted output power as follows:

Channel	Frequency	Mode	Bluetooth RF Output Power
Ch00	2402MHz	GFSK	-6.99
Ch19	2440MHz	GFSK	-5.05
Ch39	2480MHz	GFSK	-4.29

- Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.
- The product has left and right earphones, the same schematic diagram, only the worst left earphone test results are displayed in the report

3.2 Test Mode

3.2.1 Antenna Port Conducted Measurement

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 5.0 – LE GFSK
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH19_2440 MHz Mode 3: CH39_2480 MHz

3.2.2 Radiated Emission Test (Below 1GHz)

Radiated	Bluetooth BR 1Mbps GFSK
Test Cases	Mode 1: CH00_2402 MHz

- Note : 1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type. Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.
2. Following channel(s) was (were) selected for the final test as listed above

3.2.3 Radiated Emission Test (Above 1GHz)

Radiated Test Cases	Bluetooth BR 1Mbps GFSK
	Mode 1: CH00_2402 MHz
	Mode 2: CH19_2440 MHz
	Mode 3: CH39_2480 MHz

- Note : 1. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.
2. Following channel(s) was (were) selected for the final test as listed above
3. For frequency above 18GHz, the measured value is much lower than the limit, therefore, it is not reflected in the report.

3.2.4 Power Line Conducted Emission Test:

AC Conducted Emission	Mode 1 : Bluetooth Linking + charging stand + charging from adapter
-----------------------------	---


3.3 Support Equipment

Manufacturer	Description	Model	Serial Number	Certificate
Lenovo	Notebook	Xiaoxinchao5000	PF0QPQMH	FCC sDoC
NA	Micro USB Cable	NA	NA	NA
XIAOMI	Charger	MDY-08-ES	4A418083222353C	FCC sDoC


3.4 Test Setup

The EUT is continuously communicating to the Bluetooth tester during the tests.


EUT was set in the Hidden menu mode to enable BT communications.




Setup diagram for Conducted Test




Setup diagram for Radiation(9KHz~30MHz) Test




Setup diagram for Radiation(Below 1G) Test



Setup diagram for Radiation(Above1G) Test



Setup diagram for AC Conducted Emission Test



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5 + 10 = 15 \text{ (dB)} \end{aligned}$$

For all radiated test items:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Over Limit (dB μ V/m) = Level(dB μ V/m) - Limit Level (dB μ V/m)

4. Test Result

4.1 6dB and 99% Bandwidth Measurement

4.1.1 Limit of 6dB and 99% Bandwidth

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

4.1.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set to the maximum power setting and enable the EUT transmit continuously
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.

4.1.3 Test Result of 6dB Bandwidth

Refer to Appendix A of this test report.

4.1.4 Test Result of 99% Bandwidth

Refer to Appendix B of this test report.

4.2 Peak Output Power Measurement

4.2.1 Limit of Peak Output Power

FCC §15.247 (b)(3)

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to spectrum analyzer.
3. Set to the maximum power setting and enable the EUT transmit continuously
4. Set the $RBW \geq DTS$ Bandwidth, $VBW \geq 3 * RBW$, $Span \geq 1.5 * DTS$ Bandwidth, Detector=Peak, Sweep time=auto couple, Trace mode=max holde.
5. Allow trace to fully stabilize, Use peak marker function to determine the peak amplitude level.
6. Measure the conducted output power

4.2.3 Test Result of Peak Output Power

Refer to Appendix C of this test report.

4.3 Power Spectral Density Measurement

4.3.1 Limits of Power Spectral Density

FCC§15.247(e)

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

4.3.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
5. Measure and record the results in the test report.
6. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

4.3.3 Test Result of Power Spectral Density

Refer to Appendix D of this test report.

4.4 Conducted Band Edges and Spurious Emission Measurement

4.4.1 Limit of Conducted Band Edges and Spurious Emission

FCC §15.247 (d)

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

4.4.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

4.4.3 Test Result of Conducted Band Edges

Refer to Appendix E of this test report.

4.4.4 Test Result of Conducted Spurious Emission

Refer to Appendix F of this test report.

4.5 Radiated Band Edges and Spurious Emission Measurement

4.5.1 Limit of Radiated Band Edges and Spurious Emission

FCC §15.247 (d)

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.


Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

4.5.2 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The measurement distance is 3 meter.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control

level for the tested mode of operation.

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth 5.0 - LE	44.80	1.12	0.89	1kHz




4.5.3 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

4.5.4 Test Result of Radiated Spurious at Band Edges

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.405GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH00(2402MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.29	27.38	4.11	35.61	37.17	74.00	-36.83	Peak
2390.000	42.42	27.56	4.18	35.79	38.37	74.00	-35.63	Peak
2402.480	58.01	27.59	4.19	35.82	53.97	74.00	-20.03	Peak

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.405GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 343




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	29.97	27.38	4.11	35.61	25.85	54.00	-28.15	Average
2390.000	30.05	27.56	4.18	35.79	26.00	54.00	-28.00	Average
2402.060	52.49	27.58	4.19	35.82	48.44	54.00	-5.56	Average

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.405GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH00(2402MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		


Data: 339



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.24	27.38	4.11	35.61	37.12	74.00	-36.88	Peak
2390.000	41.16	27.56	4.18	35.79	37.11	74.00	-36.89	Peak
2402.480	61.58	27.59	4.19	35.82	57.54	74.00	-16.46	Peak

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.405GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	29.03	27.38	4.11	35.61	24.91	54.00	-29.09	Average
2390.000	28.98	27.56	4.18	35.79	24.93	54.00	-29.07	Average
2402.060	55.81	27.58	4.19	35.82	51.76	54.00	-2.24	Average

Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.477GHz~2.51GHz	Polarization :	Horizontal


Test Site : 3m Chamber
 Temp/Humi : 25℃/64%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : Ble CH39(2480MHz)
 Power rating: DC 3.0-4.2V
 EUT : TWS STICK iPX4 TCH XT-49
 Model No. : HM-AU-BE-209 XT-49



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.366	67.40	27.76	4.26	36.00	63.42	74.00	-10.58	Peak
2483.500	41.02	27.76	4.26	36.00	37.04	74.00	-36.96	Peak
2500.000	40.35	27.80	4.28	36.04	36.39	74.00	-37.61	Peak

Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.477GHz~2.51GHz	Polarization :	Horizontal


Test Site : 3m Chamber
 Temp/Humi : 25℃/64%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : Ble CH39(2480MHz)
 Power rating: DC 3.0-4.2V
 EUT : TWS STICK iPX4 TCH XT-49
 Model No. : HM-AU-BE-209 XT-49



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.003	60.99	27.76	4.26	35.99	57.02	54.00	3.02	Average
2483.500	29.44	27.76	4.26	36.00	25.46	54.00	-28.54	Average
2500.000	28.58	27.80	4.28	36.04	24.62	54.00	-29.38	Average

Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.477GHz~2.51GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 25℃/64%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : Ble CH39(2480MHz)
 Power rating: DC 3.0-4.2V
 EUT : TWS STICK iPX4 TCH XT-49
 Model No. : HM-AU-BE-209 XT-49




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.366	64.52	27.76	4.26	36.00	60.54	74.00	-13.46	Peak
2483.500	40.62	27.76	4.26	36.00	36.64	74.00	-37.36	Peak
2500.000	40.12	27.80	4.28	36.04	36.16	74.00	-37.84	Peak

Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.477GHz~2.51GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH39(2480MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 348




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.003	58.96	27.76	4.26	35.99	54.99	54.00	0.99	Average
2483.500	28.72	27.76	4.26	36.00	24.74	54.00	-29.26	Average
2500.000	28.46	27.80	4.28	36.04	24.50	54.00	-29.50	Average

4.5.1 Test Result of Radiated Spurious Emission (1GHz ~ 10th Harmonic)

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2402.000	56.76	27.58	4.19	35.82	52.71	74.00	-21.29	Peak


Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Test Site	: 3m Chamber	Temp/Humi	: 25°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 354




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	33.08	30.93	6.09	36.03	34.07	54.00	-19.93	Average
4804.000	41.62	30.93	6.09	36.03	42.61	74.00	-31.39	Peak
7206.000	25.91	35.39	9.22	34.25	36.27	54.00	-17.73	Average
7206.000	39.21	35.39	9.22	34.25	49.57	74.00	-24.43	Peak
9608.000	27.35	38.39	12.26	32.19	45.81	54.00	-8.19	Average
9608.000	40.81	38.39	12.26	32.19	59.27	74.00	-14.73	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH00(2402MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2402.000	61.34	27.58	4.19	35.82	57.29	74.00	-16.71	Peak


Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH00(2402MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Test Site	: 3m Chamber	Temp/Humi	: 25°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 356




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	32.95	30.93	6.09	36.03	33.94	54.00	-20.06	Average
4804.000	41.56	30.93	6.09	36.03	42.55	74.00	-31.45	Peak
7206.000	25.85	35.39	9.22	34.25	36.21	54.00	-17.79	Average
7206.000	40.20	35.39	9.22	34.25	50.56	74.00	-23.44	Peak
9608.000	27.35	38.39	12.26	32.19	45.81	54.00	-8.19	Average
9608.000	41.43	38.39	12.26	32.19	59.89	74.00	-14.11	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	BLE CH19 (2440 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH19(2440MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2440.000	66.10	27.67	4.22	35.90	62.09	74.00	-11.91	Peak


Test Mode :	BLE CH19 (2440 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH19(2440MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Test Site	: 3m Chamber	Temp/Humi	: 25°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: BLE CH19(2440MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 360




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	28.13	31.03	6.08	35.98	29.26	54.00	-24.74	Average
4880.000	41.29	31.03	6.08	35.98	42.42	74.00	-31.58	Peak
7320.000	25.87	35.67	9.20	34.29	36.45	54.00	-17.55	Average
7320.000	39.55	35.67	9.20	34.29	50.13	74.00	-23.87	Peak
9760.000	26.41	38.51	12.50	32.03	45.39	54.00	-8.61	Average
9760.000	39.99	38.51	12.50	32.03	58.97	74.00	-15.03	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	BLE CH19 (2440 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH19(2440MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2440.000	65.28	27.67	4.22	35.90	61.27	74.00	-12.73	Peak


Test Mode :	BLE CH19 (2440 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH19(2440MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Test Site	: 3m Chamber	Temp/Humi	: 25°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH19(2440MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 358




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	28.46	31.03	6.08	35.98	29.59	54.00	-24.41	Average
4880.000	41.89	31.03	6.08	35.98	43.02	74.00	-30.98	Peak
7320.000	25.83	35.67	9.20	34.29	36.41	54.00	-17.59	Average
7320.000	40.43	35.67	9.20	34.29	51.01	74.00	-22.99	Peak
9760.000	26.54	38.51	12.50	32.03	45.52	54.00	-8.48	Average
9760.000	40.05	38.51	12.50	32.03	59.03	74.00	-14.97	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH39(2480MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	67.22	27.76	4.26	35.99	63.25	74.00	-10.75	Peak


Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH39(2480MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Test Site	: 3m Chamber	Temp/Humi	: 25°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: BLE CH39(2480MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 362




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	32.20	31.14	6.07	35.93	33.48	54.00	-20.52	Average
4960.000	41.98	31.14	6.07	35.93	43.26	74.00	-30.74	Peak
7440.000	24.81	35.96	9.04	34.32	35.49	54.00	-18.51	Average
7440.000	38.79	35.96	9.04	34.32	49.47	74.00	-24.53	Peak
9920.000	26.49	38.64	13.24	31.87	46.50	54.00	-7.50	Average
9920.000	41.47	38.64	13.24	31.87	61.48	74.00	-12.52	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH39(2480MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.000	64.42	27.76	4.26	35.99	60.45	74.00	-13.55	Peak


Test Mode :	BLE CH39 (2480 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH39(2480MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Test Site	: 3m Chamber	Temp/Humi	: 25°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH39(2480MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		

Data: 364




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	32.91	31.14	6.07	35.93	34.19	54.00	-19.81	Average
4960.000	43.06	31.14	6.07	35.93	44.34	74.00	-29.66	Peak
7440.000	25.16	35.96	9.04	34.32	35.84	54.00	-18.16	Average
7440.000	38.33	35.96	9.04	34.32	49.01	74.00	-24.99	Peak
9920.000	26.84	38.64	13.24	31.87	46.85	54.00	-7.15	Average
9920.000	40.22	38.64	13.24	31.87	60.23	74.00	-13.77	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

4.5.2 Test Result of Radiated Spurious Emission (30MHz ~ 1GHz)

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: Ble CH00(2402MHz)	Power rating	: DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
239.520	52.18	12.58	3.02	32.48	35.30	46.00	-10.70	QP
287.050	51.58	13.92	3.32	32.49	36.33	46.00	-9.67	QP
335.550	50.80	14.63	3.60	32.51	36.52	46.00	-9.48	QP
359.800	50.00	15.00	3.74	32.53	36.21	46.00	-9.79	QP
371.440	47.59	15.23	3.81	32.53	34.10	46.00	-11.90	QP
455.830	45.16	17.37	4.24	32.59	34.18	46.00	-11.82	QP

Test Mode :	BLE CH00 (2402 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: Ble CH00(2402MHz)	Power rating:	DC 3.0-4.2V
EUT	: TWS STICK iPX4 TCH XT-49		
Model No.	: HM-AU-BE-209 XT-49		



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
143.490	42.17	14.17	2.32	32.48	26.18	43.50	-17.32	QP
167.740	44.23	13.41	2.51	32.48	27.67	43.50	-15.83	QP
383.080	44.81	15.46	3.88	32.54	31.61	46.00	-14.39	QP
430.610	44.44	16.72	4.11	32.57	32.70	46.00	-13.30	QP
504.330	41.58	18.00	4.45	32.63	31.40	46.00	-14.60	QP
526.640	39.61	18.54	4.57	32.65	30.07	46.00	-15.93	QP

4.6 AC Conducted Emission Measurement

4.6.1 Limit of AC Conducted Emission

FCC §15.207

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


*Decreases with the logarithm of the frequency.

4.6.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


4.6.3 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24°C
Test Engineer :	Jack Liu	Relative Humidity :	52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Linking + charging stand + charging from adapter		



Result Level= Reading Level + LISN Factor + Cable Loss

Test Mode :	Mode 1	Temperature :	24°C
Test Engineer :	Jack Liu	Relative Humidity :	52%
Test Voltage :	120Vac / 60Hz	Phase :	NEUTRAL
Function Type :	Bluetooth Linking + charging stand + charging from adapter		



Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	Result level dBuV	Limit level dBuV	Over limit dB	Remark
0.155	30.30	9.56	0.02	39.88	65.74	-25.86	QP
0.155	26.40	9.56	0.02	35.98	55.74	-19.76	Average
0.200	28.90	9.56	0.03	38.49	63.62	-25.13	QP
0.200	11.10	9.56	0.03	20.69	53.62	-32.93	Average
0.222	26.50	9.56	0.03	36.09	62.74	-26.65	QP
0.222	8.00	9.56	0.03	17.59	52.74	-35.15	Average
0.505	10.20	9.59	0.02	19.81	56.00	-36.19	QP
0.505	-2.60	9.59	0.02	7.01	46.00	-38.99	Average
0.558	8.70	9.59	0.02	18.31	56.00	-37.69	QP
0.558	-2.60	9.59	0.02	7.01	46.00	-38.99	Average
0.683	14.50	9.59	0.01	24.10	56.00	-31.90	QP
0.683	2.60	9.59	0.01	12.20	46.00	-33.80	Average

Result Level= Reading Level + LISN Factor + Cable Loss

4.7 Antenna Requirements

4.7.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded..

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 Antenna Connected Construction

An Ceramics Antenna design is used.

4.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	Keysight	N9010A	MY56070788	2020-01-15	2021-01-14	Conducted
Power Sensor	Keysight	U2021XA	MY56510025	2020-01-16	2021-01-15	Conducted
Power Sensor	Keysight	U2021XA	MY57030005	2020-01-16	2021-01-15	Conducted
Power Sensor	Keysight	U2021XA	MY56510018	2020-01-16	2021-01-15	Conducted
Power Sensor	Keysight	U2021XA	MY56480002	2020-01-16	2021-01-15	Conducted
Thermal Chamber	Howkin	UHL-34	19111801	2020-05-09	2021-05-08	Conducted
Base Station	R&S	CMW 270	101231	2020-01-16	2021-01-15	Conducted
Signal Generator (Interferer)	Keysight	N5182B	MY56200384	2020-02-21	2021-02-20	Conducted
Signal Generator (Blocker)	Keysight	N5171B	MY56200661	2020-01-15	2021-01-14	Conducted

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV 40	101433	2020-01-16	2021-01-15	Radiation
Amplifier	Sonoma	310	363917	2020-01-15	2021-01-14	Radiation
Amplifier	Schwarzbeck	BBV 9718	327	2020-01-15	2021-01-14	Radiation
Amplifier	Narda	TTA1840-35-HG	2034380	2020-05-22	2021-05-21	Radiation
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	2020-02-14	2023-02-13	Radiation
Broadband Antenna	Schwarzbeck	VULB 9168	9168-757	2018-08-31	2021-08-30	Radiation
Horn Antenna	Schwarzbeck	BBHA 9120 D	1677	2020-02-14	2023-02-13	Radiation
Horn Antenna	COM-POWER	AH-1840	101117	2018-06-20	2021-06-19	Radiation
Test Software	Audix	E3	6.111221a	N/A	N/A	Radiation
Filter	Micro-Tronics	BRM 50702	G266	N/A	N/A	Radiation

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
LISN	R&S	ENV216	102125	2020-01-08	2021-01-07	Conducted
LISN	R&S	ENV432	101327	2020-01-08	2021-01-07	Conducted
EMI Test Receiver	R&S	ESR3	102143	2020-01-16	2021-01-15	Conducted
EMI Test Software	Audix	E3	N/A	N/A	N/A	Conducted

N/A: No Calibration Required

6. Uncertainty of Evaluation

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.42dB
Radiated emission	30MHz ~ 1GMHz	2.50dB
	1GHz ~ 18GHz	3.51dB
	18GHz ~ 40GHz	3.96dB

MEASUREMENT	UNCERTAINTY
Occupied Channel Bandwidth	±196.4Hz
RF output power, conducted	±2.31dB
Power density, conducted	±2.31dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Appendix A: DTS Bandwidth

Test Result


TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_BT5.0	Ant1	2402	1.308	2401.296	2402.604	0.5	PASS
		2440	1.364	2439.288	2440.652	0.5	PASS
		2480	1.260	2479.308	2480.568	0.5	PASS

Test Graphs

BLE_BT5.0_Ant1_2402



BLE_BT5.0_Ant1_2440



BLE_BT5.0_Ant1_2480



Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_BT5.0	Ant1	2402	2.0915	2400.974	2403.065	---	PASS
		2440	2.0747	2438.981	2441.056	---	PASS
		2480	2.0951	2478.969	2481.064	---	PASS

Test Graphs






Appendix C: Maximum conducted output power

Test Result


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_BT5.0	Ant1	2402	-6.99	<=30	PASS
		2440	-5.05	<=30	PASS
		2480	-4.29	<=30	PASS

Test Graphs


BLE_BT5.0_Ant1_2402



BLE_BT5.0_Ant1_2440



BLE_BT5.0_Ant1_2480



Appendix D: Maximum power spectral density

Test Result

TestMode	Antenna	Channel	Result [dBm/10kHz]	Result [dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_BT5.0	Ant1	2402	-10.58	-15.35	<=8	PASS
		2440	-8.87	-13.64	<=8	PASS
		2480	-7.93	-12.70	<=8	PASS


Note:

calculating the RBW=3kHz value:


$-10.58 \text{ (AV.PSD At RBW=10kHz)} - 10 \cdot \log(30/10) = -15.35 \text{ (AV.PSD At RBW=3kHz)}$

Test Graphs


BLE_BT5.0_Ant1_2402



BLE_BT5.0_Ant1_2440



BLE_BT5.0_Ant1_2480




Appendix E: Band edge measurements

Test Result


TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_BT5.0	Ant1	Low	2402	-7.31	-38.22	<=-27.31	PASS
		High	2480	-4.57	-46.72	<=-24.57	PASS

Test Graphs

BLE_BT5.0_Ant1_Low_2402



BLE_BT5.0_Ant1_High_2480



Appendix F: Conducted Spurious Emission

Test Result


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_BT5.0	Ant1	2402	Reference	-7.25	-7.25	---	PASS
			30~1000	30~1000	-67.163	<=-27.249	PASS
			1000~26500	1000~26500	-47.653	<=-27.249	PASS
		2440	Reference	-5.28	-5.28	---	PASS
			30~1000	30~1000	-67.862	<=-25.276	PASS
			1000~26500	1000~26500	-47.318	<=-25.276	PASS
		2480	Reference	-4.40	-4.40	---	PASS
			30~1000	30~1000	-67.069	<=-24.404	PASS
			1000~26500	1000~26500	-48.108	<=-24.404	PASS

Test Graphs

BLE_BT5.0_Ant1_2402_0~Reference



BLE_BT5.0_Ant1_2402_30~1000




BLE_BT5.0_Ant1_2402_1000~26500



BLE_BT5.0_Ant1_2440_0-Reference



BLE_BT5.0_Ant1_2440_30-1000




BLE_BT5.0_Ant1_2440_1000-26500



BLE_BT5.0_Ant1_2480_0-Reference



BLE_BT5.0_Ant1_2480_30~1000



BLE_BT5.0_Ant1_2480_1000~26500



Appendix G: Setup Photographs




Fig. 1 Radiated emission setup photo(Below 30MHz)




Fig. 2 Radiated emission setup photo(30MHz-1GHz)




Fig. 3 Radiated emission setup photo(Above 1GHz)



Fig. 4 Power line conducted emission setup photo

-----End of the report-----