
FCC Test Report

Report No.: AGC03393230603FE10

FCC ID : 2AB4FD500

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : Digital Two-way Radio

BRAND NAME : N/A

MODEL NAME : D500, D505, D506, D507, D508, D509

APPLICANT : Fujian Juston Electronic Equipment Co., Ltd.

DATE OF ISSUE : Aug. 04, 2023

STANDARD(S) : FCC Part 90 Rules

REPORT VERSION : V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug. 04, 2023	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	7
2.3 RELATED SUBMITTAL(S) / GRANT (S)	8
2.4 TEST METHODOLOGY	8
2.5 CALCULATION OF EMISSION INDICATORS	8
2.6 SPECIAL ACCESSORIES	8
2.7 EQUIPMENT MODIFICATIONS	8
3. TEST ENVIRONMENT	9
3.1 ADDRESS OF THE TEST LABORATORY	9
3.2 TEST FACILITY	9
3.3 ENVIRONMENTAL CONDITIONS	10
3.4 MEASUREMENT UNCERTAINTY	10
3.5 LIST OF EQUIPMENTS USED	11
4.SYSTEM TEST CONFIGURATION	12
4.1 EUT CONFIGURATION	12
4.2 EUT EXERCISE	12
4.3 CONFIGURATION OF TESTED SYSTEM	12
4.4 EQUIPMENT USED IN TESTED SYSTEM	12
4.5 SUMMARY OF TEST RESULTS	13
5.DESCRPTION OF TEST MODES	14
6.FREQUENCY TOLERANCE	15
6.1 PROVISIONS APPLICABLE	15
6.2 MEASUREMENT PROCEDURE	15
6.3 MEASUREMENT SETUP	15
6.4 MEASUREMENT RESULTS	16
7. EMISSION BANDWIDTH	18
7.1 PROVISIONS APPLICABLE	18
7.2 MEASUREMENT PROCEDURE	18
7.3 MEASUREMENT SETUP	18
7.4 MEASUREMENT RESULTS	19
8. SPURIOUS RADIATED EMISSION	23
8.1 PROVISIONS APPLICABLE	23
8.2 MEASUREMENT PROCEDURE	23

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.3 MEASUREMENT SETUP	24
8.4 MEASUREMENT RESULTS.....	25
8.5 EMISSION MASK PLOT	34
9.MODULATION CHARACTERISTICS	38
9.1 PROVISIONS APPLICABLE.....	38
9.2 MEASUREMENT METHOD	38
9.3 MEASUREMENT SETUP	38
9.4 MEASUREMENT RESULTS.....	39
10. MAXIMUM TRANSMITTER POWER	43
10.1 PROVISIONS APPLICABLE.....	43
10.2 MEASUREMENT METHOD	43
10.3 MEASUREMENT METHOD	43
10.4 MEASUREMENT RESULTS	45
11. SPURIOUS EMISSION ON ANTENNA PORT	48
11.1 PROVISIONS APPLICABLE	48
11.2 MEASUREMENT METHOD.....	48
11.3 MEASUREMENT SETUP	48
11.4 MEASUREMENT RESULTS.....	49
12.TRANSMITTER FREQUENCY BEHAVIOR.....	55
12.1 PROVISIONS APPLICABLE.....	55
12.2 MEASUREMENT SETUP	55
12.3 MEASUREMENT METHOD	56
12.4 MEASURET RESULTS.....	58
13. AUDIO LOW PASS FILTER RESPONSE	59
13.1 PROVISIONS APPLICABLE.....	59
13.2 MEASUREMENT METHOD	60
13.3 MEASUREMENT SETUP	60
13.4 MEASURET RESULTS.....	61
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	63
APPENDIX II: PHOTOGRAPHS OF TEST EUT	63

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


1. GENERAL INFORMATION

Applicant	Fujian Juston Electronic Equipment Co., Ltd.
Address	No.886, Changfeng Street, Shudou Industrial Park, Licheng District, Quanzhou Fujian China 362000
Manufacturer	Fujian Juston Electronic Equipment Co., Ltd.
Address	No.886, Changfeng Street, Shudou Industrial Park, Licheng District, Quanzhou Fujian China 362000
Factory	Fujian Juston Electronic Equipment Co., Ltd.
Address	No.886, Changfeng Street, Shudou Industrial Park, Licheng District, Quanzhou Fujian China 362000
Product Designation	Digital Two-way Radio
Brand Name	N/A
Test Model	D500
Series Model(s)	D505, D506, D507, D508, D509
Difference Description	Only the model name & cover designs are different
Deviation from Standard	None
Date of receipt of test item	Jun. 19, 2023
Date of Test	Jun. 19, 2023~Aug. 03, 2023
Test Result	Pass

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 90. The test results of this report relate only to the tested sample identified in this report.

Prepared By



Bibo Zhang
(Project Engineer)

Aug. 04, 2023

Reviewed By



Calvin Liu
(Reviewer)

Aug. 04, 2023

Approved By



Max Zhang
Authorized Officer

Aug. 04, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	V1.1	
Software Version	V1.06	
Power Supply	DC 7.4V 1600mAh	
Adapter Information	Input: AC 100-240V 50/60Hz, 0.2A Output: DC 8.4V 0.4A	
Communication Type	Voice / Data Voice / Tone only	
Operation Frequency Range	From 400MHz to 470MHz--UHF	
Modulation Type	Analog Voice:	FM
	Digital (Voice + Data):	4FSK
Channel Separation	Analog Voice:	12.5 kHz
	Digital (Voice + Data):	12.5 kHz
Emission Designator	Analog Voice:	11K0F3E
	Digital (Voice + Data):	☒ UHF:6K29F1D-5W-12.5kHz ☒ UHF:6K27F1W-1W-12.5kHz
Rated Output Power	5W/1W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Maximum Transmitter Power	35.88dBm(5W-12.5kHz) 29.91dBm(1W-12.5kHz)	
Antenna Designation	Detachable	
Antenna Gain	2.15dBi	
Frequency Tolerance	1.99ppm	

Note:

1. The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
2. This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.
3. The actual working frequency band of the device is UHF: 400-470MHz. According to the frequency division requirements of KDB634817 and the federal frequency allocation requirements, the working frequency band that the device needs to meet is UHF: 406.1-470MHz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.2 TEST FREQUENCY LIST

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
Analog/ Digital	12.5 kHz	400-470MHz	Bottom	406.125 MHz
	12.5 kHz	400-470MHz	Middle	453.2125 MHz
	12.5 kHz	400-470MHz	Middle	458.2125 MHz
	12.5 kHz	400-470MHz	Top	469.975 MHz

Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **2AB4FD500**, filing to comply with Part 2, Part 90 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 90	Private Land Mobile Radio Services
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
3	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
4	ANSI TIA-102.CAAA-E	Project 25 Digital C4FM/CQPSK Transceiver Measurement Methods
5	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
6	KDB 971168 D01	KDB 971168 D01 Power Means License Digital Systems v03r01
7	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01
8	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01

2.5 CALCULATION OF EMISSION INDICATORS

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For FM Mode (ChannelSpacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$$

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1W

The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.

F1D and F1W portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.

2.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS
Temperature range (°C)	15 - 35	-20 - 50
Relative humidity range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC 7.4V	LV:DC 6.29V/HV: DC 8.51V
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.		

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	$\pm 0.5\%$
Transmitter power conducted	$\pm 0.8\text{dB}$
Transmitter power Radiated	$\pm 1.3\text{dB}$
Conducted spurious emission 9kHz-40 GHz	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 3.2\text{ dB}$
Radiated Emission below 1GHz	$\pm 3.9\text{ dB}$
Radiated Emission above 1GHz	$\pm 4.8\text{ dB}$
Occupied Channel Bandwidth	$\pm 2\%$
FM deviation	$\pm 2\%$
Audio level	$\pm 0.98\text{dB}$
Low Pass Filter Response	$\pm 0.65\text{dB}$
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9020A	MY53300860	Jun. 01, 2023	May 31, 2024
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Jun. 01, 2023	May 31, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
preamplifier	ChengYi	EMC184045SE	980508	Oct. 29, 2021	Oct. 28, 2023
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Mar. 23, 2023	Mar. 22, 2024
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun. 03, 2023	Jun. 02, 2024
HORN ANTENNA	EM	EM-AH-10180	/	Feb.22, 2023	Feb.21, 2024
SIGNAL GENERATOR	AGILENT	E4421B	MY43351603	Feb. 17, 2023	Feb. 16, 2024
SIGNAL GENERATOR	KEYSIGHT	5182A	5182A	Feb. 17, 2023	Feb. 16, 2024
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 05, 2023	Jan. 04, 2025
ANTENNA	SCHWARZBECK	VULB9168	D69250	May 11, 2023	May 10, 2025
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2022	May 21, 2024
Small environmental tester	ESPEC	SH-242	93008290	Aug. 03, 2022	Aug. 02, 2024
RF Communication Test Set	HP	8920B	US35010161	Jun. 02, 2023	Jun. 01, 2024
Attenuator	Weinachel Corp	58-30-33	ML030	Oct. 22, 2023	Oct. 21, 2023
RF Cable	R&S	1#	--	Each time	N/A
RF Cable	R&S	2#	--	Each time	N/A
Fliter-UHF	Microwave	N25155M2	498705	May 05, 2023	May 04, 2024

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

☒ Test Accessories Come From The Laboratory

Item	Equipment	Model No.	Identifier	Note
1	Adapter	H5	Input: AC 100-240V 50/60Hz, 0.2A Output: DC 8.4V 0.4A	Accessories

☒ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	Digital Two-way Radio	D500	FCC ID: 2AB4FD500	EUT
2	Battery	H5	DC 7.4V 1600mAh	Accessories
3	Back clip	N/A	N/A	Accessories

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	FCC PART 90	Antenna Equipment	Pass
2	§90.205& 2.1046	Maximum Transmitter Power	Pass
3	§90.207& 2.1047	Modulation Characteristic	Pass
4	§2.1047	Audio Low Pass Filter Response	Pass
5	§90.209& 2.1049	Occupied Bandwidth	Pass
6	§90.210& 2.1049	Emission Mask	Pass
7	§90.213& 2.1055	Frequency Tolerance	Pass
8	§90.214	Transmitter Frequency Behavior	Pass
9	§90.210& 2.1051	Spurious Emission on Antenna Port	Pass
10	§90.210& 2.1053	Spurious Radiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5.DESCRPTION OF TEST MODES

The EUT (**Digital Two-way Radio**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

NO.	TEST MODE DESCRIPTION	CHANNEL SEPARATION
1	TX Bottom channel-UHF	12.5 kHz
2	TX Middle channel-UHF	12.5 kHz
3	TX Middle channel-UHF	12.5 kHz
4	TX Top channel-UHF	12.5 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. The battery is full-charged during the test.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
5. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

6.FREQUENCY TOLERANCE

6.1 PROVISIONS APPLICABLE

- According to FCC §2.1055,§90.213, the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 kHz channel separation and 0.0001% for 6.25 kHz channel separation.

6.2 MEASUREMENT PROCEDURE


6.2.1 Frequency stability versus environmental temperature

- Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz. Record this frequency as reference frequency.
- Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 7.4V.
- Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6.4 MEASUREMENT RESULTS

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For UHF-5W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.942	0.653	0.927	0.811	2.5	Pass
	-20	1.006	0.826	0.772	0.638		
	-10	0.546	0.661	0.665	0.662		
	0	0.857	0.706	0.664	0.381		
	10	1.060	1.012	0.667	0.458		
	20	0.876	0.917	0.830	0.564		
	30	0.863	0.880	0.960	0.565		
	40	1.060	0.705	0.705	0.473		
	50	0.743	0.768	1.072	0.643		
8.51	20	1.074	0.762	1.012	0.851		
6.29	20	0.879	0.742	0.791	0.843		

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For UHF-1W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.761	0.661	0.695	0.441	2.5	Pass
	-20	0.916	0.584	0.552	0.648		
	-10	0.584	0.647	0.634	0.547		
	0	0.898	0.637	0.928	0.864		
	10	0.898	0.973	0.979	0.364		
	20	0.504	0.782	1.045	0.952		
	30	0.793	1.098	0.629	0.429		
	40	0.989	0.720	0.546	0.821		
	50	1.064	0.750	1.095	0.881		
8.51	20	0.755	0.679	0.765	0.428		
6.29	20	0.846	0.811	0.786	0.468		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For UHF-5W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.906	0.653	0.529	0.408	2.5	Pass
	-20	0.620	0.774	0.925	0.412		
	-10	0.819	0.727	1.017	0.852		
	0	0.809	0.883	0.509	0.946		
	10	1.083	0.635	0.944	0.385		
	20	0.615	0.631	0.784	0.724		
	30	0.730	0.836	0.833	0.343		
	40	1.099	0.844	1.074	0.851		
	50	0.618	0.605	0.840	0.921		
8.51	20	0.963	1.009	0.926	0.701		
6.29	20	0.947	0.912	0.987	0.965		

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For UHF-1W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	1.077	1.098	0.743	0.509	2.5	Pass
	-20	0.640	1.093	0.595	0.689		
	-10	0.557	0.518	0.955	0.693		
	0	0.612	0.644	0.650	0.358		
	10	1.033	0.594	0.849	0.660		
	20	0.503	0.599	0.754	0.617		
	30	0.673	0.535	0.728	0.971		
	40	0.632	0.969	0.810	0.737		
	50	0.589	0.678	0.610	0.338		
8.51	20	0.794	0.838	0.502	0.821	2.5	Pass
6.29	20	0.528	0.533	0.788	0.322		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7. EMISSION BANDWIDTH

7.1 PROVISIONS APPLICABLE

FCC Part 90.209 & FCC Part 2.1049:

The authorized bandwidth shall be 11.25 kHz for 12.5 kHz channel separation and 6 kHz for 6.25 kHz channel separation.

7.2 MEASUREMENT PROCEDURE

1.The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.

Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).

2.Spectrum set as follow:


Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing, RBW=100Hz, VBW=300Hz, Sweep = auto,

Detector function = peak, Trace = max hold

3.Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.

4.Measure and record the results in the test report.

7.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

7.4 MEASUREMENT RESULTS

Measurement Result of UHF-Analog Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	9.940 kHz	10.16 kHz	11.25 kHz	Pass
453.2125 MHz	9.925 kHz	10.16 kHz	11.25 kHz	Pass
458.2125 MHz	9.934 kHz	10.16 kHz	11.25 kHz	Pass
469.975MHz	9.954 kHz	10.17 kHz	11.25 kHz	Pass


Measurement Result of UHF-Digital Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	6.142 kHz	8.599 kHz	11.25 kHz	Pass
453.2125 MHz	6.287 kHz	8.837 kHz	11.25 kHz	Pass
458.2125 MHz	6.205 kHz	8.879 kHz	11.25 kHz	Pass
469.975MHz	6.147 kHz	8.671 kHz	11.25 kHz	Pass

Measurement Result of UHF-Analog Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	9.942 kHz	10.16 kHz	11.25 kHz	Pass
453.2125 MHz	9.925 kHz	10.16 kHz	11.25 kHz	Pass
458.2125 MHz	9.935 kHz	10.16 kHz	11.25 kHz	Pass
469.975MHz	9.954 kHz	10.17 kHz	11.25 kHz	Pass

Measurement Result of UHF-Digital Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	6.076 kHz	8.317 kHz	11.25 kHz	Pass
453.2125 MHz	6.073 kHz	8.294 kHz	11.25 kHz	Pass
458.2125 MHz	6.271 kHz	9.221 kHz	11.25 kHz	Pass
469.975MHz	6.151 kHz	8.666 kHz	11.25 kHz	Pass


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.5kHz, 4FSK Modulation:458.2125MHz-5W




12.5kHz, 4FSK Modulation:469.975MHz-5W




12.5kHz, FM Modulation:406.125MHz-1W




12.5kHz, FM Modulation:453.2125MHz-1W



12.5kHz, FM Modulation:458.2125MHz-1W



12.5kHz, FM Modulation:469.975MHz-1W




12.5kHz, 4FSK Modulation:406.125MHz-1W


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Testing/Inspection Stamp is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5kHz, 4FSK Modulation:453.2125MHz-1W



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Testing/Inspection Stamp is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



12.5kHz, 4FSK Modulation:458.2125MHz-1W



12.5kHz, 4FSK Modulation:469.975MHz-1W



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8. SPURIOUS RADIATED EMISSION

8.1 PROVISIONS APPLICABLE

According to FCC §2.1053 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

Emission Mask D -for 12.5 kHz Channel Separation:

- (1) On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.


8.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- (16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- (17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.3 MEASUREMENT SETUP

Radiated Emissions 30MHz to 1GHz Test setup



Radiated Emissions Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.4 MEASUREMENT RESULTS

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.


EIRP = "Read Value" + Measured substitution value + 2.15.

Test limit calculation:

Preliminary calculation	Final Result
At least $50 + 10 \log(P) = 50 + 10 \log(5) = 56.99$ (dB)	Limit=P- Preliminary calculation=36.99-56.99=-20 dBm
At least $50 + 10 \log(P) = 50 + 10 \log(1) = 50.00$ (dB)	Limit=P- Preliminary calculation=30.00-50.00=-20 dBm


1. Factor=Antenna Factor + Cable loss. (Below 1GHz)
2. Factor=Antenna Factor+ Cable loss -Pre-amplifier. (Above 1 GHz)
3. Margin=Limit- Level
4. Test data only reflect the highest power level as the worst data

Test Mode:	TX:406.125MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-65.76	-26.57	-20.00	6.57	39.19	262	Horizontal
2	1218.5719	-23.17	-26.37	-20.00	6.37	-3.20	290	Horizontal
3	2030.5781	-29.72	-27.14	-20.00	7.14	2.58	97	Horizontal
4	2437.1687	-32.99	-29.32	-20.00	9.32	3.67	145	Horizontal
5	5686.3686	-34.71	-25.67	-20.00	5.67	9.04	196	Horizontal
6	6091.7842	-36.66	-26.78	-20.00	6.78	9.88	125	Horizontal


Test Mode:	TX:406.125MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-70.66	-31.47	-20.00	11.47	39.19	10	Vertical
2	1218.5719	-27.92	-31.12	-20.00	11.12	-3.20	293	Vertical
3	2030.5781	-26.82	-24.24	-20.00	4.24	2.58	168	Vertical
4	5686.3686	-39.86	-30.82	-20.00	10.82	9.04	104	Vertical
5	6091.7842	-34.89	-25.01	-20.00	5.01	9.88	160	Vertical
6	6498.3748	-43.06	-32.77	-20.00	12.77	10.29	150	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:453.2125MHz-FM	Polarity:	Horizontal
------------	-------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-63.14	-23.98	-20.00	3.98	39.16	258	Horizontal
2	1359.586	-29.40	-32.18	-20.00	12.18	-2.78	292	Horizontal
3	1813.1813	-33.68	-33.00	-20.00	13.00	0.68	50	Horizontal
4	2266.7767	-41.20	-37.99	-20.00	17.99	3.21	60	Horizontal
5	4078.8079	-41.67	-36.42	-20.00	16.42	5.25	42	Horizontal
6	5892.0142	-47.28	-37.75	-20.00	17.75	9.53	100	Horizontal

Test Mode:	TX:453.2125MHz-FM	Polarity:	Vertical
------------	-------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-67.79	-28.63	-20.00	8.63	39.16	351	Vertical
2	1359.586	-29.32	-32.10	-20.00	12.10	-2.78	120	Vertical
3	1813.1813	-33.86	-33.18	-20.00	13.18	0.68	186	Vertical
4	3172.7923	-43.28	-39.95	-20.00	19.95	3.33	176	Vertical
5	4078.8079	-46.53	-41.28	-20.00	21.28	5.25	20	Vertical
6	5892.0142	-48.11	-38.58	-20.00	18.58	9.53	158	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:458.2125MHz-FM	Polarity:	Horizontal
------------	-------------------	-----------	------------



FCC Part 90 OPER TX


Level [dBm]

Frequency [Hz]

— Limit ■ Final Test — Horizontal

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	917.55	-66.97	-27.58	-20.00	7.58	39.39	259	Horizontal
2	1374.8625	-31.35	-34.09	-20.00	14.09	-2.74	285	Horizontal
3	1833.1583	-32.12	-31.24	-20.00	11.24	0.88	18	Horizontal
4	2291.4541	-35.81	-32.53	-20.00	12.53	3.28	36	Horizontal
5	3666.3416	-39.78	-35.63	-20.00	15.63	4.15	341	Horizontal
6	5498.3498	-45.62	-37.02	-20.00	17.02	8.60	194	Horizontal

Test Mode:	TX:458.2125MHz-FM	Polarity:	Vertical
------------	-------------------	-----------	----------



FCC Part 90 OPER TX

Level [dBm]

Frequency [Hz]

— Limit ■ Final Test — Vertical

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	917.55	-68.32	-28.93	-20.00	8.93	39.39	243	Vertical
2	1374.8625	-30.78	-33.52	-20.00	13.52	-2.74	129	Vertical
3	1833.1583	-32.74	-31.86	-20.00	11.86	0.88	129	Vertical
4	2291.4541	-39.40	-36.12	-20.00	16.12	3.28	185	Vertical
5	3208.0458	-41.10	-37.72	-20.00	17.72	3.38	157	Vertical
6	5956.6457	-46.54	-36.85	-20.00	16.85	9.69	147	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:469.975MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	940.83	-68.34	-28.44	-20.00	8.44	39.90	273	Horizontal
2	1410.116	-30.70	-33.33	-20.00	13.33	-2.63	55	Horizontal
3	1880.163	-29.37	-28.03	-20.00	8.03	1.34	93	Horizontal
4	2350.21	-35.82	-32.38	-20.00	12.38	3.44	37	Horizontal
5	5640.5391	-39.42	-30.49	-20.00	10.49	8.93	189	Horizontal
6	6109.4109	-41.41	-31.51	-20.00	11.51	9.90	121	Horizontal

Test Mode:	TX:469.975MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	940.83	-68.80	-28.90	-20.00	8.90	39.90	3	Vertical
2	1410.116	-28.95	-31.58	-20.00	11.58	-2.63	126	Vertical
3	1880.163	-26.58	-25.24	-20.00	5.24	1.34	174	Vertical
4	2350.21	-38.46	-35.02	-20.00	15.02	3.44	202	Vertical
5	5639.3639	-44.00	-35.07	-20.00	15.07	8.93	283	Vertical
6	6109.4109	-38.69	-28.79	-20.00	8.79	9.90	166	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:406.125MHz-4FSK	Polarity:	Horizontal
------------	--------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-69.41	-30.22	-20.00	10.22	39.19	278	Horizontal
2	2030.5781	-28.33	-25.75	-20.00	5.75	2.58	93	Horizontal
3	2437.1687	-33.08	-29.41	-20.00	9.41	3.67	169	Horizontal
4	5686.3686	-35.96	-26.92	-20.00	6.92	9.04	207	Horizontal
5	6091.7842	-35.31	-25.43	-20.00	5.43	9.88	121	Horizontal
6	6498.3748	-39.70	-29.41	-20.00	9.41	10.29	141	Horizontal


Test Mode:	TX:406.125MHz-4FSK	Polarity:	Vertical
------------	--------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-70.82	-31.63	-20.00	11.63	39.19	268	Vertical
2	1625.1625	-32.84	-33.98	-20.00	13.98	-1.14	170	Vertical
3	2030.5781	-27.78	-25.20	-20.00	5.20	2.58	160	Vertical
4	3249.1749	-38.13	-34.70	-20.00	14.70	3.43	170	Vertical
5	5686.3686	-39.95	-30.91	-20.00	10.91	9.04	268	Vertical
6	6091.7842	-34.66	-24.78	-20.00	4.78	9.88	160	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:453.2125MHz-4FSK	Polarity:	Horizontal
------------	---------------------	-----------	------------



FCC Part 90 OPER TX


Level [dBm]

Frequency [Hz]

— Limit ■ Final Test — Horizontal

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-70.02	-30.86	-20.00	10.86	39.16	269	Horizontal
2	1813.1813	-36.69	-36.01	-20.00	16.01	0.68	351	Horizontal
3	3626.3876	-41.11	-37.05	-20.00	17.05	4.06	342	Horizontal
4	5438.4188	-48.03	-39.48	-20.00	19.48	8.55	269	Horizontal
5	5892.0142	-47.21	-37.68	-20.00	17.68	9.53	303	Horizontal
6	6345.6096	-49.28	-39.14	-20.00	19.14	10.14	286	Horizontal

Test Mode:	TX:453.2125MHz-4FSK	Polarity:	Vertical
------------	---------------------	-----------	----------



FCC Part 90 OPER TX

Level [dBm]

Frequency [Hz]

— Limit ■ Final Test — Vertical

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-74.53	-35.37	-20.00	15.37	39.16	359	Vertical
2	1359.586	-42.72	-45.50	-20.00	25.50	-2.78	359	Vertical
3	2510.026	-54.01	-50.18	-20.00	30.18	3.83	116	Vertical
4	4115.2365	-53.69	-48.28	-20.00	28.28	5.41	152	Vertical
5	4765.0765	-54.74	-47.05	-20.00	27.05	7.69	351	Vertical
6	5892.0142	-52.01	-42.48	-20.00	22.48	9.53	359	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:458.2125MHz-4FSK	Polarity:	Horizontal
------------	---------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	917.55	-66.50	-27.11	-20.00	7.11	39.39	300	Horizontal
2	1374.8625	-29.50	-32.24	-20.00	12.24	-2.74	290	Horizontal
3	1833.1583	-26.23	-25.35	-20.00	5.35	0.88	9	Horizontal
4	5498.3498	-38.26	-29.66	-20.00	9.66	8.60	111	Horizontal
5	5956.6457	-37.93	-28.24	-20.00	8.24	9.69	119	Horizontal
6	6414.9415	-40.50	-30.30	-20.00	10.30	10.20	119	Horizontal

Test Mode:	TX:458.2125MHz-4FSK	Polarity:	Vertical
------------	---------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	917.55	-68.42	-29.03	-20.00	9.03	39.39	240	Vertical
2	1374.8625	-28.21	-30.95	-20.00	10.95	-2.74	120	Vertical
3	1833.1583	-25.67	-24.79	-20.00	4.79	0.88	148	Vertical
4	5498.3498	-43.37	-34.77	-20.00	14.77	8.60	168	Vertical
5	5956.6457	-40.91	-31.22	-20.00	11.22	9.69	158	Vertical
6	6414.9415	-46.50	-36.30	-20.00	16.30	10.20	187	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:469.975MHz-4FSK	Polarity:	Horizontal
------------	--------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	940.83	-67.76	-27.86	-20.00	7.86	39.90	276	Horizontal
2	1410.116	-29.72	-32.35	-20.00	12.35	-2.63	55	Horizontal
3	1880.163	-28.49	-27.15	-20.00	7.15	1.34	75	Horizontal
4	2350.21	-35.87	-32.43	-20.00	12.43	3.44	27	Horizontal
5	5639.3639	-37.72	-28.79	-20.00	8.79	8.93	195	Horizontal
6	6109.4109	-38.57	-28.67	-20.00	8.67	9.90	121	Horizontal

Test Mode:	TX:469.975MHz-4FSK	Polarity:	Vertical
------------	--------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	940.83	-67.48	-27.58	-20.00	7.58	39.90	0	Vertical
2	1410.116	-28.00	-30.63	-20.00	10.63	-2.63	136	Vertical
3	1880.163	-25.59	-24.25	-20.00	4.25	1.34	174	Vertical
4	2350.21	-39.19	-35.75	-20.00	15.75	3.44	184	Vertical
5	5639.3639	-42.13	-33.20	-20.00	13.20	8.93	270	Vertical
6	6109.4109	-37.15	-27.25	-20.00	7.25	9.90	156	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


8.5 EMISSION MASK PLOT

The detailed procedure employed for Emission Mask measurements are specified as following:

-Connect the equipment as illustrated.


-Spectrum set as follow:

1. Centre frequency = fundamental frequency, Span=50kHz for 12.5kHz, RBW=100Hz, VBW=300Hz for 12.5kHz, Sweep = auto, Detector function = peak, Trace = max hold
2. Key the transmitter, and set the level of the unmodulated carrier to a fullscale reference line. This is the 0dB reference for the measurement.
3. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing). The input level shall be established at the frequency of maximum response of the audio modulating circuit.
4. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
5. Measure and record the results in the test report.




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Emission Mask D@458.2125MHz-5W-4FSK




Emission Mask D@469.975MHz-5W-4FSK




Emission Mask D@406.125MHz-1W-FM




Emission Mask D@453.2125MHz-1W-FM



Emission Mask D@458.2125MHz-1W-FM



Emission Mask D@469.975MHz-1W-FM



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.