



FCC ID: GKR436386
Report No.: T210730W06-RP1

IC: 2533B-436386

Page: 1 / 20
Rev.: 00

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C

INDUSTRY CANADA RSS-247

| | |
|--------------------------|---|
| Test Standard | FCC Part 15.247 IC RSS-247 issue 2 and IC RSS-GEN issue 5 |
| Product name | Tablet |
| Brand Name | ICON/iFit |
| Model No. | MP10-ARGON2X-C |
| Test Result | Pass |
| Statements of Conformity | Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty. |

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory).

Approved by:

Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T210730W06-RP1

Page: 2 / 20

Rev.: 00

Revision History

| Rev. | Issue Date | Revisions | Effect Page | Revised By |
|------|-------------------|---------------|-------------|--------------|
| 00 | September 8, 2021 | Initial Issue | ALL | Allison Chen |



Report No.: T210730W06-RP1

Page: 3 / 20

Rev.: 00

Table of contents

| | | |
|--|---|-----------|
| 1. | GENERAL INFORMATION | 4 |
| 1.1 | EUT INFORMATION..... | 4 |
| 1.2 | INFORMATION ABOUT THE FHSS CHARACTERISTICS | 5 |
| 1.3 | EUT CHANNEL INFORMATION | 6 |
| 1.4 | ANTENNA INFORMATION | 6 |
| 1.5 | MEASUREMENT UNCERTAINTY..... | 7 |
| 1.6 | FACILITIES AND TEST LOCATION | 8 |
| 1.7 | INSTRUMENT CALIBRATION | 8 |
| 1.8 | SUPPORT AND EUT ACCESSORIES EQUIPMENT | 9 |
| 1.9 | TEST METHODOLOGY AND APPLIED STANDARDS | 9 |
| 2. | TEST SUMMARY | 10 |
| 3. | DESCRIPTION OF TEST MODES..... | 11 |
| 3.1 | THE WORST MODE OF OPERATING CONDITION | 11 |
| 3.2 | THE WORST MODE OF MEASUREMENT | 11 |
| 4. | TEST RESULT | 12 |
| 4.1 | RADIATION SPURIOUS EMISSION | 12 |
| 4.2 | TEST DATA RE-USE SUMMARY | 19 |
| APPENDIX 1 - PHOTOGRAPHS OF EUT | | |



Report No.: T210730W06-RP1

Page: 4 / 20

Rev.: 00

1. GENERAL INFORMATION

1.1 EUT INFORMATION

| | |
|--------------------------|--|
| FCC Applicant | Compal Electronics Inc No.581 & 581-1, Ruiguang Rd., Neihu District, Taipei city, 11492 Taiwan |
| IC Applicant | COMPAL ELECTRONICS INC. No. 581 & 581-1, Ruiguang Rd., Neihu District Taipei R.O.C. 114 Taiwan |
| Manufacturer | Compal Electronics Inc No.581 & 581-1, Ruiguang Rd., Neihu District, Taipei city, 11492 Taiwan |
| Equipment | Tablet |
| Model No. | MP10-ARGON2X-C |
| Model Discrepancy | N/A |
| Trade Name | ICON/iFit |
| Received Date | July 30, 2021 |
| Date of Test | September 1, 2021 |
| Power Operation | EUT Power from Power Supply. (DC12V) |
| HW Version | LA-L521P |
| SW Version | Android 9 |
| EUT Serial # | 425339-PP21D305212 |

Remark:

1. For more details, refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS

1.2.1 Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

1.2.2 Equal Hopping Frequency Use

The channels of this system will be used equally over the long-term distribution of the hopsets.

1.2.3 Example of a 79 hopping sequence in data mode:

02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 16, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 05, 16, 68, 74, 59, 63, 55

1.2.4 System Receiver Input Bandwidth

Each channel bandwidth is 1MHz.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

1.2.5 Equipment Description

RSS-247, 5.1 (a): The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

1.3 EUT CHANNEL INFORMATION

| | |
|-------------------|--|
| Frequency Range | 2402MHz-2480MHz |
| Modulation Type | 1. GFSK for BDR-1Mbps 2. $\pi/4$ -DQPSK for EDR-2Mbps 3. 8DPSK for EDR-3Mbps |
| Number of channel | 79 Channels |

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 and RSS-GEN Table 1 for test channels

| Number of frequencies to be tested | | |
|--|-----------------------|--|
| Frequency range in which device operates | Number of frequencies | Location in frequency range of operation |
| <input type="checkbox"/> 1 MHz or less | 1 | Middle |
| <input type="checkbox"/> 1 MHz to 10 MHz | 2 | 1 near top and 1 near bottom |
| <input checked="" type="checkbox"/> More than 10 MHz | 3 | 1 near top, 1 near middle, and 1 near bottom |

1.4 ANTENNA INFORMATION

| | |
|-------------------|--|
| Antenna Type | <input checked="" type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/> Dipole <input type="checkbox"/> Coils |
| Antenna Gain | 2.47 dBi |
| Antenna Connector | IPEX |

Remark:

1.The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203.



Report No.: T210730W06-RP1

Page: 7 / 20

Rev.: 00

1.5 MEASUREMENT UNCERTAINTY

| PARAMETER | UNCERTAINTY |
|--|-------------|
| AC Powerline Conducted Emission | +/- 1.2575 |
| Emission bandwidth, 20dB bandwidth | +/- 0.0014 |
| RF output power, conducted | +/- 1.14 |
| Power density, conducted | +/- 1.40 |
| 3M Semi Anechoic Chamber / 30M~1G (Horizontally) | +/- 3.91 |
| 3M Semi Anechoic Chamber / 30M~1G (Vertically) | +/- 4.57 |
| 3M Semi Anechoic Chamber / 1G~6G | +/- 5.20 |
| 3M Semi Anechoic Chamber / 6G~18G | +/- 5.18 |
| 3M Semi Anechoic Chamber / 18G~40G | +/- 3.68 |

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.6 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

| Test site | Test Engineer | Remark |
|--------------------|---------------|---|
| AC Conduction Room | N/A | Not applicable, because EUT doesn't connect to AC Main Source direct. |
| Radiation | Ray Li | - |
| RF Conducted | N/A | Not applicable. |

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.7 INSTRUMENT CALIBRATION

| 3M 966 Chamber Test Site | | | | | |
|----------------------------------|-------------------|-----------------------|-----------------|------------|------------|
| Equipment | Manufacturer | Model | S/N | Cal Date | Cal Due |
| Band Reject Filters | MICRO TRONICS | BRM 50702 | 120 | 02/08/2021 | 02/07/2022 |
| Bilog Antenna | Sunol Sciences | JB3 | A030105 | 07/19/2021 | 07/18/2022 |
| Coaxial Cable | HUBER SUHNER | SUCOFLEX 104PEA | 20995 | 02/24/2021 | 02/23/2022 |
| Coaxial Cable | EMCI | EMC105 | 190914+327109/4 | 09/19/2020 | 09/18/2021 |
| Digital Thermo-Hygro Meter | WISEWIND | 1206 | D07 | 01/06/2021 | 01/05/2022 |
| double Ridged Guide Horn Antenna | ETC | MCTD 1209 | DRH13M02003 | 09/30/2020 | 09/29/2021 |
| Horn Antenna | ETS LINDGREN | 3116 | 00026370 | 12/11/2020 | 12/10/2021 |
| K Type Cable | Huber+Suhner | SUCOFLEX 102 | 29406/2 | 12/09/2020 | 12/08/2021 |
| K Type Cable | Huber+Suhner | SUCOFLEX 102 | 22470/2 | 12/09/2020 | 12/08/2021 |
| Pre-Amplifier | EMEC | EM330 | 060609 | 02/24/2021 | 02/23/2022 |
| Pre-Amplifier | HP | 8449B | 3008A00965 | 12/25/2020 | 12/24/2021 |
| Pre-Amplifier | MITEQ | AMF-6F-18004000-37-8P | 985646 | 09/02/2020 | 09/01/2021 |
| Signal Analyzer | R&S | FSV 40 | 101073 | 09/17/2020 | 09/16/2021 |
| Antenna Tower | CCS | CC-A-1F | N/A | N.C.R | N.C.R |
| Controller | CCS | CC-C-1F | N/A | N.C.R | N.C.R |
| Turn Table | CCS | CC-T-1F | N/A | N.C.R | N.C.R |
| Software | e3 6.11-20180419c | | | | |

Remark: Each piece of equipment is scheduled for calibration once a year.



Report No.: T210730W06-RP1

Page: 9 / 20

Rev.: 00

1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT

| EUT Accessories Equipment | | | | | |
|---------------------------|-----------|-------|-------|------------|--------|
| No. | Equipment | Brand | Model | Series No. | FCC ID |
| | N/A | | | | |

| Support Equipment | | | | | |
|-------------------|-----------|--------------|--------------|------------|--------|
| No. | Equipment | Brand | Model | Series No. | FCC ID |
| 1 | Adapter | WEIHAI POWER | HAS060123-EA | N/A | N/A |

1.9 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, RSS-247 Issue 2 and RSS-GEN Issue 5.

2. TEST SUMMARY

| FCC Standard Section | IC Standard Section | Report Section | Test Item | Result |
|----------------------|----------------------|----------------|---|--------|
| 15.203 | RSS-GEN 6.8 | 1.3 | Antenna Requirement | Pass |
| 15.247(d) | RSS-GEN 8.9, 8.10 | 4.1 | Radiation Spurious Emission (Below 1GHz) | Pass |

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

| | |
|--------------------------|---|
| Operation mode | GFSK for BDR-1Mbps (DH5) 8DPSK for EDR-3Mbps (3DH5) |
| Test Channel Frequencies | GFSK for BDR-1Mbps: 1.Lowest Channel: 2402MHz 2.Middle Channel: 2441MHz 3.Highest Channel: 2480MHz 8DPSK for EDR-3Mbps: 1.Lowest Channel: 2402MHz 2.Middle Channel: 2441MHz 3.Highest Channel: 2480MHz |

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

| Radiated Emission Measurement Below 1G | |
|--|--|
| Test Condition | Radiated Emission Below 1G |
| Power supply Mode | Mode 1: EUT power by Power Supply |
| Worst Mode | <input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4 |

Remark:

1. The worst mode was record in this test report.
 2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report

4. TEST RESULT

4.1 RADIATION SPURIOUS EMISSION

4.1.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

| Frequency | Field Strength (microvolts/m) | Magnetic H-Field (microamperes/m) | Measurement Distance (metres) |
|---------------|----------------------------------|---|-------------------------------------|
| 9-490 kHz | 2,400/F (F in kHz) | 2,400/F (F in kHz) | 300 |
| 490-1,705 kHz | 24,000/F (F in kHz) | 24,000/F (F in kHz) | 30 |
| 1.705-30 MHz | 30 | N/A | 30 |

Above 30 MHz

| Frequency (MHz) | Field Strength microvolts/m at 3 metres (watts, e.i.r.p.) | |
|--------------------|--|--------------|
| | Transmitters | Receivers |
| 30-88 | 100 (3 nW) | 100 (3 nW) |
| 88-216 | 150 (6.8 nW) | 150 (6.8 nW) |
| 216-960 | 200 (12 nW) | 200 (12 nW) |
| Above 960 | 500 (75 nW) | 500 (75 nW) |

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

RSS-Gen Table 3 and Table 5 – General Field Strength Limits for Transmitters and Receivers at Frequencies Above 30 MHz ^(Note)

| Frequency (MHz) | Field Strength microvolts/m at 3 metres (watts, e.i.r.p.) | |
|--------------------|--|--------------|
| | Transmitters | Receivers |
| 30-88 | 100 (3 nW) | 100 (3 nW) |
| 88-216 | 150 (6.8 nW) | 150 (6.8 nW) |
| 216-960 | 200 (12 nW) | 200 (12 nW) |
| Above 960 | 500 (75 nW) | 500 (75 nW) |

Note: Measurements for compliance with the limits in table 3 may be performed at distances other than 3 metres, in accordance with Section 6.6.

RSS-Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)

| Frequency | Magnetic field strength (H-Field) (μA/m) | Measurement Distance (m) |
|---------------------------|---|-----------------------------|
| 9-490 kHz ^{Note} | 6.37/F (F in kHz) | 300 |
| 490-1,705 kHz | 63.7/F (F in kHz) | 30 |
| 1.705-30 MHz | 0.08 | 30 |

Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

4.1.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

4. For harmonic, the worst case of output power was BDR-1Mbps. Therefore only BDR-1Mbps record in the report.

5. The SA setting following :

(1) Below 1G : RBW = 100kHz, VBW \geq 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G :

(2.1) For Peak measurement : RBW = 1MHz, VBW \geq 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.


(2.2) For Average measurement : RBW = 1MHz, VBW

·If Duty Cycle \geq 98%, VBW=10Hz.


·If Duty Cycle < 98%, VBW \geq 1/T.

4.1.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



4.1.4 Test Result


Below 1G Test Data

| | | | |
|------------|------------|---------------|-------------------|
| Test Mode: | BT Mode | Temp/Hum | 23.4(°C)/ 60%RH |
| Test Item | 30MHz-1GHz | Test Date | September 1, 2021 |
| Polarize | Vertical | Test Engineer | Ray Li |
| Detector | Peak | | |



| Freq. MHz | Detector Mode PK/QP/AV | Spectrum Reading Level dBμV | Factor dB | Actual FS dBμV/m | Limit @3m dBμV/m | Margin dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 109.54 | Peak | 41.84 | -10.53 | 31.31 | 43.50 | -12.19 |
| 115.36 | Peak | 36.45 | -9.74 | 26.71 | 43.50 | -16.79 |
| 308.39 | Peak | 30.54 | -8.52 | 22.02 | 46.00 | -23.98 |
| 473.29 | Peak | 31.57 | -3.55 | 28.02 | 46.00 | -17.98 |
| 709.00 | Peak | 36.40 | 0.18 | 36.58 | 46.00 | -9.42 |
| 946.65 | Peak | 34.14 | 3.66 | 37.80 | 46.00 | -8.20 |

| | | | |
|------------|------------|---------------|-------------------|
| Test Mode: | BT Mode | Temp/Hum | 23.4(°C)/ 60%RH |
| Test Item | 30MHz-1GHz | Test Date | September 1, 2021 |
| Polarize | Horizontal | Test Engineer | Ray Li |
| Detector | Peak | | |



| Freq. MHz | Detector Mode PK/QP/AV | Spectrum Reading Level dBμV | Factor dB | Actual FS dBμV/m | Limit @3m dBμV/m | Margin dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 83.35 | Peak | 40.94 | -15.86 | 25.08 | 40.00 | -14.92 |
| 160.95 | Peak | 33.54 | -10.60 | 22.94 | 43.50 | -20.56 |
| 301.60 | Peak | 31.44 | -8.75 | 22.69 | 46.00 | -23.31 |
| 473.29 | Peak | 32.34 | -3.55 | 28.79 | 46.00 | -17.21 |
| 757.50 | Peak | 39.80 | 0.90 | 40.70 | 46.00 | -5.30 |
| 946.65 | Peak | 33.39 | 3.66 | 37.05 | 46.00 | -8.95 |

4.2 TEST DATA RE-USE SUMMARY

Introduction Section:

The application re-uses data collected on a similar device. The subject device of this application (Model: MP10-ARGON2X-C, FCC ID: GKR436386, IC: 2533B-436386) is electrically identical to the reference device (Model: MP10-ARGON2-C, FCC ID: GKR425339, IC: 2533B-425339) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01.

Differences Brief Description:

The WLAN and Bluetooth hardware of this device are identical to the implementation in
FCC ID: GKR436386

IC: 2533B-436386

The Product Equality Declaration document includes detailed information about the changes between the devices. The data from that application has been verified through appropriate spot checks to demonstrate compliance for this device as shown in the summary table below.



Report No.: T210730W06-RP1

Page: 20 / 20

Rev.: 00

Spot Check Verification Result Summary

| Equipment Class | Reference FCC ID / IC No. | Folder Test | Report Title/ Section |
|-----------------|---------------------------|----------------|---|
| DSS-BT | GKR425339 / 2533B-425339 | T210413W02-RP1 | All Section (Except for Radiation Spurious Emission below 1GHz) |

Summery of the spot check for Unlicensed bands and Licensed bands

In order to confirm hardware similarity of the subject device with the reference device, we used same setting power to radiated emission measurement were performed on the subject device for the Band edge and Harmonic, the test result were similar with FCC ID: GKR425339 / IC: 2533B-425339.

BT

| Report | Test Item | Mode / CH. | Measured Frequency (MHz) | GKR425339 / 2533B-425339 | | | GKR436386 / 2533B-436386 | | | Gap (dB) | |
|----------|-------------------|------------|--------------------------|--------------------------|---------|-----------|--------------------------|---------|-----------|----------|---------|
| | | | | Peak | Average | Ant. Pol. | Peak | Average | Ant. Pol. | Peak | Average |
| DSS (BT) | Band edge | DH5 / Low | 2390 | 44.1 | 32.74 | H | 43.9 | 32.62 | H | 0.2 | 0.12 |
| | Emission 1G~26.5G | DH5 / Mid | 4882 | 41.21 | - | H | 40.19 | - | H | 1.02 | - |
| | | | 7323 | 45.27 | - | H | 45.25 | - | H | 0.02 | - |

| Report | Test Item | Mode / CH. | Ant. Pol. | Measured Frequency (MHz) | GKR425339 / 2533B-425339 | | Measured Frequency (MHz) | GKR436386 / 2533B-436386 | | Gap (dB) | |
|----------|-----------|------------|-----------|--------------------------|--------------------------|---------|--------------------------|--------------------------|---------|----------|---------|
| | | | | | Peak | Average | | Peak | Average | Peak | Average |
| DSS (BT) | LF | DH5 / Mid | V | 51.34 | 37.81 | - | 946.65 | 37.8 | - | 0.01 | - |

- End of Test Report -