

FCC Test Report

Report No.: AGC11758240103FR01

| FCC ID | : | 2A482-EA10 |
|-----------------------|---|--------------------------------------|
| APPLICATION PURPOSE | : | Original Equipment |
| PRODUCT DESIGNATION | : | Baseus True Wireless Earphones |
| BRAND NAME | : | baseus |
| MODEL NAME | : | Baseus Bowie 30, Baseus Bowie 35 |
| APPLICANT | : | Shenzhen Baseus Technology Co., Ltd. |
| DATE OF ISSUE | : | Mar. 27, 2024 |
| STANDARD(S) | : | FCC Part 15 Subpart C §15.247 |
| REPORT VERSION | : | V1.0 |







Report Revise Record

| Report Version | Report Version Revise Time | | Valid Version | Notes | |
|----------------|----------------------------|---------------|---------------|-----------------|--|
| V1.0 | / | Mar. 27, 2024 | Valid | Initial Release | |



Table of Contents

| 1. General Information | 5 |
|--|----|
| 2. Product Information | 6 |
| 2.1 Product Technical Description | 6 |
| 2.2 Test Frequency List | 6 |
| 2.3 Related Submittal(S) / Grant (S) | 7 |
| 2.4 Test Methodology | 7 |
| 2.5 Receiver Input Bandwidth | 7 |
| 2.6 Equally Average Use of Frequencies And Behaviour | 7 |
| 2.7 Pseudorandom Frequency Hopping Sequence | |
| 2.8 Special Accessories | 9 |
| 2.9 Equipment Modifications | 9 |
| 2.10 Antenna Requirement | 9 |
| 3. Test Environment | |
| 3.1 Address of The Test Laboratory | |
| 3.2 Test Facility | |
| 3.3 Environmental Conditions | 11 |
| 3.4 Measurement Uncertainty | 11 |
| 3.5 List of Equipment Used | |
| 4.System Test Configuration | 14 |
| 4.1 EUT Configuration | |
| 4.2 EUT Exercise | |
| 4.3 Configuration of Tested System | 14 |
| 4.4 Equipment Used in Tested System | 14 |
| 4.5 Summary of Test Results | |
| 5. Description of Test Modes | |
| 6. RF Output Power Measurement | |
| 6.1 Provisions Applicable | |
| 6.2 Measurement Procedure | |
| 6.3 Measurement Setup (Block Diagram of Configuration) | |
| 6.4 Measurement Result | |
| 7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement | |
| 7.1 Provisions Applicable | |
| 7.2 Measurement Procedure | |
| 7.3 Measurement Setup (Block Diagram of Configuration) | |
| 7.4 Measurement Results | |
| 8. Conducted Band Edge and Out-of-Band Emissions | |
| 8.1 Provisions Applicable | |
| 8.2 Measurement Procedure | |
| 8.3 Measurement Setup (Block Diagram of Configuration) | |
| | 07 |



| 9. Radiated Spurious Emission | 57 |
|--|----|
| 9.1 Measurement Limit | 57 |
| 9.2 Measurement Procedure | |
| 9.3 Measurement Setup (Block Diagram of Configuration) | 60 |
| 9.4 Measurement Result | 61 |
| 10. Number of Hopping Frequency Measurement | 72 |
| 10.1 Provisions Applicable | 72 |
| 10.2 Measurement Procedure | 72 |
| 10.3 Measurement Setup (Block Diagram of Configuration) | 72 |
| 10.4 Measurement Result | 72 |
| 11. Time of Occupancy (Dwell Time) Measurement | 74 |
| 11.1 Provisions Applicable | 74 |
| 11.2 Measurement Procedure | 74 |
| 11.3 Measurement Setup (Block Diagram of Configuration) | 74 |
| 11.4 Measurement Result | 74 |
| 12. Frequency Separation Measurement | 78 |
| 12.1 Provisions Applicable | 78 |
| 12.2 Measurement Procedure | 78 |
| 12.3 Measurement Setup (Block Diagram of Configuration) | 78 |
| 12.4 Measurement Result | 78 |
| 13. AC Power Line Conducted Emission Test | 80 |
| 13.1 Measurement Limit | 80 |
| 13.2 Measurement Setup (Block Diagram of Configuration) | 80 |
| 13.3 Preliminary Procedure of Line Conducted Emission Test | |
| 13.4 Final Procedure of Line Conducted Emission Test | 81 |
| 13.5 Measurement Results | |
| Appendix I: Photographs of Test Setup | |
| Appendix II: Photographs of Test EUT | 83 |



1. General Information

| Applicant | Shenzhen Baseus Technology Co., Ltd. |
|------------------------------|--|
| Address | 2nd Floor, Building B, Baseus Intelligence Park, No.2008, Xuegang Rd, Gangtou Community, Bantian Street, Longgang District, Shenzhen, China |
| Manufacturer | Shenzhen Baseus Technology Co., Ltd. |
| Address | 2nd Floor, Building B, Baseus Intelligence Park, No.2008, Xuegang Rd, Gangtou Community, Bantian Street, Longgang District, Shenzhen, China |
| Factory | N/A |
| Address | N/A |
| Product Designation | Baseus True Wireless Earphones |
| Brand Name | baseus |
| Test Model | Baseus Bowie 30 |
| Series Model(s) | Baseus Bowie 35 |
| Difference Description | All the same except for the model name and the charging case plastic appearance and screen printing. |
| Date of receipt of test item | Jan. 15, 2024 |
| Date of Test | Jan. 15, 2024 to Mar. 27, 2024 |
| Deviation from Standard | No any deviation from the test method |
| Condition of Test Sample | Normal |
| Test Result | Pass |
| Test Report Form No | AGCER-FCC-BR_EDR-V1 |
| | |

Note: The test results of this report relate only to the tested sample identified in this report.

Thea Huang Prepared By Thea Huang Mar. 27, 2024 (Project Engineer)

Calvin Liu (Reviewer)

Mar. 27, 2024

Approved By

Reviewed By

Max Zhang (Authorized Officer)

Mar. 27, 2024

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



2. Product Information

2.1 Product Technical Description

| Frequency Band | 2400MHz-2483.5MHz |
|---------------------------|--|
| Operation Frequency Range | 2402MHz-2480MHz |
| Bluetooth Version | V5.3 |
| Modulation Type | BR 🖾 GFSK, EDR 🖾 π /4-DQPSK, 🖾 8DPSK |
| Number of channels | 79 Channels |
| Channel Separation | 1 MHz |
| Maximum Transmitter Power | Left headset: 5.273dBm |
| Hardware Version | V1.1_01 |
| Software Version | V1.0 |
| Antenna Designation | FPC Antenna |
| Antenna Gain | 2.92dBi |
| Power Supply | DC 3.85V by battery or DC 5V by adapter |
| Adapter Information | N/A |
| Note: | |

Note:

The EUT includes left and right channel earphones, the schematic diagram is the same, but the PCB Layout is different. The RF output power and radiated emission below 30MHz of each earphone has been tested and recorded in the report. For other test items, due to the higher power, the left headset has been tested and recorded in this report, which is the worst case.

2.2 Test Frequency List

| Frequency Band | Channel Number | Frequency | | |
|----------------|----------------|--------------|--|--|
| | 0 | 2402 MHz | | |
| | 1 | 2403 MHz | | |
| | : | : 2441MHz | | |
| 2400~2483.5MHz | 39 | | | |
| | : | : | | |
| | 77 | 2479 MHz | | |
| | 78 | 2480 MHz | | |



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2A482-EA10**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

| No. | Identity | Document Title | | | |
|-----|--|---|--|--|--|
| 1 | FCC 47 CFR Part 2 | Frequency allocations and radio treaty matters; general rules and regulations | | | |
| 2 | FCC 47 CFR Part 15 | Radio Frequency Devices | | | |
| 3 | ANSI C63.10-2013 | American National Standard for Testing Unlicensed Wireless Devices | | | |
| 4 | KDB 558074 D01 15.247 Meas Guidance v05r02 | Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules | | | |

2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.6 Equally Average Use of Frequencies And Behaviour

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:


The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

| 4 | 4 | 35 | 78 | 03 | 20 | 76 | 02 | 19 | | 21 | 64 | 75 |
|---|---|----|----|-----|--------|----|----|----|---|--------|----|----|
| Γ | | | | l l | | l | 1 | | | | | |
| | | | | l i | - | | | | | 1 | | |
| | | | | ; | 1 | ; | - | | | i | | |
| L | | | | | _i | | i | | 1 | ¦ | | |

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



2.8 Special Accessories

Not available for this EUT intended for grant.

2.9 Equipment Modifications

Not available for this EUT intended for grant.

2.10 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.92dBi.



3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

| | Normal Conditions |
|-------------------------|-------------------|
| Temperature range (°C) | 15 - 35 |
| Relative humidity range | 20 % - 75 % |
| Pressure range (kPa) | 86 - 106 |
| Power supply | DC 3.85V |

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

| Item | Measurement Uncertainty | | |
|---|----------------------------|--|--|
| Uncertainty of Conducted Emission for AC Port | $U_c = \pm 2.9 \text{ dB}$ | | |
| Uncertainty of Radiated Emission below 1GHz | $U_c = \pm 3.9 \text{ dB}$ | | |
| Uncertainty of Radiated Emission above 1GHz | $U_c = \pm 4.9 \text{ dB}$ | | |
| Uncertainty of total RF power, conducted | $U_c = \pm 0.8 \text{ dB}$ | | |
| Uncertainty of RF power density, conducted | $U_c = \pm 2.6 \text{ dB}$ | | |
| Uncertainty of spurious emissions, conducted | U _c = ±2 % | | |
| Uncertainty of Occupied Channel Bandwidth | U _c = ±2 % | | |



AGC-EM-A139

3.5 List of Equipment Used

| • R | RF Conducted Test System | | | | | | | | |
|-------------|--------------------------|----------------------------------|--------------|------------|------------|------------------------------|------------------------------|--|--|
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | | |
| \boxtimes | AGC-ER-E036 | Spectrum Analyzer | Agilent | N9020A | MY49100060 | 2023-06-01 | 2024-05-31 | | |
| \boxtimes | AGC-ER-E062 | Power Sensor | Agilent | U2021XA | MY54110007 | 2023-03-03 | 2024-03-02 | | |
| \boxtimes | AGC-ER-E062 | Power Sensor | Agilent | U2021XA | MY54110007 | 2024-02-01 | 2025-01-31 | | |
| \boxtimes | AGC-ER-E063 | Power Sensor | Agilent | U2021XA | MY54110009 | 2023-03-03 | 2024-03-02 | | |
| | AGC-ER-E063 | Power Sensor | Agilent | U2021XA | MY54110009 | 2024-02-01 | 2025-01-31 | | |
| \boxtimes | AGC-EM-A152 | 6dB Attenuator | Eeatsheep | LM-XX-6-5W | N/A | 2023-06-09 | 2024-06-08 | | |
| | N/A | RF Connection Cable | N/A | 1# | N/A | Each time | N/A | | |
| \boxtimes | N/A | RF Connection Cable | N/A | 2# | N/A | Each time | N/A | | |
| ● R | adiated Spuric | ous Emission | | | | | | | |
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | | |
| \boxtimes | AGC-EM-E046 | EMI Test Receiver | R&S | ESCI | 10096 | 2023-02-18 | 2024-02-17 | | |
| \boxtimes | AGC-EM-E046 | EMI Test Receiver | R&S | ESCI | 10096 | 2024-02-01 | 2025-01-31 | | |
| | AGC-EM-E116 | EMI Test Receiver | R&S | ESCI | 100034 | 2023-06-03 | 2024-06-02 | | |
| \boxtimes | AGC-EM-E061 | Spectrum Analyzer | Agilent | N9010A | MY53470504 | 2023-06-01 | 2024-05-31 | | |
| \boxtimes | AGC-EM-E086 | Loop Antenna | ZHINAN | ZN30900C | 18051 | 2022-03-12 | 2024-03-11 | | |
| | AGC-EM-E086 | Loop Antenna | ZHINAN | ZN30900C | 18051 | 2024-03-05 | 2026-03-04 | | |
| | AGC-EM-E001 | Wideband Antenna | SCHWARZBECK | VULB9168 | D69250 | 2023-05-11 | 2025-05-10 | | |
| \boxtimes | AGC-EM-E029 | Broadband Ridged Horn Antenna | ETS | 3117 | 00034609 | 2023-03-23 | 2025-03-22 | | |
| | AGC-EM-E082 | | SCHWARZBECK | BBHA 9170 | #768 | 2023-09-24 | 2025-09-23 | | |
| | AGC-EM-E146 | Pre-amplifier | ETS | 3117-PA | 00246148 | 2022-08-04 | 2024-08-03 | | |
| \boxtimes | AGC-EM-A119 | 2.4G Filter | SongYi | N/A | N/A | 2023-06-01 | 2024-05-31 | | |
| | AGC-EM-A138 | 6dB Attenuator | Eeatsheep | LM-XX-6-5W | N/A | 2023-06-09 | 2024-06-08 | | |
| | | | | 1 | 1 | 1 | | | |

| AC Power Line Conducted Emission | | | | | | | | | |
|----------------------------------|---------------|-------------------|--------------|------------|------------|------------------------------|------------------------------|--|--|
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | | |
| | AGC-EM-E045 | EMI Test Receiver | R&S | ESPI | 101206 | 2023-06-03 | 2024-06-02 | | |
| | AGC-EM-E023 | AMN | R&S | 100086 | ESH2-Z5 | 2023-06-03 | 2024-06-02 | | |
| | AGC-EM-A130 | 6dB Attenuator | Eeatsheep | LM-XX-6-5W | DC-6GZ | 2023-06-09 | 2024-06-08 | | |

Eeatsheep

LM-XX-6-5W

N/A

2023-06-09

2024-06-08

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

6dB Attenuator



| Test Software | | | | | | | | |
|---------------|---------------|---------------------|--------------|----------------------|---------------------|--|--|--|
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Version Information | | | |
| | AGC-EM-S001 | CE Test System | R&S | ES-K1 | V1.71 | | | |
| | AGC-EM-S003 | RE-Test System | FARA | EZ-EMC | VRA-03A | | | |
| \boxtimes | AGC-ER-S012 | BT/WIFI-Test System | Tonscend | JS1120-2 | 2.6 | | | |
| \square | AGC-EM-S011 | RSE Test System | Tonscend | TS+-Ver2.1(JS36-RSE) | 4.0.0.0 | | | |



4.System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement: Test Accessories Come From The Laboratory

| No. | Equipment | Model No. | Manufacturer | Specification Information | Cable | | | |
|-----|-------------|-----------|--------------|---------------------------|-------|--|--|--|
| 1 | Control Box | USB-TTL | | | | | | |

Test Accessories Come From The Manufacturer

| No. | Equipment | Model No. | Manufacturer | Specification Information | Cable |
|-----|--------------------------------------|--------------------|---|---------------------------|-------|
| 1 | Baseus True Wireless Earphones | Baseus Bowie 30 | Shenzhen Baseus Technology Co., Ltd. | 2A482-EA10 | |



4.5 Summary of Test Results

| Item | FCC Rules | Description of Test | Result |
|------|----------------------|---|----------------|
| 1 | §15.203&15.247(b)(4) | Antenna Equipment | Pass |
| 2 | §15.247 (b)(1) | RF Output Power | Pass |
| 3 | §15.247 (a)(1) | 20 dB Bandwidth | Pass |
| 4 | §15.247 (d) | Conducted Band Edge and Out-of-Band Emissions | Pass |
| 5 | §15.209 | Radiated Spurious Emission | Pass |
| 6 | §15.247 (a)(1)(iii) | Number of Hopping Frequency | Pass |
| 7 | §15.247 (a)(1)(iii) | Time of Occupancy | Pass |
| 8 | §15.247 (a)(1) | Frequency Separation | Pass |
| 9 | §15.207 | AC Power Line Conducted Emission | Not applicable |

Note: The BT function cannot transmit when charging.



5. Description of Test Modes

| Summary table of Test Cases | | | | |
|------------------------------------|---|--|--|--|
| Test Item | Data Rate / Modulation | | | |
| iest nem | Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK) | | | |
| Radiated & Conducted Test Cases | Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (Battery powered) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (Battery powered) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (Battery powered) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (Battery powered) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (Battery powered) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered) Mode 6: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered) Mode 7: Bluetooth Tx CH00_2402 MHz_3Mbps (Battery powered) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered) Mode 10: Bluetooth Tx Hopping-1Mbps (Battery powered) Mode11: Bluetooth Tx Hopping-2Mbps (Battery powered) Mode12: Bluetooth Tx Hopping-3Mbps (Battery powered) | | | |
| AC Conducted Emission | Not applicable | | | |

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. 3. 4. The battery is full-charged during the test.
- For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting Diagram

| BT_Tool | | | | Ξ Σ | 3 |
|-----------------------------------|------------|--------------|------|-----|----|
| COMx Baudrate | | | | | |
| Classic BLE | | | | | |
| Test Mode | | | | | - |
| FCC Test 🔘 | BT address | | | | |
| DUT Test 🖱 | 5555555555 | 55 | Stop | | |
| RF Control | | | | | |
| RF Mode TX TE | ST 🔹 | Packet Type | DH5 | • | |
| Hopping OFF | • | TX Frequency | 2480 | • | |
| TX Power 7 | | RX Frequency | | + | |
| Scenario PRBS | Pattern | | | • | |
| | | | | | |
| LOG: BR/EDR Test | | | | ^ | • |
| LOG: Test end LOG: BR/EDR Test | | | | | |
| LOG: Test end | | | | | |
| LOG: BR/EDR Test | | | | | |
| LOG: Test end | | | | 13 | 1 |
| LOG: BR/EDR Test | | | | E | |
| COM9 is open | 150 | 0000bps | | | -+ |



6. RF OUTPUT POWER MEASUREMENT

6.1 Provisions Applicable

The maximum out power permissible output power is 1 Watt for all frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

The maximum out power permissible output power is 0.125 watts for all other frequency hopping systems in the 2400-2483.5 MHz band.

6.2 Measurement Procedure

⊠For Peak power test:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW \geq RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

\boxtimes For Average power test:

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required


6.3 Measurement Setup (Block Diagram of Configuration)

 \boxtimes For Average power test setup





\boxtimes For peak power test setup



6.4 Measurement Result

Left headset:

| Test Data of Conducted Output Power | | | | | | | |
|-------------------------------------|-------------------------|---------------------|-----------------|--------------|--|--|--|
| Test Mode | Test Frequency (MHz) | Peak Power (dBm) | Limits (dBm) | Pass or Fail | | | |
| | 2402 | 4.946 | ≤21 | Pass | | | |
| GFSK | 2441 | 4.744 | ≤21 | Pass | | | |
| | 2480 | 5.165 | ≤21 | Pass | | | |
| | 2402 | 4.949 | ≤21 | Pass | | | |
| π /4-DQPSK | 2441 | 4.744 | ≤21 | Pass | | | |
| | 2480 | 5.260 | ≤21 | Pass | | | |
| | 2402 | 4.994 | ≤21 | Pass | | | |
| 8DPSK | 2441 | 4.773 | ≤21 | Pass | | | |
| | 2480 | 5.273 | ≤21 | Pass | | | |

Test Result of Average Output Power (Reporting Only)

| Test Data of Conducted Output Power | | | | | | |
|-------------------------------------|-------------------------|------------------------|-----------------|--------------|--|--|
| Test Mode | Test Frequency (MHz) | Average Power (dBm) | Limits (dBm) | Pass or Fail | | |
| | 2402 | 2.862 | ≤21 | Pass | | |
| GFSK | 2441 | 2.635 | ≤21 | Pass | | |
| | 2480 | 3.214 | ≤21 | Pass | | |
| | 2402 | 2.749 | ≤21 | Pass | | |
| π /4-DQPSK | 2441 | 2.659 | ≤21 | Pass | | |
| | 2480 | 3.124 | ≤21 | Pass | | |
| | 2402 | 2.883 | ≤21 | Pass | | |
| 8DPSK | 2441 | 2.659 | ≤21 | Pass | | |
| | 2480 | 3.230 | ≤21 | Pass | | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., LtdAttestation of Global Compliance(Shenzhen)Std & Tech Co., LtdTel: +86-755 2523 4088E-mail: agc@agccert.comWeb: http://www.agccert.com/






Test Graphs of Conducted Output Power

























Right headset:

| Test Data of Conducted Output Power | | | | | | |
|-------------------------------------|-------------------------|---------------------|-----------------|--------------|--|--|
| Test Mode | Test Frequency (MHz) | Peak Power (dBm) | Limits (dBm) | Pass or Fail | | |
| | 2402 | 4.198 | ≤21 | Pass | | |
| GFSK | 2441 | 3.869 | ≤21 | Pass | | |
| | 2480 | 4.249 | ≤21 | Pass | | |
| | 2402 | 4.105 | ≤21 | Pass | | |
| π /4-DQPSK | 2441 | 3.931 | ≤21 | Pass | | |
| | 2480 | 4.319 | ≤21 | Pass | | |
| | 2402 | 4.175 | ≤21 | Pass | | |
| 8DPSK | 2441 | 3.937 | ≤21 | Pass | | |
| | 2480 | 4.309 | ≤21 | Pass | | |

Test Result of Average Output Power (Reporting Only)


| Test Data of Conducted Output Power | | | | | | |
|-------------------------------------|-------------------------|------------------------|-----------------|--------------|--|--|
| Test Mode | Test Frequency (MHz) | Average Power (dBm) | Limits (dBm) | Pass or Fail | | |
| | 2402 | 2.104 | ≤21 | Pass | | |
| GFSK | 2441 | 1.638 | ≤21 | Pass | | |
| | 2480 | 2.214 | ≤21 | Pass | | |
| | 2402 | 2.058 | ≤21 | Pass | | |
| π /4-DQPSK | 2441 | 1.869 | ≤21 | Pass | | |
| | 2480 | 2.251 | ≤21 | Pass | | |
| | 2402 | 2.114 | ≤21 | Pass | | |
| 8DPSK | 2441 | 1.847 | ≤21 | Pass | | |
| | 2480 | 2.236 | ≤21 | Pass | | |






Test Graphs of Conducted Output Power




















7. 20DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH MEASUREMENT

7.1 Provisions Applicable


There is no corresponding limit requirement for this test item.

7.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 6.9.2 (20dB BW).

- The 20dB bandwidth spectrum analyzer setting reference is as follows:
- 1. Set RBW ≥ 1% to 5% of the 20dB bandwidth
- 2. VBW = Approximately three times RBW
- 3. Span = Approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated
- 9. with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20
- 10. dB relative to the maximum level in the fundamental emission.
- The 99% bandwidth spectrum analyzer setting reference is as follows:
- 1. Span = 1.5 times to 5 times the OBW
- 2. Set RBW = 1% to 5% the OBW
- 3. VBW \geq 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace was allowed to stabilize

7.3 Measurement Setup (Block Diagram of Configuration)






7.4 Measurement Results

| Test Data of Occupied Bandwidth and -20dB Bandwidth | | | | | | | |
|---|-------------------------|---------------------------------|--------------------------|--------|--------------|--|--|
| Test Mode | Test Frequency (MHz) | 99% Occupied Bandwidth (MHz) | -20dB Bandwidth (MHz) | Limits | Pass or Fail | | |
| | 2402 | 0.844 | 0.939 | N/A | Pass | | |
| GFSK | 2441 | 0.855 | 0.938 | N/A | Pass | | |
| | 2480 | 0.857 | 0.940 | N/A | Pass | | |
| | 2402 | 1.110 | 1.178 | N/A | Pass | | |
| π /4-DQPSK | 2441 | 1.111 | 1.178 | N/A | Pass | | |
| | 2480 | 1.113 | 1.178 | N/A | Pass | | |
| | 2402 | 1.114 | 1.187 | N/A | Pass | | |
| 8DPSK | 2441 | 1.116 | 1.184 | N/A | Pass | | |
| | 2480 | 1.117 | 1.188 | N/A | Pass | | |

Test Graphs of Occupied Bandwidth and -20 Bandwidth





















8. CONDUCTED BAND EDGE AND OUT-OF-BAND EMISSIONS

8.1 Provisions Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.10.4 and 7.8.8:


- Reference level measurement
- 1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- Emission level measurement
- 1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Trace was allowed to stabilize
- 8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands







































































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands
























9. RADIATED SPURIOUS EMISSION

9.1 Measurement Limit

15.209 Limit in the below table has to be followed

| Frequencies | Field Strength | Measurement Distance |
|-------------|--------------------|----------------------|
| (MHz) | (microvolts/meter) | (meters) |
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

9.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average

Any rerabsolute voltage during a Oph second interval during which the field strength is easy its maximum values tion Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the guasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

| Spectrum Parameter | Setting |
|-----------------------|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |
| Start ~Stop Frequency | 1GHz~26.5GHz |
| | 1MHz/3MHz for Peak, 1MHz/3MHz for Average |

The following table is the setting of spectrum analyzer and receiver.

| Receiver Parameter | Setting |
|-----------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

• Average Measurements above 1GHz (Method VB)


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle \ge 98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW \geq 1/T. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize




9.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



9.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported. **Left headset:**

| EUT Name Baseus True Wireless Earphones Model Name Baseus Bowie 30 Temperature 23.4 °C Relative Humidity 58.7% Pressure 960hPa Test Voltage Normal Voltage Test Mode Mode 9 Antenna Polarity Horizontal 72.0 dtiw/m Limit Magin: | | Radiated Emission Test Results at 30MHz-1GHz | | | | | | | | | |
|---|---------|--|--------------------------------|---|------------------|------------------------------------|---|-------------------|-------------|--------------|------------|
| Pressure 960hPa Test Voltage Normal Voltage Test Mode Mode 9 Antenna Polarity Horizontal Image: Test Woltage Mode 9 Image: Test Voltage Horizontal Image: Test Woltage Horizontal Image: Test Voltage Image: Test Voltage <th>EUT N</th> <th>ame</th> <th colspan="5">Baseus True Wireless Earphones</th> <th>Model Na</th> <th>me</th> <th>Baseus Bo</th> <th>owie 30</th> | EUT N | ame | Baseus True Wireless Earphones | | | | | Model Na | me | Baseus Bo | owie 30 |
| Test Mode Mode 9 Antenna Polarity Horizontal 720 dbuV/m | Tempe | erature | 23.4℃ | | | | | Relative Humidity | | 58.7% | |
| Final Data List Margin [MHz] Limit [Margin [MB]] Angle [P] Polarity [M] 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.3 100 170 Horizontal | Pressu | ure | 960 | hPa | | | | Test Volta | ige | Normal Vo | ltage |
| Final Data List Freq. [MHz] Level [GB] Factor [GB] Limit (HHz) Margin (GB) Height (CT) Angle (CT) Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.83 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.3 100 170 Horizontal | Test M | ode | Мос | le 9 | | | | Antenna I | Polarity | Horizontal | |
| Final Data Level (MHz) Factor (MHz) Limit (dB) Margin (dB) Height (cm) Angle (f) Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 14.39 100 260 Horizontal 4 607.7867 31.61 25.14 46.00 14.3 100 170 Horizontal | | 72.0 dBuV/m | | | | | | | | | |
| Final Data List Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB]V/m] Margin [dB] Height [Cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 14.39 100 260 Horizontal 4 607.7867 31.61 25.14 46.00 14.3 100 170 Horizontal | | | | | | | | | | | |
| Final Data List Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB]V/m] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | | | | | | | | | | |
| Final Data List Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB]V/m] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | | | | | | | | | F | |
| Final Data List Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB]V/m] Margin [dB] Height [Cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 14.39 100 260 Horizontal 4 607.7867 31.61 25.14 46.00 14.3 100 170 Horizontal | | | | | | | | | | | |
| Final Data List Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB]V/m] Margin [dB] Height [Cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 14.39 100 260 Horizontal 4 607.7867 31.61 25.14 46.00 14.3 100 170 Horizontal | | | | | | | _ | | 3 | × | |
| Final Data List Factor Limit Margin Height Angle Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.33 100 170 Horizontal | | 32 | | | | | | | , Au mart | way was and | |
| Image: Second | | | | 1 | 1. and the lines | 2 | | a well and well | Want ma | | |
| 30.000 40 50 60 70 80 (MHz) 300 400 500 600 700 1000.000 Final Data List NO. Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | السم | How when here and here | door the consignificant property with the | muhana | and the strategic to see the state | 411 har 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 / 1 | Malater | | | |
| 30.000 40 50 60 70 80 (MHz) 300 400 500 600 700 1000.000 Final Data List NO. Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | | | | | | | | | | |
| 30.000 40 50 60 70 80 (MHz) 300 400 500 600 700 1000.000 Final Data List NO. Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | | | | | | | | | | |
| Final Data List NO. Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dB]V/m] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | -8 | | | | | | | | | |
| NO. Freq. [MHz] Level [dBµV/m] Factor [dB] Limit [dBµV/m] Margin [dB] Height [cm] Angle [°] Polarity 1 43.8119 20.67 13.63 40.00 19.33 100 150 Horizontal 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | | 30.00 |)0 4 | 0 50 60 70 | 80 | (MHz) | | 300 | 400 500 600 | 0 700 1000.0 | DO |
| NO. [MHz] [dBµV/m] [dB] [dBµV/m] [dB] [dB] [dB] [dB] [cm] [order red red red red red red red red red | Final D | ata List | | | | | | | | | |
| 2 127.6645 22.99 15.94 43.50 20.51 100 120 Horizontal 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | NO. | | | | | | 1 | | - | | Polarity |
| 3 443.2943 32.94 24.98 46.00 13.06 100 100 Horizontal 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | 1 | 43.811 | 9 | 20.67 | 13.63 | 40.00 | | 19.33 | 100 | 150 | Horizontal |
| 4 607.7867 31.61 25.14 46.00 14.39 100 260 Horizontal 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | 2 | 127.66 | 45 | 22.99 | 15.94 | 43.50 | | 20.51 | 100 | 120 | Horizontal |
| 5 682.3484 31.70 24.63 46.00 14.3 100 170 Horizontal | 3 | 443.29 | 43 | 32.94 | 24.98 | 46.00 | | 13.06 | 100 | 100 | Horizontal |
| | 4 | 607.78 | 67 | 31.61 | 25.14 | 46.00 | | 14.39 | 100 | 260 | Horizontal |
| | 5 | 682.34 | 84 | 31.70 | 24.63 | 46.00 | | 14.3 | 100 | 170 | Horizontal |
| 6 887.6099 36.90 30.25 46.00 9.1 100 150 Horizontal | 6 | 887.60 | 99 | 36.90 | 30.25 | 46.00 | | 9.1 | 100 | 150 | Horizontal |



| | Radiated Emission Test Results at 30MHz-1GHz | | | | | | | | | |
|---------|--|-------------------|----------------|---|----------------|------------------------|-----------------------|----------|--|--|
| EUT N | ame Ba | aseus True Wirele | ess Earpho | ones | Model Na | me | Baseus Bo | owie 30 | | |
| Tempe | erature 23 | 3.4 ℃ | | | Relative H | Relative Humidity58.7% | | | | |
| Pressu | u re 96 | 60hPa | | | Test Volta | ige | Normal Vo | ltage | | |
| Test M | lode Mo | ode 9 | | | Antenna | Polarity | Vertical | | | |
| | 72.0 dBu∀/m | | | | | | | | | |
| | 32 | | | Hurring and a second | | | Limit: — Margin: — | | | |
| | -8 30.000 | 40 50 60 70 | 80 | (MHz) | 300 | 400 500 60 | 0 700 1000.00 | 00 | | |
| Final D | Data List | | | | | | | | | |
| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity | | |
| 1 | 48.8429 | 25.69 | 16.99 | 40.00 | 14.31 | 100 | 180 | Vertical | | |
| 2 | 59.8588 | 25.33 | 17.10 | 40.00 | 14.67 | 100 | 160 | Vertical | | |
| 3 | 66.2661 | 25.01 | 17.04 | 40.00 | 14.99 | 100 | 200 | Vertical | | |
| 4 | 441.7425 | 31.32 | 26.02 | 46.00 | 14.68 | 100 | 240 | Vertical | | |
| 5 | 721.7259 | 35.36 | 28.64 | 46.00 | 10.64 | 100 | 110 | Vertical | | |
| 6 | 952.0937 | 36.64 | 30.52 | 46.00 | 9.36 | 100 | 130 | Vertical | | |

RESULT: Pass



Right headset:

| | Radiated Emission Test Results at 30MHz-1GHz | | | | | | | | | |
|----------|--|-------------------|----------------|---|----------------|----------------|-----------------------|------------|--|--|
| EUT Na | ame l | Baseus True Wirel | ess Earpho | ones | Model Na | me | Baseus Bo | owie 30 | | |
| Tempe | rature | 23.4℃ | | | Relative H | lumidity | 58.7% | | | |
| Pressu | re 🤅 | 960hPa | | | Test Volta | ige | Normal Vo | ltage | | |
| Test Mo | ode | Mode 9 | | | Antenna I | Polarity | Horizontal | | | |
| | 72.0 dBuV/m | | | | | | | | | |
| | | | | | | | .imit: — Aargin: — | | | |
| Final Da | -8 30.000 | 40 50 60 70 | 80 | аланананананананананананананананананана | 300 | 400 500 600 | |)0 | | |
| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity | | |
| 1 | 45.6948 | | 13.50 | 40.00 | 19.2 | 100 | 140 | Horizontal | | |
| 2 | 100.9338 | 8 23.75 | 16.21 | 43.50 | 19.75 | 100 | 160 | Horizontal | | |
| 3 | 132.2204 | 4 23.11 | 15.67 | 43.50 | 20.39 | 100 | 130 | Horizontal | | |
| 4 | 196.5098 | 8 21.58 | 14.10 | 43.50 | 21.92 | 100 | 220 | Horizontal | | |
| 5 | 455.9057 | 7 29.45 | 24.54 | 46.00 | 16.55 | 100 | 140 | Horizontal | | |
| 6 | 827.4932 | 2 34.74 | 27.15 | 46.00 | 11.26 | 100 | 110 | Horizontal | | |



| Radiated Emission Test Results at 30MHz-1GHz | | | | | | | | | |
|--|----------------------------|-------------------|----------------|----------|----------------|----------------------------|-----------------------|----------|--|
| EUT Name | Bas | seus True Wirele | ess Earpho | ones | Model | Name | Baseus Bo | owie 30 | |
| Temperatur | 'e 23. | 4 °C | | | Relati | ve Humidity | 58.7% | | |
| Pressure | 960 |)hPa | | | Test V | oltage | Normal Vo | oltage | |
| Test Mode | Мо | de 9 | | | Anten | na Polarity | Vertical | | |
| | /2.0 dBuV/ | m | | | | | | | |
| | | | | | | | Limit: — Margin: — | | |
| -8 | | 40 50 60 70 | 80 | (MHz) | 300 | kelvedaren Karren gerenten | | 00 | |
| Final Data L | | | Factor | Limit | Morgin | Hoight | Anglo | | |
| | ⁻ req. ∕IHz] | Level [dBµV/m] | Factor [dB] | [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity | |
| 1 48 | .6719 | 23.92 | 16.99 | 40.00 | 16.08 | 100 | 150 | Vertical | |
| 2 127 | 7.2176 | 25.71 | 17.88 | 43.50 | 17.79 | 100 | 200 | Vertical | |
| 3 44 | 1.7425 | 31.73 | 26.02 | 46.00 | 14.27 | 100 | 250 | Vertical | |
| 4 599 | 9.3212 | 34.08 | 26.08 | 46.00 | 11.92 | 100 | 210 | Vertical | |
| 5 649 | 9.6597 | 35.05 | 26.83 | 46.00 | 10.95 | 100 | 180 | Vertical | |
| 6 955 | 5.4380 | 35.93 | 30.38 | 46.00 | 10.07 | 100 | 150 | Vertical | |

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Level.

2. All test modes had been pre-tested. The mode 9 is the worst case and recorded in the report.



| EUT Name | Baseus True | e Wireless Ea | rphones | Model Name | | Baseu | Baseus Bowie 30 | | |
|---|-----------------------------------|------------------------------|-----------------------------------|-------------------|----------------------------|------------------------------------|---------------------|--|--|
| Temperature | 23.4 ℃ | | | Relati | ive Humidity | 58.7% | 58.7% | | |
| Pressure | 960hPa | | | Test Voltage | | Norma | al Voltage | | |
| Fest Mode | Mode 7 | | | Anter | nna Polarity | Horizo | ntal | | |
| | | | | | | | | | |
| Frequency | Meter Reading | Factor | Emission | sion Level Limits | | Margin | Value Type | | |
| (MHz) | (dBµV) | (dB) | (dBµV/ | m) | (dBµV/m) | (dB) | value Type | | |
| 4804.000 | 46.25 | 0.08 | 46.33 | 3 | 74 | -27.67 | peak | | |
| 4804.000 | 36.47 | 0.08 | 36.55 | 5 | 54 | -17.45 | AVG | | |
| 7206.000 | 42.12 | 2.21 | 44.33 | 3 | 74 | -29.67 | peak | | |
| 7206.000 | 31.83 | 2.21 | 34.04 | 4 | 54 | -19.96 | AVG | | |
| | | | | | | | | | |
| Remark: | | | | | | | | | |
| Factor = Anter | nna Factor + Cab | le Loss – Pre- | amplifier. | | | | | | |
| EUT Name | Baseus True | e Wireless Ea | rphones | Mode | I Name | Baseu | s Bowie 30 | | |
| Temperature | 23.4 ℃ | | | Relati | ive Humidity | 58.7% | | | |
| Pressure | 960hPa | | | Test \ | /oltage | Norma | al Voltage | | |
| Test Mode | Mode 7 | | | Anter | nna Polarity | Vertica | al | | |
| | | | | | | | 1 | | |
| Frequency | Meter Reading | Factor | Emission | Level | Limits | Margin | | | |
| Frequency (MHz) | Meter Reading (dBµV) | Factor (dB) | | | | Margin (dB) | Value Type | | |
| | Meter Reading (dBµV) 46.63 | | Emission (dBµV/ 46.71 | m) | Limits (dBµV/m) 74 | - | Value Type | | |
| (MHz) | (dBµV) | (dB) | (dBµV/ | m) 1 | (dBµV/m) | (dB) | | | |
| (MHz) 4804.000 | (dBµV) 46.63 | (dB) 0.08 | (dBµV/ 46.71 | m) 1 2 | (dBµV/m) 74 | (dB) -27.29 | peak | | |
| (MHz) 4804.000 4804.000 | (dBµV) 46.63 36.74 | (dB) 0.08 0.08 | (dBµV/ 46.71 36.82 | m) 1 2 9 | (dBµV/m) 74 54 | (dB) -27.29 -17.18 | peak AVG | | |
| (MHz) 4804.000 4804.000 7206.000 | (dBµV) 46.63 36.74 42.58 | (dB) 0.08 0.08 2.21 | (dBµV/ 46.71 36.82 44.75 | m) 1 2 9 | (dBµV/m) 74 54 74 | (dB) -27.29 -17.18 -29.21 | peak AVG peak | | |
| (MHz) 4804.000 4804.000 7206.000 | (dBµV) 46.63 36.74 42.58 | (dB) 0.08 0.08 2.21 | (dBµV/ 46.71 36.82 44.75 | m) 1 2 9 | (dBµV/m) 74 54 74 | (dB) -27.29 -17.18 -29.21 | peak AVG peak | | |

Radiated Emissions Test Results Above 1 GHz

RESULT: Pass



| EUT Name | Baseus True Wireless Earphones | | | | | l Name | | Baseu | s Bowie 30 | |
|------------------|--------------------------------|---------------|---------------|----------------|------------------|----------|-------|-----------------|------------|----------|
| Temperature | | 23.4 ℃ | | | Relat | ive Humi | dity | 58.7% | | |
| Pressure | | 960hPa | | | Test | Voltage | | Normal Voltage | | |
| Test Mode Mode 8 | | | | | Antenna Polarity | | | Horizo | Horizontal | |
| | | | | | | | | | | |
| Frequen | су | Meter Reading | Facto | r Emissio | n Level | Limits | | Margin | Value Type | <u> </u> |
| (MHz) | | (dBµV) | (dB) | (dBµ\ | //m) | (dBµV/m | 1) | (dB) | value Type | , |
| 4882.00 | 0 | 45.74 | 0.14 | 45.8 | 38 | 74 | | -28.12 | peak | |
| 4882.00 | 0 | 37.59 | 0.14 | 37.7 | 73 | 54 | | -16.27 | AVG | |
| 7323.00 | 0 | 42.63 | 2.36 | 44.9 | 99 | 74 | | -29.01 | peak | |
| 7323.00 | 0 | 33.45 | 2.36 | 35.8 | 31 | 54 | | -18.19 | AVG | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| Remark: | | | | | | | | | | |
| Factor = A | ntenna | Factor + Ca | able Loss – I | Pre-amplifier. | | | | | | |
| EUT Name | | Baseus Tr | ue Wireless | s Earphones | Mode | I Name | | Baseus Bowie 30 | | |
| Temperature | | 23.4 ℃ | | | Relat | ive Humi | dity | 58.7% | | |
| Pressure | | 960hPa | | | Test | Voltage | | Norma | I Voltage | |
| Test Mode | | Mode 8 | | | Anter | nna Pola | rity | Vertica | I | |
| Frequency | Motor | Reading | Factor | Emission Lev | | Limits | Margi | n | | |
| (MHz) | _ | dBµV) | (dB) | (dBµV/m) | | IBµV/m) | (dB) | | Value Type | |
| 4882.000 | · · | 15,89 | 0.14 | 46.03 | | 74 | -27.9 | | peak | |
| 4882.000 | 1 | 37.46 | 0.14 | 37.6 | | 54 | -27.9 | | AVG | |
| 7323.000 | - | 12.12 | 2.36 | 44.48 | | 74 | -29.5 | | peak | |
| 7323.000 | | 32.36 | 2.36 | 34.72 | | 54 | -19.2 | | AVG | |
| | | | 2.30 | | | | 10.2 | - | - | |
| | | | | | | | | | | |
| Remark: | | | | | | | | | | |

Radiated Emissions Test Results for Above 1 GHz

RESULT: Pass



| Radiated Emissions | Test Results for Above 1 GHz |
|--------------------|------------------------------|
| | |

| EUT Name | Baseus True | Wireless Ea | rphones | Model Name | | Baseus | Baseus Bowie 30 | |
|---|--|---|--|--|---|--|--|--|
| Temperature | 23.4 ℃ | | | Relati | ve Humidity | 58.7% | | |
| Pressure | 960hPa | | | Test V | Test Voltage | | Voltage | |
| Test Mode | Mode 9 | | | Anten | na Polarity | Horizont | al | |
| | | | | | | | | |
| Frequency | Meter Reading | Factor | Emissio | on Level Limits | | Margin | Value Type | |
| (MHz) | (dBµV) | (dB) | (dBµ | ıV/m) | (dBµV/m) | (dB) | value Type | |
| 4960.000 | 46.59 | 0.22 | 46 | .81 | 74 | -27.19 | peak | |
| 4960.000 | 36.46 | 0.22 | 36 | .68 | 54 | -17.32 | AVG | |
| 7440.000 | 42.41 | 2.64 | 45 | .05 | 74 | -28.95 | peak | |
| 7440.000 | 32.56 | 2.64 | 35 | 5.2 | 54 | -18.8 | AVG | |
| | + + | | | | | | | |
| | • | | | | · · · · · | | • | |
| Remark: | | | | | | | | |
| | nna Factor + Cable | e Loss – Pre- | amplifier. | | | | | |
| | nna Factor + Cable Baseus True | | | Mode | Name | Baseus | Bowie 30 | |
| Factor = Ante | | | | | l Name ve Humidity | Baseus 58.7% | Bowie 30 | |
| Factor = Ante | Baseus True | | | Relati | | | | |
| Factor = Ante EUT Name Temperature Pressure | Baseus True 23.4℃ | | | Relati Test V | ve Humidity | 58.7% | | |
| Factor = Ante EUT Name Temperature Pressure Test Mode | Baseus True 23.4℃ 960hPa Mode 9 | Wireless Ea | rphones | Relati Test V Anten | ve Humidity /oltage | 58.7% Normal Vertical | Voltage | |
| Factor = Anter | Baseus True 23.4℃ 960hPa Mode 9 Meter Reading | Wireless Ea Factor | rphones | Relati Test V Anten | ve Humidity /oltage na Polarity Limits | 58.7% Normal Vertical Margin | | |
| Factor = Ante | Baseus True 23.4℃ 960hPa Mode 9 Meter Reading (dBµV) | Wireless Ea Factor (dB) | rphones Emissic | Relati Test V Anten | ve Humidity /oltage na Polarity Limits (dBµV/m) | 58.7% Normal Vertical Margin (dB) | Voltage Value Type | |
| Factor = Ante EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 | Baseus True 23.4℃ 960hPa Mode 9 Meter Reading | Wireless Ea Factor (dB) 0.22 | rphones Emissic (dBµ 46 | Relati Test V Anten on Level | ve Humidity /oltage na Polarity Limits | 58.7% Normal V Vertical Margin (dB) -27.82 | Voltage | |
| Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) | Baseus True 23.4℃ 960hPa Mode 9 Meter Reading (dBµV) 45.96 | Wireless Ea Factor (dB) | rphones Emissic (dBµ 46 36 | Relati Test V Anten | ve Humidity foltage na Polarity Limits (dBµV/m) 74 | 58.7% Normal Vertical Margin (dB) | Voltage Value Type peak | |
| Factor = Ante EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 4960.000 | Baseus True 23.4 °C 960hPa Mode 9 Meter Reading (dBµV) 45.96 35.82 | Wireless Ea Factor (dB) 0.22 0.22 | rphones Emissic (dBµ 46 36 44 | Relati Test V Anten On Level IV/m) .18 .04 | Ve Humidity /oltage na Polarity Limits (dBµV/m) 74 54 | 58.7% Normal Vertical Margin (dB) -27.82 -17.96 | Voltage Value Type peak AVG | |
| Factor = Ante EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 7440.000 | Baseus True 23.4 °C 960hPa Mode 9 Meter Reading (dBµV) 45.96 35.82 41.44 | Wireless Ea Factor (dB) 0.22 0.22 2.64 | rphones Emissic (dBµ 46 36 44 | Relati Test V Anten | ve Humidity /oltage na Polarity Limits (dBµV/m) 74 54 74 | 58.7% Normal Vertical Vertical (dB) -27.82 -17.96 -29.92 | Voltage Value Type peak AVG peak | |
| Factor = Ante EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 7440.000 | Baseus True 23.4 °C 960hPa Mode 9 Meter Reading (dBµV) 45.96 35.82 41.44 | Wireless Ea Factor (dB) 0.22 0.22 2.64 | rphones Emissic (dBµ 46 36 44 | Relati Test V Anten | ve Humidity /oltage na Polarity Limits (dBµV/m) 74 54 74 | 58.7% Normal Vertical Vertical (dB) -27.82 -17.96 -29.92 | Voltage Value Type peak AVG peak | |

RESULT: Pass

Note:


- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All test modes had been tested. The 8DPSK modulation is the worst case and recorded in the report.




| EUT Name | Baseus True Wireless Earphones | Model Name | Baseus Bowie 30 |
|-------------|--------------------------------|-------------------|-----------------|
| Temperature | 23.4 °C | Relative Humidity | 58.7% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna Polarity | Horizontal |

Band Edge Emission Test Results for Restricted Bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




Band Edge Emission Test Results for Restricted Bands

| EUT Name | Baseus Earphones | True | Wireless | Model Name | Baseus Bowie 30 |
|-------------|---------------------|------|----------|-------------------|-----------------|
| Temperature | 23.4 ℃ | | | Relative Humidity | 58.7% |
| Pressure | 960hPa | | | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | | | Antenna Polarity | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: Pass