



## RF Exposure Evaluation

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $Pd = (P_{out} * G) / (4 * \pi * r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **P<sub>out</sub>** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, and highest channel individually.

**Test Result of RF Exposure Evaluation**

For 2.4G Wi-Fi worst case

Antenna Gain: 2.03dBi

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm <sup>2</sup> )	Power Density At 20 cm (mW/cm <sup>2</sup> )	Test Results
2412	20.00	20.43	20±1	125.893	1.60	1	0.04	Pass
2437	20.00	22.23	22±1	199.526	1.60	1	0.0633	Pass
2462	20.00	20.71	20±1	125.893	1.60	1	0.0400	Pass

For BLE

Antenna Gain: 3.48dBi

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm <sup>2</sup> )	Power Density At 20 cm (mW/cm <sup>2</sup> )	Test Results
2412	20.00	18.92	18±1	79.43282	2.23	1	0.0352	Pass
2437	20.00	15.08	15±1	39.81072	2.23	1	0.0176	Pass
2462	20.00	10.23	10±1	12.58925	2.23	1	0.0056	Pass

**Simultaneous Transmission for SAR Exclusion**

The 2.4G Wi-Fi and BLE can transmit at the same, need consider simultaneous transmission. Maximum Simultaneous transmission SAR Ratio for BLE and 2.4G Wi-Fi

Maximum SAR Ratio BLE	Maximum SAR Ratio 2.4G Wi-Fi	$\Sigma$ SAR ratio BLE + SAR ratio 2.4G Wi-Fi	Limit	Results
0.0352	0.0633	0.0985	1	PASS

Remark: 1. Output power including tune-up tolerance;

2.Max. SAR Ratio=Max. Evaluation Values/Sar Limit, So:

Maximum SAR Ratio BLE =0.0352/1=0.0352

Maximum SAR Ratio 2.4G Wi-Fi =0.0633/1=0.0633

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.