FCC Test Report (BT-EDR)

Report No.:	RF180627E05-2
FCC ID:	Q87-03367
Test Model:	WHW01P
Series Model:	VLP01P, A01P
Received Date:	June 27, 2018
Test Date:	July 04 to Aug. 15, 2018
Issued Date:	Aug. 23, 2018
Applicant:	Linksys LLC
Address:	121 Theory Drive, Irvine, CA 92617, USA
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
Lab Address:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.
Test Location (1):	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.
Test Location (2):	No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.
FCC Registration / Designation Number:	723255 / TW2022 for Test Location (1) 736135 / TW0004 for Test Location (2)

Testing Laboratory
2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record 4

1 Certificate of Conformity 5

2 Summary of Test Results 6

2.1 Measurement Uncertainty 6
2.2 Modification Record 6

3 General Information 7

3.1 General Description of EUT (BT-EDR) 7
3.2 Description of Test Modes 9
3.2.1 Test Mode Applicability and Tested Channel Detail 10
3.3 Description of Support Units 12
3.3.1 Configuration of System under Test 12
3.4 General Description of Applied Standards 13

4 Test Types and Results 14

4.1 Radiated Emission and Bandedge Measurement 14
4.1.1 Limits of Radiated Emission and Bandedge Measurement 14
4.1.2 Test Instruments 15
4.1.3 Test Procedures 17
4.1.4 Deviation from Test Standard 18
4.1.5 Test Setup 18
4.1.6 EUT Operating Conditions 19
4.1.7 Test Results 20
4.2 Conducted Emission Measurement 27
4.2.1 Limits of Conducted Emission Measurement 27
4.2.2 Test Instruments 27
4.2.3 Test Procedures 28
4.2.4 Deviation from Test Standard 28
4.2.5 Test Setup 28
4.2.6 EUT Operating Condition 28
4.2.7 Test Results 29
4.3 Number of Hopping Frequency Used 31
4.3.1 Limits of Hopping Frequency Used Measurement 31
4.3.2 Test Setup 31
4.3.3 Test Instruments 31
4.3.4 Test Procedure 31
4.3.5 Deviation from Test Standard 31
4.3.6 Test Results 32
4.4 Dwell Time on Each Channel 33
4.4.1 Limits of Dwell Time on Each Channel Measurement 33
4.4.2 Test Setup 33
4.4.3 Test Instruments 33
4.4.4 Test Procedures 33
4.4.5 Deviation from Test Standard 33
4.4.6 Test Results 34
4.5 Channel Bandwidth 38
4.5.1 Limits of Channel Bandwidth Measurement 38
4.5.2 Test Setup 38
4.5.3 Test Instruments 38
4.5.4 Test Procedure 38
4.5.5 Deviation from Test Standard 38
4.5.6 EUT Operating Condition 38
4.5.7 Test Results 39
4.6 Hopping Channel Separation 40
4.6.1 Limits of Hopping Channel Separation Measurement 40

4.6.2 Test Setup 40
4.6.3 Test Instruments 40
4.6.4 Test Procedure 40
4.6.5 Deviation from Test Standard 40
4.6.6 Test Results 41
4.7 Maximum Output Power 42
4.7.1 Limits of Maximum Output Power Measurement 42
4.7.2 Test Setup 42
4.7.3 Test Instruments 42
4.7.4 Test Procedure 42
4.7.5 Deviation from Test Standard 42
4.7.6 EUT Operating Condition 42
4.7.7 Test Results 43
4.8 Conducted Out of Band Emission Measurement 44
4.8.1 Limits of Conducted Out of Band Emission Measurement 44
4.8.2 Test Instruments 44
4.8.3 Test Procedure 44
4.8.4 Deviation from Test Standard 44
4.8.5 EUT Operating Condition 44
4.8.6 Test Results 44

5 Pictures of Test Arrangements 47

Appendix – Information on the Testing Laboratories 48

Release Control Record

Issue No.	Description	Date Issued
RF180627E05-2	Original release.	Aug. 23, 2018

1 Certificate of Conformity

Product:	Velop Plug-In
Brand:	Linksys
Test Model:	WHW01P
Series Model:	VLP01P, A01P
Sample Status:	ENGINEERING SAMPLE
Applicant:	Linksys LLC
Test Date:	July 04 to Aug. 15, 2018
Standards:	47 CFR FCC Part 15, Subpart C (Section 15.247) ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Mary Ko , **Date:** Aug. 23, 2018

Mary Ko / Specialist

Approved by : , **Date:** Aug. 23, 2018

May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.05dB at 0.61485MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.205 & 209 & 15.247(d)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -5.6dB at 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is U.FL not a standard connector.

Note: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.33 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.10 dB
	6GHz ~ 18GHz	4.85 dB
	18GHz ~ 40GHz	5.24 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (BT-EDR)

Product	Velop Plug-In
Brand	Linksys
Test Model	WHW01P
Series Model	VLP01P, A01P
Driver version	1.1.6.189558
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	AC100~240V
Modulation Type	GFSK, π/4-DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3Mbps
Operating Frequency	2.402 ~ 2.480GHz
Number of Channel	79
Output Power	5.508mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA

Note:

1. The EUT has below model names, which are identical to each other in all aspects except for the following information:

Brand Name	Model Name	Difference
Linksys	WHW01P	for marketing requirement
	VLP01P	
	A01P	
From the above models, model: **WHW01P** was selected as representative model for the test and its data was recorded in this report.		

2. There are WLAN, Bluetooth technology used for the EUT. The EUT has below radios as following table:

Radio 1	**Radio 2**
WLAN (2.4GHz+5GHz)	Bluetooth

3. Simultaneously transmission condition.

Condition	**Technology**		
1	WLAN 2.4GHz	WLAN 5GHz	Bluetooth
Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.			

4. The antennas provided to the EUT, please refer to the following table:

WLAN						
Ant. No.	Chain No.	Ant. Net Gain (dBi)	Freq. range (GHz)	Ant. Type	Connecter Type	Cable Length (mm)
1 (Left)	Chain 0	2.41	2.4~2.4835	Dipole	U.FL	53
		3.15	5.15~5.85			
2 (Right)	Chain 1	3.2	2.4~2.4835	Dipole	U.FL	77
		3.9	5.15~5.85			

Bluetooth					
Ant. No.	Ant. Net Gain (dBi)	Freq. range (GHz)	Ant. Type	Connecter Type	Cable Length (mm)
3	2.13	2.402~2.480	IFA	U.FL	53

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Description of Test Modes

79 channels are provided for BT-EDR mode:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

Radiated Emission Test (Above 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	78	FHSS	GFSK	DH5

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	78	FHSS	GFSK	DH5

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	20deg. C, 64%RH	120Vac, 60Hz	Frank chuang
RE<1G	22deg. C, 68%RH	120Vac, 60Hz	Frank chuang
PLC	26deg. C, 79%RH	120Vac, 60Hz	Eagle Chen
APCM	25deg. C, 60%RH	120Vac, 60Hz	Jyunchun Lin

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Console Cable	1	0.05	No	0	Supplied by client(for RF Setup)

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For Below 1GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 08, 2017	July 07, 2018
Pre-Amplifier EMCI	EMC001340	980142	Feb. 09, 2018	Feb. 08, 2019
Loop Antenna(*) Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001	Jan. 15, 2018	Jan. 14, 2019
RF Cable	NA	LOOPCAB-002	Jan. 15, 2018	Jan. 14, 2019
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Nov. 09, 2017	Nov. 08, 2018
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 29, 2017	Nov. 28, 2018
RF Cable	8D	966-4-1	Mar. 21, 2018	Mar. 20, 2019
RF Cable	8D	966-4-2	Mar. 21, 2018	Mar. 20, 2019
RF Cable	8D	966-4-3	Mar. 21, 2018	Mar. 20, 2019
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Oct. 03, 2017	Oct. 02, 2018
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 4.
4. The CANADA Site Registration No. is 20331-2
5. Loop antenna was used for all emissions below 30 MHz.
6. Tested Date: July 04, 2018

For other test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 05, 2018	July 04, 2019
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Dec. 12, 2017	Dec. 11, 2018
Pre-Amplifier Mini-Circuits	ZVA-183-S+	AMP-ZVA-03	May 10, 2018	May 09, 2019
RF Cable	EMC104-SM-SM-1200	160923	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-2000	150318	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-5000	150321	Jan. 29, 2018	Jan. 28, 2019
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 29, 2018	Jan. 28, 2019
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Dec. 14, 2017	Dec. 13, 2018
RF Cable	EMC102-KM-KM-1200	160925	Jan. 29, 2018	Jan. 28, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. The CANADA Site Registration No. is 20331-2
4. Tested Date: July 18, 2018

4.1.3 Test Procedures

For Radiated emission below 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Setup

For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
a. Controlling software (QDART_1.0.38) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.4 PK	74.0	-19.6	1.86 H	49	56.6	-2.2
2	2390.00	47.8 AV	54.0	-6.2	1.86 H	49	50.0	-2.2
3	*2402.00	94.4 PK			1.86 H	49	96.7	-2.3
4	*2402.00	64.3 AV			1.86 H	49	66.6	-2.3
5	4804.00	39.6 PK	74.0	-34.4	3.19 H	60	37.8	1.8
6	4804.00	9.5 AV	54.0	-44.5	3.19 H	60	7.7	1.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	57.7 PK	74.0	-16.3	2.35 V	240	59.9	-2.2
2	**2390.00**	**48.4 AV**	**54.0**	**-5.6**	**2.35 V**	**240**	**50.6**	**-2.2**
3	*2402.00	95.6 PK			2.35 V	240	97.9	-2.3
4	*2402.00	65.5 AV			2.35 V	240	67.8	-2.3
5	4804.00	44.1 PK	74.0	-29.9	2.00 V	87	42.3	1.8
6	4804.00	14.0 AV	54.0	-40.0	2.00 V	87	12.2	1.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	94.4 PK			1.88 H	51	97.0	-2.6
2	*2441.00	64.3 AV			1.88 H	51	66.9	-2.6
3	4882.00	39.3 PK	74.0	-34.7	3.15 H	83	37.3	2.0
4	4882.00	9.2 AV	54.0	-44.8	3.15 H	83	7.2	2.0
5	7323.00	44.0 PK	74.0	-30.0	2.97 H	31	35.6	8.4
6	7323.00	13.9 AV	54.0	-40.1	2.97 H	31	5.5	8.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	95.8 PK			2.37 V	259	98.4	-2.6
2	*2441.00	65.7 AV			2.37 V	259	68.3	-2.6
3	4882.00	42.6 PK	74.0	-31.4	2.11 V	60	40.6	2.0
4	4882.00	12.5 AV	54.0	-41.5	2.11 V	60	10.5	2.0
5	7323.00	46.6 PK	74.0	-27.4	2.37 V	259	38.2	8.4
6	7323.00	16.5 AV	54.0	-37.5	2.37 V	259	8.1	8.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	94.5 PK			1.79 H	68	97.1	-2.6
2	*2480.00	64.4 AV			1.79 H	68	67.0	-2.6
3	2483.50	54.2 PK	74.0	-19.8	1.79 H	68	56.6	-2.4
4	2483.50	24.1 AV	54.0	-29.9	1.79 H	68	26.5	-2.4
5	4960.00	40.1 PK	74.0	-33.9	3.11 H	65	38.0	2.1
6	4960.00	10.0 AV	54.0	-44.0	3.11 H	65	7.9	2.1
7	7440.00	45.9 PK	74.0	-28.1	2.87 H	20	37.1	8.8
8	7440.00	15.8 AV	54.0	-38.2	2.87 H	20	7.0	8.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	97.3 PK			2.37 V	256	99.9	-2.6
2	*2480.00	67.2 AV			2.37 V	256	69.8	-2.6
3	2483.50	58.3 PK	74.0	-15.7	2.37 V	256	60.7	-2.4
4	2483.50	28.2 AV	54.0	-25.8	2.37 V	256	30.6	-2.4
5	4960.00	43.8 PK	74.0	-30.2	2.05 V	72	41.7	2.1
6	4960.00	13.7 AV	54.0	-40.3	2.05 V	72	11.6	2.1
7	7440.00	45.9 PK	74.0	-28.1	3.31 V	205	37.1	8.8
8	7440.00	15.8 AV	54.0	-38.2	3.31 V	205	7.0	8.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

BT_8DPSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.7 PK	74.0	-19.3	1.80 H	42	56.9	-2.2
2	2390.00	47.6 AV	54.0	-6.4	1.80 H	42	49.8	-2.2
3	*2402.00	90.4 PK			1.80 H	42	92.7	-2.3
4	*2402.00	60.3 AV			1.80 H	42	62.6	-2.3
5	4804.00	39.8 PK	74.0	-34.2	3.14 H	76	38.0	1.8
6	4804.00	9.7 AV	54.0	-44.3	3.14 H	76	7.9	1.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.2 PK	74.0	-19.8	2.33 V	245	56.4	-2.2
2	2390.00	47.9 AV	54.0	-6.1	2.33 V	245	50.1	-2.2
3	*2402.00	93.7 PK			2.33 V	245	96.0	-2.3
4	*2402.00	63.6 AV			2.33 V	245	65.9	-2.3
5	4804.00	42.2 PK	74.0	-31.8	2.06 V	63	40.4	1.8
6	4804.00	12.1 AV	54.0	-41.9	2.06 V	63	10.3	1.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.2 PK			1.80 H	48	92.8	-2.6
2	*2441.00	60.1 AV			1.80 H	48	62.7	-2.6
3	4882.00	39.6 PK	74.0	-34.4	3.08 H	70	37.6	2.0
4	4882.00	9.5 AV	54.0	-44.5	3.08 H	70	7.5	2.0
5	7323.00	44.2 PK	74.0	-29.8	2.87 H	33	35.8	8.4
6	7323.00	14.1 AV	54.0	-39.9	2.87 H	33	5.7	8.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.7 PK			2.35 V	263	96.3	-2.6
2	*2441.00	63.6 AV			2.35 V	263	66.2	-2.6
3	4882.00	42.0 PK	74.0	-32.0	2.05 V	69	40.0	2.0
4	4882.00	11.9 AV	54.0	-42.1	2.05 V	69	9.9	2.0
5	7323.00	47.3 PK	74.0	-26.7	3.30 V	213	38.9	8.4
6	7323.00	17.2 AV	54.0	-36.8	3.30 V	213	8.8	8.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	90.5 PK			1.84 H	58	93.1	-2.6
2	*2480.00	60.4 AV			1.84 H	58	63.0	-2.6
3	2483.50	54.7 PK	74.0	-19.3	1.84 H	58	57.1	-2.4
4	2483.50	24.6 AV	54.0	-29.4	1.84 H	58	27.0	-2.4
5	4960.00	40.0 PK	74.0	-34.0	3.13 H	73	37.9	2.1
6	4960.00	9.9 AV	54.0	-44.1	3.13 H	73	7.8	2.1
7	7440.00	43.8 PK	74.0	-30.2	2.93 H	34	35.0	8.8
8	7440.00	13.7 AV	54.0	-40.3	2.93 H	34	4.9	8.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.7 PK			2.41 V	263	96.3	-2.6
2	*2480.00	63.6 AV			2.41 V	263	66.2	-2.6
3	2483.50	54.5 PK	74.0	-19.5	2.41 V	263	56.9	-2.4
4	2483.50	24.4 AV	54.0	-29.6	2.41 V	263	26.8	-2.4
5	4960.00	42.0 PK	74.0	-32.0	2.01 V	68	39.9	2.1
6	4960.00	11.9 AV	54.0	-42.1	2.01 V	68	9.8	2.1
7	7440.00	47.4 PK	74.0	-26.6	3.27 V	204	38.6	8.8
8	7440.00	17.3 AV	54.0	-36.7	3.27 V	204	8.5	8.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

Below 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 78	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	117.90	26.5 QP	43.5	-17.0	1.50 H	70	36.5	-10.0
2	244.83	27.7 QP	46.0	-18.3	1.00 H	40	36.8	-9.1
3	311.54	31.5 QP	46.0	-14.5	1.00 H	25	38.0	-6.5
4	379.17	32.6 QP	46.0	-13.4	1.00 H	50	37.3	-4.7
5	421.28	34.2 QP	46.0	-11.8	1.00 H	320	37.8	-3.6
6	637.54	30.8 QP	46.0	-15.2	1.50 H	79	29.4	1.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	46.05	33.0 QP	40.0	-7.0	1.00 V	164	41.0	-8.0
2	133.57	24.8 QP	43.5	-18.7	1.00 V	76	33.6	-8.8
3	253.25	24.9 QP	46.0	-21.1	1.00 V	90	33.7	-8.8
4	304.34	28.1 QP	46.0	-17.9	1.00 V	305	35.1	-7.0
5	417.83	32.1 QP	46.0	-13.9	1.00 V	341	35.8	-3.7
6	639.35	30.9 QP	46.0	-15.1	1.00 V	120	29.5	1.4

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	100375	May 15, 2018	May 14, 2019
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK-8127	8127-522	Aug. 31, 2017	Aug. 30, 2018
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV 216	10072	June 04, 2018	June 03, 2019
RF Cable	5D-FB	COACAB-002	Feb. 23, 2018	Feb. 22, 2019
10 dB PAD EMEC	STI02-2200-10	001	Mar. 16, 2018	Mar. 15, 2019
50 ohms Terminator	N/A	EMC-03	Sep. 22, 2017	Sep. 21, 2018
50 ohms Terminator	N/A	EMC-02	Sep. 22, 2017	Sep. 21, 2018
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:
1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conducted Room C
3 The VCCI Con C Registration No. is C-3611.
4 Tested Date: Aug. 15, 2018

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.

4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.47033	10.00	31.99	24.99	41.99	34.99	56.51	46.51	-14.52	-11.52
2	**0.61485**	**10.01**	**41.85**	**32.94**	**51.86**	**42.95**	**56.00**	**46.00**	**-4.14**	**-3.05**
3	0.72425	10.02	32.12	25.22	42.14	35.24	56.00	46.00	-13.86	-10.76
4	0.99377	10.05	27.66	19.33	37.71	29.38	56.00	46.00	-18.29	-16.62
5	1.87111	10.06	26.66	17.11	36.72	27.17	56.00	46.00	-19.28	-18.83
6	3.92579	10.19	25.66	16.33	35.85	26.52	56.00	46.00	-20.15	-19.48

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.47033	10.02	27.99	19.78	38.01	29.80	56.51	46.51	-18.50	-16.71
2	0.61877	10.03	38.22	29.80	48.25	39.83	56.00	46.00	-7.75	-6.17
3	0.72425	10.04	28.55	20.95	38.59	30.99	56.00	46.00	-17.41	-15.01
4	1.25000	10.06	21.77	11.89	31.83	21.95	56.00	46.00	-24.17	-24.05
5	1.91409	10.08	25.11	16.75	35.19	26.83	56.00	46.00	-20.81	-19.17
6	2.81255	10.14	25.56	14.50	35.70	24.64	56.00	46.00	-20.30	-21.36

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK





8DPSK





4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

GFSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) * 6.32 = 322.32 times	0.438	141.2	400
DH3	17 (times / 5 sec) * 6.32 = 107.44 times	1.72	184.8	400
DH5	10 (times / 5 sec) * 6.32 = 63.2 times	3.04	192.1	400

Note: Test plots of the transmitting time slot are shown on next page.

DH1


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
[T2] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 3 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dB
Marker 1 [T1]
-57.10 dBm
1.272000 ms
Delta 2 [T1]
2.10 dB
438.000000 us
Center 2.441 GHz
300 us/

DH3


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
[T2] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dB
Marker 1 [T1]
-55.50 dBm
1.640000 ms
Delta 2 [T1]
5.80 dB
1.720000 ms
Center 2.441 GHz
500 us/

DH5


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
[T2] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 8 ms
[T1] MP VIEW
[T2] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dB
Marker 1 [T1]
-54.01 dBm
2.448000 ms
Delta 2 [T1]
4.54 dB
3.040000 ms
Center 2.441 GHz
800 us/

8DPSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	51 (times / 5 sec) * 6.32 = 322.32 times	0.522	168.3	400
3DH3	17 (times / 5 sec) * 6.32 = 107.44 times	1.7	182.6	400
3DH5	10 (times / 5 sec) * 6.32 = 63.2 times	2.992	189.1	400

Note: Test plots of the transmitting time slot are shown on next page.

3DH1





3DH3





3DH5





4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.96	1.29
39	2441	0.96	1.29
78	2480	0.96	1.29

Spectrum Plot of Worst Value	
GFSK / CH 0	**8DPSK / CH 0**
	

4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.

c. By using the MaxHold function record the separation of two adjacent channels.

d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.00	0.96	1.29	0.64	0.86	Pass
39	2441	1.00	1.00	0.96	1.29	0.64	0.86	Pass
78	2480	1.00	1.00	0.96	1.29	0.64	0.86	Pass

Note: The minimum limit is two-third 20dB bandwidth.

Spectrum Plot of Worst Value

GFSK / CH0



8DPSK / CH0



4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

Channel	Frequency (MHz)	Peak Output Power (mW)		Peak Output Power (dBm)		Power Limit (mW)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	2.911	2.36	4.64	3.73	125	Pass
39	2441	4.742	3.707	6.76	5.69	125	Pass
78	2480	5.508	4.236	7.41	6.27	125	Pass

Spectrum Plot of Worst Value	
GFSK / CH78	**8DPSK / CH78**
	

4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.

4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_ Low Channel



Hopping disabled_ High Channel



Hopping enabled_ Low Channel



Hopping enabled_ High Channel



8DPSK

Hopping disabled_ Low Channel



Hopping disabled_ High Channel



Hopping enabled_ Low Channel



Hopping enabled_ High Channel



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linkou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---