









































































































































7 OCCUPIED BANDWIDTH

Applicable Standard: FCC §2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power.

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	MXA Series Spectrum Analyzer	N9020A	MY51240300	2013.12.10	2014.12.10
DTS	DTS 40dB Attenuator	DTS100-40-3-1	09112005	2014.06.13	2015.06.13

***statement of traceability:** ZTE Corporation Reliability Testing Center attests that all calibration has been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

The RF out of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation. 99%Power bandwidth was recorded.

Environmental Conditions

Temperature:	20 ° C
Relative Humidity:	53%
ATM Pressure:	1009mbar

Test Result: Pass

Test Mode: Transmitting LTE

Test Data

Channel Bandwidth: 20M+20M

Port	Carrier Freq. c1+c2(MHz)	Occupied Bandwidth(MHz)		
		QPSK	16QAM	64QAM
0	2506+2526	37.49	37.44	37.6
1		37.49	37.44	37.6
2		37.49	37.44	37.6
3		37.49	37.44	37.6
4		37.49	37.44	37.6
5		37.49	37.44	37.6
6		37.49	37.44	37.6
7		37.49	37.44	37.6
0	2536+2556	37.46	37.47	37.62
1		37.46	37.47	37.62
2		37.46	37.47	37.62
3		37.46	37.47	37.62
4		37.46	37.47	37.62
5		37.46	37.47	37.62
6		37.46	37.47	37.62
7		37.46	37.47	37.62
0	2566+2586	37.16	37.37	37.61
1		37.16	37.36	37.61
2		37.16	37.36	37.61
3		37.16	37.37	37.61
4		37.16	37.37	37.61
5		37.16	37.37	37.61
6		37.16	37.37	37.61
7		37.16	37.36	37.61







































