



# **TEST REPORT**

**Test Report No. : UL-EMC-RP13559945JD20B V2.0**

**Manufacturer** : Apple Inc.  
**Type of Equipment** : Information Technology Equipment (ITE)  
**Model No. / HVIN** : A2520  
**PMN** : Apple Magic Keyboard with Touch ID and Numeric Keypad  
**FCC ID** : BCGA2520  
**ISED Canada Certification No.** : 579C-A2520  
**Test Standard** : 47CFR15.107, 47CFR15.109 and ICES-003 Issue 6 January 2016  
**Test Result** : Complied

**Version 2.0 supersedes all previous versions**

1. This report may not be reproduced except in full, without the written approval of UL International (UK) Ltd.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above standards.
4. The test results in this report are traceable to the national or international standards.

**Date of issue:**

07 April 2021

**Checked by:**

*Adam Brown*  
Test Engineer

**Company Signatory:**

*Matthew Owen*  
Operations Leader



This laboratory is accredited by the United Kingdom Accreditation Service (UKAS).

UKAS is one of the signatories to the International Laboratory Accreditation Co-operation (ILAC) Arrangement for the mutual recognition of test reports.

The tests reported herein have been performed in accordance with its terms of accreditation.

The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by UL International (UK) Ltd is under license. Other trademarks and trade names are those of their respective owners.

**UL International (UK) Ltd**

Units 1-3 Horizon, Kingsland Business Park, Wade Road, Basingstoke, Hampshire, RG24 8AH, UK.

Telephone: +44 (0)1256 312000

This page has been intentionally left blank.

---

**TABLE OF CONTENTS**

<b>1. Customer Details .....</b>	<b>4</b>
<b>2. Summary of Testing .....</b>	<b>5</b>
<b>3. Equipment under Test (EUT) .....</b>	<b>6</b>
<b>4. Support Equipment.....</b>	<b>7</b>
<b>5. Measurement Uncertainty and Decision Rule .....</b>	<b>8</b>
<b>6. Measurements, Examinations and Derived Results .....</b>	<b>9</b>
<b>7. Graphical Test Results .....</b>	<b>14</b>
<b>8. Test Configuration Drawing .....</b>	<b>19</b>
<b>9. Report Revision History .....</b>	<b>21</b>

---

**1. CUSTOMER DETAILS**

<b>Company Name:</b>	Apple Inc.
----------------------	------------

<b>Address:</b>	1 Apple Park Way Cupertino CA 95014 USA
-----------------	--

<b>Contact Name:</b>	Stuart Thomas
----------------------	---------------

## 2. SUMMARY OF TESTING

### 2.1. Test Specification

1.	Reference:	47CFR15.107 and 47CFR15.109
	Title:	Code of Federal Regulations - Title 47 (Telecommunication): Part 15 (Radio Frequency Devices) - Subpart B (Unintentional Radiators) – Sections 15.107 and 15.109 October 1, 2020 Edition (including all applicable amendments up to December 9 2020)
2.	Reference:	ICES-003 Issue 6 January 2016
	Title:	Information Technology Equipment (Including Digital Apparatus) – Limits and Methods of Measurement
Site Registration:		FCC: 621311 / UK2011 ISED Canada: 20903 / UK0001

### 2.2. Summary of Test Results

FCC Reference	IC Reference	Measurement Type	Result
15.107	6.1	Conducted Emissions (AC Mains Input / Output Ports)	Complied
15.109	6.2	Radiated Emissions (Enclosure)	Complied

### 2.3. Location of Testing

All the measurements described in this report were performed at the premises of UL International (UK) Ltd, Unit 1 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire RG24 8AH.

### 2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above, nor from the requirements defined in the basic standards called up within it.

### 3. EQUIPMENT UNDER TEST (EUT)

#### 3.1. Description of EUT

The EUT was Bluetooth Keyboard.

#### 3.2. Identification of Equipment under Test (EUT)

ID#	Description	Brand Name	Model No	Serial No
E1	Bluetooth Keyboard	Apple	A2520	F0T047300160VX90U

#### 3.3. Port Identification

Port	Description	Possible Length (m)	Type	Connector
P1.1	Enclosure	Not applicable	Enclosure	Not applicable
P1.2	Lightning	< 3	Signal / DC Power	Lightning

#### 3.4. Operating Modes

Mode Reference	Definition
Charging	The EUT was charging from the Mains using an AC to DC Power Adapter but not Bluetooth connection was established. The EUT was left to go into a power saving state.

#### 3.5. Configuration and Peripherals

<b>Description:</b>	Please refer to <i>section 9. Test Configuration Drawing</i> for schematic drawing(s) of the test configuration(s) employed in the course of testing.
---------------------	---

#### 3.6. Modifications

No modifications were made to the EUT during the course of testing.

#### 3.7. Additional Information Related to Testing

<b>Equipment Category:</b>	Information Technology Equipment (ITE)
<b>Intended Operating Environment:</b>	Residential / Commercial
<b>Intended Installation:</b>	Table Top
<b>Cycle Time:</b>	Less than 1 second
<b>Power Supply Requirement(s):</b>	5.1 V DC from AC to DC Power Adapter powered from 120 VAC, 60 Hz. 3.8 VDC Internal Battery
<b>Weight:</b>	367 g
<b>Dimensions:</b>	(419 x 115 x 10) mm
<b>Hardware Version Number:</b>	REV1.0
<b>Software Version Number:</b>	0xF125
<b>FCC ID Number:</b>	BCGA2520
<b>ISED Number</b>	579C-A2520
<b>Highest Internally Generated Operating Frequency:</b>	2480 MHz

## 4. SUPPORT EQUIPMENT

### 4.1. Identification of Support Equipment

Description	Manufacturer	Model No	Serial No
AC to DC Power Adapter	Apple	A2118	None Stated

### 4.2. Interconnecting Cables

Cable Type	Shielded	Length (m)	Ferrite	Connection 1	Connection 2
Multicore	Yes	1.0	No	EUT	AC to DC Power Adapter
Direct Connection				AC to DC Power Adapter	AC Supply

## 5. MEASUREMENT UNCERTAINTY AND DECISION RULE

### 5.1. Overview

No measurement can ever be perfect and those imperfections give rise to error. Consequently, the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement regarding the uncertainty of approximation.

Note that compliance is determined solely upon the results of compliance measurements and does not take into account measurement uncertainties. The measurement uncertainty values quoted in this report are for information only as they do not influence the associated test results.

### 5.2. Method of calculation

The methods used to calculate the uncertainties included within this test report are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty, the published guidance of the United Kingdom Accreditation Service (UKAS) is followed.

### 5.3. Equipment Accuracy and Decision Rule

Measurement system instrumentation with an accuracy specification meeting the accuracy specification limits or that has an uncertainty within prescribed limits detailed in the specification or standard shall be used. When providing a statement of conformity to a technical specification or standard, unless inherent in the requested technical specification or standard, the decision rule applied shall be the Accuracy Method (as defined in IEC Guide 115) in determining compliance. The measurement result is considered in conformance with the requirement criteria if it is within the prescribed limit.



---

## 6. MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS

### 6.1. General Comments

6.1.1. This section contains the test result sheets for the measurements listed in Section **2.2**.

**Summary of Test Results** (above).

6.1.2. The measurement uncertainties stated in the test result sheets were calculated in accordance with documented best practice and represent a confidence level of 95%. Where only confidence level is given, it has been demonstrated that the relevant items of test equipment used meet the specified requirements in the standard with at least this level of confidence.

6.1.3. Please refer to Section **5. Measurement Uncertainty** on page 8 for details of our treatment of measurement uncertainty.

## RADIATED EMISSIONS - TEST RESULTS

This test is covered by the scope of UL International (UK) Ltd's UKAS Accreditation under ISO/IEC 17025:2017.

### GENERAL INFORMATION

JOB NUMBER:	13559945JD20	TEST SITE ID:	Site 52
EUT:	A2520	TEMPERATURE:	19 °C to 20 °C
TEST ENGINEER:	Pawel Zackiewicz	RELATIVE HUMIDITY:	47 % to 48 %
DATE OF TEST:	15 Dec 2020	ATMOSPHERIC PRESSURE:	1008mb to 1008 mb
FIELD TYPE:	Electric Field	MEASUREMENT DISTANCE:	3 & 1 Metres
UNCERTAINTY:	< 1 GHz: ± 3.91 dB > 1 GHz: ± 3.45 dB	EQUIPMENT CLASS:	Class B
MEASUREMENT UNITS:	dBµV/m	TEST ENVIRONMENT:	Test Site

### TEST SPECIFICATION DETAILS

The EUT has been configured and tested in accordance with the methods and procedures detailed within the following basic standard:

REFERENCE:	ANSI C63.4:2014
TITLE:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

### COMMENTS

○ Measurements were performed in a semi-anechoic chamber, at distances of 3 metres (30 MHz to 6 GHz) and 1 metre (6 GHz to 18 GHz). The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable.

Below 1 GHz, maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

Above 1 GHz, the orientation of the EUT emanating the highest emission levels was determined using exploratory measurements with an antenna and spectrum analyser prior to the formal measurements. For the final test, emissions the EUT was rotated whilst positioned in the previously determined worst case orientation only.

○ The recorded disturbance level (field strength) was calculated from the level indicated by the measuring receiver, adjusted by a correction factor (CF in dB), calculated using the formula:

$$CF (dB) = CAtt (dB) + AF (dB/m) - PGain (dB)$$

Where:

CAtt (dB): Conducted Path Attenuation (Cables + Attenuators)

AF (dB/m): Antenna Factor

PGain (dB): External Preamplifier Gain

### DEVIATIONS FROM TEST SPECIFICATION

There were no deviations from the test configuration and measurement arrangements defined in the test specification (identified above).

### EUT RELATED

OPERATING MODE:	Charging
FUNCTION(S) MONITORED:	Not Applicable

### MEASUREMENT RESULTS

No.	Frequency (MHz)	Polarisation	Detector	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Graph No.	Result
1	41.053	Vertical	Quasi-Peak	15.2	40.0	24.8	GPH\13559945JD20\001	Complied
2	50.043	Horizontal	Quasi-Peak	11.4	40.0	28.7	GPH\13559945JD20\001	Complied
3	96.101	Vertical	Quasi-Peak	10.0	43.5	33.6	GPH\13559945JD20\001	Complied
4	207.461	Vertical	Quasi-Peak	11.7	43.5	31.8	GPH\13559945JD20\001	Complied
5	274.054	Horizontal	Quasi-Peak	16.6	46.0	29.4	GPH\13559945JD20\001	Complied
6	845.356	Vertical	Quasi-Peak	24.9	46.0	21.1	GPH\13559945JD20\001	Complied
7	1000 to 12750	Refer to Note 1					GPH\13559945JD20\002 to 005	Complied

**NOTES**

1	No emissions were noted above the noise floor of the measurement system; therefore, no further measurements were made.
---	--

**TEST EQUIPMENT USED**

UL ID	INSTRUMENT DESCRIPTION	MODEL NUMBER	CALIBRATION DUE	INTERVAL
K0032	3m Semi-Anechoic Chamber 1	N/A	11 Feb 2021	12
M2046	Thermo-Hygrometer	608-H1	28 Sep 2021	12
M2050	44 GHz EMI Test Receiver	ESW44	26 Nov 2021	12
G0543	Amplifier 9kHz - 1GHz	310N	06 Nov 2021	12
A3077	3 dB Attenuator	1812 BW-N3 W5+	Calibrated before use	N/A
A3159	5 dB Attenuator - 5W	1735 BW-N5 W5+	Calibrated as part of system	N/A
A2903	Trilog Broadband Antenna	VULB 9163	02 Mar 2021	12
A1227	1 to 26.5 GHz Amplifier	8449B	13 Aug 2021	12
A1834	3 dB Attenuator	8491B	02 Mar 2021	12
A1817	1-18 GHz Horn Antenna	3115	05 Nov 2021	12
C1817	1 metre N-male to N-male RF cable	Sucoflex 104A	13 Aug 2021	12
C1831	2 metre N-male to N-male RF cable	Sucoflex 104A	13 Aug 2021	12
C1824	15 metre N-male to N-male RF cable	Sucoflex 104A	13 Aug 2021	12
C1826	8 metre N-male to N-male RF cable	Sucoflex 104A	13 Aug 2021	12
C1839	1 metre N-male to N-male RF cable	SA90-195-1MTR	27 May 2021	12
C1838	1 metre N-male to N-male RF cable	SA90-195-1MTR	13 Aug 2021	12
C1804	2 metre N-male to N-male RF cable	SA90-195-2MTR	27 May 2021	12
C1836	3 metre N-male to N-male RF cable	SA90-195-3MTR	13 Aug 2021	12
C1803	1 metre N-male to N-male RF cable	SA90-195-1MTR	27 May 2021	12

**CONDUCTED EMISSIONS - TEST RESULTS**

This test is covered by the scope of UL International (UK) Ltd's UKAS Accreditation under ISO/IEC 17025:2017.

**GENERAL INFORMATION**

<b>JOB NUMBER:</b>	13559945JD20	<b>TEST SITE ID:</b>	Site 56
<b>EUT:</b>	A2520	<b>TEMPERATURE:</b>	20 °C To 20 °C
<b>TEST ENGINEER:</b>	Adam Brown	<b>RELATIVE HUMIDITY:</b>	45 % To 45 %
<b>DATE OF TEST:</b>	11 Dec 2020	<b>ATMOSPHERIC PRESSURE:</b>	986 mb To 986 mb
<b>UNCERTAINTY:</b>	± 1.96 dB	<b>EQUIPMENT CLASS:</b>	Class B
<b>EUT CATEGORY:</b>	Not Applicable	<b>MEASUREMENT METHOD:</b>	LISN (AC)
<b>PORT UNDER TEST:</b>	AC Power Input	<b>EUT SUPPLY VOLTAGE:</b>	120 VAC / 60 Hz

**TEST SPECIFICATION DETAILS**

The EUT has been configured and tested in accordance with the methods and procedures detailed within the following basic standard:

<b>REFERENCE:</b>	ANSI C63.4:2014
<b>TITLE:</b>	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

**COMMENTS**

○ The recorded disturbance level (voltage) was calculated from the level indicated by the measuring receiver, adjusted by a correction factor (CF in dB), calculated using the formula:

$$CF (dB) = CAtt (dB) + PLAtt (dB) + VDF (dB)$$

Where:

CAtt (dB): Conducted Path Attenuation (Cables + Attenuators)

PLAtt (dB): Pulse Limiter Attenuation

VDF (dB): Voltage Division Factor of LISN

**DEVIATIONS FROM TEST SPECIFICATION**

There were no deviations from the test configuration and measurement arrangements defined in the test specification (identified above).

**EUT RELATED**

<b>OPERATING MODE:</b>	Charging
<b>FUNCTION(S) MONITORED:</b>	Not Applicable

**MEASUREMENT RESULTS**

No.	Frequency (MHz)	Line	Detector	Level (dBμV)	Limit (dBμV)	Margin (dB)	Graph No.	Result
1	0.168	Live	CISPR Average	26.0	55.1	29.0	GPH\13559945JD20\006	Complied
2	0.168	Live	Quasi-Peak	45.0	65.1	20.0	GPH\13559945JD20\006	Complied
3	0.249	Live	Quasi-Peak	40.7	61.8	21.1	GPH\13559945JD20\006	Complied
4	0.251	Live	CISPR Average	22.6	51.7	29.1	GPH\13559945JD20\006	Complied
5	0.332	Live	CISPR Average	19.9	49.4	29.5	GPH\13559945JD20\006	Complied
6	0.332	Live	Quasi-Peak	38.0	59.4	21.4	GPH\13559945JD20\006	Complied
7	0.416	Live	Quasi-Peak	36.1	57.5	21.4	GPH\13559945JD20\006	Complied
8	0.431	Live	CISPR Average	18.6	47.2	28.6	GPH\13559945JD20\006	Complied
9	0.499	Live	Quasi-Peak	33.5	56.0	22.5	GPH\13559945JD20\006	Complied
10	0.508	Live	CISPR Average	17.1	46.0	28.9	GPH\13559945JD20\006	Complied
11	0.591	Live	Quasi-Peak	31.3	56.0	24.7	GPH\13559945JD20\006	Complied
12	0.593	Live	CISPR Average	17.4	46.0	28.6	GPH\13559945JD20\006	Complied
13	0.663	Live	Quasi-Peak	29.4	56.0	26.6	GPH\13559945JD20\006	Complied

**MEASUREMENT RESULTS**

No.	Frequency (MHz)	Line	Detector	Level (dBµV)	Limit (dBµV)	Margin (dB)	Graph No.	Result
14	0.674	Live	CISPR Average	17.3	46.0	28.7	GPH\13559945JD20\006	Complied
15	0.746	Live	Quasi-Peak	26.8	56.0	29.2	GPH\13559945JD20\006	Complied
16	0.751	Live	CISPR Average	14.7	46.0	31.3	GPH\13559945JD20\006	Complied
17	1.016	Live	Quasi-Peak	24.0	56.0	32.0	GPH\13559945JD20\006	Complied
18	1.019	Live	CISPR Average	19.1	46.0	26.9	GPH\13559945JD20\006	Complied
19	0.152	Neutral	CISPR Average	21.0	55.9	34.9	GPH\13559945JD20\007	Complied
20	0.164	Neutral	Quasi-Peak	39.3	65.3	26.0	GPH\13559945JD20\007	Complied
21	0.247	Neutral	Quasi-Peak	34.9	61.9	27.0	GPH\13559945JD20\007	Complied
22	0.251	Neutral	CISPR Average	18.7	51.7	33.0	GPH\13559945JD20\007	Complied
23	0.330	Neutral	Quasi-Peak	31.0	59.5	28.5	GPH\13559945JD20\007	Complied
24	0.344	Neutral	CISPR Average	17.5	49.1	31.6	GPH\13559945JD20\007	Complied
25	0.418	Neutral	Quasi-Peak	27.8	57.5	29.7	GPH\13559945JD20\007	Complied
26	0.431	Neutral	CISPR Average	18.5	47.2	28.8	GPH\13559945JD20\007	Complied
27	0.499	Neutral	Quasi-Peak	24.7	56.0	31.3	GPH\13559945JD20\007	Complied
28	0.508	Neutral	CISPR Average	16.1	46.0	29.9	GPH\13559945JD20\007	Complied
29	0.582	Neutral	Quasi-Peak	21.1	56.0	35.0	GPH\13559945JD20\007	Complied
30	0.584	Neutral	CISPR Average	17.1	46.0	28.9	GPH\13559945JD20\007	Complied
31	1.025	Neutral	CISPR Average	15.0	46.0	31.0	GPH\13559945JD20\007	Complied
32	1.030	Neutral	Quasi-Peak	19.3	56.0	36.7	GPH\13559945JD20\007	Complied



**TEST EQUIPMENT USED**



UL ID	INSTRUMENT DESCRIPTION	MODEL NUMBER	CALIBRATION DUE	INTERVAL
K0036	Conducted Emissions / Immunity Test Laboratory 2	N/A	Calibration not required	N/A
M2048	Thermo-Hygrometer	608-H1	28 Sep 2021	12
N0613	Site 56 Test PC	Motherboard Asus Z97-P	Calibration not required	N/A
M2051	3.6 GHz EMI Test Receiver	ESR3	14 Oct 2021	12
A1828	N-Type Pulse Limiter	ESH3-Z2	03 Nov 2021	12
A2086	2 Line LISN	ENV216 (3560.6550.13)	26 Feb 2021	12
M524	300V 4800VA 1ph Harmonics/Flicker Test system	6843A	Calibrated before use	N/A

## 7. GRAPHICAL TEST RESULTS



7.1. This section contains the graphical results for the measurements listed in Section **2.2. Summary of Test Results** (above).


Graph Reference Number	Title
GPH\13559945JD20\001	Radiated Emissions (30 MHz to 1 GHz)
GPH\13559945JD20\002	Radiated Emissions (1 GHz to 3 GHz)
GPH\13559945JD20\003	Radiated Emissions (3 GHz to 6 GHz)
GPH\13559945JD20\004	Radiated Emissions (6 GHz to 10 GHz)
GPH\13559945JD20\005	Radiated Emissions (10 GHz to 12.75 GHz)
GPH\13559945JD20\006	Conducted Emissions (150 kHz to 30 MHz) Live
GPH\13559945JD20\007	Conducted Emissions (150 kHz to 30 MHz) Neutral

**GPH\13559945JD20\001 - Radiated Emissions (30 MHz to 1 GHz)****GPH\13559945JD20\002 - Radiated Emissions (1 GHz to 3 GHz)**

**GPH\13559945JD20\003 - Radiated Emissions (3 GHz to 6 GHz)****GPH\13559945JD20\004 - Radiated Emissions (6 GHz to 10 GHz)**



**GPH\13559945JD20\005 - Radiated Emissions (10 GHz to 12.75 GHz)****GPH\13559945JD20\006 - Conducted Emissions (150 kHz to 30 MHz) – Live**

**GPH\13559945JD20\007 - Conducted Emissions (150 kHz to 30 MHz) – Neutral**


## 8. TEST CONFIGURATION DRAWING

8.1. This section contains the Test Configuration Drawings for the measurements listed in Section 7: Measurements, Examinations and Derived Results.

Test Configuration Reference Number	Title
DRG\13559945JD20\001	Schematic Diagram of the EUT, Support Equipment and Interconnecting Cables Used During Testing

**DRG\13559945JD20\001 - Schematic Diagram of the EUT, Support Equipment and Interconnecting Cables Used During Testing**

**Configuration of EUT and Local Support Equipment**



**Configuration of Remote Support Equipment**

## 9. REPORT REVISION HISTORY

9.1. This section contains the report revision history.

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	-	-	Initial Version.
2.0	1, 6	Cover, 3.7	Removed "-" from FCC ID.