

# TEST REPORT

## CERTIFICATE OF CONFORMITY

**Standard:** 47 CFR FCC Part 15, Subpart B, Class B  
ANSI C63.4-2014  
ANSI C63.4a-2017

**Report No.:** FDBDKG-WTW-P22040386B

**Product:** Wireless Keyboard

**FCC ID.:** JNZYR0067

**Brand:** Logitech

**Model No.:** Y-R0067

**Received Date:** 2023/9/6

**Test Date:** 2023/10/28

**Issued Date:** 2023/12/14

**Applicant:** Logitech Far East Ltd.

**Address:** #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

**Test Location:** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

**FCC Registration /**

**Designation Number:** 960022 / TW1058

Approved by: \_\_\_\_\_

Ken Lu / Manager

, Date: \_\_\_\_\_

2023/12/14

This test report consists of 16 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vito Lung / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1 Certificate.....</b>	<b>4</b>
<b>2 Summary of Test Results .....</b>	<b>5</b>
2.1 Measurement Uncertainty .....	5
2.2 Supplementary Information .....	5
<b>3 General Information .....</b>	<b>6</b>
3.1 Description of EUT .....	6
3.2 Primary Clock Frequencies of Internal Source.....	7
3.3 Features of EUT .....	7
3.4 Operating Modes of EUT and Determination of Worst Case Operating Mode .....	8
3.5 Test Program Used and Operation Descriptions .....	9
3.6 Connection Diagram of EUT and Peripheral Devices .....	9
3.7 Configuration of Peripheral Devices and Cable Connections .....	9
<b>4 Test Instruments .....</b>	<b>10</b>
4.1 Radiated Emissions up to 1 GHz .....	10
<b>5 Limits of Test Items.....</b>	<b>11</b>
5.1 Radiated Emissions up to 1 GHz .....	11
<b>6 Test Arrangements.....</b>	<b>12</b>
6.1 Radiated Emissions up to 1 GHz .....	12
<b>7 Test Results of Test Item .....</b>	<b>13</b>
7.1 Radiated Emissions up to 1 GHz .....	13
<b>8 Pictures of Test Arrangements .....</b>	<b>15</b>
<b>9 Information of the Testing Laboratories .....</b>	<b>16</b>

## Release Control Record

Issue No.	Description	Date Issued
FDBDKG-WTW-P22040386B	Original release.	2023/12/14

## 1 Certificate

**Product:** Wireless Keyboard

**Brand:** Logitech

**Test Model:** Y-R0067

**Sample Status:** Engineering sample

**Applicant:** Logitech Far East Ltd.

**Test Date:** 2023/10/28

**Standard:** 47 CFR FCC Part 15, Subpart B, Class B  
ANSI C63.4–2014  
ANSI C63.4a–2017

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

## 2 Summary of Test Results

The test items that the EUT needs to perform according to its difference information (see section 3.1, Note 1) with the original report evaluation are as follows:

Standard / Clause	Test Item	Result	Remark
FCC Part 15.109	Radiated Emissions up to 1 GHz	Pass	Minimum passing Class B margin is -5.79 dB at 923.53 MHz

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)	Maximum allowable uncertainty (±)
Radiated Emissions up to 1 GHz	30 MHz ~ 1 GHz	4.43 dB	6.3 dB ( $U_{\text{CISPR}}$ )

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

### 2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

### 3 General Information

#### 3.1 Description of EUT

Product	Wireless Keyboard
Brand	Logitech
Test Model	Y-R0067
Sample Status	Engineering sample
Operating Software	NA
Power Supply Rating	3 Vdc from battery
Accessory Device	NA
Data Cable Supplied	NA
Wireless Operating Frequency	2405MHz ~ 2474MHz

Note:

1. This is a supplementary report of Report No.: FC180115E03. The differences between them are as below information:
  - ◆ Inductors and capacitors will be changed from 0402 to 0201 size (include L1, L3, L2, C4, C5, C1, C2, C6, C7, C3, C10, C16)
  - ◆ Crystal XT1 package from PTH to SMD (mount method change): XT1, C12
2. According to above conditions and the applicant's requirement, only radiated emissions (up to 1GHz) test item needs to be performed. And all data are verified to meet the requirements.
3. The EUT may have a lot of colors for marketing requirement.
4. The product be supplied by primary alkaline batteries.

### 3.2 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 2474, provided by Logitech Far East Ltd., for detailed internal source, please refer to the manufacturer's specifications.

### 3.3 Features of EUT

The tests reported herein were performed according to the method specified by Logitech Far East Ltd., for detailed feature description, please refer to the manufacturer's specifications or user's manual.

### 3.4 Operating Modes of EUT and Determination of Worst Case Operating Mode

Test mode is presented in the report as below.


Test Condition	
Mode	Radiated Emissions up to 1 GHz
A	Typical Operation + Input Power(3 Vdc from battery) + Remark(Normal mode)



### 3.5 Test Program Used and Operation Descriptions

1. Turn on the power of all equipment.
2. EUT links with support unit A (PC) via wireless.
3. Support unit A (PC) runs "Note.exe" to check typical use condition of EUT via presses "H" key.
4. Support unit A (PC) runs "EMC test.exe" then sends "H" messages to support unit D (Monitor).

### 3.6 Connection Diagram of EUT and Peripheral Devices



### 3.7 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	PC	Lenovo	M710s	PC0YD3ZY	N/A	Provided by Lab
B	i-pod	Apple	MD778TA/A	CC4JMCMXF4T1	N/A	Provided by Lab
C	Printer	EPSON	LQ-300+II	G88Y074085	DoC	Provided by Lab
D	Monitor	LG	24UD58	806NTSU6H462	DoC	Provided by Lab
E	Mouse	Logitech	M-U0026	810-002182_002	DoC	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB-A cable	1	0.1	Yes	0	Provided by Lab
2	USB-A to B cable	1	1.8	Yes	0	Provided by Lab
3	DP cable	1	1.8	Yes	0	Provided by Lab
4	USB-A cable	1	1.8	Yes	0	Provided by Lab

## 4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.1 Radiated Emissions up to 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Table CT	N/A	N/A	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-358	2023/10/16	2024/10/15
		9168-359	2023/10/17	2024/10/16
Fixed Attenuator Mini-Circuits	UNAT-5+	CHF-001	2023/7/1	2024/6/30
Fixed attenuator Mini-Circuits	UNAT-5+	CHF-002	2023/7/1	2024/6/30
MXE EMI Receiver Agilent	N9038A	MY50010125	2023/3/24	2024/3/23
		MY50010132	2023/6/21	2024/6/20
Preamplifier Sonoma	310N	352925	2023/7/1	2024/6/30
		352926	2023/7/1	2024/6/30
RF Coaxial Cable PEWC	8D	8DCAB-001	2023/7/1	2024/6/30
	8D-FB	CHFCAB-001-1	2023/7/1	2024/6/30
		CHFCAB-001-3	2023/7/1	2024/6/30
		CHFCAB-001-4	2023/7/1	2024/6/30
		CHFCAB-002-1	2023/7/1	2024/6/30
		CHFCAB-002-3	2023/7/1	2024/6/30
		CHFCAB-002-4	2023/7/1	2024/6/30
		CHFCAB-003-1	2023/7/1	2024/6/30
		CHFCAB-003-3	2023/7/1	2024/6/30
Software BV	ADT_Radiated_V8.7.08	N/A	N/A	N/A

#### Notes:

1. The test was performed in HC - 10m Chamber 1. The test site validated date: 2023/6/29 (NSA)
2. The VCCI Site Registration No. is R-13252.
3. Tested Date: 2023/10/28

## 5 Limits of Test Items

### 5.1 Radiated Emissions up to 1 GHz

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B, Class A	FCC 15B, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39.1	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B, Class A	FCC 15B, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40.0	50.5	40.5
88-216	54.0	43.5		
216-230	56.9	46.0		
230-960			57.5	47.5
960-1000	60.0	54.0		


Notes: 1. The lower limit shall apply at the transition frequencies.

## 6 Test Arrangements

### 6.1 Radiated Emissions up to 1 GHz

- For the table-top EUT is placed on a 0.8 meter to the top of rotating table; for the floor standing EUT shall be insulated (by insulation of 12 mm) from the horizontal reference ground plane. The rotating table is rotated 360 degrees to determine the position of the highest radiation. If the equipment requires a dedicated ground connection, this shall be provided and bonded to the RGP.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is up to 1 GHz.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency up to 1GHz.



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

## 7 Test Results of Test Item

### 7.1 Radiated Emissions up to 1 GHz


#### Mode A

Frequency Range	30 MHz ~ 1 GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120 kHz
Input Power	3 Vdc from battery	Environmental Conditions	25°C, 63% RH
Tested By	Richard Huang		

Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	52.57	18.15 QP	30.00	-11.85	4.00 H	74	30.85	-12.70
2	212.55	24.14 QP	30.00	-5.86	3.00 H	71	38.61	-14.47
3	708.03	30.38 QP	37.00	-6.62	2.00 H	34	31.77	-1.39
4	746.08	30.11 QP	37.00	-6.89	1.00 H	317	30.20	-0.09
5	887.90	30.44 QP	37.00	-6.56	1.00 H	270	28.25	2.19
6	960.62	31.11 QP	37.00	-5.89	4.00 H	126	27.46	3.65

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.




Frequency Range	30 MHz ~ 1 GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120 kHz
Input Power	3 Vdc from battery	Environmental Conditions	25°C, 63% RH
Tested By	Richard Huang		

Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.29	22.16 QP	30.00	-7.84	1.00 V	76	36.54	-14.38
2	212.07	23.61 QP	30.00	-6.39	2.00 V	353	38.76	-15.15
3	593.99	26.72 QP	37.00	-10.28	1.00 V	343	29.73	-3.01
4	746.05	29.59 QP	37.00	-7.41	2.00 V	99	29.75	-0.16
5	923.53	31.21 QP	37.00	-5.79	1.00 V	264	27.76	3.45
6	979.79	30.76 QP	37.00	-6.24	3.00 V	193	26.19	4.57

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)  
– Pre-Amplifier Factor (dB)
3. Margin value = Emission level – Limit value
4. The other emission levels were very low against the limit.



## 8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

## 9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@bureauveritas.com](mailto:service.adt@bureauveritas.com)

**Web Site:** <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---