

# RF EXPOSURE Test Report

**Product:** 2-in-1 Car Wireless Charger

**Trade Mark:** N/A

**Model Number:** X19

**FCC ID:** 2BGF3-X19

**Prepared for**

Shenzhen Tengsay Technology Co., Ltd  
502, No.7, Xikeng South Road, Xikeng Community, Fucheng Street,  
Longhua District, Shenzhen, China

**Prepared by**

Shenzhen HongBiao Certification& Testing Co., Ltd  
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan  
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,  
China  
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110  
Website: <http://www.sz-hongbiao.com>

**Table of Contents**

**1 GENERAL DESCRIPTION ..... 5**

1.1 DESCRIPTION OF EUT ..... 5

1.2 TEST MODE..... 5

1.3 TEST SETUP ..... 5

1.4 ANCILLARY EQUIPMENT ..... 5

**2 TEST FACILITIES AND ACCREDITATIONS ..... 6**

2.1 TEST LABORATORY ..... 6

2.2 ENVIRONMENTAL CONDITIONS ..... 6

2.3 MEASUREMENT UNCERTAINTY ..... 6

2.4 TEST SOFTWARE ..... 6

**3 LIST OF TEST EQUIPMENT ..... 7**

**4 RF EXPOSURE..... 8**

4.1 MAXIMUM PERMISSIBLE EXPOSURE ..... 8

4.1.1. *Limit* ..... 8

4.1.2. *Test Procedures* ..... 8

4.1.3. *Test Setup*..... 9

4.1.4. *Test Result* ..... 9

**5 PHOTOGRAPHS OF THE TEST SETUP .....11**

## TEST RESULT CERTIFICATION

**Applicant's Name**..... : Shenzhen Tengsay Technology Co., Ltd  
**Address** ..... : 502, No.7, Xikeng South Road, Xikeng Community, Fucheng Street, Longhua District, Shenzhen, China  
**Manufacturer's Name** ..... : Shenzhen Tengsay Technology Co., Ltd  
**Address** ..... : 502, No.7, Xikeng South Road, Xikeng Community, Fucheng Street, Longhua District, Shenzhen, China

### Product description

**Product name** ..... : 2-in-1 Car Wireless Charger  
**Model Number** ..... : X19

**Standards** ..... : FCC CFR 47 PART 1 , 1.1310

**Test procedure**..... : KDB 680106 D01 Wireless Power Transfer v04


This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

**Date of Test**..... :

**Date (s) of performance of tests**..... : Dec. 17, 2024~ Dec. 24, 2024

**Test Result**..... : **Pass**

**Testing Engineer** :




( Z o e S u )

**Technical Manager** :



( G a r y L u )

**Authorized Signatory** :



( L e o S u )

[illegible]

## 1 General Description

### 1.1 Description of EUT

|                            |                                                                                 |
|----------------------------|---------------------------------------------------------------------------------|
| Product name:              | 2-in-1 Car Wireless Charger                                                     |
| Model name:                | X19                                                                             |
| Series Model:              | N/A                                                                             |
| Different of series model: | N/A                                                                             |
| Operation frequency:       | 111kHz-179kHz                                                                   |
| Operational mode:          | Wireless charging                                                               |
| Modulation type:           | ASK                                                                             |
| Antenna type:              | Coil Antenna                                                                    |
| Hardware version:          | V1.0                                                                            |
| Software version:          | V1.0                                                                            |
| Battery:                   | N/A                                                                             |
| Power supply:              | Input: DC 9V/3A<br>Wireless Output: 15W Max<br>Telescopic Cable Output: 10W Max |
| Adapter information:       | N/A                                                                             |

### 1.2 Test Mode

| Pretest Test Mode | Description of Mode                   |
|-------------------|---------------------------------------|
| 1                 | AC/DC Adapter + Wireless Output: 5W   |
| 2                 | AC/DC Adapter + Wireless Output: 7.5W |
| 3                 | AC/DC Adapter + Wireless Output: 10W  |
| 4                 | AC/DC Adapter + Wireless Output: 15W  |

### 1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

### 1.4 Ancillary Equipment

| Equipment | Model  | S/N                 | Manufacturer                            |
|-----------|--------|---------------------|-----------------------------------------|
| Adapter   | CD289  | 35810               | Ugreen Group Limited                    |
| Phone     | LE2120 | 8602840564<br>41073 | Shenzhen Oneplus<br>Technology Co., Ltd |

## 2 Test Facilities and Accreditations

### 2.1 Test Laboratory

|                       |                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Site             | Shenzhen HongBiao Certification& Testing Co., Ltd                                                                                                 |
| Test Site Location    | Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China |
| Telephone:            | (86-755) 2998 9321                                                                                                                                |
| Fax:                  | (86-755) 2998 5110                                                                                                                                |
| FCC Registration No.: | CN1341                                                                                                                                            |
| A2LA Certificate No.: | 6765.01                                                                                                                                           |

### 2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

|                    |              |
|--------------------|--------------|
| Temperature:       | 15°C~35°C    |
| Relative Humidity: | 20%~75%      |
| Air Pressure:      | 98kPa~101kPa |

### 2.3 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

| Measurement Frequency Range | U, (dB)            | Note |
|-----------------------------|--------------------|------|
| RF frequency                | $2 \times 10^{-5}$ |      |
| E-field                     | $\pm 1.06$ dB      |      |
| H-field                     | $\pm 0.7$ dB       |      |
| Temperature                 | $\pm 1$ degree     |      |
| Humidity                    | $\pm 5$ %          |      |

### 2.4 Test Software

| Software name | Manufacturer | Model    | Version  |
|---------------|--------------|----------|----------|
| EHP200-TS     | Narda        | EHP-200A | Rel 1.95 |

3 List of Test Equipment

| Item | Equipment No. | Equipment name                       | Manufacturer | Model    | Serial No. | Calibration date | Due date   |
|------|---------------|--------------------------------------|--------------|----------|------------|------------------|------------|
| 1    | HB-E073       | Electric and Magnetic Field Analyzer | Narda        | EHP-200A | 180ZX11013 | 2024-05-21       | 2025-05-20 |

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 4 RF Exposure

### 4.1 Maximum Permissible Exposure

#### 4.1.1. Limit

| Frequency range(MHz)                                         | Electric field strength(V/m) | Magnetic field strength(A/m) | Power density(mW/cm2) | Averaging time(minutes) |
|--------------------------------------------------------------|------------------------------|------------------------------|-----------------------|-------------------------|
| (A) Limits for Occupational/Controlled Exposure              |                              |                              |                       |                         |
| 0.3-3.0                                                      | 614                          | 1.63                         | *100                  | 6                       |
| 3.0-30                                                       | 1842/f                       | 4.89/f                       | *900/f <sup>2</sup>   | 6                       |
| 30-300                                                       | 61.4                         | 0.163                        | 1.0 6                 | 6                       |
| 300-1500                                                     | /                            | /                            | f/300                 | 6                       |
| 1500-100000                                                  | /                            | /                            | 5                     | 6                       |
| (B) Limits for General Population/Uncontrolled Exposure      |                              |                              |                       |                         |
| 0.3-1.34                                                     | 614                          | 1.63                         | *100                  | 30                      |
| 1.34-30                                                      | 824/f                        | 2.19/f                       | *180/f <sup>2</sup>   | 30                      |
| 30-300                                                       | 27.5                         | 0.073                        | 0.2                   | 30                      |
| 300-1500                                                     | /                            | /                            | f/1500                | 30                      |
| 1500-100000                                                  | /                            | /                            | 1                     | 30                      |
| f = frequency in MHz * = Plane-wave equivalent power density |                              |                              |                       |                         |

#### 4.1.2. Test Procedures

E and H-field measurements should be made with the center of the probe at a distance of 20 cm surrounding the device and 20 cm above the top surface of the primary/client pair.

These measurements should be repeated for three different client battery levels, 1%, 50%, and 99%.

Record the test results.

KDB 680106 D01 Wireless Power Transfer v04

(1) The power transfer frequency is below 1 MHz.

(2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.

(3) A client device providing the maximum permitted load is placed in physical contact with the transmitter(i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)

(4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).


(5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios

(i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.

(6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the

design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.

#### 4.1.3. Test Setup



#### 4.1.4. Test Result


Test condition: Mode 3 operating mode with client device (1 %, 50%, 99% battery status of client device)

| Maximum permissible Exposure |            |                   |               |              |
|------------------------------|------------|-------------------|---------------|--------------|
| Battery levels               | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <1%                          | Top        | 20                | 6.0501        | 0.0602       |
| <1%                          | Bottom     | 20                | 1.5884        | 0.0917       |
| <1%                          | Left       | 20                | 2.3570        | 0.0456       |
| <1%                          | Right      | 20                | 2.0222        | 0.0470       |
| <1%                          | Front      | 20                | 2.2871        | 0.0452       |
| <1%                          | Back       | 20                | 1.2897        | 0.0452       |
| Limit                        |            |                   | 614           | 1.63         |
| Margin Limit (%)             |            |                   | 0.99%         | 5.63%        |

| Maximum permissible Exposure |            |                   |               |              |
|------------------------------|------------|-------------------|---------------|--------------|
| Battery levels               | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <50%                         | Top        | 20                | 6.0498        | 0.0568       |
| <50%                         | Bottom     | 20                | 1.5875        | 0.0905       |
| <50%                         | Left       | 20                | 2.3564        | 0.0449       |
| <50%                         | Right      | 20                | 2.0214        | 0.0462       |
| <50%                         | Front      | 20                | 2.2854        | 0.0448       |
| <50%                         | Back       | 20                | 1.2878        | 0.0434       |
| Limit                        |            |                   | 614           | 1.63         |
| Margin Limit (%)             |            |                   | 0.99%         | 5.55%        |

| Maximum permissible Exposure |            |                   |               |              |
|------------------------------|------------|-------------------|---------------|--------------|
| Battery levels               | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <99%                         | Top        | 20                | 6.0463        | 0.0541       |
| <99%                         | Bottom     | 20                | 1.5852        | 0.0865       |
| <99%                         | Left       | 20                | 2.3540        | 0.0420       |
| <99%                         | Right      | 20                | 2.0201        | 0.0438       |
| <99%                         | Front      | 20                | 2.2828        | 0.0417       |
| <99%                         | Back       | 20                | 1.2856        | 0.0411       |
| Limit                        |            |                   | 614           | 1.63         |
| Margin Limit (%)             |            |                   | 0.98%         | 5.31%        |

5 Photographs of the Test Setup



\*\*\*\*\* END OF REPORT \*\*\*\*\*