



75 Years
IN RADIO
COMMUNICATIONS

11 February, 1999

Federal Communications Commission
Authorization & Evaluation Division
7435 Oakland Mills Road
Columbia, Maryland 21046

Gentlemen:

Reference: ATH 2425317 Models 242-5317 and 242-5318

This equipment meets the requirements of the FCC Rules, Parts 90.203(e) and (g), as applicable.

Programming of this products transmit frequencies can be performed ONLY by the manufacturer or by service or maintenance personnel. The operator cannot program transmit frequencies using the equipment's external operation controls.

EF JOHNSON Division
Transcrypt International, Inc.



Craig Szczutkowski
SR. Vice President,
Product & Market Development

Corporate Headquarters: Transcrypt International, Inc. • 4800 NW 1st Street • Lincoln, NE 68521
800-894-2615 • 402-474-4800 • Fax 402-474-4858

Operations Center: Transcrypt International, Inc. • 299 Johnson Avenue • Waseca, MN 56093
FCC-ID-1.DOC 800-328-3911 • 507-835-6222 • Fax 507-835-8356



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Sub-part
2.1033(c) :

EQUIPMENT IDENTIFICATION

FCC ID: ATH2425317

NAMEPLATE DRAWING

ATTACHED, EXHIBIT 1.

LOCATION

AS PER LABEL DRAWING(S)

DATE OF REPORT

June 7, 1999

SUPERVISED BY:

A handwritten signature in black ink, reading "Morton Flom P. Eng.", is written over a horizontal line.

Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.


TABLE OF CONTENTS

| <u>RULE</u> | <u>DESCRIPTION</u> | <u>PAGE</u> |
|----------------|--|-------------|
| | Test Report | 1 |
| 2.1033(c) | General Information Required | 2 |
| 2.1033(c) (14) | Rule Summary | 5 |
| | Standard Test Conditions and Engineering Practices | 6 |
| 2.1046(a) | Carrier Output Power (Conducted) | 7 |
| 2.1051 | Unwanted Emissions (Transmitter Conducted) | 9 |
| 2.1053(a) | Field Strength of Spurious Radiation | 12 |
| 2.1049(c) (1) | Emission Masks (Occupied Bandwidth) | 15 |
| 90.214 | Transient Frequency Behavior | 26 |
| 2.1047(a) | Audio Low Pass Filter (Voice Input) | 36 |
| 2.1047(a) | Audio Frequency Response | 39 |
| 2.1047(b) | Modulation Limiting | 41 |
| 2.1055(a) (1) | Frequency Stability (Temperature Variation) | 44 |
| 2.1055(b) (1) | Frequency Stability (Voltage Variation) | 47 |
| 2.202(g) | Necessary Bandwidth and Emission Bandwidth | 48 |

PAGE NO.

1 of 48.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

- a) TEST REPORT
- b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85224
- c) Report Number: d9960004
- d) Client: E. F. Johnson Company,
Division of Transcrypt International, Inc.
P.O. Box 1249
299 Johnson Ave.
Waseca, MN 56093-0514
- e) Identification: 242-5317 and 242-5318
FCC ID: ATH2425317
Description: VHF-FM Mobile Transceiver
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: June 7, 1999
EUT Received: June 1, 1999
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by: 
Morton Flom, P. Eng.
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 48.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

90

Sub-part 2.1033

(c) (1): NAME AND ADDRESS OF APPLICANT:

E. F. Johnson Company
299 Johnson Ave.
Waseca, MN 56093-0514

MANUFACTURER:

Applicant

(c) (2): FCC ID: ATH2425317

MODEL NO'S: 242-5317 and 242-5318

(c) (3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c) (4): TYPE OF EMISSION: 16K0F3E, 11K0F3E, 14K0F3E,
16K0F1E, 11K0F1E, 14K0F1E

(c) (5): FREQUENCY RANGE, MHz: 136 to 174


(c) (6): POWER RATING, Watts: 10 to 50
Switchable x Variable N/A

(c) (7): MAXIMUM POWER RATING, Watts: 300

PAGE NO.

3 of 48.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



**THE AMERICAN
ASSOCIATION
FOR LABORATORY
ACCREDITATION**

ACCREDITED LABORATORY

A2LA has accredited


M. FLOM ASSOCIATES, INC.
Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing


The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25:1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24th day of November, 1998.



Peter Maye
President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25:1990 AND EN 45001

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85224-1571
Morton Flom Phone: 602.926.3100

ELECTRICAL (EMC)

Valid to: December 31, 2000 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

| Tests | Standard(s) |
|-------------------------|---|
| RF Emissions | FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1633; AS/NZS 3548; AS/NZS 4251.1 |
| RF Immunity | EN 50082-1; EN 50082-2; AS/NZS 4251.1 |
| Radiated Susceptibility | EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3 |
| ESD | EN 61000-4-2; IEC 1000-4-2; IEC 801-2 |
| EFT | EN 61000-4-4; IEC 1000-4-4; IEC 801-4 |
| Surge | EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5 |
| 47 CFR (POC) | 2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97 |

Peter Maye

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8307 • Phone: 301.644.3288 • Fax: 301.662.2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

PAGE NO. 4 of 48.

Subpart 2.1033 (continued)

(c) (8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 13.8

(c) (9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c) (10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:
Including description of circuitry & devices provided for
determining and stabilizing frequency, for suppression of
spurious radiation, for limiting modulation and limiting
power.

PLEASE SEE ATTACHED EXHIBITS

(c) (11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c) (12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c) (13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 x N/A

(c) (14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 48.

Sub-part

2.1033(c) (14):

TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- _____ 21 - Domestic Public Fixed Radio Services
- _____ 22 - Public Mobile Services
- _____ 22 Subpart H - Cellular Radiotelephone Service
- _____ 22.901(d) - Alternative technologies and auxiliary services
- _____ 23 - International Fixed Public Radiocommunication services
- _____ 24 - Personal Communications Services
- _____ 74 Subpart H - Low Power Auxiliary Stations
- _____ 80 - Stations in the Maritime Services
- _____ 80 Subpart E - General Technical Standards
- _____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- _____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- _____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- _____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- _____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- _____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- _____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- _____ 80 Subpart X - Voluntary Radio Installations
- _____ 87 - Aviation Services
- x 90 - Private Land Mobile Radio Services
- _____ 94 - Private Operational-Fixed Microwave Service
- _____ 95 Subpart A - General Mobile Radio Service (GMRS)
- _____ 95 Subpart C - Radio Control (R/C) Radio Service
- _____ 95 Subpart D - Citizens Band (CB) Radio Service
- _____ 95 Subpart E - Family Radio Service
- _____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- _____ 101 - Fixed Microwave Services

PAGE NO.

6 of 48.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 48.

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: 47 CFR 2.1046(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(Worst case)

FREQUENCY OF CARRIER, MHz = 155.03, 136.03, 173.97

| <u>POWER SETTING</u> | <u>R. F. POWER, WATTS</u> |
|----------------------|---------------------------|
| Low | 10 |
| High | 50 |

SUPERVISED BY:

Morton Flom P. Eng.


Morton Flom, P. Eng.

PAGE NO.

8 of 48.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



| Asset | Description | s/n |
|----------|--------------------------------|------------|
| (1) | <u>COAXIAL ATTENUATOR</u> | |
| — | i00122 Narda 766-10 | 7802 |
| — | i00123 Narda 766-10 | 7802A |
| — | i00069 Bird 8329 (30 dB) | 1006 |
| <u>x</u> | i00113 Sierra 661A-3D | 1059 |
| (2) | <u>POWER METERS</u> | |
| — | i00014 HP 435A | 1733A05836 |
| <u>x</u> | i00039 HP 436A | 2709A26776 |
| <u>x</u> | i00020 HP 8901A POWER MODE | 2105A01087 |
| (3) | <u>FREQUENCY COUNTER</u> | |
| — | i00042 HP 5383A | 1628A00959 |
| <u>x</u> | i00019 HP 5334B | 2704A00347 |
| <u>x</u> | i00020 HP 8901A FREQUENCY MODE | 2105A01087 |

PAGE NO. 9 of 48.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.

3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 155.03, 136.03, 173.97

SPECTRUM SEARCHED, GHz = 0 to 10 x F_c

MAXIMUM RESPONSE, Hz = 2820

ALL OTHER EMISSIONS = ≥ 20 dB BELOW LIMIT

LIMIT(S), dBc

$$-(50 + 10 \times \text{LOG } P) = -60 \text{ (10 Watts)}$$

$$-(50 + 10 \times \text{LOG } P) = -67 \text{ (50 Watts)}$$

SUPERVISED BY:

Morton Flom P. Eng.


Morton Flom, P. Eng.

PAGE NO.

10 of 48.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



| Asset | Description | s/n |
|---------------------------------------|--------------------------|------------|
| (1) <u>AUDIO OSCILLATOR/GENERATOR</u> | | |
| — | i00010 HP 204D | 1105A04683 |
| — | i00017 HP 8903A | 2216A01753 |
| x | i00012 HP 3312A | 1432A11250 |
| (2) <u>COAXIAL ATTENUATOR</u> | | |
| — | i00122 Narda 766-10 | 7802 |
| — | i00123 Narda 766-10 | 7802A |
| x | i00069 Bird 8329 (30 dB) | 1006 |
| x | i00113 Sierra 661A-3D | 1059 |
| (3) <u>FILTERS; NOTCH, HP, LP, BP</u> | | |
| x | i00126 Eagle TNF-1 | 100-250 |
| x | i00125 Eagle TNF-1 | 50-60 |
| x | i00124 Eagle TNF-1 | 250-850 |
| (4) <u>SPECTRUM ANALYZER</u> | | |
| x | i00048 HP 8566B | 2511A01467 |
| — | i00029 HP 8563E | 3213A00104 |

PAGE NO.

11 of 48.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g9960019: 1999-Jun-02 Wed 11:57:00
 STATE: 1:Low Power

| FREQUENCY TUNED, MHz | FREQUENCY EMISSION, MHz | LEVEL, dBm | LEVEL, dBc | MARGIN, dB |
|-------------------------|----------------------------|------------|------------|------------|
| 155.030000 | 309.999000 | -35.2 | -75.2 | -15.0 |
| 155.030000 | 464.680000 | -35.5 | -75.5 | -15.0 |
| 155.030000 | 620.598000 | -35.5 | -75.5 | -15.0 |
| 155.030000 | 775.476000 | -34.9 | -74.9 | -15.0 |
| 155.030000 | 929.880000 | -35.2 | -75.2 | -15.0 |
| 155.030000 | 1085.471000 | -35 | -75 | -15.0 |
| 155.030000 | 1240.539000 | -34.6 | -74.6 | -15.0 |
| 155.030000 | 1395.567000 | -34.6 | -74.6 | -15.0 |
| 155.030000 | 1550.044000 | -34 | -74 | -14.0 |
| 155.030000 | 1705.677000 | -34.9 | -74.9 | -14.0 |
| 155.030000 | 1860.165000 | -34.4 | -74.4 | -14.0 |
| 155.030000 | 2015.348000 | -34.9 | -74.9 | -14.0 |
| 155.030000 | 2170.013000 | -33.6 | -73.6 | -13.0 |
| 155.030000 | 2325.721000 | -33.9 | -73.9 | -13.0 |

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g9960018: 1999-Jun-02 Wed 11:54:00
 STATE: 2:High Power

| FREQUENCY TUNED, MHz | FREQUENCY EMISSION, MHz | LEVEL, dBm | LEVEL, dBc | MARGIN, dB |
|-------------------------|----------------------------|------------|------------|------------|
| 155.030000 | 310.205000 | -34.4 | -81.3 | -14.0 |
| 155.030000 | 464.839000 | -33.7 | -80.6 | -14.0 |
| 155.030000 | 619.739000 | -34.6 | -81.5 | -14.0 |
| 155.030000 | 774.826000 | -33.9 | -80.8 | -14.0 |
| 155.030000 | 930.479000 | -33.6 | -80.5 | -14.0 |
| 155.030000 | 1084.711000 | -34.2 | -81.1 | -14.0 |
| 155.030000 | 1240.269000 | -33.7 | -80.6 | -14.0 |
| 155.030000 | 1395.735000 | -33.8 | -80.7 | -14.0 |
| 155.030000 | 1550.102000 | -33.6 | -80.5 | -14.0 |
| 155.030000 | 1705.163000 | -33.6 | -80.5 | -14.0 |
| 155.030000 | 1860.825000 | -32.5 | -79.4 | -13.0 |
| 155.030000 | 2015.839000 | -33.9 | -80.8 | -13.0 |
| 155.030000 | 2170.193000 | -32.9 | -79.8 | -13.0 |
| 155.030000 | 2325.441000 | -32 | -78.9 | -13.0 |

PAGE NO. 12 of 48.
NAME OF TEST: Field Strength of Spurious Radiation
SPECIFICATION: 47 CFR 2.1053(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.12
TEST EQUIPMENT: As per attached page


MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 2.948, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. Excess power leads were coiled near the power supply.

The cables were oriented in order to obtain the maximum response. At each emission frequency, the turntable was rotated and the search antennas were raised and lowered vertically.
4. The emission was observed with both a vertically polarized and a horizontally polarized search antenna and the worst case was used.
6. The field strength of each emission within 20 dB of the limit was recorded and corrected with the appropriate cable and transducer factors.
7. The worst case for all channels is shown.
8. Measurement results: ATTACHED FOR WORST CASE

PAGE NO.

13 of 48.

RADIATED TEST SETUP

NOTES:

- (a) Search Antenna - Rotatable on boom
 (b) Non-metallic boom
 (c) Non-metallic mast
 (d) Adjustable horizontally
 (e) Equipment Under Test
 (f) Turntable
 (g) Boom adjustable in height.
 (h) External control cables routed horizontally at least one wavelength.
 (i) Rotatable
 (j) Cables routed through hollow turntable center
 (k) 30 cm or less
 (l) External power source
 (m) 10 cm diameter coil of excess cable
 (n) 25 cm (V), 1 m-7 m (V, H)
 (o) 25 cm from bottom end of 'V', 1m normally
 (p) Calibrated Cable at least 10m in length
 (q) Amplifier (optional)
 (r) Spectrum Analyzer

| Asset | Description | s/n | Cycle | Last Cal |
|-----------------------------|-----------------------------------|------------|--------|----------|
| Per ANSI C63.4-1992, 10.1.4 | | | | |
| <u>TRANSDUCER</u> | | | | |
| _____ | i00065 EMCO 3109B 100Hz-50MHz | 2336 | 12 mo. | |
| _____ | i00033 Singer 94593-1 10kHz-32MHz | 0219 | 12 mo. | |
| _____ | x i00088 EMCO 3109-B 25MHz-300MHz | 2336 | 12 mo. | Oct-98 |
| _____ | x i00089 April 2001 200MHz-1GHz | 001500 | 12 mo. | Oct-98 |
| _____ | x i00103 EMCO 3115 1GHz-18GHz | 9208-3925 | 12 mo. | Oct-98 |
| _____ | i00085 EMCO 3116 10GHz-40GHz | 2076 | 12 mo. | |
| <u>AMPLIFIER</u> | | | | |
| _____ | i00028 HP 8449A | 2749A00121 | 12 mo. | Mar-99 |
| <u>SPECTRUM ANALYZER</u> | | | | |
| _____ | i00029 HP 8563E | 3213A00104 | 12 mo. | Aug-98 |
| _____ | x i00033 HP 85462A | 3625A00357 | 12 mo. | Dec-98 |
| _____ | i00048 HP 8566B | 2511AD1467 | 6 mo. | Dec-98 |

PAGE NO. 14 of 48.

NAME OF TEST: Field Strength of Spurious Radiation

ALL OTHER EMISSIONS = ≥ 20 dB BELOW LIMIT

| EMISSION, MHz/HARMONIC | SPURIOUS LEVEL, dBc | |
|------------------------|---------------------|------|
| | Low | High |
| 2nd to 10th | <-70 | <-75 |

SUPERVISED BY:

Morton Flom, P. Eng.

Morton Flom, P. Eng.

PAGE NO. 15 of 48.
NAME OF TEST: Emission Masks (Occupied Bandwidth)
SPECIFICATION: 47 CFR 2.1049(c)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ± 2.5 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

16 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960013: 1999-Jun-02 Wed 11:29:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
NONE

SUPERVISED BY:


M. Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO.

17 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960015: 1999-Jun-02 Wed 11:32:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz,
w/LPF

SUPERVISED BY:




Morton Flom, P. Eng.

PAGE NO.

18 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960017: 1999-Jun-02 Wed 11:39:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW

SUPERVISED BY:


Morton Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO.

19 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960021: 1999-Jun-02 Wed 13:41:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
DIGITIZED VOICE
MASK: C, VHF/UHF 25kHz, no
LPF


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

20 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960023: 1999-Jun-02 Wed 13:46:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
DIGITIZED VOICE
MASK: D, VHF/UHF 12.5kHz BW


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

21 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960012: 1999-Jun-02 Wed 11:27:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
NONE


SUPERVISED BY:

M. Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO.

22 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960014: 1999-Jun-02 Wed 11:31:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz,
w/LPF

SUPERVISED BY:


Morton Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO.

23 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g9960016: 1999-Jun-02 Wed 11:37:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: D, VHF/UHF 12.5kHz BW


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

24 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g9960020: 1999-Jun-02 Wed 13:39:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 DIGITIZED VOICE
 MASK: C, VHF/UHF 25kHz, no
 LPF


SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO.

25 of 48.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g9960022: 1999-Jun-02 Wed 13:44:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 DIGITIZED VOICE
 MASK: D, VHF/UHF 12.5kHz BW

SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO. 26 of 48.
NAME OF TEST: Transient Frequency Behavior
SPECIFICATION: 47 CFR 90.214
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a guide.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:

| | |
|-------------|---------|
| step f, dBm | = -13.6 |
| step h, dBm | = -46.2 |
| step l, dBm | = 4.3 |




SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

27 of 48.


TRANSIENT FREQUENCY BEHAVIOR

| Asset | Description | s/n |
|-------|-------------------------------------|------------|
| (1) | ATTENUATOR (Removed after 1st step) | |
| x | i00112 Philco 30 dB | 989 |
| (2) | ATTENUATOR | |
| | i00112 Philco 30 dB | 989 |
| | i00172 Bird 30 dB | 989 |
| x | i00122 Narda 10 dB | 7802 |
| | i00123 Narda 10 dB | 7802A |
| | i00110 Kay Variable | 145-387 |
| (3) | COMBINER | |
| x | i00154 4 x 25 Ω COMBINER | 154 |
| (4) | CRYSTAL DETECTOR | |
| x | i00159 HP 8470B | 1822A10054 |
| (5) | RF SIGNAL GENERATOR | |
| | i00018 HP 8656A | 2228A03472 |
| | i00031 HP 8656A | 2402A06180 |
| x | i00067 HP 8920A | 3345U01242 |
| (6) | MODULATION ANALYZER | |
| x | i00020 HP 8901A | 2105A01087 |
| (7) | SCOPE | |
| x | i00030 HP 54502A | 2927A00209 |

PAGE NO.

28 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960039: 1999-Jun-02 Wed 16:36:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME


SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO.

29 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960036: 1999-Jun-02 Wed 16:32:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME

SUPERVISED BY:


M. Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO.

30 of 48.

NAME OF TEST: Transient Frequency Behavior
g9960033: 1999-Jun-02 Wed 16:23:00
STATE: 0:General



POWER:
MODULATION:
DESCRIPTION:

n/a
Ref Gen=25 kHz Deviation
CARRIER ON TIME


SUPERVISED BY:

M. Flom P. Eng.
Morton Flom, P. Eng.

PAGE NO.

31 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960034: 1999-Jun-02 Wed 16:24:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME


SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO.

32 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960031: 1999-Jun-02 Wed 16:15:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME DIGITIZED
 VOICE


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

33 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960028: 1999-Jun-02 Wed 16:02:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME DIGITIZED
 VOICE


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

34 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960025: 1999-Jun-02 Wed 15:27:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME DIGITIZED
 VOICE


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

35 of 48.

NAME OF TEST: Transient Frequency Behavior
 g9960027: 1999-Jun-02 Wed 15:35:00
 STATE: 0:General



POWER:
 MODULATION:
 DESCRIPTION:

n/a
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME DIGITIZED
 VOICE

SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO. 36 of 48.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

37 of 48.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
 TEST B. AUDIO FREQUENCY RESPONSE
 TEST C. HUM AND NOISE LEVEL
 TEST D. RESPONSE OF LOW PASS FILTER
 TEST E. MODULATION LIMITING



Asset Description


s/n

| | |
|---------------------------------|--------------|
| (1) <u>Audio Oscillator</u> | |
| <u>i00010</u> HP 204D | 1105A04683 |
| <u>x</u> i00017 HP 8903A | 2216A01753 |
| <u>x</u> i00118 HP 33120A | US36002064 |
| | |
| (2) <u>COAXIAL ATTENUATOR</u> | |
| <u>i00122</u> NARDA 766-10 | 7802 |
| <u>i00123</u> NARDA 766-10 | 7802A |
| <u>x</u> i00113 SIERRA 661A-3D | 1059 |
| <u>i00069</u> BIRD 8329 (30 dB) | 10066 |
| | |
| (3) <u>MODULATION ANALYZER</u> | |
| <u>x</u> i00020 HP 8901A | 2105A01087 |
| | |
| (4) <u>AUDIO ANALYZER</u> | |
| <u>x</u> i00017 HP 8903A | 2216A01753 |
| | |
| (5) <u>SCOPE</u> | |
| <u>i00058</u> HP 1741A | 2215A09356 |
| <u>i00071</u> Tektronix 935 | 1935-B011343 |

PAGE NO.

38 of 48.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g9960002: 1999-Jun-02 Wed 10:25:00
STATE: 0:General



SUPERVISED BY:

M. Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO. 39 of 48.
NAME OF TEST: Audio Frequency Response
SPECIFICATION: 47 CFR 2.1047(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

40 of 48.

NAME OF TEST: Audio Frequency Response
 g9960003: 1999-Jun-02 Wed 10:28:00
 STATE: 0:General



Additional points:

| FREQUENCY, Hz | LEVEL, dB |
|---------------|-----------|
| 300 | -9.52 |
| 20000 | -34.53 |
| 30000 | -34.66 |
| 50000 | -34.44 |

Morton Flom P. Eng.

Morton Flom, P. Eng.

SUPERVISED BY:

PAGE NO. 41 of 48.
NAME OF TEST: Modulation Limiting
SPECIFICATION: 47 CFR 2.1047(b)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


42 of 48.

NAME OF TEST: Modulation Limiting
 g9960004: 1999-Jun-02 Wed 10:33:00
 STATE: 0:General

Positive
 Peaks:



Negative
 Peaks:



Morton Flom P. Eng.

Morton Flom, P. Eng.


SUPERVISED BY:

PAGE NO.


43 of 48.

NAME OF TEST: Modulation Limiting
 g9960005: 1999-Jun-02 Wed 10:37:00
 STATE: 0:General

Positive
 Peaks:



Negative
 Peaks:



Morton Flom P. Eng

Morton Flom, P. Eng.

SUPERVISED BY:

PAGE NO. 44 of 48.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

45 of 48.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY
 TEST B. CARRIER FREQUENCY STABILITY
 TEST C. OPERATIONAL PERFORMANCE STABILITY
 TEST D. HUMIDITY
 TEST E. VIBRATION
 TEST F. ENVIRONMENTAL TEMPERATURE
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




| Asset | Description | s/n |
|-------|----------------------------------|--------------|
| (1) | TEMPERATURE, HUMIDITY, VIBRATION | |
| x | i00027 Tenny Temp. Chamber | 9083-765-234 |
| — | i00 Weber Humidity Chamber | |
| — | i00 L.A.B. RVH 18-100 | |
| (2) | COAXIAL ATTENUATOR | |
| — | i00122 NARDA 766-10 | 7802 |
| — | i00123 NARDA 766-10 | 7802A |
| x | i00113 SIERRA 661A-3D | 1059 |
| — | i00069 BIRD 8329 (30 dB) | 10066 |
| (3) | R.F. POWER | |
| — | i00014 HP 435A POWER METER | 1733A05839 |
| x | i00039 HP 436A POWER METER | 2709A26776 |
| x | i00020 HP 8901A POWER MODE | 2105A01087 |
| (4) | FREQUENCY COUNTER | |
| — | i00042 HP 5383A | 1628A00959 |
| x | i00019 HP 5334B | 2704A00347 |
| x | i00020 HP 8901A | 2105A01087 |

PAGE NO.

46 of 48.

NAME OF TEST: Frequency Stability (Temperature Variation)
g9960009: 1999-Jun-03 Thu 12:27:00
STATE: 0:General



SUPERVISED BY:

M. Flom P. Eng.

Morton Flom, P. Eng.

PAGE NO. 47 of 48.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b) (1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at 25±5°C and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)
 g9960011: 1999-Jun-02 Wed 11:04:44
 STATE: 0:General

LIMIT, ppm = 2.5
 LIMIT, Hz = 388
 BATTERY END POINT (Voltage) = 11.6

| % of STV | Voltage | Frequency, MHz | Change, Hz | Change, ppm |
|----------|---------|----------------|------------|-------------|
| 85 | 11.73 | 155.037420 | 0 | 0.00 |
| 100 | 13.8 | 155.037420 | 0 | 0.00 |
| 115 | 15.87 | 155.037430 | 10 | 0.06 |
| 84 | 11.6 | 155.037440 | 20 | 0.13 |

Morton Flom P. Eng.

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 47 of 48.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

| | |
|--|-------------------------|
| MAXIMUM MODULATION (M), kHz | = 3 |
| MAXIMUM DEVIATION (D), kHz | = 5 |
| CONSTANT FACTOR (K) | = 1 |
| NECESSARY BANDWIDTH (B _N), kHz | = (2 x M) + (2 x D x K) |
| | = 16.0 |

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

| | |
|--|-------------------------|
| MAXIMUM MODULATION (M), kHz | = 3 |
| MAXIMUM DEVIATION (D), kHz | = 2.5 |
| CONSTANT FACTOR (K) | = 1 |
| NECESSARY BANDWIDTH (B _N), kHz | = (2 x M) + (2 x D x K) |
| | = 11.0 |

MODULATION = 14K0F3E

NECESSARY BANDWIDTH CALCULATION:

| | |
|--|-------------------------|
| MAXIMUM MODULATION (M), kHz | = 3 |
| MAXIMUM DEVIATION (D), kHz | = 4 |
| CONSTANT FACTOR (K) | = 1 |
| NECESSARY BANDWIDTH (B _N), kHz | = (2 x M) + (2 x D x K) |
| | = 14 |

MODULATION = 16K0F1E

NECESSARY BANDWIDTH:

| | |
|--|------|
| NECESSARY BANDWIDTH (B _N), kHz | = 16 |
| (measured at the 99.75% power bandwidth) | |

MODULATION = 11K0F1E

NECESSARY BANDWIDTH:

| | |
|--|------|
| NECESSARY BANDWIDTH (B _N), kHz | = 11 |
| (measured at the 99.75% power bandwidth) | |

MODULATION = 14K0F1E

NECESSARY BANDWIDTH:

| | |
|--|------|
| NECESSARY BANDWIDTH (B _N), kHz | = 14 |
| (measured at the 99.75% power bandwidth) | |

Morton Flom, P. Eng.

SUPERVISED BY:

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:

A handwritten signature in black ink, appearing to read "M. Flom P. Eng.", with a horizontal line drawn underneath the signature.

Morton Flom, P. Eng.

STATEMENT OF QUALIFICATIONS

EDUCATION:

1. B. ENG. in ENGINEERING PHYSICS, 1949, McGill University, Montreal, Canada.
2. Post Graduate Studies, McGill University & Sir George Williams University, Montreal.

PROFESSIONAL AFFILIATIONS:

1. ARIZONA SOCIETY OF PROFESSIONAL ENGINEERS (NSPE), #026 031 821.
2. ORDER OF ENGINEERS (QUEBEC) 1949. #45 34.
3. ASSOCIATION OF PROFESSIONAL ENGINEERS, GEOPHYSICISTS & GEOLOGISTS OF ALBERIA #5916.
4. REGISTERED ENGINEERING CONSULTANT - INDUSTRY CANADA, Certification & Engineering Bureau.
5. IEEE, Lifetime member no. 041/204 (Member since 1947).

EXPERIENCE:

1. Research/Development/Senior Project Engineer. R.C.A. LIMITED (4 years).
2. Owner/Chief Engineer of Electronics. Design/Manufacturing & Cable TV Companies (10 years)
3. CONSULTING ENGINEER (over 25 years).



MORTON FLOM, P. Eng.