



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

Test Report

Report No. : CQASZ20201200043EX-01

Applicant: Midmark RTLS Solutions, Inc.

Address of Applicant: 2600 Miller Creek Dr., Traverse City, MI 49684

Manufacturer: MOKO TECHNOLOGY LIMITED

Address of Manufacturer: 2F, Building1, No.37 Xiaxintang Xintang village, Fucheng Street, Longhua District, Shenzhen, Guangdong Province, China

Factory: MOKO TECHNOLOGY LIMITED

Address of Factory: 2F, Building1, No.37 Xiaxintang Xintang village, Fucheng Street, Longhua District, Shenzhen, Guangdong Province, China

Equipment Under Test (EUT):

Product: Plug-In BLE Sensor

Model No.: VER5800

Brand Name: N/A

FCC ID: OGUVER5800

Standards: 47 CFR Part 15, Subpart C

Date of Test: 2020-02-17 to 2020-02-28

Date of Issue: 2020-12-11

Test Result : PASS*

Tested By:

Tom Chen

(Tom chen)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200200089E-01	Rev.01	Initial report	2020-03-02
CQASZ20201101383E-01	Rev.02	For specific changes, please refer to the note1	2020-11-20
CQASZ20201200043EX-01	Rev.03	For specific changes, please refer to the note2	2020-12-11

Note1:

	Before change	After change
Item number	CQASZ20200200089E-01	CQASZ20201101383E-01
Applicant:	MOKO TECHNOLOGY LIMITED	Royal Hydroponics LLC
Address of Applicant:	2F, Building1, No.37 Xiaxintang Xintang village, Fucheng Street, Longhua District, Shenzhen, Guangdong Province, China	121 Leavitt Road Suite 148 Amherst, OH 44001
EUT Name:	Bluetooth Gateway Plug Mini	HydroMesh Smart Plug
Model No.	MK110	HSP110
Brand Name:	N/A	by Royal Hydroponics

Note2:

	Before change	After change
Item number	CQASZ20201101383E-01	CQASZ20201200043EX-01
Applicant:	Royal Hydroponics LLC	Midmark RTLS Solutions, Inc.
Address of Applicant:	121 Leavitt Road Suite 148 Amherst, OH 44001	2600 Miller Creek Dr., Traverse City, MI 49684
EUT Name:	HydroMesh Smart Plug	Plug-In BLE Sensor
Model No.	HSP110	VER5800
Brand Name:	by Royal Hydroponics	N/A

This test report (Ref. No.: CQASZ20201200043EX-01) All test data comes from source test reports (Ref. No.: CQASZ20200200089E-01). Only on the basis of the original report change Applicant and Address of Applicant. The tested samples have not been changed, it's just a different model name.

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 DUTY CYCLE	8
4.4 DESCRIPTION OF SUPPORT UNITS	11
4.5 TEST LOCATION	11
4.6 TEST FACILITY	11
4.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY	12
4.8 DEVIATION FROM STANDARDS	12
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	12
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	12
4.11 EQUIPMENT LIST	13
5 TEST RESULTS AND MEASUREMENT DATA	14
5.1 ANTENNA REQUIREMENT	14
5.2 CONDUCTED EMISSIONS	15
5.3 CONDUCTED PEAK OUTPUT POWER	19
5.4 6dB OCCUPY BANDWIDTH	21
5.5 POWER SPECTRAL DENSITY	31
5.6 RADIATED SPURIOUS EMISSIONS	37
5.6.1 Radiated emission below 1GHz	40
5.6.2 Transmitter emission above 1GHz	42
5.7 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	44
6 PHOTOGRAPHS - EUT TEST SETUP	50
6.1 RADIATED SPURIOUS EMISSION	50
6.2 CONDUCTED EMISSION	51
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	52

4 General Information

4.1 Client Information

Applicant:	Midmark RTLS Solutions, Inc.
Address of Applicant:	2600 Miller Creek Dr., Traverse City, MI 49684
Manufacturer:	MOKO TECHNOLOGY LIMITED
Address of Manufacturer:	2F, Building1, No.37 Xiaxintang Xintang village, Fucheng Street, Longhua District, Shenzhen, Guangdong Province, China

4.2 General Description of EUT

Product Name:	Plug-In BLE Sensor					
Model No.:	VER5800					
Trade Mark:	N/A					
Type of Modulation:	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) BLE(GFSK)					
Channel Spacing:	IEEE 802.11b/g/n(HT20):20MHz IEEE 802.11n(HT40):40MHz BLE:2MHz					
Operation Frequency:	IEEE 802.11b;IEEE 802.11g;IEEE 802.11n HT20					
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
	1	2412	6	2437	11	2462
	2	2417	7	2442		
	3	2422	8	2447		
	4	2427	9	2452		
	5	2432	10	2457		
	IEEE 802.11n HT40					
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
	1	2422	4	2437	7	2452
	2	2427	5	2442		
	3	2432	6	2447		
	BLE					

		Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	
		1	2402	2	2404	
		3	2406	4	2408	
		5	2410	6	2412	
		7	2414	8	2416	
		9	2418	10	2420	
		11	2422	12	2424	
		13	2426	14	2428	
		15	2430	16	2432	
		17	2434	18	2436	
		19	2438	20	2440	
		21	2442	22	2444	
		23	2446	24	2448	
		25	2450	26	2452	
		27	2454	28	2456	
		29	2458	30	2460	
		31	2462	32	2464	
		33	2466	34	2468	
		35	2470	36	2472	
		37	2474	38	2476	
		39	2478	40	2480	
Antenna Type:	PCB antenna					
Antenna:	0 dBi gain					
Power Supply:	AC 120V/60Hz					

For 802.11b/g/n (HT20,HT40):

Test mode	Low Channel	Middle Channel	High Channel
IEEE 802.11b;IEEE 802.11g;IEEE 802.11n HT20	2412MHz	2437MHz	2462MHz
IEEE 802.11n HT40	2422MHz	2437MHz	2452MHz

Note:

1. Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.
2. In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on X-plane.


4.3 Duty Cycle

Temperature	25°C	Relative Humidity	55%	Test Voltage	120V/60Hz
Mode	Fre(MHz)	On time(ms)	Total Time(ms)	Duty Cycle	Duty Factor
802.11b	2437	8.26090	8.31880	99.30%	0.00
802.11g	2437	1.37681	1.53623	89.62%	0.48
802.11n HT20	2437	1.28986	1.38406	93.19%	0.31
802.11n HT40	2437	0.64058	0.75942	84.35%	0.74


Note:

1. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle ≥ 98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor(consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. The on-time time is transmission duration(T).


802.11b 2437MHz




802.11g 2437MHz



802.11n HT20 2437MHz



802.11n HT40 2437MHz



4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
N/A	N/A	N/A	N/A	N/A

4.5 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **ISED Registration No.: 22984-1**

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2019/10/2 5	2020/10/2 4
Spectrum analyzer	R&S	FSU26	CQA-038	2019/10/2 5	2020/10/2 4
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2019/10/2 5	2020/10/2 4
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2019/10/2 1	2020/10/2 0
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2019/9/26	2020/9/25
Bilog Antenna	R&S	HL562	CQA-011	2019/9/26	2020/9/25
Horn Antenna	R&S	HF906	CQA-012	2019/9/25	2020/9/24
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2019/9/26	2020/9/25
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2019/9/26	2020/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2019/9/26	2020/9/25
Antenna Connector	CQA	RFC-01	CQA-080	2019/9/26	2020/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2019/9/26	2020/9/25
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2019/9/26	2020/9/25
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2019/9/26	2020/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2019/10/2 3	2020/10/2 2
EMI Test Receiver	R&S	ESPI3	CQA-013	2019/9/26	2020/9/25
LISN	R&S	ENV216	CQA-003	2019/10/2 5	2020/10/2 4
Coaxial cable	CQA	N/A	CQA-C009	2019/10/2 5	2020/10/2 4

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.


5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is a PCB antenna. Antenna Gain : 0dBi	


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207,		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		

Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find at lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data


Live Line:



No.	Frequency (MHz)	Reading (dBuV)	Lisn/Isn (dB)	Cab_L (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1590	31.31	9.6	0.22	41.13	55.52	-14.39	AVG	
2	0.1635	40.28	9.6	0.22	50.10	65.28	-15.18	QP	
3	0.1995	29.92	9.6	0.23	39.75	53.63	-13.88	AVG	
4	0.2040	38.17	9.6	0.23	48.00	63.45	-15.45	QP	
5	0.2220	37.87	9.6	0.23	47.70	62.74	-15.04	QP	
6	0.2265	29.11	9.6	0.23	38.94	52.58	-13.64	AVG	
7	0.3120	36.96	9.6	0.24	46.80	59.92	-13.12	QP	
8	0.3255	30.13	9.6	0.24	39.97	49.57	-9.60	AVG	
9	0.3660	38.47	9.59	0.24	48.30	58.59	-10.29	QP	
10	0.3660	31.98	9.59	0.24	41.81	48.59	-6.78	AVG	
11	0.4065	31.52	9.58	0.24	41.34	47.72	-6.38	AVG	
12	0.4110	38.78	9.58	0.24	48.60	57.63	-9.03	QP	

Remarks: 1. Result=Reading+Lisn+Cab_L
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Neutral Line:



Remarks: 1. Result=Reading+Lisn+Cab_L

2. If the average limit is met when using a quasi-peak detector.
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <pre> graph LR EUT[EUT] --- PM[Power Meter] </pre>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20/HT40) ; Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Measurement Data

Test Mode	CH	Conducted Power (dBm)	Duty Factor	Result (dBm)	Limit (dBm)
IEEE 802.11 b	CH1	13.72	0	13.72	30
	CH6	13.85	0	13.85	30
	CH11	13.16	0	13.16	30
IEEE 802.11 g	CH1	10.81	0.48	11.29	30
	CH6	10.12	0.48	10.60	30
	CH11	10.46	0.48	10.94	30
IEEE 802.11 n HT20	CH1	9.63	0.31	9.94	30
	CH6	9.83	0.31	10.14	30
	CH11	9.76	0.31	10.07	30
IEEE 802.11 n HT40	CH1	6.71	0.74	7.45	30
	CH4	7.42	0.74	8.16	30
	CH7	7.60	0.74	8.34	30
Conclusion: PASS					

5.4 6dB Occupy Bandwidth




Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 1, Connected the EUT's antenna port to spectrum analyzer device. 2, Follow the test procedure as described in KDB 558074 (1). Set resolution bandwidth (RBW) = 100 kHz. (2). Set the video bandwidth (VBW) $\geq 3 \times$ RBW. (3). Detector = Peak. (4). Trace mode = max hold. (5). Sweep = auto couple. (6). Allow the trace to stabilize. (7). Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ,802.11n(HT40)Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass




Measurement Data




Test Mode	CH	6dB bandwidth (MHz)	20dB bandwidth (MHz)	Limit (KHz)
IEEE 802.11 b	CH1	9.055	16.224	>500
	CH6	9.619	16.209	>500
	CH11	9.538	16.369	>500
IEEE 802.11 g	CH1	15.136	18.437	>500
	CH6	15.689	18.627	>500
	CH11	15.839	18.254	>500
IEEE 802.11 n HT 20	CH1	15.197	18.289	>500
	CH6	14.985	18.306	>500
	CH11	15.166	18.354	>500
IEEE 802.11 n HT 40	CH1	35.125	39.233	>500
	CH4	35.066	39.548	>500
	CH7	35.055	39.572	>500
Conclusion: PASS				




Test plot as follows:

Graphs_6dB Occupy Bandwidth

IEEE 802.11b 2412MHz	
IEEE 802.11b 2437MHz	
IEEE 802.11b 2462MHz	


IEEE 802.11g 2412MHz	 Agilent Ch Freq 2.412 GHz Trig Free Occupied Bandwidth Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.412 GHz Span 40 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts) Occupied Bandwidth 16.2419 MHz Transmit Freq Error 43.902 kHz x dB Bandwidth 15.136 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39200000 GHz Stop Freq 2.43200000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
IEEE 802.11g 2437MHz	 Agilent Ch Freq 2.437 GHz Trig Free Occupied Bandwidth Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.437 GHz Span 40 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts) Occupied Bandwidth 16.2744 MHz Transmit Freq Error -29.278 kHz x dB Bandwidth 15.689 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.41700000 GHz Stop Freq 2.45700000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off
IEEE 802.11g 2462MHz	 Agilent Ch Freq 2.462 GHz Trig Free Occupied Bandwidth Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.462 GHz Span 40 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts) Occupied Bandwidth 16.2927 MHz Transmit Freq Error -31.886 kHz x dB Bandwidth 15.839 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44200000 GHz Stop Freq 2.48200000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off

IEEE 802.11n HT20 2412MHz	 Agilent Ch Freq 2.412 GHz Trig Free Center Freq 2.4120000 GHz Start Freq 2.3920000 GHz Stop Freq 2.4320000 GHz CF Step 4.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.412 GHz Span 40 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts) Occupied Bandwidth 16.2578 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -3.330 kHz x dB Bandwidth 15.197 MHz
IEEE 802.11n HT20 2437MHz	 Agilent Ch Freq 2.437 GHz Trig Free Center Freq 2.4370000 GHz Start Freq 2.4170000 GHz Stop Freq 2.4570000 GHz CF Step 4.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.437 GHz Span 40 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts) Occupied Bandwidth 16.2689 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -26.634 kHz x dB Bandwidth 14.985 MHz
IEEE 802.11n HT20 2462MHz	 Agilent Ch Freq 2.462 GHz Trig Free Center Freq 2.4620000 GHz Start Freq 2.4420000 GHz Stop Freq 2.4820000 GHz CF Step 4.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.462 GHz Span 40 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts) Occupied Bandwidth 16.2608 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -46.624 kHz x dB Bandwidth 15.166 MHz


IEEE 802.11n HT40 2422MHz	 Agilent Ch Freq 2.422 GHz Center Freq 2.42200000 GHz Start Freq 2.39700000 GHz Stop Freq 2.44700000 GHz CF Step 5.00000000 MHz Freq Offset 0.00000000 Hz Signal Track On Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.422 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts) Span 50 MHz Occupied Bandwidth 35.6520 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error 62.858 kHz x dB Bandwidth 35.125 MHz
IEEE 802.11n HT40 2437MHz	 Agilent Ch Freq 2.437 GHz Center Freq 2.43700000 GHz Start Freq 2.41200000 GHz Stop Freq 2.46200000 GHz CF Step 5.00000000 MHz Freq Offset 0.00000000 Hz Signal Track On Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts) Span 50 MHz Occupied Bandwidth 35.5652 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -33.210 kHz x dB Bandwidth 35.066 MHz
IEEE 802.11n HT40 2452MHz	 Agilent Ch Freq 2.452 GHz Center Freq 2.45200000 GHz Start Freq 2.42700000 GHz Stop Freq 2.47700000 GHz CF Step 5.00000000 MHz Freq Offset 0.00000000 Hz Signal Track On Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.452 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts) Span 50 MHz Occupied Bandwidth 35.6693 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB Transmit Freq Error -69.238 kHz x dB Bandwidth 35.055 MHz

Graphs_20dB Bandwidth


IEEE 802.11b
2412MHz









IEEE 802.11b
2437MHz






IEEE 802.11b
2462MHz




IEEE 802.11g 2412MHz	 Agilent Ch Freq 2.412 GHz Trig Free Center Freq 2.41200000 GHz Start Freq 2.39200000 GHz Stop Freq 2.43200000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.412 GHz Span 40 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 16.4575 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 19.378 kHz x dB Bandwidth 18.437 MHz
IEEE 802.11g 2437MHz	 Agilent Ch Freq 2.437 GHz Trig Free Center Freq 2.43700000 GHz Start Freq 2.41700000 GHz Stop Freq 2.45700000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.437 GHz Span 40 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 16.4043 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -7.282 kHz x dB Bandwidth 18.627 MHz
IEEE 802.11g 2462MHz	 Agilent Ch Freq 2.462 GHz Trig Free Center Freq 2.46200000 GHz Start Freq 2.44200000 GHz Stop Freq 2.48200000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.462 GHz Span 40 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 16.4626 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -423.274 Hz x dB Bandwidth 18.254 MHz

IEEE 802.11n HT20 2412MHz	 Agilent Ch Freq 2.412 GHz Trig Free Center Freq 2.41200000 GHz Start Freq 2.39200000 GHz Stop Freq 2.43200000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.412 GHz Span 40 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 16.5086 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 21.005 kHz x dB Bandwidth 18.289 MHz
IEEE 802.11n HT20 2437MHz	 Agilent Ch Freq 2.437 GHz Trig Free Center Freq 2.43700000 GHz Start Freq 2.41700000 GHz Stop Freq 2.45700000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.437 GHz Span 40 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 16.5230 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -13.643 kHz x dB Bandwidth 18.306 MHz
IEEE 802.11n HT20 2462MHz	 Agilent Ch Freq 2.462 GHz Trig Free Center Freq 2.46200000 GHz Start Freq 2.44200000 GHz Stop Freq 2.48200000 GHz CF Step 4.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.462 GHz Span 40 MHz #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 16.4727 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -55.691 kHz x dB Bandwidth 18.354 MHz

IEEE 802.11n HT40 2422MHz	 Agilent Ch Freq 2.422 GHz Trig Free Center Freq 2.4220000 GHz Start Freq 2.3820000 GHz Stop Freq 2.4620000 GHz CF Step 8.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.422 GHz Span 80 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 36.0802 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 127.434 kHz x dB Bandwidth 39.233 MHz
IEEE 802.11n HT40 2437MHz	 Agilent Ch Freq 2.437 GHz Trig Free Center Freq 2.4370000 GHz Start Freq 2.3970000 GHz Stop Freq 2.4770000 GHz CF Step 8.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.437 GHz Span 80 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 35.9970 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error 62.714 kHz x dB Bandwidth 39.548 MHz
IEEE 802.11n HT40 2452MHz	 Agilent Ch Freq 2.452 GHz Trig Free Center Freq 2.4520000 GHz Start Freq 2.4120000 GHz Stop Freq 2.4920000 GHz CF Step 8.0000000 MHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Ref 10 dBm Atten 20 dB #Peak Log 10 dB/ Center 2.452 GHz Span 80 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 4 ms (401 pts) Occupied Bandwidth 36.0574 MHz Occ BW % Pwr 99.00 % x dB -20.00 dB Transmit Freq Error -76.448 kHz x dB Bandwidth 39.572 MHz

5.5 Power Spectral Density




Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 1, Connected the EUT's antenna port to spectrum analyzer device. 2, Follow the test procedure as described in KDB 558074 (1). Set analyzer center frequency to DTS channel center frequency. (2). Set the span to 1.5 times the DTS bandwidth. (3). Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. (4). Set the VBW $\geq 3 \text{ RBW}$. (5). Detector = peak. (6). Sweep time = auto couple. (7). Trace mode = max hold. (8). Allow trace to fully stabilize. (9). Use the peak marker function to determine the maximum amplitude level. (10). If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20/HT40) ; Only the worst case is recorded in the report.
Limit:	$\leq 8.00 \text{ dBm/3kHz}$
Test Results:	Pass




Measurement Data




Test Mode	CH	Power density (dBm/3kHz)	Duty Factor	Result (dBm/kHz)	Limit (dBm/3kHz)
IEEE 802.11 b	CH1	-7.273	0	-7.273	8
	CH6	-6.713	0	-6.713	8
	CH11	-6.698	0	-6.698	8
IEEE 802.11 g	CH1	-11.05	0.48	-10.57	8
	CH6	-12.67	0.48	-12.19	8
	CH11	-12.67	0.48	-12.19	8
IEEE 802.11 n HT 20	CH1	-12.38	0.31	-12.07	8
	CH6	-12.55	0.31	-12.24	8
	CH11	-13.11	0.31	-12.80	8
IEEE 802.11 n HT 40	CH1	-16.57	0.74	-15.83	8
	CH6	-16.42	0.74	-15.68	8
	CH11	-16.21	0.74	-15.50	8
Conclusion: PASS					

Test plot as follows:

Graphs	
IEEE 802.11b 2412MHz	Agilent Spectrum Analyzer screenshot for IEEE 802.11b at 2412 MHz. The plot shows a signal level around -7.273 dBm. Parameters: Center 2.412 GHz, Span 13.6 MHz, Res BW 3 kHz, VBW 10 kHz, Sweep 1.555 s (401 pts).
IEEE 802.11b 2437MHz	Agilent Spectrum Analyzer screenshot for IEEE 802.11b at 2437 MHz. The plot shows a signal level around -6.713 dBm. Parameters: Center 2.437 GHz, Span 14.5 MHz, Res BW 3 kHz, VBW 10 kHz, Sweep 1.658 s (401 pts).
IEEE 802.11b 2462MHz	Agilent Spectrum Analyzer screenshot for IEEE 802.11b at 2462 MHz. The plot shows a signal level around -6.698 dBm. Parameters: Center 2.462 GHz, Span 14.4 MHz, Res BW 3 kHz, VBW 10 kHz, Sweep 1.647 s (401 pts).




IEEE 802.11g 2412MHz	
IEEE 802.11g 2437MHz	
IEEE 802.11g 2462MHz	

IEEE 802.11n HT20 2412MHz	
IEEE 802.11n HT20 2437MHz	
IEEE 802.11n HT20 2462MHz	

IEEE 802.11n HT40 2422MHz	
IEEE 802.11n HT40 2437MHz	
IEEE 802.11n HT40 2452MHz	


5.6 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:	
	 Figure 1. Below 30MHz
 Figure 2. 30MHz to 1GHz	 Figure 3. Above 1 GHz
Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.


	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode Through Pre-scan, 802.11b, 802.11g M, 802.11n (HT20, HT40) find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report.
Test Results:	Pass

5.6.1 Radiated emission below 1GHz



Remarks: 1. Result=Reading+Antenna+Cable
 2. If Peak Result complies with QP Limit, QP Result is deemed to comply with QP Limit.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



Remarks: 1. Result=Reading+Antenna+Cable
2. If Peak Result complies with QP Limit, QP Result is deemed to comply with QP Limit.

5.6.2 Transmitter emission above 1GHz

Test mode: 802.11b(1Mbps)				Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	52.31	-4.03	48.28	74	-25.72	peak	H
4824.000	37.72	-4.03	33.69	54	-20.31	AVG	H
7236.000	50.18	1.66	51.84	74	-22.16	peak	H
7236.000	36.64	1.66	38.30	54	-15.70	AVG	H
4824.000	53.40	-4.03	49.37	74	-24.63	peak	V
4824.000	38.53	-4.03	34.50	54	-19.50	AVG	V
7236.000	49.89	1.66	51.55	74	-22.45	peak	V
7236.000	36.45	1.66	38.11	54	-15.89	AVG	V

Test mode: 802.11b(1Mbps)				Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	53.54	-4.26	49.28	74	-24.72	peak	H
4874.000	36.59	-4.26	32.33	54	-21.67	AVG	H
7311.000	51.06	1.18	52.24	74	-21.76	peak	H
7311.000	37.95	1.18	39.13	54	-14.87	AVG	H
4874.000	55.76	-4.26	51.50	74	-22.50	peak	V
4874.000	39.81	-4.26	35.55	54	-18.45	AVG	V
7311.000	50.46	1.18	51.64	74	-22.36	peak	V
7311.000	36.77	1.18	37.95	54	-16.05	AVG	V

Test mode:802.11b(1Mbps)				Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	52.63	-4.12	48.51	74	-25.49	peak	H
4924.000	36.31	-4.12	32.19	54	-21.81	AVG	H
7386.000	49.61	1.46	51.07	74	-22.93	peak	H
7386.000	35.16	1.46	36.62	54	-17.38	AVG	H
4924.000	52.32	-4.12	48.20	74	-25.80	peak	V
4924.000	36.04	-4.12	31.92	54	-22.08	AVG	V
7386.000	48.50	1.46	49.96	74	-24.04	peak	V
7386.000	35.74	1.46	37.20	54	-16.80	AVG	V

Remark:

- 1) The 1Mbps of rate of ANT 1 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.7 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz


Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the

	measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode Through Pre-scan, 802.11b,802.11g M,802.11n(HT20,HT40) find the 802.11n HT40 is the worst case. Only the worst case is recorded in the report.
Test Results:	Pass

Test data:


Test mode: 802.11n HT40	Test channel:	Lowest	Polarization	Vertical
-------------------------	---------------	--------	--------------	----------



	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2375.00	27.64	6.60	34.59	38.90	38.55	74.00	35.45	Peak
2	2390.00	27.64	6.62	34.62	39.53	39.17	74.00	34.83	Peak
3	2400.00	27.61	6.62	34.64	51.59	51.18	74.00	22.82	Peak
4	2418.20	27.60	6.64	34.74	84.27	83.77	74.00	-9.77	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Test mode: 802.11n HT40	Test channel:	Lowest	Polarization	Horizontal
-------------------------	---------------	--------	--------------	------------




	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2382.80	27.64	6.60	34.62	41.03	40.65	74.00	33.35	Peak
2	2390.00	27.64	6.62	34.62	38.66	38.30	74.00	35.70	Peak
3	2400.00	27.61	6.62	34.64	50.60	50.19	74.00	23.81	Peak
4	2420.00	27.60	6.66	34.74	87.43	86.95	74.00	-12.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.

2. The emission levels that are 20dB below the official limit are not reported.


Test mode: 802.11n HT40	Test channel:	Highest	Polarization	Horizontal
-------------------------	---------------	---------	--------------	------------



	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2464.72	27.58	6.69	34.98	88.88	88.17	74.00	-14.17	Peak
2	2483.50	27.58	6.71	35.11	51.26	50.44	74.00	23.56	Peak
3	2483.92	27.58	6.71	35.11	53.20	52.38	74.00	21.62	Peak
4	2486.92	27.58	6.71	35.11	46.15	45.33	74.00	28.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Test mode: 802.11n HT40	Test channel:	Highest	Polarization	Vertical
-------------------------	---------------	---------	--------------	----------



	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2464.72	27.58	6.69	34.98	83.66	82.95	74.00	-8.95	Peak
2	2483.50	27.58	6.71	35.11	47.51	46.69	74.00	27.31	Peak
3	2483.92	27.58	6.71	35.11	53.94	53.12	74.00	20.88	Peak
4	2488.30	27.58	6.73	35.11	42.01	41.21	74.00	32.79	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission


9KHz~30MHz:



30MHz~1GHz:



Above 1GHz:







6.2 Conducted Emission






7 Photographs - EUT Constructional Details



Test model No.: VER5800












Antenna



THE END