

# **TEST REPORT**

Product Name: TabletModel Number: M12, TPC12-PSContains FCC ID: 2BEA6TPC121

Prepared for Address	:	Vantron Technology, Inc. 48434 Milmont Drive Fremont, California 94538-7324, United States
Prepared by Address		EMTEK (SHENZHEN) CO., LTD. Building 69, Majialong Industry Zone,Nanshan District, Shenzhen Guangdong, China Tel: (0755) 26954280 Fax: (0755) 26954282
Report Number Date(s) of Tests Date of issue	:	ENS2410220034W01002R October 23, 2024 to November 6, 2024 November 6, 2024



## **Table of Contents**

1	TEST F	RESULT CERTIFICATION	3
2	EUT TI	ECHNICAL DESCRIPTION	5
3	SUMM	ARY OF TEST RESULT	6
4	TEST N	/IETHODOLOGY	7
	4.1 4.2 4.3	GENERAL DESCRIPTION OF APPLIED STANDARDS MEASUREMENT EQUIPMENT USED DESCRIPTION OF TEST MODES	7 7 7
5	FACIL	TIES AND ACCREDITATIONS	9
	5.1 5.2 5.3	FACILITIES EQUIPMENT LABORATORY ACCREDITATIONS AND LISTINGS	9 9 9
6	TEST S	YSTEM UNCERTAINTY	10
7	SETUP	OF EQUIPMENT UNDER TEST	11
	7.1 7.2 7.3 7.4 7.5 7.6	RADIO FREQUENCY TEST SETUP 1 RADIO FREQUENCY TEST SETUP 2 CONDUCTED EMISSION TEST SETUP. BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM. SUPPORT EQUIPMENT. RADIATED SPURIOUS EMISSION	11 11 14 15 15 16



## **1 TEST RESULT CERTIFICATION**

Applicant	:	Vantron Technology, Inc.
Address	:	48434 Milmont Drive Fremont, California 94538-7324, United States
Manufacturer	:	Vantron Technology, Inc.
Address	:	48434 Milmont Drive Fremont, California 94538-7324, United States
EUT	:	Tablet
Model Name	:	M12, TPC12-PS
Trademark	:	Vantron

Measurement Procedure Used:

APPLICABLE STANDARDS				
STANDARD TEST RESULT				
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS			
IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021) IC RSS-247 Issue 3(08-2023)	PASS			

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2, Part 15.247, IC RSS-247 Issue 3 and IC RSS-GEN, Issue 5.

The test results of this report relate only to the tested sample identified in this report

Date of Test :

October 23, 2024 to November 6, 2024

Prepared by :

Una Yu/Editor

Reviewer :

Joe Xia/Supervisor

Joe Xid

Approve & Authorized Signer :

Lisa Wang/Manager

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



## **Modified History**

Version	Report No.	Revision Date	Summary
Ver.1.0	ENS2410220034W01002R	/	Original Report
Note: Th FPC ant Change Radiated test item	is change is to request approval enna, According to the requirem Policy v06, the antenna types ar d Spurious Emission tests were p s remained unchanged based of	for mobile category spe ents for antenna Change re different and the gain performed to verify RF co n the module report.	cific host product, Antenna Type is e in KDB178919 D01 Permissive value is greater than the original, ompliance,and the results of other





## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product:	Tablet
Model Number:	M12, TPC12-PS (The same product, different names sold to different customers or regions)
Sample:	2#
Device Type:	Bluetooth_BT
Data Rate:	1Mbps for GFSK modulation 2Mbps forπ/4-DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, π/4-DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Antenna Type:	FPC Antenna
Antenna Gain:	Ant2: 5 dBi (Note: The antenna information is provided by the customers, which will have a certain impact on the test results.)
Power Supply:	DC 12V( from adapter), DC 7.6V from Internal Battery
Temperature Range:	0-40°C

Note: for more details, please refer to the User's manual of the EUT.



## **3 SUMMARY OF TEST RESULT**

FCC Part Clause	IC Part Clause	Test Parameter	Verdict	Remark	
15.247(d)	RSS-Gen 8.9 RSS-Gen 8.10				
15.209 15.205	RSS-Gen 6.13 RSS-247, 3.3 RSS-247, 5.5	Radiated Spurious Emissions	PASS		
NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.					

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for **ContainsFCC ID:2BEA6TPC121** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.





## 4 TEST METHODOLOGY

#### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards: FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C IC RSS-GEN, Issue 5(04-2018)+A1(03-2019)+A2(02-2021) IC RSS-247 Issue 3(08-2023) FCC KDB 558074 D01 15.247 Meas Guidance v05r02

#### 4.2 MEASUREMENT EQUIPMENT USED

#### **For Spurious Emissions Test**

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Pre-Amplifier Bonn BLMA 011001		BLMA 011001N	2213967A	2024/10/23	1Year
EMI Test Receiver	Rohde & Schwarz	ESR7	102551	2024/10/23	1Year
Bilog Antenna	Schwarzbeck	VULB9163	9163142	2024/7/8	2Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1198	2023/6/2	2Year
Pre-Amplifier	Bonn	BLMA 0118-5G	2213967B-01	2024/10/23	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV3044	101290	2024/10/23	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2023/5/12	2Year
Pre-Amplifier	Lunar EM	LNA18G26-40	J1012131010 001	2024/5/11	1Year
Pre-Amplifier	Lunar EM	LNA26G40-40	J1013131028 001	2024/5/11	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2023/5/12	2Year
Cable	H+B	NmSm-05-C150 52	N/A	2024/5/15	1 Year
Cable	H+B	NmSm-2-C1520 1	N/A	2024/5/15	1 Year
Cable	H+B	NmNm-7-C1570 2	N/A	2024/5/15	1 Year
Cable	H+B	SAC-40G-1	414	2024/5/15	1 Year
Cable	H+B	SUCOFLEX104	MY14871/4	2024/5/15	1 Year
Cable	H+B	BLU18A-NmSm- 6500	D8501	2024/5/15	1 Year
Band reject Filter(50dB)	WI/DE	WRCGV-2400(2 400-2485MHz)	2	2024/5/15	1 Year

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn

Report No. ENS2410220034W01002R



#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation(DH5); 2Mbps for  $\pi$ /4-DQPSK modulation(2DH5); 3Mbps for 8DPSK modulation(3DH5);)were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441		
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
				78	2480
Note: fc=2402MHz+(k-1)×1MHz k=1 to 79					

Test Frequency and channel for Bluetooth

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480



## 5 FACILITIES AND ACCREDITATIONS

#### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

#### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

#### 5.3 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description	
EMC Lab. :	Accredited by CNAS The Certificate Registration Number is L2291. The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)
	<b>Accredited by FCC</b> Designation Number: CN1204 Test Firm Registration Number: 882943
	Accredited by A2LA The Certificate Number is 4321.01.
	Accredited by Industry Canada The Conformity Assessment Body Identifier is CN0008
Name of Firm : Site Location :	EMTEK (SHENZHEN) CO., LTD. Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



## **6 TEST SYSTEM UNCERTAINTY**

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Parameter	Measurement Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5°C
Humidity	±3%

Measurement Uncertainty for a level of Confidence of 95%



## 7 SETUP OF EQUIPMENT UNDER TEST

#### 7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



#### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

#### Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

#### Above 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

#### Above 1GHz:

(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Measurements shall be taken, using the following steps, at a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment (see RSS-Gen for applicable versions of ANSI and CISPR standards).

 (1) Line the ground plane with absorbers between the transmitter and the receive antenna to minimize reflections. The absorbers used should have a minimum-rated attenuation of 20 dB through the measurement frequency range of interest. The absorbers shall be positioned to replicate the layout used when compliance with the applicable acceptability criterion was achieved, as set forth in the aforementioned standards on site validation.
(2) Set the height of the receive antenna to 1.5 m. The receive antenna must be one that was designed and fabricated to operate over the entire frequency range of interest, for example, an appropriate standard gain horn.
(3) The distance between the receive antenna and the radiating source shall be sufficient in order to ensure far-field conditions.

(4) Mount the transmitter at a height of 1.5 m.

(5) Configure the device under test (DUT) to produce the maximum power spectral density as measured while assessing compliance with Section 6.2.2 (i.e. channel frequency, modulation type and data rate). If the DUT is equipped with a detachable antenna and the antenna is intended for remote installation (i.e. tower-mounted), the DUT may be substituted with a suitable signal generator. The level and frequency settings on the generator shall be set so as to reproduce the maximum power spectral density, measured within a 1 MHz bandwidth, obtained while assessing compliance to Section 6.2.2.

(6) Position the transmitter or the radiating antenna so that elevation pattern measurements can be taken.

(7) Find the 0° reference point in the horizontal plane.

(8) Care should be taken when positioning the receive antenna to avoid cross-polarization. Antennas of known mounting polarization should be assessed with the receive antenna oriented in the same polarity. If the

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn

Report No. ENS2410220034W01002R



polarization of the transmit antenna is unknown or the transmit antenna can be mounted in either polarization, e.i.r.p. measurements should be performed to find which

mounting polarity provides the highest e.i.r.p. value. Testing shall be carried out with the receive antenna and the DUT mounted in each polarity.

(9) The emission shall be centred on the display of the spectrum analyzer with the following settings: i. If the power spectral density of the DUT was assessed with a peak detector and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

ii. If the power spectral density of the DUT was assessed using a sample detector with power averaging and the antenna cannot be detached from the DUT, the spectrum analyzer shall be set to a sample detector, configured to produce 100 power averages and set with a resolution bandwidth, as well as a video bandwidth of 1 MHz. iii. If the antenna can be detached from the DUT, a continuous wave (CW) signal equal to that of the power spectral density measurement may be used, the spectrum analyzer shall be set to peak detector with a resolution bandwidth and video bandwidth of 1 MHz.

(10) Rotate the turntable 360° recording the field strength at each step. Throughout the main beam of the antenna, the step size shall be kept to a maximum of 1°.

Once outside the main beam of the antenna, the maximum step size shall be as follows, when compared to the requirements of Section 6.2.2:

i. Between 0° and 8°, maximum step size of 2°;

ii. Between 8° and 40°, maximum step size of 4°;

iii. Between 40° and 45°, maximum step size of 1°;

iv. Between 45° and 90°, maximum step size of 5°.

Once the mask reaches 90°, the mask will be inverted and the step size will follow in the same manner as above. For the purpose of this procedure, the main beam of the antenna is defined as the 3 dB beamwidth. (11) Convert the measured field strength values in terms of e.i.r.p. density (dBW/1 MHz) using the following

equation:

e.i.r.p density(dBW/MHz)=10log((E\*r)<sup>2</sup>/30)

E = field strength in V/m

r = measurement distance in metres

(12) Plot the results against the emission mask with reference to the horizontal plane.

(13) Using the plot, the 0° can be rotated to determine the worst-case installation tilt angle.

(14) Testing shall be performed using the highest gain antenna for every antenna type, if applicable.

(15) Antenna type(s), antenna model number(s), and worst-case tilt angle(s) necessary to remain compliant with the elevation mask requirement set forth in Section 6.2.2(3) of RSS-247 shall be clearly indicated in the user manual.

The following figure is an example of a polar elevation mask measured using the Method 1 reference to dBµV/m at 3 m.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





(a) Radiated Emission Test Set-Up, Frequency Below 30MHz

(b)Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz



**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



#### 7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.





#### 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
1	1	1	/

Auxiliary Cable List and Details						
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite			
/	/	1	/			

Auxiliary Equipment List and Details						
Description	Manufacturer	Model	Serial Number			
1	1	1	1			

#### Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



#### 7.6 RADIATED SPURIOUS EMISSION

#### 7.6.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02 According to IC RSS-Gen and RSS-247

#### 7.6.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands							
MHz	MHz	MHz	GHz				
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15				
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46				
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75				
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5				
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2				
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5				
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7				
6.26775-6.26825	123-138	2200-2300	14.47-14.5				
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2				
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4				
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12				
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0				
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8				
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5				
12.57675-12.57725	322-335.4	3600-4400	(2)				
13.36-13.41							

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

#### 7.6.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

#### 7.6.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

 $\mathsf{VBW} \geq \mathsf{RBW}$ 

Sweep = auto

**深圳信测标准技术服务股份有限公司**地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn邮箱:cs.rep@emtek.com.cn



Detector function = peak Trace = max hold For Below 1GHz: The EUT was placed on a turn table which is 0.8m above ground plane. Maximum procedure was performed on the highest emissions to ensure EUT compliance. Span = wide enough to fully capture the emission being measured RBW = 100 kHz for  $VBW \ge RBW$ Sweep = auto Detector function = peak Trace = max hold For Below 30MHz: The EUT was placed on a turn table which is 0.8m above ground plane. Maximum procedure was performed on the highest emissions to ensure EUT compliance. Span = wide enough to fully capture the emission being measured RBW = 9kHz $VBW \ge RBW$ Sweep = auto Detector function = peak Trace = max hold For Below 150KHz: The EUT was placed on a turn table which is 0.8m above ground plane. Maximum procedure was performed on the highest emissions to ensure EUT compliance. Span = wide enough to fully capture the emission being measured RBW = 200Hz $VBW \ge RBW$ Sweep = auto Detector function = peak Trace = max hold Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT,

measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

#### 7.6.5 Test Results

Spurious Emission below 30MHz(9KHz to 30MHz)

Temperature:	22° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK È	ÁÝ	PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)( dB); Limit line=Specific limits(dBuV) + distance extrapolation factor

**深圳信测标准技术服务股份有限公司**地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All the antenna(Antenna 1) and modes(GFSK,  $\pi$ /4-DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) resultrecorded was report as below:

Test mode:	GFS	K	Frequen		Channel 0: 2402MHz		
Freq.	Ant.Pol.	Emis Level(d	sion BuV/m)	Limit 3m	(dBuV/m)	Ove	r(dB)
	H/V	PK	AV	PK	AV	PK	AV
6864.375	V	55.07	38.22	74.00	54.00	18.93	15.78
9903.75	V	61.90	42.88	74.00	54.00	12.10	11.12
15980.62	V	64.16	44.29	74.00	54.00	9.84	9.71
8424.375	Н	57.37	40.92	74.00	54.00	16.63	13.08
9892.5	Н	61.74	42.73	74.00	54.00	12.26	11.27
17480.62	Н	64.06	46.82	74.00	54.00	9.94	7.18

Channel 39: 2441MHz Test mode: **GFSK** Frequency: Ant.Pol. Emission Level(dBuV/m) Limit 3m(dBuV/m) Over(dB) Freq. (MHz) H/V PK AV PK AV ΡK AV 7783.125 V 55.95 39.20 74.00 54.00 18.05 14.80 9890.625 V 62.71 42.24 74.00 54.00 11.29 11.76 17671.87 V 64.74 74.00 54.00 46.44 9.26 7.56 57.22 74.00 8452.5 Н 41.00 54.00 16.78 13.00 Н 42.55 74.00 54.00 11.45 9901.875 61.95 12.05 Н 17544.37 65.42 47.78 74.00 54.00 8.58 6.22

Test mode: GFSK

SK

Frequency:

Channel 78: 2480MHz

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
8398.125	V	58.04	58.04	74.00	54.00	15.96	13.19
11512.5	V	62.66	62.66	74.00	54.00	11.34	9.51
17077.5	V	64.42	64.42	74.00	54.00	9.58	6.83
8431.875	Н	57.77	41.10	74.00	54.00	16.23	12.90
9941.25	Н	62.61	42.31	74.00	54.00	11.39	11.69
16074.37	H	64.13	43.10	74.00	54.00	9.87	10.90

Note:

(1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant\_F + Cab\_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All the antenna(Antenna 1) and modes(GFSK,  $\pi$ /4-DQPSK, 8DPSK, Hopping) mode have been tested, and the worst(Antenna 1,GFSK, Hopping) resultrecorded was report as below:

Test mode:	GFSK	Frequency:		annel 0: 2402MH	Z
Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.94	Н	45.47	74.00	37.92	54.00
2388.3461	V	45.01	74.00	38.16	54.00

Test mode:	GFSK	Frequency: Cha		annel 78: 2480MHz	
Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.97	Н	45.55	74.00	37.78	54.00
2484.20	V	46.04	74.00	37.84	54.00

Test mode:	GFSK	Frequency: Hopping			
Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.16	Н	44.64	74.00	37.72	54.00
2487.13	Н	46.13	74.00	38.23	54.00
2389.12	V	44.46	74.00	37.93	54.00
2484.85	V	44.95	74.00	38.01	54.00

Note:

(1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant\_F + Cab\_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

















■ Spurious Emission below 1GHz(30MHz to 1GHz)

All the antenna(Antenna 1) and modes(GFSK,  $\pi$ /4-DQPSK, 8DPSK) mode have been tested, and the worst(Antenna 1,GFSK) resultrecorded was report as below:



Suspe	Suspected Data List									
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity		
1	65.9259	38.11	-18.24	19.87	PK	40.00	20.13	Vertical		
2	72.7227	37.80	-19.21	18.59	PK	40.00	21.41	Vertical		
3	167.8779	51.08	-19.13	31.95	PK	43.50	11.55	Vertical		
4	602.8729	32.26	-6.54	25.72	PK	46.00	20.28	Vertical		
5	690.2603	32.21	-6.55	25.66	PK	46.00	20.34	Vertical		
6	837.8478	31.38	-4.72	26.66	PK	46.00	19.34	Vertical		
				1						

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]
1	65.9259	-18.24	18.54	40.00	21.46
2	72.7227	-19.21	17.98	40.00	22.02
3	167.8779	-19.13	31.34	43.50	12.16
4	602.8729	-6.54	23.82	46.00	22.18
5	690.2603	-6.55	23.76	46.00	22.24
6	837.8478	-4.72	26.44	46.00	19.56

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Mode: BT 2402 120 110-100-90 -80 -70 Level[dBµV/m] 60 -FCC PART 15 C-QP Limit 50 -40-1 mg 30 -20 -10-0 30M 100M 1G Frequency[Hz] - QP Limit Horizontal PK QP Detector

#### Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	159.1391	50.71	-19.47	31.24	PK	43.50	12.26	Horizontal
2	173.7037	52.13	-18.88	33.25	PK	43.50	10.25	Horizontal
3	388.2883	39.34	-11.55	27.79	PK	46.00	18.21	Horizontal
4	453.3433	38.65	-10.64	28.01	PK	46.00	17.99	Horizontal
5	840.7608	32.47	-4.63	27.84	PK	46.00	18.16	Horizontal
6	956.3063	31.54	-2.64	28.90	PK	46.00	17.10	Horizontal

Final Data List											
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]						
1	159.1391	-19.47	29.37	43.50	14.13						
2	173.7037	-18.88	32.66	43.50	10.84						
3	388.2883	-11.55	27.53	46.00	18.47						
4	453.3433	-10.64	27.75	46.00	18.25						
5	840.7608	-4.63	26.86	46.00	19.14						
6	956.3063	-2.64	28.25	46.00	17.75						

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn







#### Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	65.9259	38.27	-18.24	20.03	PK	40.00	19.97	Vertical
2	157.1972	41.10	-19.51	21.59	PK	43.50	21.91	Vertical
3	166.9069	51.44	-19.17	32.27	PK	43.50	11.23	Vertical
4	605.7858	32.07	-6.66	25.41	PK	46.00	20.59	Vertical
5	703.8539	31.48	-6.16	25.32	PK	46.00	20.68	Vertical
6	845.6156	31.02	-4.41	26.61	PK	46.00	19.39	Vertical

Final Data List											
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]						
1	65.9259	-18.24	19.53	40.00	20.47						
2	157.1972	-19.51	21.09	43.50	22.41						
3	166.9069	-19.17	31.45	43.50	12.05						
4	605.7858	-6.66	25.30	46.00	20.70						
5	703.8539	-6.16	25.21	46.00	20.79						
6	845.6156	-4.41	24.89	46.00	21.11						

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





#### Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	159.1391	50.10	-19.47	30.63	PK	43.50	12.87	Horizontal
2	168.8488	56.00	-19.10	36.90	PK	43.50	6.60	Horizontal
3	420.3303	39.28	-11.87	27.41	PK	46.00	18.59	Horizontal
4	452.3724	38.13	-10.68	27.45	PK	46.00	18.55	Horizontal
5	841.7317	33.29	-4.58	28.71	PK	46.00	17.29	Horizontal
6	950.4805	31.82	-2.97	28.85	PK	46.00	17.15	Horizontal

Final Data List										
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]					
1	159.1391	-19.47	29.43	43.50	14.07					
2	168.8488	-19.10	36.42	43.50	7.08					
3	420.3303	-11.87	26.60	46.00	19.40					
4	452.3724	-10.68	26.64	46.00	19.36					
5	841.7317	-4.58	28.62	46.00	17.38					
6	950.4805	-2.97	28.76	46.00	17.24					

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Mode: BT 2480 120 110-100-90 -80 -70 Level[dBµV/m] 60 -FCC PART 15 C-QP Limit 50 -40-30 -20-10-0 30M 100M 1G Frequency[Hz] - QP Limit - Vertical PK QP Detector

#### Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	65.9259	37.42	-18.24	19.18	PK	40.00	20.82	Vertical
2	167.8779	51.36	-19.13	32.23	PK	43.50	11.27	Vertical
3	582.4825	34.13	-7.34	26.79	PK	46.00	19.21	Vertical
4	647.5375	33.04	-7.31	25.73	PK	46.00	20.27	Vertical
5	794.1542	32.62	-5.97	26.65	PK	46.00	19.35	Vertical
6	954.3644	31.25	-2.75	28.50	PK	46.00	17.50	Vertical

# Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]
1	65.9259	-18.24	17.31	40.00	22.69
2	167.8779	-19.13	32.03	43.50	11.47
3	582.4825	-7.34	25.31	46.00	20.69
4	647.5375	-7.31	24.25	46.00	21.75
5	794.1542	-5.97	25.89	46.00	20.11
6	954.3644	-2.75	27.41	46.00	18.59

**深圳信测标准技术服务股份有限公司** 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





Suspe	Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity			
1	158.1682	50.56	-19.49	31.07	PK	43.50	12.43	Horizontal			
2	162.0521	54.94	-19.37	35.57	PK	43.50	7.93	Horizontal			
3	420.3303	38.64	-11.87	26.77	PK	46.00	19.23	Horizontal			
4	453.3433	38.16	-10.64	27.52	PK	46.00	18.48	Horizontal			
5	841.7317	32.86	-4.58	28.28	PK	46.00	17.72	Horizontal			
6	871.8318	32.57	-3.80	28.77	PK	46.00	17.23	Horizontal			

Final Data List										
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]					
1	158.1682	-19.49	31.00	43.50	12.50					
2	162.0521	-19.37	35.50	43.50	8.00					
3	420.3303	-11.87	26.37	46.00	19.63					
4	453.3433	-10.64	25.84	46.00	20.16					
5	841.7317	-4.58	26.60	46.00	19.40					
6	871.8318	-3.80	27.81	46.00	18.19					

\*\*\* End of Report \*\*\*