



# EMC

## TEST REPORT

REPORT NO. : F89040701

MODEL NO. : 9001AH

DATE OF TEST : April 11, 2000

PREPARED FOR: BEHAVIOR TECH COMPUTER CORP.

ADDRESS : 2F, NO.51, TUNG HSING. RD.,  
TAIPEI, TAIWAN, R.O.C.

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory

11F, NO.1, SEC.4, NAN-KING EAST RD.,  
TAIPEI, TAIWAN, R.O.C.

This test report consists of 15 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



## **TABLE OF CONTENTS**

1. CERTIFICATION.....	3
2. GENERAL INFORMATION .....	4
2.1    GENERAL DESCRIPTION OF EUT .....	4
2.2    DESCRIPTION OF SUPPORT UNITS .....	5
2.3    TEST METHODOLOGY AND CONFIGURATION .....	5
3. TEST INSTRUMENTS .....	6
3.1    TEST INSTRUMENTS (EMISSION) .....	6
3.2    LIMITS OF CONDUCTED AND RADIATED EMISSION.....	7
4. TEST RESULTS (EMISSION).....	8
4.1    RADIO DISTURBANCE .....	8
4.2    EUT OPERATION CONDITION .....	8
4.3    TEST DATA OF CONDUCTED EMISSION .....	9
4.4    TEST DATA OF RADIATED EMISSION.....	11
5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN....	13
6. APPENDIX - INFORMATION OF THE TESTING LABORATORY .....	15

**1. CERTIFICATION**

Issue Date: April 12, 2000

Product : USB KEYBOARD  
Trade Name : BTC  
Model No. : 9001AH  
Applicant : BEHAVIOR TECH COMPUTER CORP.  
Standard : FCC Part 15, Subpart B, Class B  
ANSI C63.4-1992  
CISPR 22:1993+A1: 1995+A2: 1996, Class B

We hereby certify that one sample of the designation has been tested in our facility on April 11, 2000. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

The test results show that the EUT as described in this report is in compliance with the Class B limits of conducted and radiated emission of applicable standards

TESTED BY : Eric Chang , DATE: 4/12/2000  
( Eric Chang )

CHECKED BY : Yemmy Soong , DATE: 4/12/2000  
( Yemmy Soong )

APPROVED BY : Mike Su , DATE: 4/12/2000  
( Mike Su )

**ADVANCE DATA TECHNOLOGY CORPORATION**

Accredited Laboratory



## **2. GENERAL INFORMATION**

### **2.1 GENERAL DESCRIPTION OF EUT**

Product	:	USB KEYBOARD
Model No.	:	9001AH
Power Supply	:	DC 5V (from PC)
Data Cable	:	Shielded (1.8 m)

Note: The EUT is a USB KEYBOARD with two USB ports and speaker volume control.

For more detailed features description, please refer to manufacturer' s specification or User's Manual.



## 2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

No	Product	Brand	Model No.	FCC ID	I/O Cable
1	PERSONAL COMPUTER	IBM	2187-12W	FCC DoC Approved	Nonshielded Power (1.8m)
2	MONITOR	ADI	PD-959	FCC DoC Approved	Shielded Signal (1.8m) Nonshielded Power (1.8m)
3	PRINTER	HP	2225C+	DSI6XU2225	Shielded Signal (1.2m) Nonshielded Power (1.9m)
4	MODEM	ACEEX	1414	IFAXDM1414	Shielded Signal (1.2m) Nonshielded Power (1.9m)
5	USB MOUSE	BTC	M-U48A	JNZ21360	Shielded Signal (1.1m)
6	USB JOYSTICK	GRAND	PC GAME PAD	NA	Shielded Signal (1.9m)
7	SPEAKER	J-S	J-008	NA	Shielded Signal (1.2m)

## 2.3 TEST METHODOLOGY AND CONFIGURATION

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 1992. Radiated testing was performed at an antenna to EUT distance of 10 m on an open area test site.

Please refer to the photos of test configuration in Item 5.



### 3. TEST INSTRUMENTS

#### 3.1 TEST INSTRUMENTS (EMISSION)

##### CONDUCTED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ Test Receiver	ESHS30	828109/007	July 13, 2000
ROHDE & SCHWARZ Artificial Mains Network	ESH3-Z5	839135/006	July 7, 2000
EMCO-L.I.S.N.	3825/2	9204-1964	July 7, 2000
Shielded Room	Site 2	ADT-C02	NA

- Note: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months.
- And the calibrations are traceable to NML/ROC and NIST/USA.

##### RADIATED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated until
HP Spectrum Analyzer	8590L	3544A00941	Dec. 05, 2000
HP Pre-Amplifier	8447D	2944A08312	Sept. 7, 2000
HP Preamplifier	8347A	3307A01088	Aug. 30, 2000
HP Preamplifier	8449B	3008A01201	Dec. 14, 2000
R&S Receiver	ESVS10	844594/010	Sept. 29, 2000
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2000
ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Aug. 30, 2000
CHASE BILOG Antenna	CBL6111A	1500	Aug. 30, 2000
EMCO Double Ridged Guide Antenna	3115	9312-4192	March 29, 2001
EMCO Turn Table	1060-04	1196	NA
EMCO Tower	1051	1264	NA
Open Field Test Site	Site 1	ADT-R01	Aug. 27, 2000

- Note: 1. The measurement uncertainty is less than +/- 3dB, which is calculated as per NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months.
- And the calibrations are traceable to NML/ROC and NIST/USA.



### 3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION

#### LIMIT OF RADIATED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (at 10m) *	Class B (at 10m) *
	dBuV/m	dBuV/m
30 - 230	40	30
230 - 1000	47	37

\* Detector Function: Quasi-Peak

#### LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	Peak	Average	Peak	Average
Above 1000	80.0	60.0	74.0	54.0

- Note: (1) The lower limit shall apply at the transition frequencies.  
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### LIMIT OF CONDUCTED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- Note: (1) The lower limit shall apply at the transition frequencies.  
 (2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz  
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



## 4. TEST RESULTS (EMISSION)

### 4.1 RADIO DISTURBANCE

Frequency Range : 0.15 - 30 MHz (Conducted Emission)  
30 - 1000 MHz (Radiated Emission)  
Input Voltage : 120 Vac, 60 Hz (from PC)  
Temperature : 21 degree C  
Humidity : 60 %  
Atmospheric Pressure : 1000 mbar

TEST RESULT	Remarks
PASS	Minimum passing margin of conducted emission: -10.4 dB at 0.204 MHz Minimum passing margin of radiated emission: - 5.7 dB at 216.03 MHz

### 4.2 EUT OPERATION CONDITION

1. Turn on the power of all equipment.
2. PC runs a test program to enable all functions.
3. PC reads and writes messages from FDD and HDD.
4. EUT sends "H" character to PC.
5. PC sends "H" messages to monitor and monitor displays "H" patterns on screen.
6. PC sends "H" messages to modem.
7. PC sends "H" messages to printer, and the printer prints them on paper.
8. PC sends audio messages to speaker.
9. Repeat steps 3-9.





### 4.3 TEST DATA OF CONDUCTED EMISSION

EUT: USB KEYBOARDMODEL: 9001AH6 dB Bandwidth: 10 kHzPHASE: LINE (L)

Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.204	0.2	52.8	-	53.0	-	63.4	53.4	-10.4	-
0.411	0.2	43.5	-	43.7	-	57.6	47.6	-13.9	-
0.513	0.2	40.7	-	40.9	-	56.0	46.0	-15.1	-
4.011	0.2	40.1	-	40.3	-	56.0	46.0	-15.7	-
6.828	0.5	42.4	-	42.9	-	60.0	50.0	-17.1	-
13.438	0.8	32.9	-	33.7	-	60.0	50.0	-26.3	-

- Remarks:
1. "\*": Undetectable
  2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": The Quasi-peak emission level also meets average limit and measurement with the average detector is unnecessary.
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.



## TEST DATA OF CONDUCTED EMISSION

EUT: USB KEYBOARDMODEL: 9001AH6 dB Bandwidth: 10 kHzPHASE: NEUTRAL (N)

Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.204	0.2	50.2	-	50.4	-	63.4	53.4	-13.0	-
0.411	0.2	46.5	-	46.7	-	57.6	47.6	-10.9	-
0.513	0.2	41.7	-	41.9	-	56.0	46.0	-14.1	-
4.011	0.2	40.5	-	40.7	-	56.0	46.0	-15.3	-
6.828	0.5	42.3	-	42.8	-	60.0	50.0	-17.2	-
13.438	0.7	32.6	-	33.3	-	60.0	50.0	-26.7	-

- Remarks:
1. "\*": Undetectable
  2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  3. "-": The Quasi-peak emission level also meets average limit and measurement with the average detector is unnecessary.
  4. The emission levels of other frequencies were very low against the limit.
  5. Margin value = Emission level - Limit value
  6. Emission Level = Correction Factor + Reading Value.



#### 4.4 TEST DATA OF RADIATED EMISSION

EUT: **USB KEYBOARD**MODEL: **9001AH**ANT. POLARITY: HorizontalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
120.03	12.7	10.8	23.5	30.0	-6.5	400	324
144.02	12.9	7.5	20.4	30.0	-9.6	400	56
168.03	11.3	8.8	20.1	30.0	-9.9	400	129
180.58	10.6	7.8	18.4	30.0	-11.6	400	94
216.03	11.1	8.9	20.0	30.0	-10.0	400	265
288.05	14.7	8.5	23.2	37.0	-13.8	327	279
360.03	16.8	8.2	25.0	37.0	-12.0	198	167
408.02	18.5	10.5	29.0	37.0	-8.0	231	142

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)  
+ Reading value (dBuV).
  2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level - Limit value



## TEST DATA OF RADIATED EMISSION

EUT: **USB KEYBOARD**MODEL: **9001AH**ANT. POLARITY: VerticalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M


Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
48.01	9.9	12.2	22.1	30.0	-7.9	124	269
60.01	7.0	13.7	20.7	30.0	-9.3	166	238
120.03	12.7	9.6	22.3	30.0	-7.7	100	201
144.03	12.9	8.6	21.5	30.0	-8.5	100	136
168.03	11.3	12.6	23.9	30.0	-6.1	100	5
216.03	11.1	13.2	24.3	30.0	-5.7	100	345
288.04	14.7	8.3	23.0	37.0	-14.0	100	329
336.02	16.0	8.7	24.7	37.0	-12.3	140	138

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)  
+ Reading value (dBuV).
  2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level - Limit value




## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN

### CONDUCTED EMISSION TEST



## RADIATED EMISSION TEST







## 6. APPENDIX - INFORMATION OF THE TESTING LABORATORY

### Information of the testing laboratory

We, ADT Corp., are founded in 1988, to provide our best service in EMC and Safety consultation. Our laboratory is accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

● USA	FCC, UL, NVLAP
● Germany	TUV Rheinland TUV Product Service
● Japan	VCCI
● New Zealand	RFS
● Norway	NEMKO, DNV
● U.K.	INCHCAPE
● R.O.C.	BSMI

Enclosed please find some certificates of our laboratory obtained from approval agencies. If you have any comments, please feel free to contact us with the following:

**Lin Kou EMC Lab.:**

Tel: 886-2-26032180

Fax: 886-2-26022943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab.:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Design Center:**

Tel: 886-2-26093195

Fax: 886-2-26093184

E-mail: [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)<http://www.adt.com.tw>