

Host Unit Information of ThinkPad T30 Series


- **Host PC Information**
- **Host PC Labeling**
- **Antenna Information**

Host PC Information


The left antenna in LCD is used for both RF transmission and receiving with half duplex switching mode. The right antenna is used for RF receiver only. When the Wireless LAN card is in RF receiving state, one of the antennas is selected automatically to have a good quality of radiocommunication.



Host PC Labeling



Bottom view, Front side

 Marca Registrada ®Registered Trademark of International Business Machines Corporation Manufactured by IBM Made In Mexico	Type 2367 16V --- 4.5A This Product contains a Lithium Ion Battery, Lithium Battery and Cathode Fluorescent Lamp which contains mercury. Please refer to User Manual or follow Local Ordlnances or Regulations for Disposal of this machine. This Class B digital apparatus meets all requirements of the Canadian Interference Causing Equipment Regulations Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.	MAC Address
COPYRIGHTED CODE AND PARTS CONTAINED HEREIN. ©COPYRIGHT 1981, 2002 IBM CORP.  Tested To Comply With FCC Standards FOR HOME OR OFFICE USE	AUSTRALIA WARNING: ONLY EQUIPMENT THAT HAS A TELECOMMUNICATIONS COMPLIANCE LABEL MAY BE CONNECTED TO THE HEADSET PORT. Apparatus Claims of U.S. Patent Nos. 4,831,803; 4,577,216; 4,819,098 and 4,907,093 licenced for limited viewing uses only.     US LISTED LTE167G	

Antenna Information

1. Antenna Specification

Transmission Antenna assembly overview

Designator (Parts Number)	Manufacture	Antenna type	Cable type and length	Gain (dBi) Note 1)
LCD left antenna 46L4819	IBM Japan Ltd.	Inverted F type Antenna	coax 560mm	0.53 dBi (peak)
LCD right antenna 46L4818			coax 800mm	-0.80 dBi (peak)


Notes:

1a. Includes all cable losses

1b. Antenna type should be Omni Directional and have gain of 3.0 dBi or less regarding the IBM internal specification.

2. Radiation characteristic of antenna


The left antenna



Note1) The measurement was performed at 3 frequencies (2400, 2450, 2500MHz).

Note2) The maximum antenna gain was found around **60 degree** angle from measuring apparatus in **horizontal** polarization at the lowest frequency(2.40GHz).


The right antenna



Note1) The measurement was performed at 3 frequencies (2400, 2450, 2500MHz).



Note2) The maximum antenna gain was found around **- 70 degree** angle from measuring apparatus in **horizontal** polarization at the lowest frequency(2.40GHz).

3. Antenna Locations



4. Exterior Photo of Antennas

(Inverted F type Antenna and Cable)



Left antenna : IBM P/N: 46L4819 Cable : coax 560 mm
Right antenna : IBM P/N: 46L4818 Cable : coax 800 mm