FCC ID: 2BBT5-TH50

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT: Left

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-1.77	0.67	-2±1	-1	0.79	<5	0.24622	3.00	YES
	2.441	-3.1	0.49	-3±1	-2	0.63	<5	0.19716	3.00	YES
	2.480	-2.01	0.63	-2±1	-1	0.79	<5	0.25018	3.00	YES
π/4- DQPSK	2.402	0.3	1.07	0±1	1	1.26	<5	0.39023	3.00	YES
	2.441	-1.15	0.77	-1±1	0	1.00	<5	0.31247	3.00	YES
	2.480	-0.1	0.98	0±1	1	1.26	<5	0.39651	3.00	YES
8-DPSK	2.402	0.62	1.15	0±1	1	1.26	<5	0.39023	3.00	YES
	2.440	-1.1	0.78	-1±1	0	1.00	<5	0.31241	3.00	YES
	2.480	0.2	1.05	0±1	1	1.26	<5	0.39651	3.00	YES

Conclusion:

For the max result : 0.39651≤3.0 for 1g SAR, SAR is not required.

Signature: Date: 2025-01-18

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.