

FCC LISTED, REGISTRATION
NUMBER: 720267

Informe de ensayo n°:
Test report No:

IC LISTED REGISTRATION
NUMBER IC 4621A-1

NIE: 46227RRF.001

Test report

USA FCC Part 15.247, 15.207, 15.209
CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz,
and 5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-
Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

Identificación del objeto ensayado.....: Identification of item tested	CENTRAL BODY CONTROLLER
Marca Trademark	Tesla Motors
Modelo y/o referencia tipo Model and /or type reference	Central Body Controller
Other identification of the product	FCC ID: 2AEIM-1031503 IC: 20098-1031503
Final HW version	Version 1
Final SW version	Version 1
Características Features	---
Fabricante Manufacturer	TESLA MOTORS, INC 3500 Deer Creek Rd, Palo Alto, CA 94304 USA
Método de ensayo solicitado, norma.....: Test method requested, standard	USA FCC Part 15.247 10-1-14 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 10-1-14 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 1 (May 2015). CANADA RSS-Gen Issue 4 (November 2014). Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 05/06/2014. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Resultado.....: Summary	IN COMPLIANCE
Aprobado por (nombre / cargo y firma) Approved by (name / position & signature)	A. Llamas RF Lab. Manager

Fecha de realización	2015-07-31
Date of issue	
Formato de informe No.	FDT08_16
Report template No	

Index

Competences and guarantees.....	4
General conditions.....	4
Uncertainty	4
Usage of samples.....	4
Test sample description	5
Identification of the client	5
Testing period.....	5
Environmental conditions.....	5
Remarks and comments.....	7
Testing verdicts	8
Appendix A – Test result.....	9

Competences and guarantees

AT4 wireless is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

AT4 wireless is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621A-1.

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the AT4 wireless internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
46227/011	Central Body Controller module with antenna connectors	Central Body Controller	---	2015-07-13
46227/004	Antenna	---	---	2015-07-13
46227/005	Antenna	---	---	2015-07-13
46227/006	Antenna	---	---	2015-07-13

1. Sample S/01 has undergone the following test(s):

All radiated tests indicated in appendix A.

Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
46227/011	Central Body Controller module with antenna connectors	Central Body Controller	---	2015-07-13

1. Sample S/02 has undergone the following test(s):

All conducted tests indicated in appendix A.

Test sample description

The test sample consists of a Central body controller with Bluetooth Low Energy.

Identification of the client

TESLA MOTORS, INC
3500 Deer Creek Rd, Palo Alto, CA 94304 USA

Testing period

The performed test started on 2015-07-15 and finished on 2015-07-16.

The tests have been performed at AT4 wireless.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

Remarks and comments

1: Used instrumentation:

Conducted Measurements

		Last Cal. date	Cal. due date
1.	Spectrum Analyzer Agilent E4440A	2014/05	2016/05
2.	DC power supply R&S NGPE 40/40	2014/11	2017/11

Radiated Measurements

		Last Cal. date	Cal. due date
1.	Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2.	BiconicalLog antenna ETS LINDGREN 3142E	2014/03	2017/03
3.	Multi Device Controller EMCO 2090	N.A.	N.A.
4.	Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2013/11	2016/11
5.	Double-ridge Guide Horn antenna 14-40 GHz SCHWARZBECK BBHA 9170	2014/03	2017/03
6.	EMI Test Receiver R&S ESU 26	2013/08	2015/08
7.	Spectrum analyser Rohde & Schwarz FSW50	2013/10	2015/10
8.	RF pre-amplifier 10 MHz-6 GHz SCHWARZBECK BBV9743	2015/03	2016/03
9.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-3A	2015/05	2016/05
10.	RF pre-amplifier BONN BLMA 1840-1M 18-40 GHz.	2014/02	2016/02

Testing verdicts

Not applicable	:	N/A
Pass	:	P
Fail	:	F
Not measured	:	N/M

FCC PART 15 PARAGRAPH / RSS-247		VERDICT			
		NA	P	F	NM
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (1)	6 dB Bandwidth	P			
Section 15.247 Subclause (b) / RSS-247 5.4. (4)	Maximum output power and antenna gain	P			
Section 15.247 Subclause (d) / RSS-247 5.5	Emission limitations conducted (Transmitter)	P			
Section 15.247 Subclause (d) / RSS-247 5.5. ..	Band-edge emissions compliance (Transmitter)	P			
Section 15.247 Subclause (e) / RSS-247 5.2. (2)	Power spectral density	P			
Section 15.247 Subclause (d) / RSS-247 5.5. ...	Emission limitations radiated (Transmitter)	P			

Appendix A – Test result

INDEX

TEST CONDITIONS	11
Occupied Bandwidth	12
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (1). 6 dB Bandwidth	15
Section 15.247 Subclause (b) / RSS-247 5.4. (4). Maximum output power and antenna gain	18
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter)	21
Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)	24
Section 15.247 Subclause (e) / RSS-247 5.2. (2) Power spectral density	26
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)	29

TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 12.5 \text{ Vdc}$$

Type of power supply = DC voltage from external power supply.

Type of antenna = External attachable antenna.

Declared Gain for antenna (maximum) = 3 dBi

TEST FREQUENCIES FOR CONDUCTED TESTS:

Lowest channel: 2402 MHz

Middle channel: 2440 MHz

Highest channel: 2480 MHz

TEST FREQUENCIES FOR RADIATED TESTS:

Lowest range: 2402 MHz, 2404 MHz, 2406 MHz

Middle range: 2438 MHz, 2440 MHz, 2442 MHz

Highest range: 2476 MHz, 2478 MHz 2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyzer.

The Equipment under test (EUT) incorporates 3 identical Bluetooth Low Energy modules which cannot transmit simultaneously at the same frequency. The conducted tests were performed in one antenna port corresponding to one module (Master module).

RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

The Equipment under test (EUT) incorporates 3 identical Bluetooth Low Energy modules which cannot transmit simultaneously at the same frequency. The radiated spurious emissions tests were performed with the 3 modules operating at 3 different adjacent channels in the low, mid and high ranges of the operating band, as the worst case.


Occupied Bandwidth

RESULTS


(see next plots).

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
99% bandwidth (MHz)	1.064	1.060	1.057
-26 dBc bandwidth (MHz)	1.640	1.620	1.642
Measurement uncertainty (kHz)	±7		


Lowest Channel



Middle Channel



Highest channel



Section 15.247 Subclause (a) (2) / RSS-247 5.2. (1). 6 dB Bandwidth

SPECIFICATION

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS


6 dB Bandwidth (see next plots).

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
6 dB Spectrum bandwidth (kHz)	716.7	700.7	704.7
Measurement uncertainty (kHz)	±7		


Verdict: PASS

6 dB BANDWIDTH.


Lowest Channel



Middle Channel



Highest Channel



Section 15.247 Subclause (b) / RSS-247 5.4. (4). Maximum output power and antenna gain

SPECIFICATION

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).
 The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS

The maximum peak conducted output power was measured using the method according to point 9.1.1. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 05/06/2014.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

MAXIMUM OUTPUT POWER. See next plots.

Maximum declared antenna gain: 3 dBi.


	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
Maximum conducted power (dBm)	-2.45	-3.25	-4.12
Maximum EIRP power (dBm)	0.55	-0.25	-1.12
Measurement uncertainty (dB)	±1.5		

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.


Verdict: PASS

CONDUCTED PEAK POWER.


Lowest frequency



Middle frequency



Highest frequency



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

RESULTS:

Reference Level Measurement

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
Reference Level Measurement (dBm)	-3.43	-4.24	-5.11
Measurement uncertainty (dB)	±1.5		

Lowest frequency 2402 MHz

All peaks are more than 20 dB below the limit.

Middle frequency 2440 MHz


All peaks are more than 20 dB below the limit.

Highest frequency 2480 MHz

All peaks are more than 20 dB below the limit.


Verdict: PASS

Lowest frequency (2402 MHz)




Note: The peak above the limit is the carrier frequency.

Middle frequency (2440 MHz)



Note: The peak above the limit is the carrier frequency.

Highest frequency (2480 MHz)



Note: The peak above the limit is the carrier frequency.

Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)


SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

RESULTS:

1. LOW FREQUENCY SECTION. CONDUCTED.


See next plot.



Verdict: PASS

2. HIGH FREQUENCY SECTION. CONDUCTED.

See next plot.



Verdict: PASS

Section 15.247 Subclause (e) / RSS-247 5.2. (2) Power spectral density

SPECIFICATION

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

The maximum power spectral density level in the fundamental emission was measured using the method PKPSD (Peak PSD) according to point 10.2. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 05/06/2014.


Power spectral density (see next plots).

	Lowest frequency 2402 MHz	Middle frequency 2440 MHz	Highest frequency 2480 MHz
Power spectral density (dBm)	-4.56	-5.29	-6.04
Measurement uncertainty (dB)	±1.5		


Verdict: PASS

Power spectral density.


Lowest Channel



Middle Channel



Highest Channel



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)) / RSS-Gen 8.9.:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz-1000 MHz.

The spurious signals detected do not depend on the operating channel.

Spurious signals at less than 20 dB below the limit.

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
30.388	V	Quasi-Peak	27.67	± 4.12
37.663	V	Quasi-Peak	36.38	± 4.12
74.038	V	Quasi-Peak	29.11	± 4.12

Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dBμV/m at 3 m) are measured with RMS detector for checking compliance with the average limit.

1. CHANNEL: LOWEST RANGE (2402 MHz, 2404 MHz, 2406 MHz). Highest peak levels.

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2.389615	V	Peak	47.95	± 4.00
4.813750	V	Peak	39.82	± 4.00

2. CHANNEL: MIDDLE RANGE (2438 MHz, 2440 MHz, 2442 MHz). Highest peak levels.


Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
4.881750	V	Peak	41.22	± 4.00

3. CHANNEL: HIGHEST RANGE (2476 MHz, 2478 MHz 2480 MHz). Highest peak levels.

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBμV/m)	Measurement Uncertainty (dB)
2.483790	V	Peak	53.94	± 4.00
4.954250	V	Peak	40.44	± 4.00

Verdict: PASS


FREQUENCY RANGE 30 MHz-1000 MHz.



(This plot is valid for all three ranges).


FREQUENCY RANGE 1 GHz to 3 GHz.

LOWEST RANGE (2402 MHz, 2404 MHz, 2406 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

MIDDLE RANGE (2438 MHz, 2440 MHz, 2442 MHz).



Note: The peak shown in the plot above the limit is the carrier frequency.


HIGHEST RANGE (2476 MHz, 2478 MHz 2480 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 GHz to 18 GHz.


LOWEST RANGE (2402 MHz, 2404 MHz, 2406 MHz).




MIDDLE RANGE (2438 MHz, 2440 MHz, 2442 MHz).



HIGHEST RANGE (2476 MHz, 2478 MHz 2480 MHz).




FREQUENCY RANGE 18 GHz to 26 GHz.




(This plot is valid for all three ranges).

FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)


LOWEST RANGE (2402 MHz, 2404 MHz, 2406 MHz).



MIDDLE RANGE (2438 MHz, 2440 MHz, 2442 MHz).




HIGHEST RANGE (2476 MHz, 2478 MHz 2480 MHz).




FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)

LOWEST RANGE (2402 MHz, 2404 MHz, 2406 MHz).



MIDDLE RANGE (2438 MHz, 2440 MHz, 2442 MHz).



HIGHEST RANGE (2476 MHz, 2478 MHz, 2480 MHz).

