

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	CD+G/MP3+G KARAOKE PLAYER WITH BLUETOOTH
Model Name	SML385U, SML385UBK, SML385UW, SML385BT, SML385BTW, SML385BTBK, SML392BT, SML392BTBK, SML392BTW, SML385BTXX, SML392BTXX, SML385UXX (XX means unit color, it can be A to Z or N/A)
FCC ID	2AAXO-SML385UXX

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

$$P_t = 2.097 \text{ dBm} = 1.62 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47

§15.247.

The result for RF exposure evaluation  $\text{SAR} = (1.62 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.44 (\text{GHz})}] = 0.51 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.

