

# **FCC Test Report**

Report No.: AGC13525230201FE02

FCC ID	:	2AATLK265B-PR
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	WiFi/BT module
BRAND NAME	:	FN-LINK
MODEL NAME	:	K265B-PR
APPLICANT	:	FN-LINK TECHNOLOGY LIMITED
DATE OF ISSUE	:	Sep. 04, 2023
STANDARD(S)	:	FCC Part 15.247
<b>REPORT VERSION</b>	:	V1.0
<u>Attestation of (</u>	Flo	obai compliance (Shenzhen) Co., Ltd

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.





#### **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 04, 2023	Valid	Initial Release



# **TABLE OF CONTENTS**

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	7
2.4. TEST METHODOLOGY	7
2.5. SPECIAL ACCESSORIES	7
2.6. EQUIPMENT MODIFICATIONS	7
2.7. ANTENNA REQUIREMENT	7
3. MEASUREMENT UNCERTAINTY	9
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	11
5.1. CONFIGURATION OF TESTED SYSTEM	11
5.2. EQUIPMENT USED IN TESTED SYSTEM	11
5.3. SUMMARY OF TEST RESULTS	11
6. TEST FACILITY	
7. PEAK OUTPUT POWER	13
7.1. MEASUREMENT PROCEDURE	
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
7.3. LIMITS AND MEASUREMENT RESULT	14
8. BANDWIDTH	
8.1. MEASUREMENT PROCEDURE	
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3. LIMITS AND MEASUREMENT RESULTS	
9. CONDUCTED SPURIOUS EMISSION	25
9.1. MEASUREMENT PROCEDURE	25
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	25
9.3. MEASUREMENT EQUIPMENT USED	25
9.4. LIMITS AND MEASUREMENT RESULT	



10.1. MEASUREMENT PROCEDURE	37
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
10.3. MEASUREMENT EQUIPMENT USED	37
10.4. LIMITS AND MEASUREMENT RESULT	
11. RADIATED EMISSION	41
11.1. MEASUREMENT PROCEDURE	41
11.2. TEST SETUP	42
11.3. LIMITS AND MEASUREMENT RESULT	43
11.4. TEST RESULT	43
12. LINE CONDUCTED EMISSION TEST	57
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	57
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	57
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	58
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	58
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	58
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	61
APPENDIX B: PHOTOGRAPHS OF EUT	



# **1. VERIFICATION OF COMPLIANCE**

Applicant	FN-LINK TECHNOLOGY LIMITED		
Address	No.8, Litong Road, Liuyang Economic & Technical Development Zone, Changsha, Hunan, CHINA		
Manufacturer	FN-LINK TECHNOLOGY LIMITED		
Address	No.8, Litong Road, Liuyang Economic & Technical Development Zone, Changsha, Hunan, CHINA		
Factory	FN-LINK TECHNOLOGY LIMITED		
Address	No.8, Litong Road, Liuyang Economic & Technical Development Zone, Changsha, Hunan, CHINA		
Product Designation	WiFi/BT module		
Brand Name	FN-LINK		
Test Model	K265B-PR		
Date of receipt of test item	Feb. 12, 2023		
Date of test	Feb. 12, 2023 to Sep. 04, 2023		
Deviation	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BLE/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By

Alan Duan Ser

Alan Duan (Project Engineer)

Sep. 04, 2023

**Reviewed By** 

Calvin Liu (Reviewer) Sep. 04, 2023

Approved By

Max Zhang

Max Zhang

(Authorized Officer)

Sep. 04, 2023



# 2. GENERAL INFORMATION

# 2.1. PRODUCT DESCRIPTION

The EUT is designed as a "WiFi/BT module". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz	
RF Output Power	GFSK 1Mbps: 1.797dBm (Max) GFSK 2Mbps: 1.707dBm (Max)	
Bluetooth Version	V5.2	
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE ⊠GFSK 1Mbps ⊠GFSK 2Mbps	
Number of channels	40 Channels	
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)	
Antenna Gain	4.59dBi	
Hardware Version	1.0	
Software Version	1.0	
Power Supply	DC 12V by adapter	

# 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency		
2400~2483.5MHz	0	2402 MHz		
	1	2404 MHz		
	:	:		
	38	2478 MHz		
	39	2480 MHz		



# 2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for FCC ID: 2AATLK265B-PR filing to comply with the FCC Part 15.247 requirements.

#### 2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **2.5. SPECIAL ACCESSORIES**

Refer to section 5.2.

#### 2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.

#### 2.8. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle Duty Cycle Factor (%) (dB)		1/ T Minimum VBW (kHz)	
BLE_1Mbps	95	15.20	8.18	10.53	
BLE_2Mbps	59	9.45	10.25	16.95	


Remark:

1. Duty Cycle factor = 10 \* log (1/ Duty cycle)

2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value



The test plots as follows:





# **3. MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y  $\pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_{c} = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



# **4. DESCRIPTION OF TEST MODES**

NO.	TEST MODE DESCRIPTION
1	Low channel TX for GFSK 1Mbps
2	Middle channel TX for GFSK 1Mbps
3	High channel TX for GFSK 1Mbps
4	Low channel TX for GFSK 2Mbps
5	Middle channel TX for GFSK 2Mbps
6	High channel TX for GFSK 2Mbps

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.

2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.


その時間が回転の部 そりたち、60時間は10年10 (abel object at 0x0870M220) 开始下載bluetooth firmware ici reset success ici reset success ici object cond avd4 onde tord4 0x01 0x22 0xr6 0x00 0x01 0x04 0xr6 10x1 0x12 0x16 0x00 0x01 0x04 0xr6 0x17 0x10	Scenario Option		Data Rate Options Facket Type DH1 ~ Data Length(hytes) 27
0x00 0x00 0x00 0x00 0x00 0x00 0x00	Transmit 0 unwhitened	~	Poll Period (frames) 1
Jué 0x3 0xb 0x0 0x28 0x0 0x0 0x1 0x0 0x22 0x24 0xae 0x55 0x0 0x4 0xe 0x4 0x1 0xd Domestion complete: handle 0x39 Juni 0x12 0x12 0x16 0x86 0x33 0x64 0x99 0x19 0x59 0x1a 0x4f Set Sync word 0K			Nodulation
	Channel Option		Disable Modulation
	Hopping Mode single frequency	$\sim$	
	Tz Channel 0	~	Whitening Status
	Rz Channel 0	~	Whitening Enable Whitening Disable
	Power Control		
	Enable Pover Control		Enter LAF 0x000000 Calc
	Set Fower Control Level		
WISYCF 140.0II			
MSVCP140_1.dll	0	Change	
opengl32sw.dll pyexpat.pyd			Get BER Get PER Get Munber
python3.dll	Access Code (Nex)		
python39.dll			
Ot5Bluetooth.dl	LSB MSB		
Qt5Concurrent.dll			
Qt5Core.dll	54f1a59f999b433ed5	Set	
Qt5DBus.dll		Jet	LE Rx end Hei Reset OK Done
Qt5Designer.dll	Override with 1010 Pattern		
Qt5Gamepad.dll			



# **5. SYSTEM TEST CONFIGURATION**

# **5.1. CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:



Conducted Emission Configure:

EUT	AE

# **5.2. EQUIPMENT USED IN TESTED SYSTEM**

Item	Equipment	Model No. ID or Specification		Remark
1	WiFi/BT module	K265B-PR	2AATLK265B-PR	EUT
2 Adaptor		JF012WR-0900150UH	Input: AC100-240V,50-60Hz	AE
2	2 Adapter	JI UIZWIN-090015000	Output: DC12V2A	AL

#### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



# 6. TEST FACILITY

Test software

Test Site	Attestation of C	Attestation of Global Compliance (Shenzhen) Co., Ltd				
Location		1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China				
Designation Number	CN1259	CN1259				
FCC Test Firm Registration Number	975832	975832				
A2LA Cert. No.	5054.02	5054.02				
Description	Attestation of C	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA				
TEST EQUIPMENT OF CONDUCTED EMISSION TEST						
Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due	
TEST RECEIVER	R&S	ESPI	101206	Jun. 03, 2023	Jun. 02, 2024	
LISN	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024	

ES-K1(Ver.V1.71)

N/A

N/A

N/A

# TEST EQUIPMENT OF RADIATED EMISSION TEST

R&S

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Jun. 01, 2023	May 31, 2024
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2023	Apr. 22, 2024
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



# 7. PEAK OUTPUT POWER


# 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2. RBW≥DTS bandwidth
- 3. VBW≥3\*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for cables.

#### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP







#### 7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power					
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail	
	2402	0.341	≪30	Pass	
GFSK 1M	2440	0.647	≪30	Pass	
	2480	1.797	≪30	Pass	
	2402	0.266	≪30	Pass	
GFSK 2M	2440	0.565	≪30	Pass	
	2480	1.707	≪30	Pass	


# Test Graphs of Conducted Output Power


















# 8. BANDWIDTH

# **8.1. MEASUREMENT PROCEDURE**

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW $\ge$ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak

4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

# 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail
	2402	1.016	0.660	≥0.5	Pass
GFSK 1M	2440	1.011	0.662	≥0.5	Pass
	2480	1.017	0.656	≥0.5	Pass
	2402	2.030	1.136	≥0.5	Pass
GFSK 2M	2440	2.036	1.121	≥0.5	Pass
	2480	2.036	1.126	≥0.5	Pass

# 8.3. LIMITS AND MEASUREMENT RESULTS





# Test Graphs of Occupied Bandwidth

















#### Test Graphs of DTS Bandwidth











# 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

# 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

# 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

#### 9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT					
Angliaghta Limita	Measurement Result				
Applicable Limits	Test Data	Criteria			
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS			






#### Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands










































#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands







# **10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY**

### **10.1. MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

### **10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

Refer to Section 7.2.


### **10.3. MEASUREMENT EQUIPMENT USED**

Refer to Section 6.

### **10.4. LIMITS AND MEASUREMENT RESULT**


	Test Data of Co	nducted Output Power Sp	pectral Density	
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail
	2402	-15.478	≪8	Pass
GFSK 1M	2440	-15.149	≪8	Pass
	2480	-14.122	≪8	Pass
	2402	-20.029	≪8	Pass
GFSK 2M	2440	-19.693	≪8	Pass
	2480	-18.593	≪8	Pass






#### Test Graphs of Conducted Output Power Spectral Density












# **11. RADIATED EMISSION**

### **11.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



### 11.2. TEST SETUP





# **11.3. LIMITS AND MEASUREMENT RESULT**

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 11.4. TEST RESULT

### Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.




				Г	kadi	ated	emi	ssion from	1 301		1000			-				
EUT				WiFi/E	3T n	nodul	е			Mode	l Nam	е		K2	265B-	PR		
Temperature				25° C	;					Relati	ive Hu	imidi	ity	55	.4%			
Pressure				960hF	Pa					Test Voltage			Nc	ormal	Volt	tage		
Test Mode				Mode	3					Anten	nna			Ho	orizor	ntal		
<b>72.0</b> d	dB uV⊅	m																
32	(Received)	g letters	Utudeal	L			www.hty	and the second	<b>_</b>	eser Necky Provide	1×		<b>*</b>		mil: argin:			
-8																		
30.000	)	40	50	60 2	70 8	0		(MHz)			300	400	500	600	700	100	⊥ 0.000	
Ν	No.	Mk.		Freq.		Read Leve	-	Correct Factor		asure nent		nit	Ove	er				
_				MHz		dBu	V	dB	dE	8uV/m	dE	3/m	dB		Dete	ctor		
_	1		352	.9433		10.9	)2	17.42	2	8.34	46.	00	-17.6	66	pea	ak		
_	2		366	.8231		12.7	8'	17.80	3	0.58	46.	00	-15.4	42	pea	ak		
_	3		460	.7271		5.0	)7	26.23	3	1.30	46.	00	-14.7	70	pea	ak		
_	4		625	.0780		8.2	24	25.23	3	3.47	46.	00	-12.	53	pea	ak		
_	5	*	750	.1083		15.1	5	24.06	3	9.21	46.	00	-6.7	9	pea	ak		
_	6		975	.7529		6.8	35	29.02	3	5.87	54.	00	-18.1	13	pea	ak		

### Radiated emission from 30MHz to 1000MHz

#### **RESULT: PASS**



EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical



#### RESULT: PASS Note:

1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.



#### Radiated emission above 1GHz

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	45.26	0.08	45.34	74	-28.66	peak
4804.000	36.12	0.08	36.2	54	-17.8	AVG
7206.000	40.18	2.21	42.39	74	-31.61	peak
7206.000	31.59	2.21	33.8	54	-20.2	AVG
emark:						

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4804.000	45.19	0.08	45.27	74	-28.73	peak
4804.000	35.87	0.08	35.95	54	-18.05	AVG
7206.000	40.12	2.21	42.33	74	-31.67	peak
7206.000	29.68	2.21	31.89	54	-22.11	AVG
emark:						
emark:						
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			



EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	45.18	0.14	45.32	74	-28.68	peak
4880.000	36.27	0.14	36.41	54	-17.59	AVG
7320.000	41.05	2.36	43.41	74	-30.59	peak
7320.000	32.49	2.36	34.85	54	-19.15	AVG
Remark:						
=actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier.			

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	46.18	0.14	46.32	74	-27.68	peak
4880.000	38.54	0.14	38.68	54	-15.32	AVG
7320.000	40.15	2.36	42.51	74	-31.49	peak
7320.000	31.59	2.36	33.95	54	-20.05	AVG
emark:						



EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	47.15	0.22	47.37	74	-26.63	peak
4960.000	37.84	0.22	38.06	54	-15.94	AVG
7440.000	41.54	2.64	44.18	74	-29.82	peak
7440.000	31.59	2.64	34.23	54	-19.77	AVG
emark:						

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	46.28	0.22	46.5	74	-27.5	peak
4960.000	35.27	0.22	35.49	54	-18.51	AVG
7440.000	41.06	2.64	43.7	74	-30.3	peak
7440.000	31.59	2.64	34.23	54	-19.77	AVG
emark:						
JUIDIN.						

#### **RESULT: PASS**

### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


All test modes had been tested. The GFSK 1Mbps is the worst case and recorded in the report.



EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

# Test result for band edge emission at restricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




# **RESULT: PASS**




#### Report No.: AGC13525230201FE02 Page 50 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**



#### Report No.: AGC13525230201FE02 Page 51 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**



#### Report No.: AGC13525230201FE02 Page 52 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**




#### Report No.: AGC13525230201FE02 Page 53 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**




#### Report No.: AGC13525230201FE02 Page 54 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**




#### Report No.: AGC13525230201FE02 Page 55 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




#### **RESULT: PASS**




#### Report No.: AGC13525230201FE02 Page 56 of 61

EUT	WiFi/BT module	Model Name	K265B-PR
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



# **12. LINE CONDUCTED EMISSION TEST**


### **12.1. LIMITS OF LINE CONDUCTED EMISSION TEST**

Frequency	Maximum RF Line Voltage				
Frequency	Q.P.( dBuV)	Average( dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





# 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 12V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


# 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

# 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Line Conducted Emission Test Line 1-L



#### "agc\_fin" MEASUREMENT RESULT:


2023/5/26 9:44 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.406000 0.426000 0.434000 0.502000 0.530000 0.654000	32.60 31.50 31.40 39.40 36.20 27.40	6.2 6.2 6.2 6.2 6.2 6.3	58 57 56 56 56	25.1 25.8 25.8 16.6 19.8 28.6	QP QP	L1 L1 L1 L1 L1 L1

# MEASUREMENT RESULT: "agc\_fin2"

2023/5/26 9:44 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.426000	21.70	6.2	47	25.6	AV	L1
0.498000	36.60	6.2	46	9.4	AV	ь1
0.526000	28.60	6.2	46	17.4	AV	ь1
0.938000	18.70	6.3	46	27.3	AV	L1
0.962000	16.90	6.3	46	29.1	AV	ь1
1.058000	20.60	6.3	46	25.4	AV	L1







### MEASUREMENT RESULT: "agc\_fin"

2023/5/26 9:47 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.390000 0.406000 0.426000 0.498000 0.530000 3.730000	29.40 31.30 32.20 40.20 35.30 26.50	6.2 6.2 6.2 6.2 6.2 6.4	58 58 57 56 56	28.7 26.4 25.1 15.8 20.7 29.5	QP QP	N N N N N

#### MEASUREMENT RESULT: "agc fin2"

2023/5/26 9:47 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.406000	23.30	6.2	48	24.4	AV	N
0.426000	20.70	6.2	47	26.6	AV	N
0.498000	35.20	6.2	46	10.8	AV	N
0.530000	29.90	6.2	46	16.1	AV	N
0.966000	15.30	6.3	46	30.7	AV	N
1.026000	20.70	6.3	46	25.3	AV	N

#### **RESULT: PASS**

Note: All the test modes had been tested, the GFSK 1Mbps was the worst case. Only the data of the worst case would be record in this test report.



# **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC13525230201AP02

# **APPENDIX B: PHOTOGRAPHS OF EUT**

Refer to the Report No.: AGC13525230201AP03

----END OF REPORT----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.