

Report No.: SHEM200700598303

Page: 1 of 7

1 Cover Page

RF Exposure REPORT

Application No.: SHEM2007005983CR FCC ID: 2AGOFRC421A

Applicant: HCS (Suzhou) Limited

Address of Applicant: 19F-20F, Building B-3rd, No. 209 Zhuyuan Road, New District, Suzhou,

P.R. China

Factory: WUJIANG CENTURY BILLION ELECTRONIC TECHNOLOGY CO., LTD

Address of Factory: No.149 West Tun Cun Road Tongli Town Wujiang Suzhou Jiangsu

People's Republic of China 215216

Equipment Under Test (EUT):

EUT Name: Remote Control **Model No.:** RC4213403/02BR,

Add Model No.: RC4213801/02BR, RC4213401/02BR, RC4213402/02BR, Babylon

RCU,RC421XXXX/XXR,RC421XXXX/XXBR ("X"=0-9."B"means packed

with battery)

Standard(s): FCC Rules 47 CFR §2.1093

KDB447498 D01 General RF Exposure Guidance v06

Date of Receipt: 2020-07-20

Date of Test: 2020-09-16 to 2020-10-17

Date of Issue: 2020-10-19

Test Result: Pass*

arlan Shan

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

检验检测专用章 Sinspection & Testing Services GS-CSTV Made Jechnical Services (Apha) Co., Linds Center Film Services (Apha) Co., Linds Center Film Services (Apha) Co., Linds (Apha)

DPFOVAIS IN WITLING.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Con

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM200700598303

Page: 2 of 7

Revision Record				
Version	Description	Date	Remark	
00	Original	2020-10-19	/	

Authorized for issue by:		
	Bril Wu	
	Bill Wu / Project Engineer	
	Parlam Zhan	
	Parlam Zhan /Reviewer	



Report No.: SHEM200700598303

Page: 3 of 7

2 Contents

			Page
1	CO	/ER PAGE	1
2	CON	NTENTS	3
3	GEN	NERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	DETAILS OF E.U.T	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	TES	ST STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS	6
5	MEA	ASUREMENT AND CALCULATION	7
	5.1	MAXIMUM TRANSMIT POWER	7
	5.2	RE EXPOSURE CALCULATION	7



Report No.: SHEM200700598303

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

	Power supply:	DC 3.0V By 2*AAA size batteries	
--	---------------	---------------------------------	--

3.2 Details of E.U.T.

BLE

Antenna Gain:	-5dBi
Antenna Type:	PCB Antenna
Bluetooth Version:	V5.0 LE
Data Rate:	1 Mbps,2 Mbps
Channel Spacing:	2MHz
Modulation Type:	GFSK
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz

RF4CE

14 102		
Antenna Gain:	-5dBi	
Antenna Type:	PCB Antenna	
Channel Spacing:	5MHz	
Modulation Type:	O-QPSK	
Number of Channels:	16	
Operation Frequency:	2405MHz to 2480MHz	



Report No.: SHEM200700598303

Page: 5 of 7

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (LAB CODE: 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

• FCC (Designation Number: CN5033)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

• ISED (CAB Identifier: CN0020)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM200700598303

Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max power of channel)/(min test separation distance)]*[$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion. For 2.4G band device, the limit of worse case is

 $P_{\text{max}} \le 3.0^{\circ} D_{\text{min}} / \sqrt{f} = 3.0^{\circ} 5 / \sqrt{2.480} = 9.525 \text{mW}$



Report No.: SHEM200700598303

Page: 7 of 7

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200700598301& SHEM200700598302.

Test Data:

		Power[dBm]		Power[mW]	
Test Mode	Test Channel	1M	2M	1M	2M
BLE	2402	4.71	4.73	2.96	2.97
BLE	2440	5.03	5.01	3.18	3.17
BLE	2480	4.15	4.08	2.60	2.56

Test Mode	Test Channel	Power[dBm]	Power[mW]
RF4CE	2405	4.74	2.98
RF4CE	2440	5.02	3.18
RF4CE	2480	4.18	2.62

5.2 RF Exposure Calculation

The Max Conducted Peak Output Power is 3.18mW.

Conducted Peak Output Power =3.18mW < 9.525mW

So the SAR report is not required.

-- End of the Report--