

TEST REPORT

Applicant Name: Shenzhen Neutop Optoelectronics Co., Ltd
Address: 502, BLDG 4, Pingshan minQi Technology Park, No. 65 Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen China
Report Number: 2401A63533E-RF-00A
FCC ID: 2BEGB-YX07

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Projector
Model No.: D005
Multiple Model(s) No.: D003, D004
Trade Mark: N/A
Date Received: 2024-12-04
Issue Date: 2025-04-23

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Allen Bai

Allen Bai
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUMMARY OF TEST RESULTS.....	9
TEST EQUIPMENT LIST	10
REQUIREMENTS AND TEST PROCEDURES	12
AC LINE CONDUCTED EMISSIONS.....	12
RADIATED EMISSIONS	14
20 dB EMISSION BANDWIDTH.....	17
CHANNEL SEPARATION TEST	19
QUANTITY OF HOPPING CHANNEL TEST	20
TIME OF OCCUPANCY (DWEELL TIME)	21
PEAK OUTPUT POWER MEASUREMENT	22
BAND EDGES.....	23
ANTENNA REQUIREMENT	24
TEST DATA AND RESULTS.....	25
AC LINE CONDUCTED EMISSIONS.....	25
RADIATED EMISSIONS	28
20 dB EMISSION BANDWIDTH.....	50
99% OCCUPIED BANDWIDTH	54
CHANNEL SEPARATION.....	58
NUMBER OF HOPPING FREQUENCY	61
MAXIMUM CONDUCTED OUTPUT POWER	64
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	68
TIME OF OCCUPANCY (DWEELL TIME)	72
RF EXPOSURE EVALUATION	76
EUT PHOTOGRAPHS.....	78
TEST SETUP PHOTOGRAPHS	79

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401A63533E-RF-00A	Original Report	2025-04-23

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Projector
Tested Model	D005
Multiple Model(s)	D003, D004
Frequency Range	2402~2480MHz
Transmit Peak Power	6.86dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification[#]	2.5dBi (provided by the applicant)
Voltage Range	DC 29V from adapter
Sample serial number	2VID-1 for Conducted and Radiated Emissions Test 2VID-7 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model:SOY-2900380-410-B Input:100-240V~50/60Hz 2.5A Max Output:29.0V~3.8A 110.2W

Note: The Multiple models are electrically identical with the test model except for model name and colors. Please refer to the declaration letter[#] for more detail, which was provided by manufacturer.

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.207, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.63dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
2	2404	42	2444
...
...
36	2438	75	2477
37	2439	76	2478
38	2440	77	2479
39	2441	78	2480
EUT was tested with Channel 0, 39 and 78.			

EUT Exercise Software

Exercise Software [#]	Secure CRT
Power Level [#]	6

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
OUPU	Receptacle	PDU-OP1606K	6971041358020
Vivo	Earphone	XE160	Unknown
Dell	Mouse	MS116t	Unknown
Dell	Notebook	Latitude 7280	B0CB5M2
Sandisk	USB disk	CZ73-64G	Unknown


External I/O Cable

Cable Description	Length (m)	From Port	To
Shielded un-detachable DC cable	1.2	EUT	Adapter
Unshielded detachable AC cable	1.5	Adapter	LISN/Receptacle
Unshielded un-detachable earphone cable	1.0	EUT	Earphone
Unshielded un-detachable USB cable	1.5	EUT	Mouse
Unshielded detachable HDMI cable	2	EUT	Notebook

For Conducted Emissions:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.205, §15.209, §15.247(d)	Radiated Spurious Emission	Compliant
FCC §15.247(a)(1)	20 dB Emission Bandwidth	Compliant
FCC §15.247(a)(1)	Channel Separation	Compliant
FCC §15.247(a)(1)(iii)	Number of Hopping Frequency	Compliant
FCC §15.247(a)(1)(iii)	Time of Occupancy (dwell time)	Compliant
FCC §15.247(b)(1)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247 (i), §1.1307 (b) (3) & §2.1091	Maximum Permissible Exposure(MPE)	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Multiplex Switch Test Control Set	DT7220FSU	DQ77926	2024/06/18	2025/06/17
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40-N	102259	2024/12/04	2025/12/03
MARCONI	10dB Attenuator	6534/3	2942	2024/06/27	2025/06/26

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


REQUIREMENTS AND TEST PROCEDURES

AC Line Conducted Emissions

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


Radiated Emissions

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak
Above 1 GHz	Harmonics				
	1MHz	3 MHz	/	PK	Peak
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)				
	Band Edge & Other Emissions				
	1MHz	3 MHz	/	PK	Peak
	1MHz	≥10 Hz	/	Average	Peak

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

20 dB Emission Bandwidth

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “–xx dB down” requirement; that is, if the requirement calls for measuring the –20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an un-modulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “–xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an un-modulated carrier, then turn the EUT modulation on, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Channel Separation Test

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined.



Note: The limit is $\frac{2}{3} \times 20$ dB bandwidth

Quantity of Hopping Channel Test

Applicable Standard


Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.3

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.

It might prove necessary to break the span up into sub ranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels.



Time of Occupancy (Dwell Time)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.4

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.


Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} &(\text{Number of hops in the period specified in the requirements}) = (\text{number of hops on spectrum analyzer}) \\ &\times (\text{period specified in the requirements} / \text{analyzer sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.



Peak Output Power Measurement

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:


a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW $>$ 20 dB bandwidth of the emission being measured.
- 3) VBW \geq RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was added with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

Band Edges


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached, the antenna gain[#] is 2.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant


TEST DATA AND RESULTS

AC Line Conducted Emissions

Environmental Conditions

Temperature (°C)	21-26	Relative Humidity (%)	36-50
ATM Pressure (kPa)	101-103	Test engineer	Macy Shi
Test date	2024/12/31		
EUT operation mode	Transmitting(Maximum output power mode, EDR (8DPSK) Low Channel)		

AC 120V 60 Hz, Line



Condition: Line


Project : 2401A63533E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:Auto SWT:Auto

		Read		LISN	Cable	Limit	Over	
	Freq	Level	Level	Factor	Loss	Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.174	16.03	36.53	10.40	10.10	54.77	-18.24	Average
2	0.174	20.26	40.76	10.40	10.10	64.77	-24.01	QP
3	0.247	16.29	36.72	10.35	10.08	51.86	-15.14	Average
4	0.247	23.29	43.72	10.35	10.08	61.86	-18.14	QP
5	0.305	19.37	39.79	10.31	10.11	50.10	-10.31	Average
6	0.305	24.66	45.08	10.31	10.11	60.10	-15.02	QP
7	0.661	14.41	34.92	10.37	10.14	46.00	-11.08	Average
8	0.661	20.67	41.18	10.37	10.14	56.00	-14.82	QP
9	2.358	5.60	26.10	10.32	10.18	46.00	-19.90	Average
10	2.358	14.15	34.65	10.32	10.18	56.00	-21.35	QP
11	9.156	9.91	30.26	10.15	10.20	50.00	-19.74	Average
12	9.156	21.86	42.21	10.15	10.20	60.00	-17.79	QP

AC 120V 60 Hz, Neutral



Condition: Neutral

Project : 2401A63533E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:Auto SWT:Auto


		Read		LISN	Cable	Limit	Over	
	Freq	Level	Level	Factor	Loss	Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.180	18.36	38.91	10.45	10.10	54.50	-15.59	Average
2	0.180	20.72	41.27	10.45	10.10	64.50	-23.23	QP
3	0.299	20.39	41.19	10.69	10.11	50.28	-9.09	Average
4	0.299	24.46	45.26	10.69	10.11	60.28	-15.02	QP
5	0.589	14.04	34.81	10.65	10.12	46.00	-11.19	Average
6	0.589	19.70	40.47	10.65	10.12	56.00	-15.53	QP
7	0.809	13.70	34.24	10.42	10.12	46.00	-11.76	Average
8	0.809	20.50	41.04	10.42	10.12	56.00	-14.96	QP
9	4.746	8.11	28.70	10.40	10.19	46.00	-17.30	Average
10	4.746	16.77	37.36	10.40	10.19	56.00	-18.64	QP
11	9.059	12.83	33.57	10.54	10.20	50.00	-16.43	Average
12	9.059	21.51	42.25	10.54	10.20	60.00	-17.75	QP

Radiated Emissions**Environmental Conditions**

Temperature (°C)	23.1-24.2	Relative Humidity (%)	40.2-50.8
ATM Pressure (kPa):	101.5	Test engineer:	Anson Su & Zenos Qiao
Test date:	2024/12/19-2024/12/27		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, EDR (8DPSK) Low Channel) Above 1GHz: Transmitting(Maximum output power mode, EDR (8DPSK) Low Channel)		
Note:	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. For the radiated spurious emission below 30MHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number: 2401A63533E-RF
Test Mode : BT Transmitting
Setting PK RBW: 0.3KHz VBW:1KHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.01	32.12	26.88	59.00	126.81	-67.81	Peak
2	0.02	29.70	21.91	51.61	120.12	-68.51	Peak
3	0.04	27.15	20.72	47.87	114.96	-67.09	Peak
4	0.06	25.32	26.41	51.73	111.93	-60.20	Peak
5	0.11	21.49	33.08	54.57	106.89	-52.32	Peak
6	0.12	20.97	34.28	55.25	106.20	-50.95	Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number: 2401A63533E-RF
Test Mode : BT Transmitting
Setting PK RBW: 10KHz VBW:30KHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.48	6.87	43.13	50.00	94.06	-44.06	Peak
2	0.69	4.03	42.54	46.57	70.74	-24.17	Peak
3	0.90	1.97	42.53	44.50	68.43	-23.93	Peak
4	1.16	0.76	41.77	42.53	66.19	-23.66	Peak
5	1.34	0.25	40.53	40.78	64.88	-24.10	Peak
6	1.57	-0.39	41.02	40.63	63.49	-22.86	Peak


30MHz-1GHz_Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2401A63533E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq Factor		Read	Limit	Over	Remark
	MHz	dB/m	Level	Line	Limit	
			dBuV	dBuV/m	dBuV/m	dB
1	93.44	-17.60	49.95	32.35	43.50	-11.15 QP
2	122.40	-11.20	44.79	33.59	43.50	-9.91 QP
3	191.91	-14.02	45.00	30.98	43.50	-12.52 QP
4	378.42	-9.19	41.30	32.11	46.00	-13.89 QP
5	480.11	-6.34	34.98	28.64	46.00	-17.36 QP
6	827.86	-1.93	33.10	31.17	46.00	-14.83 QP

30MHz-1GHz_Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2401A63533E-RF
Test Mode : BT Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	92.26	-17.81	49.73	31.92	43.50	-11.58	QP
2	193.43	-13.89	40.20	26.31	43.50	-17.19	QP
3	376.27	-9.25	36.84	27.59	46.00	-18.41	QP
4	495.07	-5.93	38.00	32.07	46.00	-13.93	QP
5	619.35	-4.87	44.70	39.83	46.00	-6.17	QP
6	628.37	-4.58	44.00	39.42	46.00	-6.58	QP

Above 1GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave					
8DPSK							
Low Channel							
4804	60.34	PK	H	-7.79	52.55	74	-21.45
4804	59.03	PK	V	-7.79	51.24	74	-22.76
Middle Channel							
4882	59.45	PK	H	-7.58	51.87	74	-22.13
4882	58.18	PK	V	-7.58	50.60	74	-23.40
High Channel							
4960	58.22	PK	H	-7.57	50.65	74	-23.35
4960	56.97	PK	V	-7.57	49.40	74	-24.60

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded. The test result of peak was less than the limit of average, so just peak values were recorded.

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Average Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel							
4804	52.55	H	-24.73	27.82	54	-26.18	Harmonic
4804	51.24	V	-24.73	26.51	54	-27.49	Harmonic
Middle Channel							
4882	51.87	H	-24.73	27.14	54	-26.86	Harmonic
4882	50.60	V	-24.73	25.87	54	-28.13	Harmonic
High Channel							
4960	50.65	H	-24.73	25.92	54	-28.08	Harmonic
4960	49.40	V	-24.73	24.67	54	-29.33	Harmonic


Note: Average level= Peak level + Duty Cycle Corrected Factor

Worst case duty cycle:

Duty cycle = Ton/100ms = 2.899*2/100=0.05798


Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.05798 = -24.73

BT_Duty Cycle_1s



ProjectNo.:2401A63533E-RF Tester:Zenos Qiao
Date: 19.DEC.2024 22:10:52

BT_Duty Cycle_100ms




ProjectNo.:2401A63533E-RF Tester:Zenos Qiao

Date: 19.DEC.2024 22:15:21

Test plots


Left Band edge_Horizontal



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2381.330	-10.96	64.07	53.11	74.00	-20.89	Peak
2	2390.000	-10.98	62.02	51.04	74.00	-22.96	Peak


Left Band edge_Vertical



Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT-3DH5-2402

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2378.757 -10.96	63.41	52.45	74.00	-21.55	Peak
2	2390.000 -10.98	61.14	50.16	74.00	-23.84	Peak


Right Band edge_Horizontal_Peak



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT-3DH5-2480

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.32	50.35	74.00	-23.65 Peak
2	2488.958	-10.98	66.05	55.07	74.00	-18.93 Peak


Right Band edge_Horizontal_Average



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2480

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	51.58	40.61	54.00	-13.39	Average
2 2483.527	-10.97	51.70	40.73	54.00	-13.27	Average


Right Band edge_Vertical_Peak



Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT-3DH5-2480

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.59	49.62	74.00	-24.38 Peak
2	2491.643	-10.98	65.13	54.15	74.00	-19.85 Peak

Right Band edge_Vertical_Average




Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2480

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2483.500	-10.97	50.66	39.69	54.00	-14.31	Average
2 2484.333	-10.97	50.72	39.75	54.00	-14.25	Average

1-18GHz (Listed with the worst harmonic margin test plot)


1-4GHz_Horizontal



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit	Over	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3963.996	-9.31	43.91	34.60	54.00	-19.40	Average
2	3963.996	-9.31	57.79	48.48	74.00	-25.52	Peak


1-4GHz_Vertical



Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3926.491	-9.57	43.72	34.15	54.00	-19.85	Average
2	3926.491	-9.57	57.86	48.29	74.00	-25.71	Peak


4-18GHz_Horizontal_Peak



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4804.000	-7.79	60.34	52.55	74.00	-21.45	Peak
2	17931.740	12.86	48.32	61.18	74.00	-12.82	Peak


4-18GHz_Horizontal_Average



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2402

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17993.000	13.17	34.26	47.43	54.00	-6.57	Average


4-18GHz_Vertical_Peak



Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4804.000	-7.79	59.03	51.24	74.00	-22.76	Peak
2	17980.750	13.11	48.00	61.11	74.00	-12.89	Peak


4-18GHz_Vertical_Average



Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2402

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 17995.880	13.17	34.20	47.37	54.00	-6.63	Average


18-25GHz_Horizontal



Condition : Horizontal
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	19401.930	15.08	28.75	43.83	54.00	-10.17	Average
2	19401.930	15.08	37.78	52.86	74.00	-21.14	Peak

18-25GHz_Vertical



Condition : Vertical
Project No. : 2401A63533E-RF
Tester : Zenos Qiao
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak
: Average reading:RBW:1MHz VBW:1kHz Detector:Peak
Note : BT-3DH5-2402

Freq		Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	19373.920	15.11	28.90	44.01	54.00	-9.99	Average
2	19373.920	15.11	37.99	53.10	74.00	-20.90	Peak

20 dB Emission Bandwidth

Test Information:

Sample No.:	2VID-7	Test Date:	2024/12/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	N/A


Environmental Conditions:

Temperature: (°C):	26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
-----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Channel	Result (MHz)
DH1	Low Channel	0.784
	Middle Channel	0.784
	High Channel	0.784
2DH1	Low Channel	1.275
	Middle Channel	1.271
	High Channel	1.271
3DH1	Low Channel	1.283
	Middle Channel	1.283
	High Channel	1.286

DH1_Low 0.784MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:15:20

DH1_Middle 0.784MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:42:22

DH1_High 0.784MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:03:54

2DH1_Low 1.275MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:07:46

2DH1_Middle 1.271MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:11:21

2DH1_High 1.271MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:17:33

3DH1_Low 1.283MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:21:30

3DH1_Middle 1.283MHz



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:27:55

3DH1_High 1.286MHz



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:34:09

99% Occupied Bandwidth

Test Information:


Sample No.:	2VID-7	Test Date:	2024/12/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	N/A

Environmental Conditions:


Temperature: (°C):	26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
-----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Channel	99% OBW (MHz)
DH1	Low Channel	0.724
	Middle Channel	0.724
	High Channel	0.724
2DH1	Low Channel	1.166
	Middle Channel	1.166
	High Channel	1.163
3DH1	Low Channel	1.163
	Middle Channel	1.163
	High Channel	1.163




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:16:50




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:42:56




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:06:01



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:09:15




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:11:56




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:19:40

3DH1_Low 1.163MHz




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:23:02

3DH1_Middle 1.163MHz



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:28:29

3DH1_High 1.163MHz



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:36:17

Channel Separation

Test Information:

Sample No.:	2VID-7	Test Date:	2025/02/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass


Environmental Conditions:

Temperature: (°C):	26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
-----------------------	------	------------------------------	----	------------------------	-------

Test Data:

Mode	Channel	Result (MHz)	Limit (MHz)	Verdict
DH1	Middle Channel	1.010	0.857	Pass

Note: Only the BDR (GFSK) mode result is reported since EDR ($\pi/4$ -DQPSK) and EDR (8DPSK) modes have the exact same channel plan, and the limit is the maximum 20dB bandwidth *2/3.



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:38:19

Number of Hopping Frequency

Test Information:


Sample No.:	2VID-7	Test Date:	2024/12/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
-----------------------	------	------------------------------	----	------------------------	-------

Test Data:

Mode	Channel	Result	Limit	Verdict
DH1	Hopping Channel	79	15	Pass
2DH1	Hopping Channel	79	15	Pass
3DH1	Hopping Channel	79	15	Pass



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 05:41:59

Maximum Conducted Output Power

Test Information:


Sample No.:	2VID-7	Test Date:	2024/12/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:


Temperature: (°C):	26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
-----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Channel	Result (dBm)	Limit (dBm)	Verdict
DH1	Low Channel	4.44	21.00	Pass
	Middle Channel	4.40	21.00	Pass
	High Channel	4.10	21.00	Pass
2DH1	Low Channel	6.58	21.00	Pass
	Middle Channel	6.49	21.00	Pass
	High Channel	6.43	21.00	Pass
3DH1	Low Channel	6.86	21.00	Pass
	Middle Channel	6.80	21.00	Pass
	High Channel	6.55	21.00	Pass




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:17:48




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:43:17




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:06:21




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:09:36




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:12:33




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:20:01



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:23:24



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:28:50



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:36:38

100 kHz Bandwidth of Frequency Band Edge

Test Information:


Sample No.:	2VID-7	Test Date:	2024/12/25~2025/02/19
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:


Temperature: (°C):	25.4~26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4~101.7
-----------------------	-----------	---------------------------	----	------------------------	-------------

Test Data:


Mode	Channel	Result (dB)	Limit (dB)	Verdict
DH1	Low Channel	48.07	20.00	Pass
	High Channel	46.48	20.00	Pass
	Hopping_Lower Channel	43.01	20.00	Pass
	Hopping_Upper Channel	43.28	20.00	Pass
2DH1	Low Channel	48.25	20.00	Pass
	High Channel	48.06	20.00	Pass
	Hopping_Lower Channel	47.03	20.00	Pass
	Hopping_Upper Channel	46.95	20.00	Pass
3DH1	Low Channel	47.50	20.00	Pass
	High Channel	47.44	20.00	Pass
	Hopping_Lower Channel	46.83	20.00	Pass
	Hopping_Upper Channel	46.92	20.00	Pass




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 02:16:14




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:05:27




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:39:56



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:42:03




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:08:39




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:19:06

2DH1_Hopping_Lower




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:48:56

2DH1_Hopping_Upper




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:50:56

3DH1_Low




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:22:26

3DH1_High




ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 03:35:43

3DH1_Hopping_Lower



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:52:49

3DH1_Hopping_Upper



ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 19.FEB.2025 14:54:50

Time of Occupancy (dwell time)

Test Information:

Sample No.:	2VID-7	Test Date:	2024/12/25
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rainbow Zhu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.5	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.4
-----------------------	------	------------------------------	----	------------------------	-------

Test Data:

Mode	Channel	Pulse width (ms)	Dwell time (s)	Limit (s)	Verdict
DH1	Hopping Channel	0.396	0.127	0.400	Pass
DH3	Hopping Channel	1.661	0.266	0.400	Pass
DH5	Hopping Channel	2.931	0.313	0.400	Pass
2DH1	Hopping Channel	0.403	0.129	0.400	Pass
2DH3	Hopping Channel	1.661	0.266	0.400	Pass
2DH5	Hopping Channel	2.925	0.312	0.400	Pass
3DH1	Hopping Channel	0.403	0.129	0.400	Pass
3DH3	Hopping Channel	1.665	0.266	0.400	Pass
3DH5	Hopping Channel	2.931	0.313	0.400	Pass

Note:

DH1: Dwell time = Pulse width (ms) \times (1600/2/79) \times 31.6 s

DH3: Dwell time = Pulse width (ms) \times (1600/4/79) \times 31.6 s

DH5: Dwell time = Pulse width (ms) \times (1600/6/79) \times 31.6 s

2DH1: Dwell time = Pulse width (ms) \times (1600/2/79) \times 31.6 s




2DH3: Dwell time = Pulse width (ms) \times (1600/4/79) \times 31.6 s


2DH5: Dwell time = Pulse width (ms) \times (1600/6/79) \times 31.6 s

3DH1: Dwell time = Pulse width (ms) \times (1600/2/79) \times 31.6 s

3DH3: Dwell time = Pulse width (ms) \times (1600/4/79) \times 31.6 s

3DH5: Dwell time = Pulse width (ms) \times (1600/6/79) \times 31.6 s





ProjectNo.:2401A63533E-RF Tester:Rainbow Zhu
Date: 25.DEC.2024 06:24:26



RF EXPOSURE EVALUATION

MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (W)
			(dBi)	(dBd)	(dBm)	(W)		
BLE	2402-2480	4	2.5	0.35	4.35	0.003	0.2	0.768
BT	2402-2480	7	2.5	0.35	7.35	0.005	0.2	0.768
2.4G WIFI	2412-2472	25.5	4.37	2.22	27.72	0.592	0.2	0.768
5G WIFI	5150-5250	13.0	4.22	2.07	15.07	0.032	0.2	0.768
	5725-5850	20	4.83	2.68	22.68	0.185	0.2	0.768

Note 1: The antenna gain and Conducted output power including Tune-up Tolerance was declared and provided by the manufacturer

Note 2: BT and 2.4G WIFI can be transmitted simultaneously. 2.4G WIFI and 5G WIFI should not be sent simultaneously.

The ratio= $\text{ERP}_{2.4\text{G Wi-Fi}}/\text{limit} + \text{ERP}_{\text{BT}}/\text{limit} = 0.777 < 1$

Result: Compliant

EUT PHOTOGRAPHS

Please refer to the attachment 2401A63533E-RF External photo and 2401A63533E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401A63533E-RFA Test Setup photo.

******* END OF REPORT *******