

RF Exposure Evaluation Report

Product : Smart Wi-Fi Outdoor Plug
Trade mark : meross
Model/Type reference : MSS620
Serial Number : N/A
Report Number : EED32L00157502
FCC ID : 2AMUU-MSS620V3
Date of Issue : Sep. 16, 2019
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01v06
Test result : PASS

Prepared for:

Chengdu Meross Technology Co.,Ltd.
Room 1312, Floor 13, Building 6-1, Zone E, TianFu Software Park,
GaoXin District, ChengDu, SiChuan, China.

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Jay Zheng

Jay Zheng

Compiled by:

Alex Wu

Alex Wu

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Kevin Yang

Kevin Yang

Date:

Sep. 16, 2019

Check No.: 4038879347



2 Version

Version No.	Date	Description
00	Sep. 16, 2019	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Chengdu Meross Technology Co.,Ltd.
Address of Applicant:	Room 1312, Floor 13, Building 6-1, Zone E, TianFu Software Park, GaoXin District, ChengDu, SiChuan, China.
Manufacturer:	Chengdu Meross Technology Co.,Ltd.
Address of Manufacturer:	Room 1312, Floor 13, Building 6-1, Zone E, TianFu Software Park, GaoXin District, ChengDu, SiChuan, China.
Factory:	Shenzhen Shenan Yangguang Electronics Co.,Ltd.
Address of Factory:	Building 9, No.18 of Makan Rd, Xili, Nanshan, Shenzhen City, Guangdong Province 518055

4.2 General Description of EUT

Product Name:	Smart Wi-Fi Outdoor Plug
Model No.(EUT):	MSS620
Trade Mark:	meross
EUT Supports Radios application	WiFi IEEE 802.11 /b/g/n(HT20)(HT40) 2412MHz to 2462MHz

4.3 Product Specification subjective to this standard

Frequency Range:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz		
Modulation Type:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g :OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)		
Number of Channels:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels		
Test Power Grade:	Reference Table 1 (manufacturer declare)		
Test Software of EUT:	QATool_Dbg (manufacturer declare)		
Antenna Type:	PCB antenna		
Antenna Specification	2.4GHz	Antenna Gain :	1.50 dBi (Numeric gain: 1.41)
Maximum tune up power	IEEE 802.11b Mode:	16.00 dBm	(39.811 mW)
	IEEE 802.11g Mode:	19.50 dBm	(89.125 mW)
	IEEE 802.11n HT 20 Mode:	19.00 dBm	(79.433 mW)
	IEEE 802.11n HT 40 Mode:	18.00 dBm	(63.096 mW)
Power Supply:	AC120V/60Hz		
Sample Received Date:	Jun 17, 2019		
Sample tested Date:	Jun 17, 2019 to Sep 12, 2019		
The tested sample(s) and the sample information are provided by the client.			

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	39.811	1.41	20	0.0112	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	89.125	1.41	20	0.0250	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	79.433	1.41	20	0.0223	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	63.096	1.41	20	0.0177	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00157501 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.