

# Qingdao Richmat Intelligence Technology Inc

## SAR COMPLIANCE REPORT

**Report Type:**  
FCC SAR assessment report

**Model:**  
HJ RF

**REPORT NUMBER:**  
221200050SHA-002

**ISSUE DATE:**  
January 3, 2023

**DOCUMENT CONTROL NUMBER:**  
TTRFFCCSAR-01\_V1 © 2018 Intertek



**Applicant:** Qingdao Richmat Intelligence Technology Inc  
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,  
Qingdao, Shandong Province, China.

**Manufacturer:** Qingdao Richmat Intelligence Technology Inc  
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,  
Qingdao, Shandong Province, China.


**FCC ID:** 2AJJGHJRF

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:
KDB447498 D01 General RF Exposure Guidance v07 FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

**PREPARED BY:**

**REVIEWED BY:**



---

Project Engineer  
Sky Yang

---

Reviewer  
Erick Liu

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

Report No.	Version	Description	Issued Date
221200050SHA-002	Rev. 01	Initial issue of report	January 3, 2023

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	Module
Type/Model:	HJ RF
Description of EUT:	The report is C2PC report, the following host models were added and tested.
Host models:	HJH13D, HJH103
Rating:	DC 3V battery
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	December 12, 2022
Date of test:	December 12, 2022 ~ December 26, 2022

### 1.2 Technical Specification

Frequency Range:	2405MHz ~ 2480MHz
Type of Modulation:	FSK
Channel Number:	151 channels
Channel Separation:	0.5 MHz
Antenna Information:	PCB antenna, 0dBi

### 1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 SAR Assessment

Test result: Pass

### 2.1 SAR Test Exclusion Limit

This method shall only be used at separation distances up to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula below:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

$f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20cm}$  is per Formula above.

The example values shown in below are for illustration only.

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
300	39	65	88	110	129	148	166	184	201	217	
450	22	44	67	89	112	135	158	180	203	226	
835	9	25	44	66	90	116	145	175	207	240	
1900	3	12	26	44	66	92	122	157	195	236	
2450	3	10	22	38	59	83	111	143	179	219	
3600	2	8	18	32	49	71	96	125	158	195	
5800	1	6	14	25	40	58	80	106	136	169	

### 2.2 Assessment Results

The highest EIRP adjusted with tune-up tolerance is 97.5dBuV/m – 95.3 = 2.2dBm = 1.66mW < 3mW (Test Exclusion Thresholds of 2450MHz at 5mm). Therefore, the SAR requirement is deemed to be satisfied without test.

\*\*\*\*\* END \*\*\*\*\*