

HONEYWELL INTERNATIONAL INC HONEYWELL SAFETY AND PRODUCTIVITY SOLUTIONS 9680 Old Bailes Rd. Fort Mill, SC 29707 United States

Declaration of the Modular Approval

Applicant: Honeywell International Inc

Honeywell Safety and Productivity Solutions

Address: 9680 Old Bailes Rd. Fort Mill, SC 29707 United States

FCC ID: HD5-HONST60Q Model name: HON-ST60Q

The single module transmitter has been evaluated then tested meeting the requirements under Part 15C Section 2.12 as below:

Modular approval requirement		EUT Condition	Comply
` '	ne radio elements of the modular transmitter ust have their own shielding. The physical	This modular does have its own RF shielding.	Yes
	ystal and tuning capacitors may be located ternal to the shielded radio elements.		
mo pro wi	ne modular transmitter must have buffered odulation/data inputs (if such inputs are rovided) to ensure that the module will comply ith part 15 requirements under conditions of accessive data rates or over-modulation.	The EUT has buffered data inputs, detail see block diagram and schematic.	Yes
` '	ne modular transmitter must have its own ower supply regulation.	The modular has its own power supply regulation, detail see EUT photo and schematic	Yes
an of Th att (a an ins ap	ne modular transmitter must comply with the intenna and transmission system requirements. Sections 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently tached or employ a "unique" antenna coupler at all connections between the module and the intenna, including the cable). The "professional stallation" provision of Section 15.203 is not opplicable to modules but can apply to limited odular approvals under paragraph (b) of this section.	The modular transmitter complies with the antenna requirements.	Yes
sta no co	ne modular transmitter must be tested in a and-alone configuration, <i>i.e.</i> , the module must be inside another device during testing for ampliance with part 15 requirements. Unless transmitter module will be battery powered,	The modular transmitter is tested in a stand-alone configuration.	Yes

	it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites; unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see Section 15.31(i)) must not be inside another device during testing.		
(f)	The modular transmitter must be equipped	The modular transmitter	Yes
	with either a permanently affixed label or must	has permanents fixed tag.	
	be capable of electronically displaying its FCC		
	identification number.		
	specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization requirements, which are based on the intended use/configurations.	Please refer to the user manual instructions.	Yes
(h)		The modular transmitter	Yes
	applicable RF exposure requirements in its final	complies with applicable	
	configuration.	RF exposure requirements.	
		.oquilonionio.	

Sincerely,

Name: Michael Robinson

Position: Product Compliance

Date: 2019-07-23