


|  |                                |
|--|--------------------------------|
| Product Name: Action Camera  | Report No: FCC022023-00283RF14 |
| Product Model: ARG-AC-9180BK,<br>ARG-AC-9181, ARG-AC-9182,<br>ARG-AC-9183, ARG-AC-9184,<br>ARG-AC-9185, ARG-AC-9186,<br>ARG-AC-9187, ARG-AC-9188,<br>ARG-AC-9189 | Security Classification: Open  |
| Version: V1.0  | Total Page: 8                  |

## TIRT Testing Report

|              |             |              |   |
|--------------|-------------|--------------|---|
| Prepared By: | Checked By: | Approved By: |  |
| Stone Tang   | Randy Lv    | Daniel Chen  |   |
| Stone Tang   | Randy Lv    | Daniel chen  |   |

# FCC RF EXPOSURE REPORT

## FCC ID: 2AUGWARG-AC-9180BK

**Project No.** : 2023-00283  
**Equipment** : Action Camera  
**Brand Name** : ArgomTech  
**Test Model** : ARG-AC-9180BK  
**Series Model** : ARG-AC-9181, ARG-AC-9182, ARG-AC-9183, ARG-AC-9184,  
ARG-AC-9185, ARG-AC-9186, ARG-AC-9187, ARG-AC-9188,  
ARG-AC-9189  
**Applicant** : MG Accessories & Distribution Inc  
**Address** : 12650 NW 25<sup>th</sup> Street Suite 112 Miami Florida United States 33182  
**Manufacturer** : MG Accessories & Distribution Inc  
**Address** : 12650 NW 25<sup>th</sup> Street Suite 112 Miami Florida United States 33182  
**Issued Date** : Feb.10, 2023  
**Report Version** : V1.0  
**Test Sample** : Engineering Sample No.: 20230203001157  
**Standard(s)** : FCC 47 CFR Part 2.1093 & FCC 47 CFR Part 1.1307 & FCC 47 CFR  
Part 1.1310, 447498 D04 Interim General RF Exposure Guidance v01

- The test result referred exclusively to the presented test model /sample.
- Without written approval of TIRT Inc. the test report shall not reproduced except in full.

Lab: Beijing TIRT Technology Service Co.,Ltd Shenzhen

Add: 101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan

District, Shenzhen, China

TEL: +86-0755-27087573

**REPORT ISSUED HISTORY**

| Report No.          | Version | Description     | Issued Date | Note  |
|---------------------|---------|-----------------|-------------|-------|
| FCC022023-00283RF14 | V1.0    | Original Report | 2023.02.10  | Valid |

**1. TEST FACILITY**

|   |  |
|---|--|
| Company:                                | Beijing TIRT Technology Service Co.,Ltd Shenzhen   |
| Address:                                | 101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan District, Shenzhen, China |
| CNAS Registration Number:               | CNAS L14158  |
| A2LA Registration Number:               | 6049.01  |
| FCC Accredited Lab. Designation Number: | CN1309   |
| FCC Test Firm Registration Number:      | 825524   |
| Telephone:                              | +86-0755-27087573  |

## 2. GENERAL CONCLUSION

According to FCC §§1.1307 and 447498 D04 Interim General RF Exposure Guidance v01, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW).

### 1) Option A. 1-mW Test Exemption

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

### 2) Option B. SAR-Based Exemption

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in § 1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

Accordingly, a RF source is considered an RF exempt device if its available maximum time-averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold.

This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) |    |    |     |     |     |     |     |     |     |
|-----------------|---------------|----|----|-----|-----|-----|-----|-----|-----|-----|
|                 | 5             | 10 | 15 | 20  | 25  | 30  | 35  | 40  | 45  | 50  |
| 300             | 39            | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
| 450             | 22            | 44 | 67 | 89  | 112 | 135 | 158 | 180 | 203 | 226 |
| 835             | 9             | 25 | 44 | 66  | 90  | 116 | 145 | 175 | 207 | 240 |
| 1900            | 3             | 12 | 26 | 44  | 66  | 92  | 122 | 157 | 195 | 236 |
| 2450            | 3             | 10 | 22 | 38  | 59  | 83  | 111 | 143 | 179 | 219 |
| 3600            | 2             | 8  | 18 | 32  | 49  | 71  | 96  | 125 | 158 | 195 |
| 5800            | 1             | 6  | 14 | 25  | 40  | 58  | 80  | 106 | 136 | 169 |

### 3) Option C MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

**TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES  
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

| RF Source Frequency   |   |           | Minimum Distance   |   |                    | Threshold ERP   |
|---|---|-----------|--------------------|---|--------------------|-----------------|
| $f_L$ MHz   |   | $f_H$ MHz | $\lambda_L / 2\pi$ |   | $\lambda_H / 2\pi$ | W               |
| 0.3   | — | 1.34      | 159 m              | — | 35.6 m             | $1,920 R^2$     |
| 1.34  | — | 30        | 35.6 m             | — | 1.6 m              | $3,450 R^2/f^2$ |
| 30  | — | 300       | 1.6 m              | — | 159 mm             | $3.83 R^2$      |
| 300   | — | 1,500     | 159 mm             | — | 31.8 mm            | $0.0128 R^2 f$  |
| 1,500   | — | 100,000   | 31.8 mm            | — | 0.5 mm             | $19.2 R^2$      |
| Subscripts L and H are low and high; $\lambda$ is wavelength.<br>From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns. |   |           |                    |   |                    |                 |

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using the Table 1 formula for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using the applicable Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.

P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P<sub>th,i</sub> = the exemption threshold power (Pth) according to the Table 1 formula for fixed, mobile, or portable RF source i.

ERP<sub>j</sub> = the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j.

ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π, according to the applicable Table 2 formula at the location in question.

Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.

Exposure Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable.

### 3. TEST RESULTS

| Operating Mode | Frequency (MHz) | Measured Power (dBm) | Measured Power (mW) | Ant. Gain (dBi) | EIRP (dBm) | ERP (dBm) | ERP (mW) | Separation Distance (mm) |
|----------------|-----------------|----------------------|---------------------|-----------------|------------|-----------|----------|--------------------------|
| 11B            | 2412            | -3.08                | 0.4920              | -5.94           | -9.02      | -11.16    | 0.0766   | 5                        |
|                | 2437            | -3.11                | 0.4887              | -5.94           | -9.05      | -11.19    | 0.0760   | 5                        |
|                | 2462            | -2.78                | 0.5272              | -5.94           | -8.72      | -10.86    | 0.0820   | 5                        |
| 11G            | 2412            | 1.08                 | 1.2823              | -5.94           | -4.86      | -7.00     | 0.1995   | 5                        |
|                | 2437            | 1.42                 | 1.3868              | -5.94           | -4.52      | -6.66     | 0.2158   | 5                        |
|                | 2462            | 1.59                 | 1.4421              | -5.94           | -4.35      | -6.49     | 0.2244   | 5                        |
| 11N20          | 2412            | 1.32                 | 1.3552              | -5.94           | -4.62      | -6.76     | 0.2109   | 5                        |
|                | 2437            | 1.43                 | 1.3900              | -5.94           | -4.51      | -6.65     | 0.2163   | 5                        |
|                | 2462            | 1.75                 | 1.4962              | -5.94           | -4.19      | -6.33     | 0.2328   | 5                        |

Note:

- Output power including tune up tolerance
- SAR and MPE evaluation is not required.
- Threshold  $P_{th}(mW) = 3060 * (0.5/20)^{(-\text{Log}(60/(3060 * \sqrt{2.412})))} = 2.78mW$

End of Test Report