

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological

Development District, Guangzhou, China 51 0663

Telephone: +86 (0) 20 82155555 Fax: +86 (0) 20 82075059 Email: ee.guangzhou@sgs.com

Page: 1 of 7

Report No.: GZEM150500203302

SAR Evaluation Report

The following sample(s) was/were submitted and identified on behalf of the client as: **Application No.:**GZEM1505002033CR (Ref. SZEM1504002241CR)

Applicant: Corsair Memory, Inc.

Manufacturer:Shenzhen Horn Audio Co., LtdFactory:Shenzhen Horn Audio Co., Ltd

Product Name: USB dongle
Model No.(EUT): RDA0004
Trade Mark: Corsair

FCC ID: 2AAFMRDA0004

Standards: 47 CFR Part 1.1307 (2014)

47 CFR Part 2.1093 (2014)

KDB447498D01 General RF Exposure Guidance v05r02

Date of Receipt: 2015-05-08

Date of Test: 2015-05-14 to 2015-05-22

Date of Issue: 2015-05-27

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Jerry Chan Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.asp.xand, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.asp.x. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized all teration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: GZEM150500203302

Page: 2 of 7

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-05-27		Original

Authorized for issue by:		
Tested By	Little Xiang	2015-05-14 to 2015-05-22
	(Little Xiang) /Project Engineer	Date
Prepared By	June Chen	2015-05-27
	(June Chen) /Clerk	Date
Checked By	3	2015-05-27
	(Jerry Chan) /Reviewer	Date



Report No.: GZEM150500203302

Page: 3 of 7

3 Contents

		Page
1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	GENERAL INFORMATION	4
	4.1 CLIENT INFORMATION	4
	4.3 TEST LOCATION	5
	4.6 ABNORMALITIES FROM STANDARD CONDITIONS	6
5	SAR EVALUATION	
	5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	
	5.1.3 EUT RF Exposure	



Report No.: GZEM150500203302

Page: 4 of 7

4 General Information

4.1 Client Information

Applicant:	Corsair Memory, Inc.
Address of Applicant:	47100 Bayside Pkwy, Fremont, CA 94538, USA
Manufacturer:	Shenzhen Horn Audio Co., Ltd
Address of Manufacturer:	No.6, 4 th Guihua Rd, Pingshan, Longgang, Shenzhen
Factory:	Shenzhen Horn Audio Co., Ltd
Address of Factory:	No.6, 4 th Guihua Rd, Pingshan, Longgang, Shenzhen

4.2 General Description of EUT

Product Name:	USB dongle
Model No.:	RDA0004 (RDA0004 is identical on circuitry design, PCB layout, electrical components used, internal wiring and functions ,which we chose to be tested by SGS and only different on color)
Trade Mark:	Corsair
Carrier Frequency	2425.35MHz-2477.35MHz
Modulation Type:	π/4DQPSK
Test Power Grade:	Default setting (manufacturer declare)
Test Software of EUT:	VMI Dev Software (manufacturer declare)
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	2dBi
Power Supply:	Supply by PC USB port
USB Cable:	150cm unshielded

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory, 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



Report No.: GZEM150500203302

Page: 5 of 7

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP (Lab Code: 200611-0)

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

• SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

CNAS (Lab Code: L0167)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

• FCC (Registration No.: 282399)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

• Industry Canada (Registration No.: 4620B-1)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

• VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

• CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.



Report No.: GZEM150500203302

Page: 6 of 7

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None

4.7 Other Information Requested by the Customer

None.



Report No.: GZEM150500203302

Page: 7 of 7

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v05r02

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation 17

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max Conducted Peak Output Power is -2.097dBm in highest channel(2.42535GHz);

The best case gain of the antenna is 2dBi.

EIRP = -2.097dBm + 2dBi = -0.097dBm

-0.097dBm logarithmic terms convert to numeric result is nearly 0.9779mW

According to the formula. calculate the EIRP test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]$

General RF Exposure = $(0.9779 \text{mW} / 5 \text{ mm}) \times \sqrt{2.42535 \text{GHz}} = 0.3046 \text{ }\bigcirc$

SAR requirement:

S = 3.0

②;

(1) < (2).

So the SAR report is not required.