

## Cloud Gateway Max



Compact 2.5 Gbps Cloud Gateway with 30+ UniFi device / 200+ client support and pre-installed NVR storage.

Mechanical

Dimensions	141.8 x 127.6 x 30 mm (5.6 x 5 x 1.2")
Weight	519 g (1.1 lb)
Enclosure material	Polycarbonate

Hardware

Processor	Quad-core ARM® Cortex®-A53 at 1.5 GHz
Memory information	4 GB DDR4
On-board storage	512 GB NVMe SSD
Management interface	Ethernet Bluetooth
Networking interface	LAN: (4) 1/2.5 GbE RJ45 ports WAN: (1) 1/2.5 GbE RJ45 port
Power method	USB type C (5V/5A)
Supported voltage range	100–240V AC
Max. power consumption	16.1W
ESD/EMP protection	Air: ± 8kV; Contact: ± 4kV
LCM display	0.96" status display
Button	Factory reset
LEDs	Ethernet Green: link/activity
Operating temperature	-10 to 40° C (14 to 104° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

FCC/IC - Required Statement:  
[https://dl.ui.com/compliance/FCC\\_IC\\_required\\_statement\\_2023-01-10.pdf](https://dl.ui.com/compliance/FCC_IC_required_statement_2023-01-10.pdf)

