

August 9, 2023

FCC ID: N6C-SDMAC

To whom it may concern,

We, UL Japan, Inc, hereby declare that SDIO Wireless Module, model: SX-SDMAC (FCC ID: N6C-SDMAC) of silex technology, Inc. is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances  $d$  (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources.  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d / 20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

The SAR evaluation exemption threshold is calculated as below.

$P_{th}$ (mW)	3060
$f$ (GHz)	2.462
$ERP_{20 \text{ cm}}$ (mW)	3060
$d$ (cm)	20.0

Conducted Power (dBm)	18.75
(mW)	74.99
Antenna Gain (dBi)	-0.51
EIRP (dBm)	18.24
ERP (dBm)	16.10
(mW)	40.74

The Maximum time-averaged power or ERP whichever greater is 75 mW.  
(Rounded up to two decimals place)

Thank you for your attention to this matter.



Satofumi Matsuyama  
Engineer