

YEALINK (XIAMEN) NETWORK TECHNOLOGY CO., LTD.

309, 3th Floor, No.16, Yun Ding North Road, Huli District, Xiamen City, Fujian, China

Declarations


Item	DECT IP Base Station
Model Name:	W60B
FCC ID:	T2C-W60B

Questions	Answer:
Does a system built with the EUT that implement the provisions of 47CFR 15.323(c)(5) enabling the use of the upper threshold for deferral ?	Yes
According to 47CFR15.323(c)(5).4, does your model not use bandwidth in further cooperation with other devices at any range ?	Yes
Does a system build using the EUT that operate under the provisions of 47CFR 15.323(c)(6) incorporating provisions for waiting for a channel to go clear ?	No
According to 47CFR15.323(c)(8), does EUT use the same antennas for transmission and reception as for monitoring ?	Yes
Does a system build with the EUT that operate under the provisions of 47CFR 15.323(c)(10) to test for deferral only in conjunction with a companion device ?	No
Does a system build with the EUT that operate under the provisions of 47CFR 15.323(c)(11) enabling the access criteria check on the receive channel while in the presence of collocate interferers ?	No
According to 47CFR 15.323(c)(12), does EUT not work in a mode with denies fair access to spectrum for other devices ?	Yes
The device complies with the provisions of 47CFR 15.319(f). The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals. The following table explains the reaction of device in case of either absence of information to transmit or operational failure after a connection of its companion device is established.	

Name: Stone Lu

Date: July 10, 2017

Title: Vice General Manager



Signature of applicant: