

Prüfbericht-Nr.: Test report no.:	CN250W4O 002	Auftrags-Nr.: Order no.:	168518141	Page 1 of 22 Seite 1 von 22
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2024-12-10	
Auftraggeber: Client:	Harman International Industries, Inc 8500 Balboa Blvd, Northridge, California, 91329, United States			
Prüfgegenstand: Test item:	BLUETOOTH HEADSET			
Bezeichnung / Typ-Nr.: Identification / Type no.:	SENSE LITE (Trademark: JBL)			
Auftrags-Inhalt: Order content:	Type test			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209		RSS-247 Issue 3 August 2023 RSS-Gen Issue 5 March 2019	
Wareneingangsdatum: Date of sample receipt:	2024-12-10	Refer to photos document		
Prüfmuster-Nr.: Test sample no.:	A003880376			
Prüfzeitraum: Testing period:	2024-12-10 – 2024-12-20			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date:	2025-02-28 Signed by: Harry W. C. Wu		Ausstellungsdatum: Issue date:	2025-02-28 Signed by: Alex Lan
Stellung / Position:	Project Manager		Stellung / Position:	Authorizer
Sonstiges / Other:	FCC ID: APIJBLSLITE IC: 6132A-JBLSLITE HVIN: SENSE LITE			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				
TUV Rheinland (Shenzhen) Co., Ltd., 1601-1604, 17-18F, Tower A Building 2, Shenzhen International Innovation Valley, Dashi 1st Road, Xili Street, Xili Community, Nanshan District, Shenzhen 518052, P. R. China Mail: service-gc@tuv.com · Web: www.tuv.com				

Prüfbericht-Nr.: CN250W4O 002
Test report no.:

Page 2 of 22
Seite 2 von 22

Remarks
Anmerkungen

1	The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request. <i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</i> <i>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i>
2	As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. <i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i>
3	Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report. <i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i>
4	The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019. <i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i>

Prüfbericht-Nr.: CN250W40 002
Test report no.:

Seite 3 von 22
Page 3 of 22

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 99%dB BANDWIDTH

RESULT: Pass

5.1.5 6dB BANDWIDTH

RESULT: Pass

5.1.6 FREQUENCY STABILITY

RESULT: Pass

5.1.7 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.8 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES.....	5
2.1	TEST FACILITIES.....	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	7
2.6	LOCATION OF ORIGINAL DATA	7
2.7	STATUS OF FACILITY USED FOR TESTING	7
3	GENERAL PRODUCT INFORMATION.....	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
3.5	SUBMITTED DOCUMENTS.....	10
4	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	11
4.5	TEST SETUP DIAGRAM	12
5	TEST RESULTS.....	14
5.1	TRANSMITTER REQUIREMENT & TEST SUITES.....	14
5.1.1	<i>Antenna Requirement.....</i>	<i>14</i>
5.1.2	<i>Maximum Peak Conducted Output Power.....</i>	<i>15</i>
5.1.3	<i>Conducted Power Spectral Density.....</i>	<i>16</i>
5.1.4	<i>99%dB Bandwidth</i>	<i>17</i>
5.1.5	<i>6dB Bandwidth</i>	<i>18</i>
5.1.6	<i>Frequency stability</i>	<i>19</i>
5.1.7	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>20</i>
5.1.8	<i>Radiated Spurious Emission.....</i>	<i>21</i>
6	PHOTOGRAPHS OF THE TEST SET-UP.....	22
7	LIST OF TABLES	22

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Results of Bluetooth Low Energy_Left Earbud

Appendix C: Results of Bluetooth Low Energy_Right Earbud

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District,
Shenzhen, Guangdong, China/518110

FCC Registration No.: 694916

IC Registration No.: 25069 and the CAB identifier is CN0078.

Prüfbericht-Nr.: CN250W40 002
Test report no.:

Seite 6 von 22
Page 6 of 22

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (TS8997)				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	25.09.2025
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	25.09.2025
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	25.09.2025
DC Power Supply	Keysight	E3642A	MY61276100	25.09.2025
Wireless Connectivity Tester	R&S	CMW270	102505	25.09.2025
Power Control Unit	Tonscend	JS0806-4ADC	N/A	25.09.2025
Automation Control Unit	Tonscend	JS0806-2	21C8060396	25.09.2025
Humid & Temp Programmable Tester	BOST	NTH090-60	19040801	28.02.2025
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLY23JMF	N/A
Unwanted Emission Testing (TS9975)				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	28.09.2025
Signal Analyzer	R&S	FSV 40	101439	28.09.2025
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	28.09.2025
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	28.09.2025
Amplifier	R&S	SCU-18F	180070	28.09.2025
Amplifier	R&S	SCU40A	100475	28.09.2025
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	27.09.2026
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	27.09.2026
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	27.09.2026
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	27.09.2026
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	13.09.2027

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty (k=2)
Occupied Channel Bandwidth	± 2.08 %
RF output power, conducted	± 0.99 dB
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China/518110 is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUTs are Bluetooth earbuds, the left & right earbuds support Bluetooth dual mode technology. The Bluetooth earbuds have five colors of enclosures (Black, White, Khaki, Blue, Purple).

There is no difference except the PCB layout of left and right earbuds.

For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	BLUETOOTH HEADSET
Type Designation	SENSE LITE
Trademark	JBL
FCC ID	APIJBLSLITE
IC	6132A-JBLSLITE
HVIN	SENSE LITE
Extreme Temperature Range	0°C to +45°C
Operating Voltage	Input: 5V DC Li-ion polymer cell: 3.85V, 55mAh
Technical Specification of Classical Bluetooth	
Bluetooth Core Version	Bluetooth 5.4
Operating Frequency band	2402 ~ 2480 MHz
Channel Number	79 channels
Channel separation	1MHz
Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	FPC antenna
Antenna Gain	-3.31 dBi for left earbud -4.43 dBi for right earbud (Provided by the Client)
Technical Specification of Bluetooth Low Energy	
Bluetooth Core Version	Bluetooth 5.4
Operating Frequency band	2402 – 2480 MHz
Channel Number	40 channels
Channel separation	2MHz
Data rate	1Mbps, 2Mbps
Modulation	GFSK
Antenna Type	FPC antenna
Antenna Gain	-3.31 dBi for left earbud -4.43 dBi for right earbud (Provided by the Client)

Table 3: RF Channel and Frequency of Classic Bluetooth

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	20	2422.00	40	2442.00	60	2462.00
01	2403.00	21	2423.00	41	2443.00	61	2463.00
02	2404.00	22	2424.00	42	2444.00	62	2464.00
03	2405.00	23	2425.00	43	2445.00	63	2465.00
04	2406.00	24	2426.00	44	2446.00	64	2466.00
05	2407.00	25	2427.00	45	2447.00	65	2467.00
06	2408.00	26	2428.00	46	2448.00	66	2468.00
07	2409.00	27	2429.00	47	2449.00	67	2469.00
08	2410.00	28	2430.00	48	2450.00	68	2470.00
09	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00	--	--

Table 4: RF Channel and Frequency of Bluetooth Low Energy

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	10	2422.00	20	2442.00	30	2462.00
01	2404.00	11	2424.00	21	2444.00	31	2464.00
02	2406.00	12	2426.00	22	2446.00	32	2466.00
03	2408.00	13	2428.00	23	2448.00	33	2468.00
04	2410.00	14	2430.00	24	2450.00	34	2470.00
05	2412.00	15	2432.00	25	2452.00	35	2472.00
06	2414.00	16	2434.00	26	2454.00	36	2474.00
07	2416.00	17	2436.00	27	2456.00	37	2476.00
08	2418.00	18	2438.00	28	2458.00	38	2478.00
09	2420.00	19	2440.00	29	2460.00	39	2480.00

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth LE transmitting mode
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. On, Bluetooth connecting mode
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|----------------------------------|------------------|
| - Application Form | - Photo Document |
| - Block Diagram | - Schematics |
| - FCC/IC Label and Location Info | - User Manual |
| - Operation Description | |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N or Rating
Laptop	Lenovo	T480	PF-16A6N8

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 30MHz)




Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard	:	FCC Part 15.247(b)(4) and Part 15.203
	:	RSS-Gen Clause 6.7
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has two FPC antennas, the directional gain of antennas: Left earbuds: -3.31dBi, Right earbuds: -4.43dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht-Nr.: CN250W40 002
Test report no.:

Seite 15 von 22
Page 15 of 22

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(b)(3)
 : RSS-247 Clause 5.4(d)
 Basic standard : ANSI C63.10: 2013
 Limits : < 1 Watt (Maximum Conducted Peak Power)
 : e.i.r.p. <4W
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-12-10 to 2024-12-20
 Input voltage : DC 3.85V for left and right earbud
 Operation mode : A
 Test channel : Low / Middle / High
 Ambient temperature : 20.8 °C
 Relative humidity : 48.2 %
 Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 6: Test Result of Maximum Peak Conducted Output Power

Left Earbud:

Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
1 Mbps	2402	6.90	0.0049	< 1.0
	2440	6.92	0.0049	
	2480	6.90	0.0049	
2 Mbps	2404	6.87	0.0049	
	2440	6.88	0.0049	
	2478	6.84	0.0048	
Maximum Measured Value		6.92	0.0049	

Note: The cable loss is taken into account in results and the maximum e.i.r.p. is 3.61 dBm less than 4W (36 dBm).

Right Earbud:

Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
1 Mbps	2402	7.08	0.0051	< 1.0
	2440	7.33	0.0054	
	2480	7.16	0.0052	
2 Mbps	2404	7.17	0.0052	
	2440	7.36	0.0054	
	2478	7.15	0.0052	
Maximum Measured Value		7.36	0.0054	

Note: The cable loss is taken into account in results and the maximum e.i.r.p. is 2.93 dBm less than 4W (36 dBm).

Prüfbericht-Nr.: CN250W40 002
Test report no.:

Seite 16 von 22
Page 16 of 22

5.1.3 Conducted Power Spectral Density

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(e)
 : RSS-247 Clause 5.2(b)
 Basic standard : ANSI C63.10: 2013
 Limits : 8 dBm / 3kHz
 Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-12-10 to 2024-12-20
 Input voltage : DC 3.85V for left and right earbud
 Operation mode : A
 Test channel : Low / Middle / High
 Ambient temperature : 20.8 °C
 Relative humidity : 48.2 %
 Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B&C.

Table 7: Test Result of 99% Bandwidth

Left Earbud:

Data Rate	Channel Frequency (MHz)	Measured Conducted Power Spectral Density	Limit
		(dBm / 3kHz)	
1 Mbps	2402	-9.10	8 dBm / 3kHz
	2440	-9.03	
	2480	-9.24	
2 Mbps	2402	-12.67	8 dBm / 3kHz
	2440	-11.82	
	2480	-11.89	

Right Earbud:

Data Rate	Channel Frequency (MHz)	Measured Conducted Power Spectral Density	Limit
		(dBm / 3kHz)	
1 Mbps	2402	-8.18	8 dBm / 3kHz
	2440	-7.85	
	2480	-8.03	
2 Mbps	2402	-11.38	8 dBm / 3kHz
	2440	-11.26	
	2480	-11.37	

Prüfbericht-Nr.: CN250W40 002
Test report no.:

Seite 17 von 22
Page 17 of 22

5.1.4 99%dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : RSS-Gen clause 6.7
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-12-10 to 2024-12-20
Input voltage : DC 3.85V for left and right earbud
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 20.8 °C
Relative humidity : 48.2 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B&C.

Table 8: Test Result of 99% Bandwidth

Left Earbud:

Data Rate	Channel Frequency (MHz)	Measured 99% Bandwidth	Limit
		(MHz)	
1 Mbps	2402	1.0312	/
	2440	1.0256	
	2480	1.0294	
2 Mbps	2402	2.0416	/
	2440	2.0388	
	2480	2.0406	

Right Earbud:

Data Rate	Channel Frequency (MHz)	Measured 99% Bandwidth	Limit
		(MHz)	
1 Mbps	2402	1.0325	/
	2440	1.0259	
	2480	1.0263	
2 Mbps	2402	2.0424	/
	2440	2.0653	
	2480	2.0391	

Note: The fundamental emissions stay within the allocated band 2400-2483.5MHz.

Prüfbericht-Nr.: CN250W40 002
Test report no.:

Seite 18 von 22
Page 18 of 22

5.1.5 6dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(2)
RSS-247 Clause 5.2(a)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-12-10 to 2024-12-20
Input voltage : DC 3.85V for left and right earbud
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 20.8 °C
Relative humidity : 48.2 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B&C.

Table 9: Test Result of 6dB Bandwidth

Left Earbud:

Data Rate	Channel Frequency (MHz)	Measured 6dB Bandwidth	Limit
		(MHz)	
1 Mbps	2402	0.668	>500kHz
	2440	0.672	
	2480	0.668	
2 Mbps	2402	1.132	>500kHz
	2440	1.132	
	2480	1.148	

Right Earbud:

Data Rate	Channel Frequency (MHz)	Measured 6dB Bandwidth	Limit
		(MHz)	
1 Mbps	2402	0.660	>500kHz
	2440	0.668	
	2480	0.648	
2 Mbps	2402	1.152	>500kHz
	2440	1.128	
	2480	1.168	

Prüfbericht-Nr.: **CN250W40 002**
Test report no.:

Seite 19 von 22
Page 19 of 22

5.1.6 Frequency stability

RESULT:

Pass

Test Specification

Test standard	: RSS-247 Clause 8.11
Basic standard	: ANSI C63.10: 2013
Limits	: within at least the central 80% of its permitted operating frequency band (2400-2483.5MHz)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2024-12-10 to 2024-12-20
Input voltage	: DC 3.85V for left and right earbud
Operation mode	: B
Ambient temperature	: 20.8 °C
Relative humidity	: 48.2 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B&C.

Prüfbericht-Nr.: **CN250W40 002**
Test report no.:

Seite 20 von 22
Page 20 of 22

5.1.7 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(d) RSS-247 Clause 5.5
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2024-12-10 to 2024-12-20
Input voltage	: DC 3.85V for left and right earbud
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 20.8 °C
Relative humidity	: 48.2 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B&C.

Prüfbericht-Nr.: **CN250W40 002**
Test report no.:

Seite 21 von 22
Page 21 of 22

5.1.8 Radiated Spurious Emission

RESULT:

Pass

Test Specification

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3 & 5.5
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 4 & Table 5
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	2024-12-10 to 2024-12-20
Input voltage	:	DC 3.85V for left and right earbud
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B&C.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	8
Table 3: RF Channel and Frequency of Classic Bluetooth.....	9
Table 4: RF Channel and Frequency of Bluetooth Low Energy.....	9
Table 5: List of Accessories and Auxiliary Equipment.....	11
Table 6: Test Result of Maximum Peak Conducted Output Power.....	15
Table 7: Test Result of 99% Bandwidth	16
Table 8: Test Result of 99% Bandwidth	17
Table 9: Test Result of 6dB Bandwidth.....	18

Appendix B: Test Results of Bluetooth Low Energy_Left Earbud

APPENDIX B: TEST RESULTS OF BLUETOOTH LOW ENERGY_LEFT EARBUD	1
APPENDIX B.1: TEST RESULTS OF CONDUCTED POWER SPECTRAL DENSITY	2
APPENDIX B.2: TEST RESULTS OF 6dB BANDWIDTH	5
APPENDIX B.3: TEST RESULTS OF 99% BANDWIDTH.....	8
APPENDIX B.4: TEST RESULTS OF FREQUENCY STABILITY	11
APPENDIX B.5: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH.....	13
CONDUCTED SPURIOUS EMISSION	13
BAND EDGE MEASUREMENTS	20
APPENDIX B.6: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	22
30 MHz - 1GHz.....	22
1GHz - 18GHz.....	24
APPENDIX B.7: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	36
APPENDIX B.8: TEST RESULTS OF DUTY CYCLE.....	44

Appendix B.1: Test Results of Conducted Power Spectral Density


TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-9.10	≤8.00	PASS
		2440	-9.03	≤8.00	PASS
		2480	-9.24	≤8.00	PASS
BLE_2M	Ant1	2402	-12.67	≤8.00	PASS
		2440	-11.82	≤8.00	PASS
		2480	-11.89	≤8.00	PASS

BLE_1M Ant1 2402



BLE_1M Ant1 2440







Appendix B.2: Test Results of 6dB Bandwidth

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.668	2401.660	2402.328	0.5	PASS
		2440	0.672	2439.652	2440.324	0.5	PASS
		2480	0.668	2479.656	2480.324	0.5	PASS
BLE_2M	Ant1	2402	1.132	2401.428	2402.560	0.5	PASS
		2440	1.132	2439.416	2440.548	0.5	PASS
		2480	1.148	2479.408	2480.556	0.5	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE 1M Ant1 2480



BLE 2M Ant1 2402



BLE 2M Ant1 2440





Appendix B.3: Test Results of 99% Bandwidth


TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0312	2401.4876	2402.5188	---	---
		2440	1.0256	2439.4886	2440.5142	---	---
		2480	1.0294	2479.4852	2480.5146	---	---
BLE_2M	Ant1	2402	2.0416	2400.9877	2403.0293	---	---
		2440	2.0388	2438.9922	2441.0310	---	---
		2480	2.0406	2478.9911	2481.0317	---	---

BLE_1M Ant1 2402



BLE_1M Ant1 2440







Appendix B.4: Test Results of Frequency stability

Test Channel (MHz)	2402
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.85V	2401.990	-10	-4.16	10
DC 3.47V	2401.990	-10	-4.16	
DC 4.24V	2401.992	-8	-3.33	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2401.986	-14	-5.83	10
-20	2401.989	-11	-4.58	
-10	2401.990	-10	-4.16	
0	2401.990	-10	-4.16	
10	2401.991	-9	-3.75	
20	2401.990	-10	-4.16	
30	2401.991	-9	-3.75	
40	2401.992	-8	-3.33	
50	2401.992	-8	-3.33	
55	2401.991	-9	-3.75	

Test Channel (MHz)	2440
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.85V	2439.992	-8	-3.28	10
DC 3.47V	2439.993	-7	-2.87	
DC 4.24V	2439.992	-8	-3.28	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2439.985	-15	-6.15	10
-20	2439.984	-16	-6.56	
-10	2439.990	-10	-4.10	
0	2439.992	-8	-3.28	
10	2439.991	-9	-3.69	
20	2439.991	-9	-3.69	
30	2439.993	-7	-2.87	
40	2439.994	-6	-2.46	
50	2439.994	-6	-2.46	
55	2439.994	-6	-2.46	

Test Channel (MHz)	2480
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.85V	2479.992	-8	-3.23	10
DC 3.47V	2479.993	-7	-2.82	
DC 4.24V	2479.993	-7	-2.82	

Test result of frequency tolerance of temperature variation


Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2479.987	-13	-5.24	10
-20	2479.987	-13	-5.24	
-10	2479.988	-12	-4.84	
0	2479.989	-11	-4.44	
10	2479.990	-10	-4.03	
20	2479.991	-9	-3.63	
30	2479.991	-9	-3.63	
40	2479.991	-9	-3.63	
50	2479.992	-8	-3.23	
55	2479.991	-9	-3.63	


Appendix B.5: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

Conducted Spurious Emission

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	5.50	5.50	---	PASS
			30~1000	5.50	-48.87	≤-14.5	PASS
			1000~26500	5.50	-40.08	≤-14.5	PASS
		2440	Reference	5.34	5.34	---	PASS
			30~1000	5.34	-48.35	≤-14.66	PASS
			1000~26500	5.34	-40.13	≤-14.66	PASS
		2480	Reference	5.37	5.37	---	PASS
			30~1000	5.37	-48.64	≤-14.63	PASS
			1000~26500	5.37	-39.95	≤-14.63	PASS
BLE_2M	Ant1	2402	Reference	6.14	6.14	---	PASS
			30~1000	6.14	-47.07	≤-13.86	PASS
			1000~26500	6.14	-39.14	≤-13.86	PASS
		2440	Reference	6.24	6.24	---	PASS
			30~1000	6.24	-47.1	≤-13.76	PASS
			1000~26500	6.24	-39.13	≤-13.76	PASS
		2480	Reference	5.92	5.92	---	PASS
			30~1000	5.92	-47.7	≤-14.08	PASS
			1000~26500	5.92	-38.84	≤-14.08	PASS















Band edge measurements

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	6.40	-48.55	≤-13.60	PASS
		High	2480	5.87	-50.85	≤-14.13	PASS
BLE_2M	Ant1	Low	2402	6.38	-41.26	≤-13.62	PASS
		High	2480	6.07	-49.75	≤-13.93	PASS

BLE 1M Ant1 Low 2402



BLE 1M Ant1 High 2480



BLE 2M Ant1 Low 2402



BLE 2M Ant1 High 2480



Appendix B.6: Test Results of Radiated Spurious Emissions


Note:

- 1) This testing was carried out on different modulations, but only the worst case was presented in this report.
- 2) Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

30 MHz - 1GHz

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.967692	14.99	40.00	25.01	100.0	H	218.0	-18.8
107.935769	12.44	43.50	31.06	100.0	H	32.0	-19.1
283.058077	15.89	46.00	30.11	100.0	H	359.0	-16.7
724.445385	24.34	46.00	21.66	100.0	H	168.0	-7.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.327692	15.23	40.00	24.77	100.0	V	240.0	-22.2
102.861923	12.52	43.50	30.98	100.0	V	208.0	-19.0
270.783846	15.16	46.00	30.84	100.0	V	314.0	-16.9
415.388462	18.89	46.00	27.11	100.0	V	63.0	-13.4
942.732692	27.94	46.00	18.06	100.0	V	290.0	-4.4

1GHz - 18GHz

Note: The highest waveform in the figure is Bluetooth Fundamental.

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4811.500000	---	41.54	54.00	12.46	150.0	H	70.0	13.3
4855.000000	52.24	---	74.00	21.76	150.0	H	57.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4824.000000	---	41.43	54.00	12.57	150.0	V	151.0	13.3
4848.500000	52.80	---	74.00	21.20	150.0	V	163.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4893.500000	53.04	---	74.00	20.96	150.0	H	31.0	13.3
4898.500000	---	41.07	54.00	12.93	150.0	H	190.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4881.500000	51.98	---	74.00	22.02	150.0	V	39.0	13.3
4904.000000	---	41.25	54.00	12.75	150.0	V	162.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4948.000000	53.02	---	74.00	20.98	150.0	H	349.0	13.3
4960.000000	---	41.21	54.00	12.79	150.0	H	184.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4935.500000	51.96	---	74.00	22.04	150.0	V	334.0	13.3
4966.500000	---	41.02	54.00	12.98	150.0	V	284.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7205.458333	---	35.92	54.00	18.08	150.0	H	328.0	8.8
7222.175000	44.48	---	74.00	29.52	150.0	H	339.0	8.7
12042.966667	50.23	---	74.00	23.77	150.0	H	271.0	16.2
12047.883333	---	43.07	54.00	10.93	150.0	H	349.0	16.4

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7222.666667	---	35.41	54.00	18.59	150.0	V	135.0	8.7
7245.283333	43.45	---	74.00	30.55	150.0	V	65.0	8.6
12144.741667	51.18	---	74.00	22.82	150.0	V	54.0	16.6
12159.000000	---	42.86	54.00	11.14	150.0	V	42.0	16.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7271.833333	43.87	---	74.00	30.13	150.0	H	359.0	8.5
7289.533333	---	35.78	54.00	18.22	150.0	H	342.0	8.4
12135.891667	50.78	---	74.00	23.22	150.0	H	256.0	16.4
12135.891667	---	42.82	54.00	11.18	150.0	H	256.0	16.4

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No./Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7277.241667	---	35.49	54.00	18.51	150.0	V	59.0	8.4
7335.750000	44.04	---	74.00	29.96	150.0	V	246.0	8.1
12143.266667	50.73	---	74.00	23.27	150.0	V	104.0	16.6
12151.133333	---	43.02	54.00	10.98	150.0	V	4.0	16.7

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7488.658333	---	35.19	54.00	18.81	150.0	H	44.0	8.7
7505.375000	43.51	---	74.00	30.49	150.0	H	79.0	8.7
12141.791667	50.99	---	74.00	23.01	150.0	H	352.0	16.5
12147.200000	---	43.15	54.00	10.85	150.0	H	221.0	16.7

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7442.933333	43.59	---	74.00	30.41	150.0	V	308.0	8.5
7458.175000	---	35.66	54.00	18.34	150.0	V	298.0	8.5
12147.691667	---	43.00	54.00	11.00	150.0	V	353.0	16.7
12156.541667	50.43	---	74.00	23.57	150.0	V	353.0	16.4

Appendix B.7: Test Results of Radiated Emissions in Restricted Bands

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2373.454412	51.67	---	74.00	22.33	150.0	H	113.0	8.5
2373.747794	---	40.47	54.00	13.53	150.0	H	70.0	8.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2330.243382	---	40.68	54.00	13.32	150.0	V	241.0	8.3
2330.480882	50.85	---	74.00	23.15	150.0	V	289.0	8.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.757353	---	42.78	54.00	11.22	150.0	H	63.0	9.0
2483.849265	52.55	---	74.00	21.45	150.0	H	149.0	9.0

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.772059	---	42.19	54.00	11.81	150.0	V	209.0	9.0
2486.514706	52.54	---	74.00	21.46	150.0	V	215.0	9.0

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2374.236765	---	40.52	54.00	13.48	150.0	H	56.0	8.5
2376.011029	51.70	---	74.00	22.30	150.0	H	271.0	8.5

EUT Information

EUT Name: BLUETOOTH HEADSET
Model: SENSE LITE
Test Mode: BLE 2M_Low channel
Order No/Sample No: A003880376-012
Test Voltage:: Battery
Remark: Temp 23 Humi:58%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2382.507353	---	40.15	54.00	13.85	150.0	V	115.0	8.5
2383.792647	52.17	---	74.00	21.83	150.0	V	261.0	8.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.694853	53.72	---	74.00	20.28	150.0	H	82.0	9.0
2483.753677	---	42.65	54.00	11.35	150.0	H	155.0	9.0

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2486.415441	53.44	---	74.00	20.56	150.0	V	357.0	9.0
2487.757353	---	41.95	54.00	12.05	150.0	V	289.0	9.0

Appendix B.8: Test Results of Duty Cycle

TestMode	Antenna	Channel	ON Time [ms]	Period [ms]	X	DC [%]	Limit	Verdict
BLE_1M	Ant1	2402	0.39	0.63	0.6190	61.90	---	---
		2440	0.39	0.63	0.6190	61.90	---	---
		2480	0.39	0.63	0.6190	61.90	---	---
BLE_2M	Ant1	2402	0.21	0.63	0.3333	33.33	---	---
		2440	0.21	0.63	0.3333	33.33	---	---
		2480	0.21	0.63	0.3333	33.33	---	---








Appendix C: Test Results of Bluetooth Low Energy_Right Earbud

APPENDIX C: TEST RESULTS OF BLUETOOTH LOW ENERGY_RIGHT EARBUD	1
APPENDIX C.1: TEST RESULTS OF CONDUCTED POWER SPECTRAL DENSITY	2
APPENDIX C.2: TEST RESULTS OF 6dB BANDWIDTH	5
APPENDIX C.3: TEST RESULTS OF 99% BANDWIDTH	8
APPENDIX C.4: TEST RESULTS OF FREQUENCY STABILITY	11
APPENDIX C.5: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH	13
CONDUCTED SPURIOUS EMISSION	13
BAND EDGE MEASUREMENTS	20
APPENDIX C.6: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	22
30 MHz - 1GHz.....	22
1GHz - 18GHz.....	24
APPENDIX C.7: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	36
APPENDIX C.8: TEST RESULTS OF DUTY CYCLE.....	44


Appendix C.1: Test Results of Conducted Power Spectral Density

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-8.18	≤8.00	PASS
		2440	-7.85	≤8.00	PASS
		2480	-8.03	≤8.00	PASS
BLE_2M	Ant1	2402	-11.38	≤8.00	PASS
		2440	-11.26	≤8.00	PASS
		2480	-11.37	≤8.00	PASS

BLE_1M Ant1 2402



BLE_1M Ant1 2440







Appendix C.2: Test Results of 6dB Bandwidth

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.660	2401.656	2402.316	0.5	PASS
		2440	0.668	2439.648	2440.316	0.5	PASS
		2480	0.648	2479.668	2480.316	0.5	PASS
BLE_2M	Ant1	2402	1.152	2401.420	2402.572	0.5	PASS
		2440	1.128	2439.412	2440.540	0.5	PASS
		2480	1.168	2479.412	2480.580	0.5	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE 1M Ant1 2480



BLE 2M Ant1 2402



BLE 2M Ant1 2440






Appendix C.3: Test Results of 99% Bandwidth


TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0325	2401.4823	2402.5148	---	---
		2440	1.0259	2439.4811	2440.5070	---	---
		2480	1.0263	2479.4820	2480.5083	---	---
BLE_2M	Ant1	2402	2.0424	2400.9910	2403.0334	---	---
		2440	2.0653	2438.9731	2441.0384	---	---
		2480	2.0391	2478.9884	2481.0275	---	---

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440







Appendix C.4: Test Results of Frequency stability

Test Channel (MHz)	2402
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.85V	2401.992	-8	-3.33	10
DC 3.47V	2401.992	-8	-3.33	
DC 4.24V	2401.993	-7	-2.91	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2401.990	-10	-4.16	10
-20	2401.989	-11	-4.58	
-10	2401.991	-9	-3.75	
0	2401.991	-9	-3.75	
10	2401.992	-8	-3.33	
20	2401.993	-7	-2.91	
30	2401.991	-9	-3.75	
40	2401.991	-9	-3.75	
50	2401.993	-7	-2.91	
55	2401.991	-9	-3.75	

Test Channel (MHz)	2440
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.85V	2439.995	-5	-2.05	10
DC 3.47V	2439.995	-5	-2.05	
DC 4.24V	2439.994	-6	-2.46	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2439.995	-5	-2.05	10
-20	2439.992	-8	-3.28	
-10	2439.991	-9	-3.69	
0	2439.993	-7	-2.87	
10	2439.994	-6	-2.46	
20	2439.995	-5	-2.05	
30	2439.995	-5	-2.05	
40	2439.994	-6	-2.46	
50	2439.993	-7	-2.87	
55	2439.994	-6	-2.46	

Test Channel (MHz)	2480
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.85V	2479.995	-5	-2.02	10
DC 3.47V	2479.994	-6	-2.42	
DC 4.24V	2479.996	-4	-1.61	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2479.989	-11	-4.44	10
-20	2479.990	-10	-4.03	
-10	2479.991	-9	-3.63	
0	2479.990	-10	-4.03	
10	2479.992	-8	-3.23	
20	2479.993	-7	-2.82	
30	2479.992	-8	-3.23	
40	2479.993	-7	-2.82	
50	2479.991	-9	-3.63	
55	2479.992	-8	-3.23	


Appendix C.5: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth


Conducted Spurious Emission

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	6.48	6.48	---	PASS
			30~1000	6.48	-41.46	≤-13.52	PASS
			1000~26500	6.48	-33.12	≤-13.52	PASS
		2440	Reference	6.74	6.74	---	PASS
			30~1000	6.74	-41.04	≤-13.26	PASS
			1000~26500	6.74	-32.51	≤-13.26	PASS
		2480	Reference	6.53	6.53	---	PASS
			30~1000	6.53	-42.23	≤-13.47	PASS
			1000~26500	6.53	-32.58	≤-13.47	PASS
BLE_2M	Ant1	2402	Reference	6.53	6.53	---	PASS
			30~1000	6.53	-41.77	≤-13.47	PASS
			1000~26500	6.53	-31.87	≤-13.47	PASS
		2440	Reference	6.49	6.49	---	PASS
			30~1000	6.49	-42.17	≤-13.51	PASS
			1000~26500	6.49	-32.08	≤-13.51	PASS
		2480	Reference	6.51	6.51	---	PASS
			30~1000	6.51	-41.44	≤-13.49	PASS
			1000~26500	6.51	-32.38	≤-13.49	PASS

BLE 1M Ant1 2402 0~Reference
















Band edge measurements

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	6.63	-44.74	≤-13.37	PASS
		High	2480	6.55	-44.16	≤-13.45	PASS
BLE_2M	Ant1	Low	2402	6.32	-42.17	≤-13.68	PASS
		High	2480	6.29	-42.99	≤-13.71	PASS

BLE 1M Ant1 Low 2402



BLE 1M Ant1 High 2480



BLE 2M Ant1 Low 2402



BLE 2M Ant1 High 2480



Appendix C.6: Test Results of Radiated Spurious Emissions


Note:

- 1) This testing was carried out on different modulations, but only the worst case was presented in this report.
- 2) Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

30 MHz - 1GHz

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.967692	14.99	40.00	25.01	100.0	H	218.0	-18.8
107.935769	12.44	43.50	31.06	100.0	H	32.0	-19.1
283.058077	15.89	46.00	30.11	100.0	H	359.0	-16.7
724.445385	24.34	46.00	21.66	100.0	H	168.0	-7.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.327692	15.23	40.00	24.77	100.0	V	240.0	-22.2
102.861923	12.52	43.50	30.98	100.0	V	208.0	-19.0
270.783846	15.16	46.00	30.84	100.0	V	314.0	-16.9
415.388462	18.89	46.00	27.11	100.0	V	63.0	-13.4
942.732692	27.94	46.00	18.06	100.0	V	290.0	-4.4

1GHz - 18GHz

Note: The highest waveform in the figure is Bluetooth Fundamental.

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4811.500000	---	41.54	54.00	12.46	150.0	H	70.0	13.3
4855.000000	52.24	---	74.00	21.76	150.0	H	57.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4824.000000	---	41.43	54.00	12.57	150.0	V	151.0	13.3
4848.500000	52.80	---	74.00	21.20	150.0	V	163.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4893.500000	53.04	---	74.00	20.96	150.0	H	31.0	13.3
4898.500000	---	41.07	54.00	12.93	150.0	H	190.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4881.500000	51.98	---	74.00	22.02	150.0	V	39.0	13.3
4904.000000	---	41.25	54.00	12.75	150.0	V	162.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4948.000000	53.02	---	74.00	20.98	150.0	H	349.0	13.3
4960.000000	---	41.21	54.00	12.79	150.0	H	184.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4935.500000	51.96	---	74.00	22.04	150.0	V	334.0	13.3
4966.500000	---	41.02	54.00	12.98	150.0	V	284.0	13.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7205.458333	---	35.92	54.00	18.08	150.0	H	328.0	8.8
7222.175000	44.48	---	74.00	29.52	150.0	H	339.0	8.7
12042.966667	50.23	---	74.00	23.77	150.0	H	271.0	16.2
12047.883333	---	43.07	54.00	10.93	150.0	H	349.0	16.4

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7222.666667	---	35.41	54.00	18.59	150.0	V	135.0	8.7
7245.283333	43.45	---	74.00	30.55	150.0	V	65.0	8.6
12144.741667	51.18	---	74.00	22.82	150.0	V	54.0	16.6
12159.000000	---	42.86	54.00	11.14	150.0	V	42.0	16.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7271.833333	43.87	---	74.00	30.13	150.0	H	359.0	8.5
7289.533333	---	35.78	54.00	18.22	150.0	H	342.0	8.4
12135.891667	50.78	---	74.00	23.22	150.0	H	256.0	16.4
12135.891667	---	42.82	54.00	11.18	150.0	H	256.0	16.4

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7277.241667	---	35.49	54.00	18.51	150.0	V	59.0	8.4
7335.750000	44.04	---	74.00	29.96	150.0	V	246.0	8.1
12143.266667	50.73	---	74.00	23.27	150.0	V	104.0	16.6
12151.133333	---	43.02	54.00	10.98	150.0	V	4.0	16.7

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7488.658333	---	35.19	54.00	18.81	150.0	H	44.0	8.7
7505.375000	43.51	---	74.00	30.49	150.0	H	79.0	8.7
12141.791667	50.99	---	74.00	23.01	150.0	H	352.0	16.5
12147.200000	---	43.15	54.00	10.85	150.0	H	221.0	16.7

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7442.933333	43.59	---	74.00	30.41	150.0	V	308.0	8.5
7458.175000	---	35.66	54.00	18.34	150.0	V	298.0	8.5
12147.691667	---	43.00	54.00	11.00	150.0	V	353.0	16.7
12156.541667	50.43	---	74.00	23.57	150.0	V	353.0	16.4

Appendix C.7: Test Results of Radiated Emissions in Restricted Bands

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2373.454412	51.67	---	74.00	22.33	150.0	H	113.0	8.5
2373.747794	---	40.47	54.00	13.53	150.0	H	70.0	8.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2330.243382	---	40.68	54.00	13.32	150.0	V	241.0	8.3
2330.480882	50.85	---	74.00	23.15	150.0	V	289.0	8.3

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.757353	---	42.78	54.00	11.22	150.0	H	63.0	9.0
2483.849265	52.55	---	74.00	21.45	150.0	H	149.0	9.0

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.772059	---	42.19	54.00	11.81	150.0	V	209.0	9.0
2486.514706	52.54	---	74.00	21.46	150.0	V	215.0	9.0

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2374.236765	---	40.52	54.00	13.48	150.0	H	56.0	8.5
2376.011029	51.70	---	74.00	22.30	150.0	H	271.0	8.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_Low channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2382.507353	---	40.15	54.00	13.85	150.0	V	115.0	8.5
2383.792647	52.17	---	74.00	21.83	150.0	V	261.0	8.5

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.694853	53.72	---	74.00	20.28	150.0	H	82.0	9.0
2483.753677	---	42.65	54.00	11.35	150.0	H	155.0	9.0

EUT Information

EUT Name:	BLUETOOTH HEADSET
Model:	SENSE LITE
Test Mode:	BLE 2M_High channel
Order No/Sample No:	A003880376-012
Test Voltage::	Battery
Remark:	Temp 23 Humi:58%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2486.415441	53.44	---	74.00	20.56	150.0	V	357.0	9.0
2487.757353	---	41.95	54.00	12.05	150.0	V	289.0	9.0

Appendix C.8: Test Results of Duty Cycle

TestMode	Antenna	Channel	ON Time [ms]	Period [ms]	X	DC [%]	Limit	Verdict
BLE_1M	Ant1	2402	0.39	0.63	0.6190	61.90	---	---
		2440	0.39	0.63	0.6190	61.90	---	---
		2480	0.39	0.63	0.6190	61.90	---	---
BLE_2M	Ant1	2402	0.20	0.63	0.3175	31.75	---	---
		2440	0.21	0.63	0.3333	33.33	---	---
		2480	0.21	0.63	0.3333	33.33	---	---

BLE_1M Ant1 2402



BLE_1M Ant1 2440



BLE 1M Ant1 2480



BLE 2M Ant1 2402



BLE 2M Ant1 2440



