

Echelon Fitness Multimedia LLC

TEST REPORT

SCOPE OF WORK

FCC TESTING—ECHKIN215-3288

REPORT NUMBER

210105036SZN-003

ISSUE DATE

20 March 2021[-----]

[REVISED DATE]

PAGES

103

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



Echelon Fitness Multimedia LLC

Application For Certification

FCC ID: 2AWD4-KS3288A

21.5 inch Screen-S

Model: ECHKIN215-3288

2.4GHz Wi-Fi Transceiver

Report No.: 210105036SZN-003

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-19]

Prepared and Checked by:

Approved by:

**Ryan Chen
Engineer**

**Peter Kang
Sr. Technical Supervisor
Date: 20 March 2021**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-19] Edition] provision.

Report prepared by:

Ryan Chen
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing
Community, GuanHu Subdistrict, LongHua District, Shenzhen,
P.R. China.
Tel: (86 755) 8614 0682 Fax: (86 755) 8601 6661

Table of Contents

1.0	<u>Summary of Test results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	<u>System Test Configuration</u>	6
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	6
3.4	Measurement Uncertainty	7
3.5	Equipment Modification	7
3.6	Support Equipment List and Description	7
4.0	<u>Measurement Results</u>	8
4.1	Maximum Conducted Output Power at Antenna Terminals	8
4.2	Minimum 6 dB RF Bandwidth	11
4.3	Maximum Power Density Reading	16
4.4	Out of Band Conducted Emissions	30
4.5	Out of Band Radiated Emissions	80
4.6	Transmitter Radiated Emissions in Restricted Bands	81
4.7	Field Strength Calculation	82
4.8	Radiated Spurious Emission	83
4.9	Conducted Emission	97
4.10	Radiated Emissions from Digital Section of Transceiver	100
4.11	Transmitter Duty Cycle Calculation and Measurements	101
5.0	<u>Equipment Photographs</u>	102
6.0	<u>Product Labelling</u>	102
7.0	<u>Technical Specifications</u>	102
8.0	<u>Instruction Manual</u>	102
9.0	<u>Confidentiality Request</u>	102
10.0	<u>Discussion of Pulse Desensitization</u>	102
11.0	<u>Test Equipment List</u>	103

1.0 Summary of Test results

Applicant: Echelon Fitness Multimedia LLC

Applicant Address: 605 Chestnut Street, 7th Floor, Chattanooga, TN 37450, USA

Manufacturer: SHENZHEN KINSTONE D&T DEVELOP CO.,LTD

Manufacturer Address: 5F, A2 B, XinJianXing Tech Industrial Park, Fengxin Road, Lou Cun, Guangming New Dist., Shenzhen, China

Model: ECHKIN215-3288

FCC ID: 2AWD4-KS3288A

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d), 15.209, FCC 15.205	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The equipment under test (EUT) is a 21.5 inch Screen-S with Bluetooth 5.0 (dual-mode) function operating in 2402-2480MHz, 2.4G WIFI function operating in 2412-2462MHz and 5G WIFI function operating in 5150MHz~5250 MHz, 5250MHz~5350MHz, 5470MHz-5725MHz, 5725MHz~5850MHz. The EUT is powered by DC 12V. For more detail information pls. refer to the user manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM for OFDM; CCK, DQPSK, DBPSK for DSSS.

Antenna Type: Integral Antenna

Antenna Gain: 1.2dBi

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the 21.5 inch Screen-S which has 2.4GHz WIFI function.

For the classic Bluetooth function was tested and demonstrated in report 210105036SZN-001.

For the BT BLE function was tested and demonstrated in report 210105036SZN-002.

For the 5GHz WIFI function was tested and demonstrated in report 210105036SZN-004.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by DC 12V from an adapter and the adapter is powered by AC 120V/60Hz during the test, only the worst data was reported in this report.

On 802.11b/g/n-HT20/n-HT40 mode, two antennas are used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The EUT and transmitting antennas were centered on the turntable.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test software: RFTTest Tool V5.4 installed in the EUT.

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by Echelon Fitness Multimedia LLC will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Remark
AC ADAPTER (Provided by Client)	L.T.E	Model: LTE65ES-S2-1 Input: 100-240VAC 2A max 50-60Hz Output: DC 12 V=5 A
Power Cord (Provided by Client)	---	Unshielded, 1.5m
TF card (Provided by Intertek)	Kingston	class10
USB*2 (Provided by Intertek)	SanDisk	Model: SDCZ36-002G-P36
HDMI Cable (Provided by Intertek)	---	Unshielded, 120cm*2
Test TV (Provided by Intertek)	SAMSUNG	Model: U28H750UQ
Test TV (Provided by Intertek)	SONY	Model: KDL-24EX520)
AUX Cable (Provided by Intertek)	---	Unshielded, 150cm*2
RJ45 Cable (Provided by Intertek)	---	Unshielded, 160cm*2
Cement resistance	---	8 Ω

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm). 2.4G band Ant gain: 1.2dBi. In MIMO (2Tx), Ant1+Ant2 Directional gain = $GANT + 10 \log(N) \text{ dBi} = 1.2 + 10 \log(2) = 4.2 \text{ dBi} < 6 \text{ dBi}$.

SISO Mode, Ant1:

IEEE 802.11b (Antenna Gain = 1.2dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	16.2	41.69
Middle Channel: 2437	16.2	41.69
High Channel: 2462	15.9	38.90

IEEE 802.11g (Antenna Gain = 1.2dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	18.7	74.13
Middle Channel: 2437	18.9	77.62
High Channel: 2462	18.3	67.61

IEEE 802.11n-HT20 (Antenna Gain = 1.2dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	18.3	67.61
Middle Channel: 2437	18.2	66.07
High Channel: 2462	18.7	74.13

IEEE 802.11n-HT40 (Antenna Gain = 1.2dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2422	18.3	67.61
Middle Channel: 2437	18.5	70.79
High Channel: 2452	18.2	66.07

SISO Mode, Ant2:

IEEE 802.11b (Antenna Gain = 1.2dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	15.0	31.62
Middle Channel: 2437	14.6	28.84
High Channel: 2462	14.3	26.92

IEEE 802.11g (Antenna Gain = 1.2dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	18.8	75.86
Middle Channel: 2437	18.4	69.18
High Channel: 2462	18.5	70.79

IEEE 802.11n-HT20 (Antenna Gain = 1.2dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	18.3	67.61
Middle Channel: 2437	18.8	75.86
High Channel: 2462	18.4	69.18

IEEE 802.11n-HT40 (Antenna Gain = 1.2dBi) (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2422	18.3	67.61
Middle Channel: 2437	18.1	64.57
High Channel: 2452	18.9	77.62

MIMO Mode:

IEEE 802.11n-HT20 (Antenna Gain = 4.2dBi) (64QAM, 6.5Mbps)				
Frequency (MHz)	Output in dBm (Peak Reading)			Output in mWatt
	Ant 1	Ant 2	Total	
Low Channel: 2412	18.3	18.1	21.2	131.83
Middle Channel: 2437	18.8	18.8	21.8	151.36
High Channel: 2462	20.4	18.7	22.6	181.97

IEEE 802.11n-HT40 (Antenna Gain = 4.2dBi) (64QAM, 13.5Mbps)				
Frequency (MHz)	Output in dBm (Peak Reading)			Output in mWatt
	Ant 1	Ant 2	Total	
Low Channel: 2422	18.3	18.4	21.3	134.90
Middle Channel: 2437	18.1	18.2	21.2	131.83
High Channel: 2452	18.9	18.1	21.5	141.25

Cable loss: 1.0 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 22.6dBm

EUT max. E.I.R.P = 22.6dBm + 4.2dBi = 26.8dBm = 478.6mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	7.770
2437	7.530
2462	7.260


IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.410
2437	16.410
2462	16.440

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.760
2437	17.760
2462	17.760

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2422	35.880
2437	36.060
2452	35.880


The test plots are attached as below.

11b Ant1 2412




Date: 2 FEB 2021 16:06:09

11b Ant1 2437




Date: 2 FEB 2021 16:10:19

11b Ant1 2462




Date: 2 FEB 2021 16:12:31

11g_Ant1_2412




Date: 2 FEB 2021 16:14:38

11g_Ant1_2437




Date: 2 FEB 2021 16:16:38

11g_Ant1_2462




Date: 2 FEB 2021 16:19:04

11N20SISO_Ant1_2412




Date: 2 FEB 2021 16:20:55

11N20SISO_Ant1_2437




Date: 2 FEB 2021 16:23:11

11N20SISO_Ant1_2462




Date: 2 FEB 2021 16:25:14

11N40SISO_Ant1_2422




Date: 2 FEB 2021 16:27:18

11N40SISO_Ant1_2437



Date: 2 FEB 2021 16:31:00

11N40SISO_Ant1_2452



Date: 2 FEB 2021 16:32:47

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

SISO Mode:

IEEE 802.11b (CCK, 1Mbps)		
Frequency (MHz)	Power Density with RBW 3KHz	
	Ant 1	Ant 2
2412	-9.20	-10.59
2437	-9.38	-11.08
2462	-9.90	-11.35

IEEE 802.11g (16QAM, 6Mbps)		
Frequency (MHz)	Power Density with RBW 3KHz	
	Ant 1	Ant 2
2412	-14.45	-15.55
2437	-14.37	-15.87
2462	-14.65	-16.27

IEEE 802.11n-HT20 (64QAM, 6.5Mbps)		
Frequency (MHz)	Power Density with RBW 3KHz	
	Ant 1	Ant 2
2412	-14.10	-15.47
2437	-14.32	-15.76
2462	-14.64	-16.15

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)		
Frequency (MHz)	Power Density with RBW 3KHz	
	Ant 1	Ant 2
2422	-23.82	-26.15
2437	-23.89	-25.76
2452	-24.88	-26.41


MIMO Mode:

IEEE 802.11n-HT20 (64QAM, 6.5Mbps)			
Frequency (MHz)	Power Density with RBW 3KHz		
	Ant 1	Ant 2	Total
2412	-13.87	-14.34	-11.09
2437	-13.45	-14.05	-10.73
2462	-14.36	-15.25	-11.77


IEEE 802.11n-HT40 (64QAM, 13.5Mbps)			
Frequency (MHz)	Power Density with RBW 3KHz		
	Ant 1	Ant 2	Total
2422	-23.58	-24.94	-21.20
2437	-23.73	-25.66	-21.58
2452	-24.23	-25.09	-21.63

The test plots are attached as below.


11B_Ant1_2412




11B_Ant1_2437



11B_Ant1_2462




11G_Ant1_2412




Date: 2.FEB.2021 16:15:24

11G_Ant1_2437




Date: 2.FEB.2021 16:17:05

11G_Ant1_2462




Date: 2.FEB.2021 16:19:31


11N20SISO_Ant1_2412




11N20SISO_Ant1_2437



11N20SISO_Ant1_2462




11N40SISO_Ant1_2422




Date: 2 FEB 2021 16:29:38

11N40SISO_Ant1_2437




Date: 2 FEB 2021 16:31:34

11N40SISO_Ant1_2452




Date: 2 FEB 2021 16:33:21

11B_Ant2_2412




Date: 2.FEB.2021 15:29:58

11B_Ant2_2437




Date: 2.FEB.2021 15:31:25

11B_Ant2_2462




Date: 2.FEB.2021 15:33:18

11G_Ant2_2412




Date: 2.FEB.2021 15:36:39

11G_Ant2_2437




Date: 2.FEB.2021 15:38:58

11G_Ant2_2462




Date: 2.FEB.2021 15:41:07

11N20SISO_Ant2_2412




Date: 2.FEB.2021 15:46:00

11N20SISO_Ant2_2437




Date: 2.FEB.2021 15:48:22

11N20SISO_Ant2_2462




Date: 2.FEB.2021 15:50:13

11N40SISO_Ant2_2422




Date: 2.FEB.2021 15:53:35

11N40SISO_Ant2_2437




Date: 2.FEB.2021 15:55:32

11N40SISO_Ant2_2452




Date: 2.FEB.2021 15:59:01

11N20MIMO_Ant1_2412




Date: 2.FEB.2021 16:46:35

11N20MIMO_Ant2_2412




Date: 2.FEB.2021 17:02:38

11N20MIMO_Ant1_2437




Date: 2.FEB.2021 16:51:12

11N20MIMO_Ant2_2437




Date: 2.FEB.2021 17:04:34

11N20MIMO_Ant1_2462




Date: 2.FEB.2021 16:52:30

11N20MIMO_Ant2_2462




Date: 2.FEB.2021 17:06:32

11N40MIMO_Ant1_2422




Date: 2.FEB.2021 16:54:48

11N40MIMO_Ant2_2422




Date: 2.FEB.2021 17:08:33

11N40MIMO_Ant1_2437




Date: 2.FEB.2021 16:56:30

11N40MIMO_Ant2_2437




Date: 2.FEB.2021 17:10:27

11N40MIMO_Ant1_2452



Date: 2.FEB.2021 16:57:42

11N40MIMO_Ant2_2452



Date: 2.FEB.2021 17:11:53

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.


The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.


The test plots are attached as below.

SISO Mode, Ant1


802.11b

Channel 01 (2412MHz) Reference Level: 4.40dBm






Channel 06 (2437MHz) Reference Level: 4.59dBm




Channel 11 (2462MHz) Reference Level: 3.43dBm

11b 2462 Ant1 0-Reference




Date: 2.FEB.2021 16:13:28

11b 2462 Ant1 1-2400




Date: 2.FEB.2021 16:13:32


11b 2462 Ant1 2483.5-25000



Date: 2.FEB.2021 16:13:39




11g_2412_Ant1_0~Reference




Date: 2.FEB.2021 16:15:52

11g_2412_Ant1_1~2400




Date: 2.FEB.2021 16:15:56



11g_2412_Ant1_2483.5~25000




Date: 2.FEB.2021 16:16:03





Channel 06 (2437MHz) Reference Level: 0.60dBm






Channel 11 (2462MHz) Reference Level: 0.26dBm




11g 2462_Ant1 2483.5~25000




Date: 2 FEB 2021 16:20:11


11b High 2462



Date: 2 FEB 2021 16:19:48




11N20SISO_Ant1_Low_2412



Date: 2.FEB.2021 16:22:02


Channel 06 (2437MHz) Reference Level: -0.11dBm

11N20SISO_Ant1_2437_0-Reference




Date: 2.FEB.2021 16:23:48

11N20SISO_Ant1_2437_1-2400



Date: 2.FEB.2021 16:23:53


11N20SISO_Ant1_2437_2483.5-25000



Date: 2.FEB.2021 16:23:59


Channel 11 (2462MHz) Reference Level: -0.70dBm

11N20SISO_Ant1_2462_0-Reference




Date: 2.FEB.2021 16:26:08

11N20SISO_Ant1_2462_1-2400




Date: 2.FEB.2021 16:26:12

11N20SISO_Ant1_2462_2483.5-25000




Date: 2.FEB.2021 16:26:19

11N20SISO_Ant1_High_2462




Date: 2.FEB.2021 16:25:58

11N40SISO_Ant1_2422_0~Reference




Date: 2 FEB 2021 16:30:05

11N40SISO_Ant1_2422_1~2400




Date: 2 FEB 2021 16:30:09

11N40SISO_Ant1_2422_2483.5~25000



Date: 2 FEB 2021 16:30:16


11N40SISO_Ant1_Low_2422



Date: 2.FEB.2021 16:29:55


Channel 06 (2437MHz) Reference Level: -3.27dBm

11N40SISO_Ant1_2437_0-Reference




Date: 2.FEB.2021 16:31:48

11N40SISO_Ant1_2437_1~2400



Date: 2.FEB.2021 16:31:52


11N40SISO_Ant1_2437_2483.5-25000



Date: 2.FEB.2021 16:31:59


Channel 11 (2452MHz) Reference Level: -3.46dBm

11N40SISO_Ant1_2452_0-Reference




Date: 2.FEB.2021 16:33:51

11N40SISO_Ant1_2452_1-2400




Date: 2.FEB.2021 16:33:56

11N40SISO_Ant1_2452_2483.5-25000




Date: 2 FEB 2021 16:34:02

11N40SISO_Ant1_High_2452




Date: 2 FEB 2021 16:33:38

11B Ant2 2412 0~Reference




Date: 2 FEB 2021 15:30:26

11B Ant2 2412 1~2400




Date: 2 FEB 2021 15:30:30

11B Ant2 2412 2483.5~25000



Date: 2 FEB 2021 15:30:37


11B_Ant2_Low_2412



Date: 2 FEB 2021 15:30:15


Channel 06 (2437MHz) Reference Level: 1.77dBm

11B_Ant2_2437_0~Reference




Date: 2 FEB 2021 15:31:36

11B_Ant2_2437_1~2400




Date: 2 FEB 2021 15:31:40

11B_Ant2_2437_2483.5~25000




Channel 11 (2462MHz) Reference Level: 1.34dBm


11B_Ant2_2462_0~Reference



11B_Ant2_2462_1~2400




11B_Ant2_2462_2483.5~25000




Date: 2 FEB 2021 15:34:00


11B_Ant2_High_2462



Date: 2 FEB 2021 15:33:34




11G_Ant2_Low_2412



Date: 2 FEB 2021 15:36:55


Channel 06 (2437MHz) Reference Level: -0.88dBm

11G_Ant2_2437_0-Reference




Date: 2 FEB 2021 15:39:12

11G_Ant2_2437_1~2400




Date: 2 FEB 2021 15:39:16

11G_Ant2_2437_2483.5~25000




Channel 11 (2462MHz) Reference Level: -1.34dBm


11G_Ant2_2462_0~Reference



11G_Ant2_2462_1~2400




11G_Ant2_2462_2483.5~25000




Date: 2 FEB 2021 15:41:46

11G_Ant2_High_2462




Date: 2 FEB 2021 15:41:24


11N20SISO_Ant2_2412_0~Reference




11N20SISO_Ant2_2412_1~2400



11N20SISO_Ant2_2412_2483.5~25000




11N20SISO_Ant2_Low_2412



Date: 2 FEB 2021 15:46:16


Channel 06 (2437MHz) Reference Level: -1.96dBm

11N20SISO_Ant2_2437_0-Reference




Date: 2 FEB 2021 15:48:36

11N20SISO_Ant2_2437_1-2400




Date: 2 FEB 2021 15:48:40

11N20SISO_Ant2_2437_2483.5~25000




Channel 11 (2462MHz) Reference Level: -2.35dBm


11N20SISO_Ant2_2462_0~Reference



11N20SISO_Ant2_2462_1~2400




11N20SISO_Ant2_2462_2483.5-25000




Date: 2 FEB 2021 15:50:51

11N20SISO_Ant2_High_2462




Date: 2 FEB 2021 15:50:29


11N40SISO_Ant2_2422_0~Reference




11N40SISO_Ant2_2422_1~2400



11N40SISO_Ant2_2422_2483.5~25000




11N40SISO_Ant2_Low_2422



Date: 2.FEB.2021 15:53:52


Channel 06 (2437MHz) Reference Level: -5.21dBm

11N40SISO_Ant2_2437_0-Reference




Date: 2.FEB.2021 15:55:43

11N40SISO_Ant2_2437_1-2400



Date: 2.FEB.2021 15:55:47


11N40SISO_Ant2_2437_2483.5-25000



Date: 2.FEB.2021 15:55:54


Channel 11 (2452MHz) Reference Level: -4.79dBm

11N40SISO_Ant2_2452_0-Reference




Date: 2.FEB.2021 15:59:28

11N40SISO_Ant2_2452_1-2400




Date: 2.FEB.2021 15:59:33

11N40SISO_Ant2_2452_2483.5~25000



Date: 2 FEB 2021 15:59:39

11N40SISO_Ant2_High_2452




Date: 2 FEB 2021 15:59:17

MIMO Mode ANT1:

802.11n-HT20


Channel 01 (2412MHz) Reference Level: -0.28dBm

11N20MIMO_Ant1_2412_0~Reference




Date: 2 FEB 2021 16:47:04

11N20MIMO_Ant1_2412_1~2400




Date: 2 FEB 2021 16:47:08

11N20MIMO_Ant1_2412_2483.5~25000



Date: 2 FEB 2021 16:47:15


11N20MIMO_Ant1_Low 2412



Date: 2 FEB 2021 16:46:52


Channel 06 (2437MHz) Reference Level: -0.04dBm

11N20MIMO_Ant1 2437 0~Reference




Date: 2 FEB 2021 16:51:23

11N20MIMO_Ant1 2437 1~2400



Date: 2 FEB 2021 16:51:27


11N20MIMO Ant1 2437 2483.5~25000



Date: 2.FEB.2021 16:51:34


Channel 11 (2462MHz) Reference Level: -0.45dBm

11N20MIMO Ant1 2462 0~Reference




Date: 2.FEB.2021 16:52:58

11N20MIMO Ant1 2462 1~2400




Date: 2.FEB.2021 16:53:02

11N20MIMO Ant1 2462 2483.5~25000




Date: 2.FEB.2021 16:53:09

11N20MIMO Ant1 High 2462




Date: 2.FEB.2021 16:52:46


11N40MIMO_Ant1_2422_0~Reference




11N40MIMO_Ant1_2422_1~2400



11N40MIMO_Ant1_2422_2483.5~25000




11N40MIMO_Ant1_Low 2422



Date: 2.FEB.2021 16:55:05


Channel 06 (2437MHz) Reference Level: -3.48dBm

11N40MIMO_Ant1 2437 0~Reference




Date: 2.FEB.2021 16:56:41

11N40MIMO_Ant1 2437 1~2400




Date: 2.FEB.2021 16:56:45

11N40MIMO Ant1 2437 2483.5~25000




Channel 11 (2452MHz) Reference Level: -3.09dBm


11N40MIMO Ant1 2452 0~Reference



11N40MIMO Ant1 2452 1~2400




11N40MIMO Ant1 2452 2483.5-25000



Date: 2 FEB 2021 16:58:20

11N40MIMO Ant1 High 2452




Date: 2 FEB 2021 16:57:59

MIMO Mode, Ant2:

802.11n-HT20


Channel 01 (2412MHz) Reference Level: -0.80dBm

11N20MIMO Ant2 2412_0~Reference




Date: 2 FEB 2021 17:03:05

11N20MIMO Ant2 2412_1~2400




Date: 2 FEB 2021 17:03:10

11N20MIMO Ant2 2412_2483.5~25000



Date: 2 FEB 2021 17:03:16


11N20MIMO_Ant2_Low_2412



Date: 2.FEB.2021 17:02:55


Channel 06 (2437MHz) Reference Level: -1.18dBm

11N20MIMO_Ant2_2437_0-Reference




Date: 2.FEB.2021 17:04:45

11N20MIMO_Ant2_2437_1-2400



Date: 2.FEB.2021 17:04:49


11N20MIMO Ant2 2437 2483.5~25000



Date: 2.FEB.2021 17:04:56


Channel 11 (2462MHz) Reference Level: -1.68dBm

11N20MIMO Ant2 2462 0~Reference




Date: 2.FEB.2021 17:06:59

11N20MIMO Ant2 2462 1~2400




Date: 2.FEB.2021 17:07:03

11N20MIMO Ant2_2462_2483.5~25000




Date: 2.FEB.2021 17:07:10

11N20MIMO Ant1_High_2462




Date: 2.FEB.2021 16:52:46


11N40MIMO_Ant2_2422_0~Reference




11N40MIMO_Ant2_2422_1~2400



11N40MIMO_Ant2_2422_2483.5~25000




11N40MIMO_Ant2_Low_2422



Date: 2.FEB.2021 17:08:49


Channel 06 (2437MHz) Reference Level: -4.40dBm

11N40MIMO_Ant2_2437_0-Reference




Date: 2.FEB.2021 17:10:37

11N40MIMO_Ant2_2437_1-2400




Date: 2.FEB.2021 17:10:42

11N40MIMO Ant2 2437 2483.5~25000




Channel 11 (2452MHz) Reference Level: -4.23dBm


11N40MIMO Ant2 2452 0~Reference



11N40MIMO Ant2 2452 1~2400




11N40MIMO Ant2 2452 2483.5-25000



Date: 2 FEB 2021 17:12:31

11N40MIMO Ant2 High 2452



Date: 2 FEB 2021 17:12:09

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental

☐ See attached data sheet

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission
at 742.520000MHz
is passed by 3.3dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf. Simultaneous transmission was considered during the test, only the worst case data is recorded in this report.

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021


Worst Case Operating Mode:

Model: ECHKIN215-3288

Simultaneous transmission

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
374.960000	36.0	1000.0	120.000	H	17.8	10.0	46.0
742.520000	42.7	1000.0	120.000	H	25.4	3.3	46.0
888.080000	39.6	1000.0	120.000	H	26.6	6.4	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Limit Line (dBuV/m) - Level (dBuV/m)

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021


Worst Case Operating Mode:

Model: ECHKIN215-3288

Simultaneous transmission

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
33.977000	32.4	1000.0	120.000	V	15.9	7.6	40.0
396.013333	36.0	1000.0	120.000	V	19.2	10.0	46.0
742.520000	42.2	1000.0	120.000	V	25.4	3.8	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) - Level (dBμV/m)

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

Radiated Emissions (above 1GHz)

Worst Case Operating Mode: SISO-ANT1-Transmitting (802.11b-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	63.3	36.8	33.5	60.0	74.0	-14.0
Horizontal	*2390.000	68.2	36.4	29.1	60.9	74.0	-13.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	49.2	36.8	33.5	45.9	54.0	-8.1
Horizontal	*2390.000	56.5	36.4	29.1	49.2	54.0	-4.8

Worst Case Operating Mode: SISO-ANT1-Transmitting (802.11b-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	62.2	36.7	33.4	58.9	74.0	-15.1
Horizontal	*7311.000	60.0	36.6	35.8	59.2	74.0	-14.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	46.5	36.7	33.4	43.2	54.0	-10.8
Horizontal	*7311.000	47.2	36.6	35.8	46.4	54.0	-7.6

Worst Case Operating Mode: SISO-ANT1-Transmitting (802.11b-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	64.7	36.8	33.3	61.2	74.0	-12.8
Horizontal	*7386.000	67.7	36.5	29.3	60.5	74.0	-13.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	49.8	36.8	33.3	46.3	54.0	-7.7
Horizontal	*7386.000	52.4	36.5	29.3	45.2	54.0	-8.8

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11g-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	64.0	36.8	33.5	60.7	74.0	-13.3
Horizontal	*2390.000	67.2	36.4	29.1	59.9	74.0	-14.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	49.8	36.8	33.5	46.5	54.0	-7.5
Horizontal	*2390.000	54.5	36.4	29.1	47.2	54.0	-6.8

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11g-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	63.8	36.7	33.4	60.5	74.0	-13.5
Horizontal	*7311.000	58.4	36.6	35.8	57.6	74.0	-16.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	47.8	36.7	33.4	44.5	54.0	-9.5
Horizontal	*7311.000	47.0	36.6	35.8	46.2	54.0	-7.8

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11g-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	65.3	36.8	33.3	61.8	74.0	-12.2
Horizontal	*7386.000	67.9	36.5	29.3	60.7	74.0	-13.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	50.2	36.8	33.3	46.7	54.0	-7.3
Horizontal	*7386.000	54.3	36.5	29.3	47.1	54.0	-6.9

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11n20-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	61.0	36.8	33.5	57.7	74.0	-16.3
Horizontal	*2390.000	66.2	36.4	29.1	58.9	74.0	-15.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	50.9	36.8	33.5	47.6	54.0	-6.4
Horizontal	*2390.000	52.6	36.4	29.1	45.3	54.0	-8.7

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11n20-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	63.3	36.7	33.4	60.0	74.0	-14.0
Horizontal	*7311.000	62.0	36.6	35.8	61.2	74.0	-12.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	49.5	36.7	33.4	46.2	54.0	-7.8
Horizontal	*7311.000	46.6	36.6	35.8	45.8	54.0	-8.2

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11n20-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	64.3	36.8	33.3	60.8	74.0	-13.2
Horizontal	*7386.000	67.4	36.5	29.3	60.2	74.0	-13.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	49.1	36.8	33.3	45.6	54.0	-8.4
Horizontal	*7386.000	51.6	36.5	29.3	44.4	54.0	-9.6

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11n40-Channel 03)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	62.2	36.8	33.5	58.9	74.0	-15.1
Horizontal	*2390.000	65.1	36.4	29.1	57.8	74.0	-16.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	45.4	36.8	33.5	42.1	54.0	-11.9
Horizontal	*2390.000	52.1	36.4	29.1	44.8	54.0	-9.2

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11n40-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	61.8	36.7	33.4	58.5	74.0	-15.5
Horizontal	*7311.000	60.3	36.6	35.8	59.5	74.0	-14.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	48.6	36.7	33.4	45.3	54.0	-8.7
Horizontal	*7311.000	46.5	36.6	35.8	45.7	54.0	-8.3

Worst Case Operating Mode:

SISO-ANT1-Transmitting (802.11n40-Channel 09)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	63.9	36.8	33.3	60.4	74.0	-13.6
Horizontal	*7356.000	68.4	36.5	29.3	61.2	74.0	-12.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	49.2	36.8	33.3	45.7	54.0	-8.3
Horizontal	*7356.000	53.7	36.5	29.3	46.5	54.0	-7.5

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11b-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	58.7	36.8	33.5	55.4	74.0	-18.6
Horizontal	*2390.000	60.6	36.4	29.1	53.3	74.0	-20.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	46.5	36.8	33.5	43.2	54.0	-10.8
Horizontal	*2390.000	51.8	36.4	29.1	44.5	54.0	-9.5

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11b-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	59.9	36.7	33.4	56.6	74.0	-17.4
Horizontal	*7311.000	58.3	36.6	35.8	57.5	74.0	-16.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	48.9	36.7	33.4	45.6	54.0	-8.4
Horizontal	*7311.000	46.9	36.6	35.8	46.1	54.0	-7.9

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11b-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	57.8	36.8	33.3	54.3	74.0	-19.7
Horizontal	*7386.000	62.2	36.5	29.3	55.0	74.0	-19.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	46.6	36.8	33.3	43.1	54.0	-10.9
Horizontal	*7386.000	51.7	36.5	29.3	44.5	54.0	-9.5

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11g-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	58.7	36.8	33.5	55.4	74.0	-18.6
Horizontal	*2390.000	63.6	36.4	29.1	56.3	74.0	-17.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	47.6	36.8	33.5	44.3	54.0	-9.7
Horizontal	*2390.000	52.3	36.4	29.1	45.0	54.0	-9.0

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11g-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	62.1	36.7	33.4	58.8	74.0	-15.2
Horizontal	*7311.000	60.0	36.6	35.8	59.2	74.0	-14.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	48.5	36.7	33.4	45.2	54.0	-8.8
Horizontal	*7311.000	47.2	36.6	35.8	46.4	54.0	-7.6

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11g-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	62.8	36.8	33.3	59.3	74.0	-14.7
Horizontal	*7386.000	67.3	36.5	29.3	60.1	74.0	-13.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	50.8	36.8	33.3	47.3	54.0	-6.7
Horizontal	*7386.000	55.3	36.5	29.3	48.1	54.0	-5.9

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11n20-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	61.7	36.8	33.5	58.4	74.0	-15.6
Horizontal	*2390.000	67.2	36.4	29.1	59.9	74.0	-14.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	48.5	36.8	33.5	45.2	54.0	-8.8
Horizontal	*2390.000	54.8	36.4	29.1	47.5	54.0	-6.5

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11n20-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	63.6	36.7	33.4	60.3	74.0	-13.7
Horizontal	*7311.000	62.1	36.6	35.8	61.3	74.0	-12.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	49.8	36.7	33.4	46.5	54.0	-7.5
Horizontal	*7311.000	49.2	36.6	35.8	48.4	54.0	-5.6

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11n20-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	63.7	36.8	33.3	60.2	74.0	-13.8
Horizontal	*7386.000	68.1	36.5	29.3	60.9	74.0	-13.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	48.7	36.8	33.3	45.2	54.0	-8.8
Horizontal	*7386.000	54.7	36.5	29.3	47.5	54.0	-6.5

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11n40-Channel 03)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	61.5	36.8	33.5	58.2	74.0	-15.8
Horizontal	*2390.000	66.2	36.4	29.1	58.9	74.0	-15.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	47.6	36.8	33.5	44.3	54.0	-9.7
Horizontal	*2390.000	52.6	36.4	29.1	45.3	54.0	-8.7

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11n40-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	60.0	36.7	33.4	56.7	74.0	-17.3
Horizontal	*7311.000	54.2	36.6	35.8	53.4	74.0	-20.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	46.8	36.7	33.4	43.5	54.0	-10.5
Horizontal	*7311.000	45.9	36.6	35.8	45.1	54.0	-8.9

Worst Case Operating Mode:

SISO-ANT2-Transmitting (802.11n40-Channel 09)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	61.1	36.8	33.3	57.6	74.0	-16.4
Horizontal	*7356.000	60.4	36.5	29.3	53.2	74.0	-20.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	47.7	36.8	33.3	44.2	54.0	-9.8
Horizontal	*7356.000	49.3	36.5	29.3	42.1	54.0	-11.9

Worst Case Operating Mode:
MIMO-Transmitting (802.11n20-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	64.1	36.8	33.5	60.8	74.0	-13.2
Horizontal	*2390.000	64.8	36.4	29.1	57.5	74.0	-16.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	46.5	36.8	33.5	43.2	54.0	-10.8
Horizontal	*2390.000	51.8	36.4	29.1	44.5	54.0	-9.5

Worst Case Operating Mode:
MIMO-Transmitting (802.11n20-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	64.6	36.7	33.4	61.3	74.0	-12.7
Horizontal	*7311.000	61.0	36.6	35.8	60.2	74.0	-13.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	47.6	36.7	33.4	44.3	54.0	-9.7
Horizontal	*7311.000	48.3	36.6	35.8	47.5	54.0	-6.5

Worst Case Operating Mode:
MIMO-Transmitting (802.11n20-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	64.6	36.8	33.3	61.1	74.0	-12.9
Horizontal	*7386.000	65.7	36.5	29.3	58.5	74.0	-15.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	49.1	36.8	33.3	45.6	54.0	-8.4
Horizontal	*7386.000	55.5	36.5	29.3	48.3	54.0	-5.7

Worst Case Operating Mode:
MIMO-Transmitting (802.11n40-Channel 03)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	60.0	36.8	33.5	56.7	74.0	-17.3
Horizontal	*2390.000	65.2	36.4	29.1	57.9	74.0	-16.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4844.000	48.7	36.8	33.5	45.4	54.0	-8.6
Horizontal	*2390.000	53.7	36.4	29.1	46.4	54.0	-7.6

Worst Case Operating Mode:
MIMO-Transmitting (802.11n40-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	63.6	36.7	33.4	60.3	74.0	-13.7
Horizontal	*7311.000	55.0	36.6	35.8	54.2	74.0	-19.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	43.7	36.7	33.4	40.4	54.0	-13.6
Horizontal	*7311.000	48.1	36.6	35.8	47.3	54.0	-6.7

Worst Case Operating Mode:
MIMO-Transmitting (802.11n40-Channel 09)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	63.9	36.8	33.3	60.4	74.0	-13.6
Horizontal	*7356.000	62.5	36.5	29.3	55.3	74.0	-18.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4904.000	49.9	36.8	33.3	46.4	54.0	-7.6
Horizontal	*7356.000	54.4	36.5	29.3	47.2	54.0	-6.8

NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Echelon Fitness Multimedia LLC
Date of Test: 16 January 2021
Model: ECHKIN215-3288

4.9 Conducted Emission

Simultaneous transmission was considered during the test, only the worst case data is recorded in this report.


Worst Case Conducted Emission
at 0.326000MHz
is passed by 15.1dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

Applicant: Echelon Fitness Multimedia LLC
Date of Test: 16 January 2021
Model: ECHKIN215-3288
Worst Case Operating Mode: Simultaneous transmission
Phase: Live

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.177000	43.6	9.000	L1	9.6	21.0	64.6
0.326000	39.9	9.000	L1	9.6	19.7	59.6
0.978000	33.1	9.000	L1	9.7	22.9	56.0
2.522000	35.4	9.000	L1	9.7	20.6	56.0
14.078000	15.5	9.000	L1	9.9	44.5	60.0
28.646000	25.4	9.000	L1	10.6	34.6	60.0


Limit and Margin AV

Frequency (MHz)	Average (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.177000	32.3	9.000	L1	9.6	22.3	54.6
0.326000	34.5	9.000	L1	9.6	15.1	49.6
0.978000	28.0	9.000	L1	9.7	18.0	46.0
2.522000	27.8	9.000	L1	9.7	18.2	46.0
14.078000	10.3	9.000	L1	9.9	39.7	50.0
28.646000	20.7	9.000	L1	10.6	29.3	50.0

Applicant: Echelon Fitness Multimedia LLC
Date of Test: 16 January 2021
Model: ECHKIN215-3288
Worst Case Operating Mode: Simultaneous transmission
Phase: Neutral

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.168000	47.0	9.000	N	9.6	18.1	65.1
0.194000	43.3	9.000	N	9.6	20.6	63.9
0.326000	38.0	9.000	N	9.6	21.6	59.6
0.534000	30.5	9.000	N	9.7	25.5	56.0
0.978000	32.6	9.000	N	9.7	23.4	56.0
2.634000	36.6	9.000	N	9.7	19.4	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.168000	33.1	9.000	N	9.6	22.0	55.1
0.194000	30.8	9.000	N	9.6	23.1	53.9
0.326000	32.3	9.000	N	9.6	17.3	49.6
0.534000	24.9	9.000	N	9.7	21.1	46.0
0.978000	27.8	9.000	N	9.7	18.2	46.0
2.634000	28.7	9.000	N	9.7	17.3	46.0

Applicant: Echelon Fitness Multimedia LLC

Date of Test: 16 February 2021

Model: ECHKIN215-3288

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part

☐ Test results are attached

☒ Included in the separated report.

Applicant: Echelon Fitness Multimedia LLC
Date of Test: 16 February 2021
Model: ECHKIN215-3288

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-13	Biconilog Antenna	ETS	3142E	00217919	2019-06-10	2021-06-10
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2019-05-24	2021-05-24
SZ061-08	Horn Antenna	ETS	3115	00092346	2019-09-07	2021-09-07
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	2019-08-13	2021-08-13
SZ056-03	Spectrum Analyzer	R&S	FSP30	101148	2020-05-27	2021-05-27
SZ185-01	EMI Receiver	R & S	ESCI	100547	2020-12-22	2021-12-22
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	2020-05-27	2021-05-27
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	2018-12-15	2021-12-15
SZ062-02	RF Cable	RADIAL	RG 213U	--	2020-12-01	2021-06-01
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	2020-12-01	2021-06-01
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	2020-12-01	2021-06-01
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	2020-05-27	2021-05-27
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2020-10-15	2021-10-15
SZ187-01	Two-Line V-Network	R & S	ENV216	100072	2020-10-27	2021-10-27
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	2020-05-27	2021-05-27
SZ188-03	Shielding Room	ETS	RFD-100	4100	2018-12-15	2021-12-15
SZ062-16	RF Cable	HUBER+SUHNER	CBL2-BN-1m	110127-2231000	2020-10-15	2021-10-15

***** End of Report *****