



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

客戶名稱 : **LG 17Z90TP**
CUSTOMER

Document No.: _____
Approval Sheet Rev.: **P2**
Spec. Rev. : **P1**

承認書

APPROVAL SHEET

產品品名/Product Model No. : **WA-P-LBLB-04-112**

客戶料號/Customer No. : **EAA65985801**

專案名稱/Project Name: **17Z90TP**

發行日期/ Issue Date : **2023/09/20**

承認日期/ Approved Date : _____

Approved by customer: (signing or stamping here)



履历表

History List

[illegible]

4-2. Impedance

50 ohm nominal

4-3. Matching circuit

None

4-4. VSWR

4-4.1 Measuring Method

1.A 50Ωcoaxial cable is connected to the antenna. Then this cable is connected


to a network analyzer to measure the VSWR

2.Keeping this jig away from metal at least 20cm


4-4.2 Measurement frequency points and VSWR value

VSWR	Frequency (Unit MHz)	Spec	1
Main Antenna	2400	≤ 3.0	1.5
	2500	≤ 3.0	1.5
	5150	≤ 3.0	1.2
	7125	≤ 3.0	1.2
	Judgement		ok
Aux Antenna	2400	≤ 3.0	1.6
	2500	≤ 3.0	1.3
	5150	≤ 3.0	1.3
	7125	≤ 3.0	1.3
	Judgement		ok

Main Antenna-1



AUX Antenna-1



UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ±

X.X = ±

X.XX = ±

ANGLES = ±

HOLEDIA = ±



佳邦科技股份有限公司

AUX Antenna-1

INPAQ TECHNOLOGY CO., LTD.

SCALE :

UNIT : mm

DRAWN BY: 毕岩

CHECKED BY: 张涛

DESIGNED BY: 周振兴

APPROVED BY: 徐克文

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-P-LBLB-04-112 Specification

DOCUMENT
NO.

PAGE REV.
P1

4-5. Efficiency and Gain

4-5.1 Measuring equipment

Measuring instrument:


Microwave chamber, Network analyzer, and standard antenna.

Instructions for microwave chamber:

This is a microwave chamber set up by our company in Suzhou. This microwave chamber belongs to a set of near-field measurement system. The size of the chamber is 2.95M * 3M * 3M.



RayZone2800 Test Setup



The microwave chamber, shown above, using a unique multi-probe technique. The aim is to reduce the measurement time of the whole measurement system. The measuring system use multi-probe array instead of single probe to scan the measured surface of the antenna under test, a single probe has the capability of measuring orthogonal polarization amplitude and phase, it also has a wide frequency range, the corresponding multi-probe array is switched quickly by electronic switch, greatly improved the measurement efficiency.

The probe model: MA186960A(400MHz~7.5GHz) . Because of its capability of broadband frequency and the orthogonal polarization function, the number of probes needed to be equipped with the system is reduced; The small size of the probe reduces the coupling between the probes, make it is possible to insert probes of other frequency bands between probes, then a single system can support a wider frequency range

UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.	
X = ±	X.X = ±	X.XX = ±	
ANGLES = ±		HOLEDIA = ±	
SCALE :		UNIT : mm	
DRAWN BY: 毕岩		CHECKED BY: 张涛	
DESIGNED BY : 周振兴		APPROVED BY : 徐克文	
TITLE : WA-P-LBLB-04-112 Specification		DOCUMENT NO.	PAGE REV. P1

4-5.2 Efficiency and Gain

Antenna gain is marked (dBi) and is based on STANDARD HORN antenna. The data shows Peak Gain and Average Gain.

4-5-2-1 Electrical specification

Frequency (MHz)	Average Efficiency (%)
2400~2500	>30
5100~5900	>30
5925~7125	>30

4-5.2-2 Efficiency and Gain Test Data

Frequency (MHz)	Main Antenna-1			Aux Antenna-1		
	Efficiency (%)	Gain w/ cable loss (dBi)	Peak Gain w/ cable loss (dBi)	Efficiency (%)	Gain w/ cable loss (dBi)	Peak Gain w/ cable loss (dBi)
2.4GHz (2400~2500MHz)	37.9	-4.2	1.5	35.9	-4.5	2.7
5.2&5.3GHz (5150~5350MHz)	33.6	-4.7	1.6	36.9	-4.3	3
5.5GHz (5470~5725MHz)	30.4	-5.1	2.5	35.7	-4.4	1.3
5.8GHz (5725~5900MHz)	36.7	-4.3	2.5	36.2	-4.4	2.3
6.2GHz (5925~6425MHz)	31.2	-5.0	0.6	37.1	-4.2	2.4
6.5GHz (6425~6525MHz)	30.5	-5.1	3.1	36.3	-4.3	2.4
6.7GHz (6525~6875MHz)	30.6	-5.1	2.8	32.4	-4.8	1.6
6.9GHz (6875~7125MHz)	28.5	-5.4	2.7	30.6	-5.1	1.4

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

SCALE : UNIT : mm

DRAWN BY: 毕岩 CHECKED BY: 张涛

DESIGNED BY: 周振兴 APPROVED BY: 徐克文


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-P-LBLB-04-112 Specification

DOCUMENT NO.

PAGE REV.
P1

4-5.2-3 Antenna 3D Radiation Pattern




5. Mechanical Specification:

Connector: I-PEX MHF 4L: 20572; Cable: RF Cable 0.81 (Main Black/Aux Gray)


Cable length: Aux Antenna L: $324.5 \pm 2\text{mm}$ (Include connector)

Main Antenna L: $275.8 \pm 2\text{mm}$ (Include connector)



UNLESS OTHER SPECIFIED TOLERANCES ON :		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.
X = ±	X.X = ±	
ANGLES = ±	HOLEDIA = ±	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
DRAWN BY: 毕岩	CHECKED BY: 张涛	
DESIGNED BY: 周振兴	APPROVED BY: 徐克文	
TITLE : WA-P-LBLB-04-112 Specification		DOCUMENT NO.
		PAGE REV. P1

Mechanical Configuration:



Material list :

Item	Description	Material	Quantity
1	PCB	PCB T0.4 WA-P-LBLB-04-112	1
2	Acetate tape	Acetate tape 18x10mm, T0.12mm	1
3	Shrink Tube	Shrink Tube black, ϕ 1.5 x45mm	1
4	Shrink Tube	Shrink Tube black, ϕ 1.5 x8mm	1
5	Cable black	Cable 0.81 black	1
6	Cable gray	Cable 0.81 gray	1
7	Connector	I-PEX MHF 4L for 0.81, 20572	2
8	TAP	TAP 3M467 74x4mm	1
9	Clamp	Clamp 0.81 5mm	2

6. UL File No:

ITEM	DESCRIPTION	SUPPLIER	UL File No
1	PCB	HA0129	E202191
2	CABLE	HA0008	E318898
		HA0053	E464731

UNLESS OTHER SPECIFIED TOLERANCES ON :

$$X = \pm \quad X.X = \pm \quad X.XX = \pm$$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE :	UNIT : mm
---------	-----------

DRAWN BY: 毕岩	CHECKED BY: 张涛
--------------	----------------

DESIGNED BY : 周振兴	APPROVED BY : 徐克文
-------------------	-------------------

TITLE : WA-P-LBLB-04-112 Specification



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT NO.

PAGE	REV.
P1	