



RADIO TEST REPORT

Report No.:STS2006043W01

Issued for

SIMCom Wireless Solutions Limited

No.633, Jinzhong Road, Shanghai, China

Product Name:	LTE/GNSS MODULE
Brand Name:	SIMCom
Model Name:	SIM7600G-H
Series Model:	SIM7600G-H miniPCIE
FCC ID:	2AJYU-8PYA007
Test Standard:	47 CFR Part 2, 22(H), 24(E), 27, 90

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.



**TEST RESULT CERTIFICATION**

Applicant's Name: SIMCom Wireless Solutions Limited
Address: No.633, Jinzhong Road, Shanghai, China
Manufacture's Name: SIMCom Wireless Solutions Limited
Address: No.633, Jinzhong Road, Shanghai, China
Product Description
Product Name: LTE/GNSS MODULE
Brand Name: SIMCom
Model Name: SIM7600G-H
Series Model: SIM7600G-H miniPCIE
Test Standards.....: 47 CFR Part 2, 22(H), 24(E), 27, 90
Test Procedure: KDB 971168 D01 v03r01, ANSI C63.26 2015

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test.....:
Date of receipt of test item.....: 16 June 2020
Date (s) of performance of tests.: 16 June 2020 ~ 12 Aug. 2020
Date of Issue: 12 Aug. 2020
Test Result: Pass

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)


Authorized Signatory :

(Vita Li)





Table of Contents	Page
1. TEST FACTORY & MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
3. CONDUCTED OUTPUT POWER	17
4. PEAK-TO-AVERAGE RATIO	41
5. RADIATED POWER AND EFFECTIVE ISOTROPIC RADIATED POWER	44
6. OCCUPIED BANDWIDTH	68
7. CONDUCTED BAND EDGE	72
8. CONDUCTED SPURIOUS EMISSION	74
9. RADIATED SPURIOUS EMISSION	75
10. FREQUENCY STABILITY	122
APPENDIX-PHOTOS OF TEST SETUP	133



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	12 Aug. 2020	STS2006043W01	ALL	Initial Issue





1. TEST FACTORY & MEASUREMENT UNCERTAINTY

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 30-1GHz	$\pm 5.6\text{dB}$
4	All emissions, radiated 1G-6GHz	$\pm 5.5\text{dB}$
5	All emissions, radiated >6G	$\pm 5.8\text{dB}$
6	Conducted Emission (9KHz-150KHz)	$\pm 3.37\text{dB}$
7	Conducted Emission (150KHz-30MHz)	$\pm 3.83\text{dB}$



2. GENERAL INFORMATION

2.1 TECHNICAL SPECIFICATIONS AND REGULATIONS

2.1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Name:	LTE/GNSS MODULE
Trade Name	SIMCom
Model Name	SIM7600G-H
Series Model	SIM7600G-H miniPCIE
Model Difference	Only different in model name and appearance.
Frequency Bands:	U.S. Bands: LTE FDD Band 2 LTE FDD Band 4 LTE FDD Band 5 LTE FDD Band 12 LTE FDD Band 13 LTE FDD Band 25 LTE FDD Band 26 LTE TDD Band 41 LTE FDD Band 66
SIM CARD:	Only support single SIM Card.
Antenna:	Dipole
Antenna gain:	Band2:1.87dBi, Band4:3.12dBi, Band5:0.91dBi, Band12:0.95dBi, Band13:2.23dBi, Band25:1.87dBi, Band26:0.91dBi, Band41:2.90dBi, Band66:3.12dBi
Power Rating:	Input: 3.8V
Extreme Vol. Limits:	3.3V to 4.2V (Nominal 3.8V)
Extreme Temp. Tolerance:	-40℃ to +85℃
Hardware version number:	V2.02
Software version number:	SIM7600M22_V2.0



2.1.2 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Product Specification Subjective To This Standard	
Tx Frequency	LTE Band 2:1850~1910MHz LTE Band 4:1710~1755MHz LTE Band 5:824~849MHz LTE Band 12:699~716MHz LTE Band 13:777~787MHz LTE Band 25:1850~1915MHz LTE Band 26:814~849MHz LTE Band 41:2496~2690MHz LTE Band 66:1710~1780MHz
Rx Frequency	LTE Band 2:1930 ~1990MHz LTE Band 4:2110~2155MHz LTE Band 5:869~894MHz LTE Band 12:729~746MHz LTE Band 13:746~756MHz LTE Band 25:1930~1995MHz LTE Band 26:859~894MHz LTE Band 41:2496~2690MHz LTE Band 66:2110~2200MHz
Bandwidth	LTE Band 2: 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz /20MHz LTE Band 4: 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz /20MHz LTE Band 5: 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 12: 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 13: 5MHz / 10MHz LTE Band 25: 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz /20MHz LTE Band 26: 1.4MHz / 3MHz / 5MHz / 10MHz/15MHz LTE Band 41: 5MHz / 10MHz / 15MHz /20MHz LTE Band 66: 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz /20MHz
Maximum Output Power	LTE Band 2: 23.20 dBm LTE Band 4: 23.67 dBm LTE Band 5: 25.30 dBm LTE Band 12: 24.35 dBm LTE Band 13: 22.06 dBm LTE Band 25: 23.46 dBm LTE Band 26: 24.16 dBm LTE Band 41: 23.16 dBm LTE Band 66: 23.08 dBm
Type of Modulation	QPSK /16QAM

RF Function	Band	UE Category UL	Modulation	Power Class	Ant Gain(dBi)	Ant Type	SIM Card
LTE	FDD:B2,B4, B5, B12,B13,B25,B26, B66	4	QPSK, 16QAM	3	B2:1.87 B4:3.12 B5:0.91 B12:0.95 B13:2.23 B25:1.87 B26:0.91 B41:2.9 B66:3.12	Dipole	1 SIM 1 is used to tested.
	TDD:B41						



2.1.3 EMISSION DESIGNATOR

LTE Band 2	Emission Designator	Emission Designator
BW(MHz)	(99%OBW)QPSK	(99%OBW)16QAM
1.4	1M10G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M52G7D	4M53W7D
10	8M93G7D	8M92W7D
15	13M4G7D	13M4W7D
20	17M9G7D	17M9W7D
LTE Band 4	Emission Designator	Emission Designator
BW(MHz)	(99%OBW)QPSK	(99%OBW)16QAM
1.4	1M10G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M52G7D	4M53W7D
10	8M93G7D	8M93W7D
15	13M4G7D	13M5W7D
20	17M9G7D	17M9W7D
LTE Band 5	Emission Designator	Emission Designator
BW(MHz)	(99%OBW)QPSK	(99%OBW)16QAM
1.4	1M11G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M51G7D	4M53W7D
10	8M91G7D	8M92W7D
LTE Band 12	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
1.4	1M11G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M52G7D	4M53W7D
10	8M95G7D	8M94W7D
LTE Band 13	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
5	4M53G7D	4M53W7D
10	8M97G7D	8M95W7D
LTE Band 25	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
1.4	1M10G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M53G7D	4M53W7D
10	8M91G7D	8M92W7D
15	13M4G7D	13M4W7D
20	17M8G7D	17M8W7D
LTE Band 26 (Part 22)	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
1.4	1M11G7D	1M10W7D
3	2M68G7D	2M68W7D
5	4M51G7D	4M53W7D
10	8M92G7D	8M92W7D
15	13M4G7D	13M5W7D



LTE Band 26 (Part 90)	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
1.4	1M10G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M53G7D	4M53W7D
10	8M92G7D	8M93W7D
LTE Band 41	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
5	4M52G7D	4M51W7D
10	8M94G7D	8M94W7D
15	13M5G7D	13M5W7D
20	17M9G7D	17M9W7D
LTE Band 66	Emission Designator	Emission Designator
BW(MHz)	(99% BW)QPSK	(99% BW)16QAM
1.4	1M11G7D	1M10W7D
3	2M69G7D	2M68W7D
5	4M52G7D	4M53W7D
10	8M93G7D	8M93W7D
15	13M4G7D	13M4W7D
20	17M9G7D	19M9W7D



2.1.4 TEST CONFIGURATION OF EQUIPMENT UNDER TEST

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 v03r01 and ANSI C63.26 2015 Power Meas. License Digital Systems with maximum output power. Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Remark:

1. The mark 'v' means that this configuration is chosen for testing
2. The mark '-' means that this bandwidth is not supported.
3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated.

ITEMS	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v			v	v	v	v	v	v	v	v
	12	v	v	v	v			v	v	v	v	v	v	v	v
	13			v	v			v	v	v	v	v		v	
	25	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	26	v	v	v	v	v		v	v	v	v	v	v	v	v
	41			v	v	v	v	v	v	v	v	v	v	v	v
	66	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak&Avera Ratio	2						v	v	v	v		v	v	v	v
	4						v	v	v	v		v	v	v	v
	5				v			v	v	v		v	v	v	v
	12				v			v	v	v		v	v	v	v
	13				v			v	v	v		v		v	
	25						v	v	v	v		v	v	v	v
	26					v		v	v	v		v	v	v	v
	41						v	v	v	v		v	v	v	v
	66						v	v	v	v		v	v	v	v
26dB&99% Bandwidth	2	v	v	v	v	v	v	v	v			v	v	v	v
	4	v	v	v	v	v	v	v	v			v	v	v	v
	5	v	v	v	v			v	v			v	v	v	v
	12	v	v	v	v			v	v			v	v	v	v
	13			v	v			v	v			v		v	
	25	v	v	v	v	v	v	v	v			v	v	v	v
	26	v	v	v	v	v		v	v			v	v	v	v
	41			v	v	v	v	v	v			v	v	v	v
	66	v	v	v	v	v	v	v	v			v	v	v	v



Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v			v	v	v		v	v	v	v
	12	v	v	v	v			v	v	v		v	v	v	v
	13			v	v			v	v	v		v		v	
	25	v	v	v	v	v	v	v	v	v		v	v	v	v
	26	v	v	v	v	v		v	v	v		v	v	v	v
	41			v	v	v	v	v	v	v		v	v	v	v
	66	v	v	v	v	v	v	v	v	v		v	v	v	v
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v	v			v	v	v
	4	v	v	v	v	v	v	v	v	v			v	v	v
	5	v	v	v	v			v	v	v			v	v	v
	12	v	v	v	v			v	v	v			v	v	v
	13			v	v			v	v	v				v	
	25	v	v	v	v	v	v	v	v	v			v	v	v
	26	v	v	v	v	v		v	v	v			v	v	v
	41			v	v	v	v	v	v	v			v	v	v
	66	v	v	v	v	v	v	v	v	v			v	v	v
Frequency Stability	2				v			v				v		v	
	4				v			v				v		v	
	5				v			v				v		v	
	12				v			v				v		v	
	13				v			v				v		v	
	25				v			v				v		v	
	26				v			v				v		v	
	41				v			v				v		v	
	66				v			v				v		v	
E.R.P.& E.I.R.P.	2	v	v	v	v	v	v	v	v	v			v	v	v
	4	v	v	v	v	v	v	v	v	v			v	v	v
	5	v	v	v	v			v	v	v			v	v	v
	12	v	v	v	v			v	v	v			v	v	v
	13			v	v			v	v	v				v	
	25	v	v	v	v	v	v	v	v	v			v	v	v
	26	v	v	v	v	v		v	v	v			v	v	v
	41			v	v	v	v	v	v	v			v	v	v
	66	v	v	v	v	v	v	v	v	v			v	v	v



Radiated Spurious Emission	2	v	v	v	v	v	v	v		v			v	v	v
	4	v	v	v	v	v	v	v		v			v	v	v
	5	v	v	v	v			v		v			v	v	v
	12	v	v	v	v			v		v			v	v	v
	13			v	v			v		v				v	
	25	v	v	v	v	v	v	v		v			v	v	v
	26	v	v	v	v	v		v		v			v	v	v
	41			v	v	v	v	v		v			v	v	v
	66	v	v	v	v	v	v	v		v			v	v	v





2.1.5 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for filing to comply with the 47 CFR Part 2, 22(H), 24(E), 27, 90.

2.1.6 SPECIAL ACCESSORIES


The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with eut intended for fcc grant together.

2.1.7 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.1.8 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.





2.1.9 CONFIGURATION OF EUT SYSTEM

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

E-1
EUT

Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.1.10 MEASUREMENT INSTRUMENTS

The radiated emission testing was performed according to the procedures of ANSI C63.26 2015 and FCC CFR 47 rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2019.10.09	2020.10.08
Signal Analyzer	Agilent	N9020A	MY51110105	2020.03.05	2021.03.04
Signal generator	Agilent	83752A	3610A02740	2019.10.09	2020.10.08
Wireless Communications Test Set	R&S	CMW 500	133884	2020.03.05	2021.03.04
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.01
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18
Bilog Antenna	TESEQ	CBL6111D	45873	2018.10.26	2021.10.25
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-2014	2019.10.15	2022.10.14
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10
Pre-Amplifier (0.1M-3GHz)	EM	EM330	060665	2019.10.09	2020.10.08
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2019.10.12	2020.10.11
Pre-Amplifier (18G-40GHz)	SKET	LNPA-1840-50	SK2018101801	2019.10.12	2020.10.11
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Temperature & Humidity	HH660	Mieo	N/A	2019.10.17	2020.10.16
Test SW	BULUN	BL410-E/18.905			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Universal Radio communication tester	R&S	CMU200	119907	2020.10.11	2021.10.10
Wireless Communications Test Set	R&S	CMW 500	133884	2020.03.05	2021.03.04
Signal Analyzer	Agilent	N9020A	MY49100060	2019.10.09	2020.10.08
Temperature & Humidity	HH660	Mieo	N/A	2019.10.17	2020.10.16
Test SW	FARAD	LZ-RF /LzRf-3A3			



2.1.11 MEASUREMENT RESULTS EXPLANATION EXAMPLE

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF Cable Loss + Attenuator Factor.




3. CONDUCTED OUTPUT POWER

3.1 DESCRIPTION OF THE CONDUCTED OUTPUT POWER MEASUREMENT

3.1.1 MEASUREMENT METHOD

A system simulator was used to establish communication with the eut. Its parameters were set to force the eut transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.
Configuration follows KDB 971168 D01 v03r01.

3.1.2 TEST SETUP



3.1.3 TEST PROCEDURES

1. The transmitter output port was connected to system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest/middle/highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.1.4 TEST RESULTS

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.86	22.93	22.88
1.4	1	2		22.61	22.72	22.62
1.4	1	5		22.40	22.45	22.33
1.4	3	0		22.11	22.19	22.12
1.4	3	1		21.87	21.96	21.85
1.4	3	2		21.61	21.68	21.56
1.4	6	0		21.33	21.46	21.36
1.4	1	0	16-QAM	22.64	22.71	22.67
1.4	1	2		22.39	22.41	22.38
1.4	1	5		22.13	22.11	22.13
1.4	3	0		21.85	21.90	21.91
1.4	3	1		21.55	21.66	21.70
1.4	3	2		21.31	21.37	21.43
1.4	6	0		21.11	21.09	21.20
3	1	0	QPSK	23.07	23.01	22.96
3	1	7		22.86	22.79	22.74
3	1	14		22.58	22.55	22.54
3	8	0		22.33	22.30	22.27
3	8	4		22.11	22.08	22.05
3	8	7		21.87	21.78	21.77
3	15	0		21.64	21.56	21.47
3	1	0	16-QAM	22.85	22.71	22.69
3	1	7		22.65	22.44	22.40
3	1	14		22.40	22.17	22.16
3	8	0		22.19	21.95	21.94
3	8	4		21.94	21.66	21.66
3	8	7		21.66	21.39	21.45
3	15	0		21.42	21.12	21.15



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.77	22.92	22.83
5	1	12		22.55	22.68	22.57
5	1	24		22.34	22.47	22.29
5	12	0		22.07	22.17	22.08
5	12	6		21.79	21.88	21.86
5	12	11		21.57	21.59	21.63
5	25	0		21.35	21.31	21.42
5	1	0	16-QAM	22.49	22.67	22.57
5	1	12		22.27	22.39	22.36
5	1	24		21.98	22.12	22.10
5	12	0		21.77	21.84	21.82
5	12	6		21.55	21.62	21.56
5	12	11		21.27	21.33	21.26
5	25	0		21.01	21.11	21.03
10	1	0	QPSK	22.89	23.09	22.66
10	1	24		22.59	22.82	22.45
10	1	49		22.36	22.58	22.22
10	25	0		22.15	22.29	22.01
10	25	12		21.90	22.06	21.73
10	25	24		21.65	21.78	21.46
10	50	0		21.44	21.52	21.25
10	1	0	16-QAM	22.68	22.83	22.38
10	1	24		22.40	22.56	22.12
10	1	49		22.10	22.33	21.84
10	25	0		21.84	22.10	21.63
10	25	12		21.54	21.85	21.35
10	25	24		21.32	21.57	21.14
10	50	0		21.10	21.35	20.90



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.99	22.97	22.77
15	1	37		22.69	22.70	22.51
15	1	74		22.47	22.43	22.24
15	36	0		22.22	22.15	21.96
15	36	18		22.01	21.89	21.73
15	36	39		21.74	21.63	21.45
15	75	0		21.53	21.36	21.21
15	1	0	16-QAM	22.74	22.73	22.55
15	1	38		22.46	22.49	22.33
15	1	75		22.25	22.25	22.09
15	36	0		22.01	21.97	21.80
15	36	18		21.80	21.76	21.58
15	36	39		21.52	21.50	21.35
15	75	0		21.26	21.24	21.15
20	1	0	QPSK	23.18	23.20	23.16
20	1	49		22.91	22.98	22.95
20	1	99		22.62	22.76	22.66
20	50	0		22.37	22.52	22.38
20	50	24		22.09	22.29	22.14
20	50	49		21.80	22.00	21.90
20	100	0		21.50	21.78	21.65
20	1	0	16-QAM	22.88	22.93	22.87
20	1	49		22.62	22.68	22.63
20	1	99		22.36	22.43	22.42
20	50	0		22.12	22.20	22.15
20	50	24		21.87	21.92	21.94
20	50	49		21.58	21.64	21.73
20	100	0		21.35	21.42	21.53



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.41	23.36	23.42
1.4	1	2		23.17	23.13	23.20
1.4	1	5		22.89	22.87	22.94
1.4	3	0		22.62	22.57	22.71
1.4	3	1		22.36	22.33	22.45
1.4	3	2		22.14	22.05	22.16
1.4	6	0		21.93	21.82	21.92
1.4	1	0	16-QAM	23.20	23.09	23.16
1.4	1	2		22.93	22.86	22.91
1.4	1	5		22.67	22.59	22.67
1.4	3	0		22.39	22.36	22.41
1.4	3	1		22.16	22.12	22.12
1.4	3	2		21.93	21.91	21.87
1.4	6	0		21.70	21.65	21.57
3	1	0	QPSK	23.40	23.52	23.49
3	1	7		23.12	23.29	23.24
3	1	14		22.84	23.06	22.98
3	8	0		22.61	22.86	22.72
3	8	4		22.31	22.61	22.52
3	8	7		22.05	22.33	22.28
3	15	0		21.77	22.05	22.02
3	1	0	16-QAM	23.13	23.32	23.25
3	1	7		22.88	23.03	23.04
3	1	14		22.62	22.74	22.81
3	8	0		22.33	22.49	22.61
3	8	4		22.10	22.21	22.39
3	8	7		21.81	21.97	22.12
3	15	0		21.56	21.68	21.89



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.38	23.43	23.40
5	1	12		23.18	23.20	23.14
5	1	24		22.91	22.99	22.90
5	12	0		22.66	22.79	22.68
5	12	6		22.38	22.49	22.39
5	12	11		22.08	22.25	22.12
5	25	0		21.80	21.98	21.89
5	1	0	16-QAM	23.14	23.22	23.14
5	1	12		22.89	22.98	22.86
5	1	24		22.60	22.77	22.59
5	12	0		22.40	22.48	22.36
5	12	6		22.11	22.22	22.07
5	12	11		21.89	22.02	21.87
5	25	0		21.65	21.75	21.65
10	1	0	QPSK	23.49	23.44	23.33
10	1	24		23.23	23.22	23.10
10	1	49		22.95	22.99	22.84
10	25	0		22.67	22.70	22.60
10	25	12		22.40	22.45	22.34
10	25	24		22.16	22.15	22.13
10	50	0		21.94	21.95	21.85
10	1	0	16-QAM	23.20	23.15	23.11
10	1	24		22.94	22.86	22.83
10	1	49		22.72	22.62	22.58
10	25	0		22.46	22.37	22.37
10	25	12		22.23	22.07	22.13
10	25	24		22.03	21.85	21.92
10	50	0		21.79	21.56	21.70



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.42	23.19	23.39
15	1	37		23.18	22.90	23.16
15	1	74		22.94	22.65	22.88
15	36	0		22.70	22.40	22.60
15	36	18		22.48	22.18	22.32
15	36	39		22.21	21.93	22.11
15	75	0		21.93	21.72	21.90
15	1	0	16-QAM	23.15	22.95	23.18
15	1	38		22.89	22.66	22.93
15	1	75		22.69	22.38	22.69
15	36	0		22.45	22.10	22.45
15	36	18		22.18	21.81	22.18
15	36	39		21.94	21.59	21.97
15	75	0		21.73	21.32	21.73
20	1	0	QPSK	23.62	23.59	23.67
20	1	49		23.33	23.34	23.45
20	1	99		23.03	23.04	23.23
20	50	0		22.78	22.83	22.99
20	50	24		22.58	22.57	22.73
20	50	49		22.36	22.35	22.45
20	100	0		22.14	22.11	22.21
20	1	0	16-QAM	23.39	23.35	23.40
20	1	49		23.17	23.05	23.11
20	1	99		22.89	22.84	22.82
20	50	0		22.60	22.63	22.56
20	50	24		22.36	22.35	22.32
20	50	49		22.11	22.09	22.11
20	100	0		21.88	21.80	21.82



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.92	24.97	25.06
1.4	1	2		24.67	24.73	24.86
1.4	1	5		24.40	24.49	24.66
1.4	3	0		24.14	24.23	24.38
1.4	3	1		23.88	23.93	24.15
1.4	3	2		23.58	23.71	23.88
1.4	6	0		23.37	23.48	23.60
1.4	1	0	16-QAM	24.71	24.74	24.82
1.4	1	2		24.45	24.47	24.58
1.4	1	5		24.24	24.17	24.31
1.4	3	0		23.99	23.87	24.02
1.4	3	1		23.70	23.59	23.73
1.4	3	2		23.47	23.34	23.52
1.4	6	0		23.25	23.04	23.32
3	1	0	QPSK	24.76	25.11	25.06
3	1	7		24.54	24.83	24.76
3	1	14		24.29	24.58	24.48
3	8	0		24.01	24.30	24.26
3	8	4		23.80	24.09	24.06
3	8	7		23.51	23.88	23.78
3	15	0		23.21	23.66	23.48
3	1	0	16-QAM	24.52	24.81	24.81
3	1	7		24.29	24.56	24.57
3	1	14		24.08	24.35	24.33
3	8	0		23.79	24.06	24.11
3	8	4		23.50	23.83	23.84
3	8	7		23.20	23.61	23.55
3	15	0		23.00	23.33	23.32



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	25.04	24.99	25.18
5	1	12		24.77	24.71	24.90
5	1	24		24.51	24.47	24.60
5	12	0		24.29	24.27	24.37
5	12	6		24.05	24.06	24.15
5	12	11		23.77	23.83	23.94
5	25	0		23.50	23.58	23.70
5	1	0	16-QAM	24.79	24.76	24.97
5	1	12		24.51	24.49	24.68
5	1	24		24.30	24.24	24.39
5	12	0		24.07	23.95	24.16
5	12	6		23.83	23.68	23.92
5	12	11		23.59	23.42	23.71
5	25	0		23.34	23.20	23.43
10	1	0	QPSK	25.26	25.30	25.28
10	1	24		24.97	25.02	24.98
10	1	49		24.77	24.79	24.73
10	25	0		24.54	24.56	24.49
10	25	12		24.27	24.28	24.23
10	25	24		24.01	24.01	23.95
10	50	0		23.76	23.75	23.70
10	1	0	16-QAM	25.00	25.02	24.99
10	1	24		24.80	24.72	24.69
10	1	49		24.55	24.46	24.49
10	25	0		24.27	24.18	24.19
10	25	12		24.06	23.93	23.92
10	25	24		23.82	23.68	23.70
10	50	0		23.54	23.48	23.44



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.07	24.25	24.16
1.4	1	2		23.87	23.98	23.89
1.4	1	5		23.60	23.72	23.66
1.4	3	0		23.38	23.45	23.45
1.4	3	1		23.13	23.18	23.19
1.4	3	2		22.86	22.92	22.91
1.4	6	0		22.62	22.66	22.69
1.4	1	0	16-QAM	23.83	24.03	23.87
1.4	1	2		23.62	23.81	23.65
1.4	1	5		23.33	23.55	23.43
1.4	3	0		23.09	23.30	23.23
1.4	3	1		22.82	23.03	22.95
1.4	3	2		22.59	22.73	22.67
1.4	6	0		22.36	22.43	22.46
3	1	0	QPSK	23.85	23.92	24.01
3	1	7		23.60	23.67	23.73
3	1	14		23.39	23.40	23.48
3	8	0		23.12	23.19	23.24
3	8	4		22.91	22.99	23.03
3	8	7		22.70	22.74	22.81
3	15	0		22.44	22.53	22.59
3	1	0	16-QAM	23.62	23.65	23.77
3	1	7		23.40	23.40	23.56
3	1	14		23.10	23.12	23.35
3	8	0		22.85	22.84	23.09
3	8	4		22.62	22.63	22.83
3	8	7		22.34	22.37	22.60
3	15	0		22.04	22.09	22.32



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.22	24.03	23.97
5	1	12		23.93	23.76	23.76
5	1	24		23.71	23.50	23.55
5	12	0		23.47	23.25	23.33
5	12	6		23.20	23.05	23.07
5	12	11		22.91	22.83	22.83
5	25	0		22.64	22.59	22.56
5	1	0	16-QAM	24.01	23.82	23.73
5	1	12		23.76	23.59	23.49
5	1	24		23.52	23.36	23.25
5	12	0		23.25	23.10	22.99
5	12	6		22.95	22.84	22.71
5	12	11		22.68	22.62	22.41
5	25	0		22.42	22.41	22.13
10	1	0	QPSK	24.31	24.25	24.35
10	1	24		24.10	23.98	24.09
10	1	49		23.81	23.74	23.83
10	25	0		23.58	23.49	23.57
10	25	12		23.37	23.22	23.33
10	25	24		23.10	23.02	23.12
10	50	0		22.88	22.79	22.87
10	1	0	16-QAM	24.10	24.00	24.13
10	1	24		23.89	23.71	23.92
10	1	49		23.63	23.49	23.64
10	25	0		23.35	23.24	23.42
10	25	12		23.07	23.04	23.16
10	25	24		22.81	22.82	22.88
10	50	0		22.53	22.62	22.59



LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.36	21.41	21.46
5	1	12		21.14	21.21	21.18
5	1	24		20.89	20.94	20.91
5	12	0		20.67	20.66	20.67
5	12	6		20.43	20.44	20.46
5	12	11		20.21	20.14	20.17
5	25	0		19.92	19.86	19.89
5	1	0	16-QAM	21.07	21.19	21.19
5	1	12		20.81	20.91	20.89
5	1	24		20.52	20.71	20.62
5	12	0		20.30	20.45	20.33
5	12	6		20.04	20.18	20.09
5	12	11		19.76	19.95	19.79
5	25	0		19.50	19.75	19.58
10	1	0	QPSK	N/A	22.06	N/A
10	1	24		N/A	21.80	N/A
10	1	49		N/A	21.60	N/A
10	25	0		N/A	21.34	N/A
10	25	12		N/A	21.12	N/A
10	25	24		N/A	20.84	N/A
10	50	0		N/A	20.59	N/A
10	1	0	16-QAM	N/A	21.85	N/A
10	1	24		N/A	21.60	N/A
10	1	49		N/A	21.35	N/A
10	25	0		N/A	21.10	N/A
10	25	12		N/A	20.86	N/A
10	25	24		N/A	20.61	N/A
10	50	0		N/A	20.35	N/A



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.16	23.05	23.20
1.4	1	2		22.91	22.78	22.98
1.4	1	5		22.68	22.52	22.73
1.4	3	0		22.45	22.32	22.46
1.4	3	1		22.22	22.02	22.23
1.4	3	2		22.01	21.78	22.00
1.4	6	0		21.75	21.49	21.75
1.4	1	0	16-QAM	22.88	22.79	22.97
1.4	1	2		22.63	22.52	22.71
1.4	1	5		22.37	22.23	22.41
1.4	3	0		22.15	21.98	22.18
1.4	3	1		21.85	21.72	21.96
1.4	3	2		21.59	21.52	21.74
1.4	6	0		21.34	21.30	21.44
3	1	0	QPSK	22.85	22.91	23.03
3	1	7		22.64	22.69	22.83
3	1	14		22.40	22.44	22.55
3	8	0		22.19	22.16	22.28
3	8	4		21.95	21.95	22.06
3	8	7		21.72	21.68	21.77
3	15	0		21.50	21.38	21.49
3	1	0	16-QAM	22.62	22.63	22.76
3	1	7		22.34	22.35	22.49
3	1	14		22.06	22.09	22.20
3	8	0		21.77	21.79	22.00
3	8	4		21.54	21.53	21.71
3	8	7		21.25	21.24	21.50
3	15	0		21.01	20.98	21.24



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.71	22.80	22.84
5	1	12		22.49	22.55	22.62
5	1	24		22.25	22.31	22.38
5	12	0		21.97	22.02	22.15
5	12	6		21.68	21.79	21.91
5	12	11		21.40	21.52	21.66
5	25	0		21.18	21.29	21.36
5	1	0	16-QAM	22.46	22.59	22.58
5	1	12		22.20	22.38	22.32
5	1	24		21.96	22.17	22.09
5	12	0		21.67	21.87	21.86
5	12	6		21.44	21.62	21.64
5	12	11		21.16	21.35	21.40
5	25	0		20.93	21.07	21.17
10	1	0	QPSK	23.18	23.05	23.16
10	1	24		22.94	22.83	22.94
10	1	49		22.71	22.57	22.71
10	25	0		22.45	22.30	22.42
10	25	12		22.20	22.07	22.16
10	25	24		21.94	21.79	21.92
10	50	0		21.73	21.58	21.66
10	1	0	16-QAM	22.94	22.75	22.93
10	1	24		22.71	22.52	22.73
10	1	49		22.50	22.31	22.47
10	25	0		22.28	22.07	22.17
10	25	12		22.05	21.86	21.93
10	25	24		21.82	21.60	21.71
10	50	0		21.52	21.32	21.47



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.06	23.17	23.22
15	1	37		22.82	22.92	22.93
15	1	74		22.52	22.68	22.67
15	36	0		22.29	22.43	22.39
15	36	18		22.07	22.20	22.18
15	36	39		21.83	21.95	21.95
15	75	0		21.57	21.69	21.65
15	1	0	16-QAM	22.79	22.94	22.99
15	1	38		22.52	22.66	22.70
15	1	75		22.25	22.44	22.45
15	36	0		22.03	22.16	22.21
15	36	18		21.81	21.89	21.99
15	36	39		21.52	21.62	21.70
15	75	0		21.25	21.41	21.47
20	1	0	QPSK	23.35	23.40	23.46
20	1	49		23.07	23.16	23.21
20	1	99		22.82	22.87	22.98
20	50	0		22.62	22.65	22.75
20	50	24		22.34	22.42	22.49
20	50	49		22.13	22.12	22.24
20	100	0		21.85	21.88	22.03
20	1	0	16-QAM	23.06	23.12	23.26
20	1	49		22.83	22.88	23.02
20	1	99		22.62	22.61	22.73
20	50	0		22.33	22.41	22.51
20	50	24		22.06	22.14	22.26
20	50	49		21.83	21.85	22.02
20	100	0		21.55	21.63	21.76



LTE Band 26(Part 22) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.77	23.69	23.81
1.4	1	2		23.50	23.44	23.53
1.4	1	5		23.22	23.20	23.31
1.4	3	0		22.97	23.00	23.02
1.4	3	1		22.72	22.77	22.75
1.4	3	2		22.52	22.53	22.51
1.4	6	0		22.29	22.28	22.30
1.4	1	0	16-QAM	23.47	23.48	23.59
1.4	1	2		23.22	23.27	23.36
1.4	1	5		22.99	23.04	23.09
1.4	3	0		22.78	22.76	22.88
1.4	3	1		22.52	22.50	22.59
1.4	3	2		22.32	22.22	22.29
1.4	6	0		22.06	22.01	22.06
3	1	0	QPSK	23.35	23.42	23.60
3	1	7		23.15	23.13	23.31
3	1	14		22.86	22.88	23.03
3	8	0		22.61	22.68	22.79
3	8	4		22.39	22.39	22.57
3	8	7		22.10	22.10	22.31
3	15	0		21.81	21.88	22.02
3	1	0	16-QAM	23.14	23.22	23.35
3	1	7		22.86	22.99	23.11
3	1	14		22.65	22.69	22.84
3	8	0		22.39	22.44	22.57
3	8	4		22.11	22.16	22.28
3	8	7		21.87	21.90	22.04
3	15	0		21.58	21.69	21.77



LTE Band 26(Part 22) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.54	23.67	23.69
5	1	12		23.27	23.39	23.47
5	1	24		23.03	23.18	23.25
5	12	0		22.76	22.92	23.00
5	12	6		22.49	22.69	22.75
5	12	11		22.21	22.47	22.53
5	25	0		21.97	22.26	22.25
5	1	0	16-QAM	23.31	23.45	23.46
5	1	12		23.04	23.21	23.21
5	1	24		22.82	22.97	22.92
5	12	0		22.55	22.73	22.68
5	12	6		22.26	22.52	22.45
5	12	11		21.99	22.30	22.20
5	25	0		21.71	22.01	21.92
10	1	0	QPSK	23.37	23.38	23.13
10	1	24		23.14	23.09	22.90
10	1	49		22.88	22.87	22.64
10	25	0		22.67	22.65	22.41
10	25	12		22.43	22.40	22.18
10	25	24		22.15	22.11	21.91
10	50	0		21.92	21.84	21.63
10	1	0	16-QAM	23.08	23.13	22.83
10	1	24		22.86	22.86	22.54
10	1	49		22.58	22.61	22.29
10	25	0		22.37	22.36	22.04
10	25	12		22.15	22.12	21.81
10	25	24		21.85	21.89	21.55
10	50	0		21.65	21.61	21.29

LTE Band 26(Part 22) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.81	23.76	23.92
15	1	37		23.55	23.54	23.69
15	1	74		23.33	23.30	23.45
15	36	0		23.12	23.01	23.25
15	36	18		22.84	22.75	23.01
15	36	39		22.61	22.46	22.74
15	75	0		22.41	22.24	22.52
15	1	0	16-QAM	23.52	23.55	23.65
15	1	38		23.25	23.28	23.45
15	1	75		23.00	22.98	23.22
15	36	0		22.76	22.77	23.01
15	36	18		22.49	22.54	22.72
15	36	39		22.21	22.31	22.47
15	75	0		21.97	22.06	22.20



LTE Band 26(Part 90) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.91	23.86	23.88
1.4	1	2		23.66	23.57	23.63
1.4	1	5		23.44	23.27	23.37
1.4	3	0		23.15	22.99	23.15
1.4	3	1		22.89	22.74	22.89
1.4	3	2		22.63	22.51	22.67
1.4	6	0		22.40	22.23	22.46
1.4	1	0	16-QAM	23.63	23.56	23.65
1.4	1	2		23.40	23.36	23.36
1.4	1	5		23.13	23.07	23.10
1.4	3	0		22.85	22.86	22.87
1.4	3	1		22.56	22.59	22.63
1.4	3	2		22.31	22.30	22.34
1.4	6	0		22.04	22.09	22.11
3	1	0	QPSK	24.03	23.95	23.94
3	1	7		23.74	23.70	23.65
3	1	14		23.47	23.49	23.42
3	8	0		23.21	23.19	23.19
3	8	4		22.93	22.94	22.96
3	8	7		22.70	22.72	22.71
3	15	0		22.41	22.51	22.50
3	1	0	16-QAM	23.82	23.75	23.68
3	1	7		23.59	23.53	23.40
3	1	14		23.35	23.28	23.15
3	8	0		23.08	23.07	22.87
3	8	4		22.82	22.86	22.63
3	8	7		22.54	22.61	22.36
3	15	0		22.26	22.34	22.09



LTE Band 26(Part 90) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.04	23.94	23.97
5	1	12		23.79	23.69	23.74
5	1	24		23.53	23.40	23.47
5	12	0		23.30	23.19	23.20
5	12	6		23.09	22.90	22.95
5	12	11		22.86	22.67	22.69
5	25	0		22.60	22.46	22.49
5	1	0	16-QAM	23.77	23.73	23.72
5	1	12		23.47	23.48	23.49
5	1	24		23.22	23.26	23.25
5	12	0		22.96	22.98	23.04
5	12	6		22.73	22.74	22.83
5	12	11		22.49	22.47	22.59
5	25	0		22.19	22.21	22.32
10	1	0	QPSK	N/A	24.16	N/A
10	1	24		N/A	23.87	N/A
10	1	49		N/A	23.60	N/A
10	25	0		N/A	23.36	N/A
10	25	12		N/A	23.11	N/A
10	25	24		N/A	22.87	N/A
10	50	0		N/A	22.62	N/A
10	1	0	16-QAM	N/A	23.87	N/A
10	1	24		N/A	23.66	N/A
10	1	49		N/A	23.41	N/A
10	25	0		N/A	23.12	N/A
10	25	12		N/A	22.90	N/A
10	25	24		N/A	22.64	N/A
10	50	0		N/A	22.37	N/A



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.88	22.80	22.86
5	1	12		22.67	22.53	22.58
5	1	24		22.43	22.24	22.36
5	12	0		22.15	22.04	22.14
5	12	6		21.91	21.81	21.85
5	12	11		21.61	21.54	21.61
5	25	0		21.40	21.34	21.40
5	1	0	16-QAM	22.61	22.56	22.64
5	1	12		22.32	22.34	22.34
5	1	24		22.07	22.06	22.12
5	12	0		21.81	21.78	21.90
5	12	6		21.51	21.49	21.65
5	12	11		21.26	21.29	21.43
5	25	0		21.01	20.99	21.14
10	1	0	QPSK	22.76	22.83	22.91
10	1	24		22.53	22.59	22.68
10	1	49		22.32	22.34	22.43
10	25	0		22.10	22.05	22.23
10	25	12		21.88	21.81	21.96
10	25	24		21.64	21.54	21.75
10	50	0		21.38	21.33	21.49
10	1	0	16-QAM	22.53	22.56	22.67
10	1	49		22.30	22.32	22.42
10	1	99		22.03	22.06	22.14
10	50	0		21.79	21.82	21.87
10	50	24		21.57	21.54	21.66
10	50	49		21.36	21.34	21.46
10	100	0		21.12	21.10	21.22



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.81	22.76	22.90
15	1	37		22.60	22.49	22.68
15	1	74		22.40	22.26	22.46
15	36	0		22.18	22.00	22.24
15	36	18		21.89	21.73	21.99
15	36	39		21.62	21.50	21.75
15	75	0		21.40	21.25	21.54
15	1	0	16-QAM	22.59	22.50	22.63
15	1	49		22.35	22.30	22.36
15	1	99		22.11	22.01	22.15
15	50	0		21.85	21.78	21.89
15	50	24		21.59	21.56	21.62
15	50	49		21.34	21.33	21.35
15	100	0		21.08	21.06	21.12
20	1	0	QPSK	23.03	23.16	23.07
20	1	49		22.77	22.87	22.86
20	1	99		22.54	22.62	22.65
20	50	0		22.33	22.35	22.42
20	50	24		22.04	22.08	22.17
20	50	49		21.74	21.86	21.90
20	100	0		21.47	21.63	21.63
20	1	0	16-QAM	22.74	22.93	22.79
20	1	49		22.45	22.72	22.57
20	1	99		22.17	22.44	22.29
20	50	0		21.95	22.15	22.09
20	50	24		21.71	21.89	21.84
20	50	49		21.50	21.67	21.62
20	100	0		21.28	21.42	21.38



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.83	22.91	22.85
1.4	1	2		22.57	22.62	22.61
1.4	1	5		22.33	22.32	22.32
1.4	3	0		22.09	22.06	22.03
1.4	3	1		21.81	21.84	21.82
1.4	3	2		21.60	21.57	21.61
1.4	6	0		21.39	21.31	21.33
1.4	1	0	16-QAM	22.63	22.67	22.59
1.4	1	2		22.34	22.47	22.32
1.4	1	5		22.09	22.21	22.06
1.4	3	0		21.80	21.98	21.80
1.4	3	1		21.52	21.76	21.56
1.4	3	2		21.26	21.51	21.31
1.4	6	0		20.98	21.25	21.03
3	1	0	QPSK	22.65	22.68	22.70
3	1	7		22.40	22.46	22.46
3	1	14		22.16	22.21	22.19
3	8	0		21.94	21.93	21.97
3	8	4		21.65	21.70	21.75
3	8	7		21.40	21.45	21.45
3	15	0		21.13	21.25	21.16
3	1	0	16-QAM	22.42	22.43	22.43
3	1	7		22.16	22.20	22.15
3	1	14		21.94	21.99	21.85
3	8	0		21.73	21.78	21.62
3	8	4		21.53	21.51	21.41
3	8	7		21.25	21.27	21.20
3	15	0		20.99	21.02	20.96



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.71	22.69	22.63
5	1	12		22.49	22.40	22.36
5	1	24		22.29	22.10	22.14
5	12	0		22.08	21.87	21.90
5	12	6		21.83	21.64	21.66
5	12	11		21.56	21.38	21.41
5	25	0		21.34	21.08	21.15
5	1	0	16-QAM	22.42	22.42	22.34
5	1	12		22.15	22.19	22.14
5	1	24		21.95	21.93	21.85
5	12	0		21.69	21.71	21.62
5	12	6		21.46	21.43	21.37
5	12	11		21.20	21.21	21.11
5	25	0		20.97	20.98	20.82
10	1	0	QPSK	22.47	22.39	22.52
10	1	24		22.19	22.13	22.30
10	1	49		21.89	21.92	22.00
10	25	0		21.69	21.66	21.74
10	25	12		21.46	21.37	21.51
10	25	24		21.18	21.16	21.25
10	50	0		20.90	20.88	20.98
10	1	0	16-QAM	22.23	22.15	22.27
10	1	24		22.02	21.87	22.04
10	1	49		21.81	21.66	21.82
10	25	0		21.57	21.36	21.59
10	25	12		21.29	21.16	21.30
10	25	24		21.00	20.90	21.06
10	50	0		20.78	20.65	20.78



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.66	22.75	22.80
15	1	37		22.37	22.52	22.56
15	1	74		22.10	22.26	22.33
15	36	0		21.81	22.06	22.06
15	36	18		21.58	21.81	21.86
15	36	39		21.30	21.57	21.63
15	75	0		21.02	21.32	21.38
15	1	0	16-QAM	22.38	22.49	22.52
15	1	38		22.14	22.23	22.27
15	1	75		21.94	22.00	22.01
15	36	0		21.64	21.72	21.76
15	36	18		21.35	21.49	21.48
15	36	39		21.09	21.22	21.27
15	75	0		20.81	20.94	21.00
20	1	0	QPSK	22.95	23.08	22.96
20	1	49		22.73	22.82	22.67
20	1	99		22.52	22.59	22.47
20	50	0		22.28	22.32	22.19
20	50	24		22.03	22.05	21.97
20	50	49		21.74	21.79	21.70
20	100	0		21.51	21.58	21.46
20	1	0	16-QAM	22.67	22.81	22.66
20	1	49		22.43	22.57	22.39
20	1	99		22.17	22.30	22.13
20	50	0		21.91	22.02	21.88
20	50	24		21.70	21.79	21.66
20	50	49		21.41	21.54	21.41
20	100	0		21.16	21.29	21.12


4. PEAK-TO-AVERAGE RATIO

4.1 DESCRIPTION OF THE CONDUCTED OUTPUT POWER MEASUREMENT

4.1.1 MEASUREMENT METHOD

Use one of the procedures presented in 4.1.3 to measure the total peak power and record as PPK. Use one of the applicable procedures presented 4.1.3 to measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:
 $PAPR (dB) = PPK (dBm) - PAvg (dBm)$.

4.1.2 TEST SETUP



4.1.3 TEST PROCEDURES

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.7 and ANSI C63.26 2015 Section 5.2.6.
2. The EUT was connected to spectrum and system simulator via a power divider
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Set the test probe and measure the peak and average power of the spectrum analyzer
5. Record the deviation as Peak to Average Ratio.

	LTE					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	30kHz	100kHz	100kHz	300kHz	300kHz
VBW	100kHz	100kHz	300kHz	300kHz	1000kHz	1000kHz
Detector	PK/AVG	PK/AVG	PK/AVG	PK/AVG	PK/AVG	PK/AVG
Trace	Max	Max	Max	Max	Max	Max
Sweep Count	Auto	Auto	Auto	Auto	Auto	Auto



4.1.4 TEST RESULTS

LTE Band 2 PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
20	1	QPSK	5.17	4.8	4.4
20	100		5.28	5.47	5.56
20	1	16-QAM	5.93	5.69	5.08
20	100		6.12	6.29	6.4
Limit			≤13dB		

LTE Band 4 PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
20	1	QPSK	4.48	4.81	4.61
20	100		5.06	5.21	5.31
20	1	16-QAM	5.49	5.61	5.47
20	100		5.8	6.07	6.13
Limit			≤13dB		

LTE Band 5 PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
10	1	QPSK	4.1	4.92	3.94
10	50		5.07	4.78	4.79
10	1	16-QAM	5.03	5.54	4.91
10	50		5.82	5.52	5.71
Limit			≤13dB		

LTE Band 12 PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
10	1	QPSK	3.79	3.67	3.56
10	50		5.28	5.55	5.16
10	1	16-QAM	4.68	4.53	4.6
10	50		5.96	6.07	5.92
Limit			≤13dB		

LTE Band 13 PAR [dBm]			
BW [MHz]	RB Size	Modulation	Middle
			P-A
10	1	QPSK	4.53
10	50		5.74
10	1	16-QAM	5.42
10	50		6.56
Limit			≤13dB



LTE Band 25 PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
20	1	QPSK	5.11	4.75	4.83
20	100		5.34	5.19	5.15
20	1	16-QAM	6.58	5.75	5.58
20	100		6.16	6.23	6.19
Limit			≤13dB		

LTE Band 26(Part 22) PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
15	1	QPSK	4.85	4.73	5.19
15	75		3.35	3.63	3.3
15	1	16-QAM	4.04	4.49	3.72
15	75		5.27	5.41	5.56
Limit			≤13dB		

LTE Band 26(Part 90) PAR [dBm]			
BW [MHz]	RB Size	Modulation	Middle
			P-A
10	1	QPSK	3.64
10	50		4.64
10	1	16-QAM	4.4
10	50		5.56
Limit			≤13dB

LTE Band 41PAR [dBm]					
			Lowest	Middle	Highest
			P-A	P-A	P-A
20	1		3.62	4.48	4.72
20	100		3.63	3.4	3.92
20	1		4.3	3.88	4.54
20	100		5.59	5.22	5.35
Limit			≤13dB		

LTE Band 66 PAR [dBm]					
BW [MHz]	RB Size	Modulation	Lowest	Middle	Highest
			P-A	P-A	P-A
20	1	QPSK	4.99	5.34	4.8
20	100		4.47	4.64	4.18
20	1	16-QAM	5.31	6.73	4.99
20	100		5.25	6.49	5.64
Limit			≤13dB		

Note: Test chart See Appendix D

5. RADIATED POWER AND EFFECTIVE ISOTROPIC RADIATED POWER

5.1 DESCRIPTION OF THE ERP/EIRP MEASUREMENT


5.1.1 MEASUREMENT METHOD

Effective radiated power output measurements by substitution method according to ANSI C63.26 2015, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems. Mobile and portable (hand-held) stations operating are limited to average ERP, Equivalent isotropic radiated power output measurements by substitution method according to ANSI C63.26 2015, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas, Mobile and portable (hand-held) stations operating are limited to average EIRP.


5.1.2 TEST SETUP

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, $RSE = R_x \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + \text{Gain (dBi)} - 107 \text{ (dBuV to dBm)}$ The SA is calibrated using following setup.



b) EUT was placed on a 1.5m non-conductive stand at a 3 m test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 m from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below:

Power=PMea+ARpl



5.1.3 TEST PROCEDURES

1. The testing follows FCC KDB 971168 D01v03r01 Section 5.6 and ANSI C63.26 2015 Section 5.2.
2. The EUT was placed on a non-conductive rotating platform 1.5 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with Peak detector.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 m in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to ANSI C63.26 2015. The EUT was replaced by dipole antenna (substitution antenna) at same location and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP/ERP = LVL + \text{Correction factor}$.
5. RB Set greater than bandwidth, VB Set spectrum analyzer Maximum support.





5.1.4 TEST RESULTS

Note: Test is divided into three directions, X/Y/Z. X pattern for the worst.

Radiated Power (EIRP) for LTE Band 2 / 1.4M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.06	2.37	10.40	20.09	Horizontal	Pass
	1	0	Middle	12.22	2.39	10.42	20.25	Horizontal	Pass
	1	0	Highest	12.18	2.40	10.44	20.22	Horizontal	Pass
	1	0	Lowest	13.45	2.37	10.40	21.48	Vertical	Pass
	1	0	Middle	13.62	2.39	10.42	21.65	Vertical	Pass
	1	0	Highest	13.59	2.40	10.44	21.63	Vertical	Pass
16QAM	1	0	Lowest	11.9	2.37	10.40	19.93	Horizontal	Pass
	1	0	Middle	12.11	2.39	10.42	20.14	Horizontal	Pass
	1	0	Highest	11.88	2.40	10.44	19.92	Horizontal	Pass
	1	0	Lowest	13.29	2.37	10.40	21.32	Vertical	Pass
	1	0	Middle	13.42	2.39	10.42	21.45	Vertical	Pass
	1	0	Highest	13.37	2.40	10.44	21.41	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 2 / 3M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.33	2.37	10.40	20.36	Horizontal	Pass
	1	0	Middle	12.22	2.39	10.42	20.25	Horizontal	Pass
	1	0	Highest	12.28	2.40	10.44	20.32	Horizontal	Pass
	1	0	Lowest	13.73	2.37	10.40	21.76	Vertical	Pass
	1	0	Middle	13.64	2.39	10.42	21.67	Vertical	Pass
	1	0	Highest	13.69	2.40	10.44	21.73	Vertical	Pass
16QAM	1	0	Lowest	12.09	2.37	10.40	20.12	Horizontal	Pass
	1	0	Middle	12.06	2.39	10.42	20.09	Horizontal	Pass
	1	0	Highest	11.96	2.40	10.44	20.00	Horizontal	Pass
	1	0	Lowest	13.47	2.37	10.40	21.50	Vertical	Pass
	1	0	Middle	13.38	2.39	10.42	21.41	Vertical	Pass
	1	0	Highest	13.3	2.40	10.44	21.34	Vertical	Pass
Limit	EIRP<2W=33dBm								



Radiated Power (EIRP) for LTE Band 2 / 5M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.09	2.37	10.40	20.12	Horizontal	Pass
	1	0	Middle	12.19	2.39	10.42	20.22	Horizontal	Pass
	1	0	Highest	12.09	2.40	10.44	20.13	Horizontal	Pass
	1	0	Lowest	13.43	2.37	10.40	21.46	Vertical	Pass
	1	0	Middle	13.63	2.39	10.42	21.66	Vertical	Pass
	1	0	Highest	13.48	2.40	10.44	21.52	Vertical	Pass
16QAM	1	0	Lowest	11.75	2.37	10.40	19.78	Horizontal	Pass
	1	0	Middle	11.83	2.39	10.42	19.86	Horizontal	Pass
	1	0	Highest	11.71	2.40	10.44	19.75	Horizontal	Pass
	1	0	Lowest	13.19	2.37	10.40	21.22	Vertical	Pass
	1	0	Middle	13.33	2.39	10.42	21.36	Vertical	Pass
	1	0	Highest	13.2	2.40	10.44	21.24	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 2 / 10M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.11	2.37	10.40	20.14	Horizontal	Pass
	1	0	Middle	12.18	2.39	10.42	20.21	Horizontal	Pass
	1	0	Highest	11.93	2.40	10.44	19.97	Horizontal	Pass
	1	0	Lowest	13.57	2.37	10.40	21.60	Vertical	Pass
	1	0	Middle	13.67	2.39	10.42	21.70	Vertical	Pass
	1	0	Highest	13.3	2.40	10.44	21.34	Vertical	Pass
16QAM	1	0	Lowest	12.03	2.37	10.40	20.06	Horizontal	Pass
	1	0	Middle	12.21	2.39	10.42	20.24	Horizontal	Pass
	1	0	Highest	11.58	2.40	10.44	19.62	Horizontal	Pass
	1	0	Lowest	13.44	2.37	10.40	21.47	Vertical	Pass
	1	0	Middle	13.56	2.39	10.42	21.59	Vertical	Pass
	1	0	Highest	12.94	2.40	10.44	20.98	Vertical	Pass
Limit	EIRP<2W=33dBm								



Radiated Power (EIRP) for LTE Band 2 / 15M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.2	2.37	10.40	20.23	Horizontal	Pass
	1	0	Middle	12.21	2.39	10.42	20.24	Horizontal	Pass
	1	0	Highest	12.06	2.40	10.44	20.10	Horizontal	Pass
	1	0	Lowest	13.67	2.37	10.40	21.70	Vertical	Pass
	1	0	Middle	13.58	2.39	10.42	21.61	Vertical	Pass
	1	0	Highest	13.5	2.40	10.44	21.54	Vertical	Pass
16QAM	1	0	Lowest	12.09	2.37	10.40	20.12	Horizontal	Pass
	1	0	Middle	12.15	2.39	10.42	20.18	Horizontal	Pass
	1	0	Highest	11.78	2.40	10.44	19.82	Horizontal	Pass
	1	0	Lowest	13.46	2.37	10.40	21.49	Vertical	Pass
	1	0	Middle	13.45	2.39	10.42	21.48	Vertical	Pass
	1	0	Highest	13.22	2.40	10.44	21.26	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 2 / 20M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.33	2.37	10.40	20.36	Horizontal	Pass
	1	0	Middle	12.47	2.39	10.42	20.50	Horizontal	Pass
	1	0	Highest	12.55	2.40	10.44	20.59	Horizontal	Pass
	1	0	Lowest	13.8	2.37	10.40	21.83	Vertical	Pass
	1	0	Middle	13.84	2.39	10.42	21.87	Vertical	Pass
	1	0	Highest	13.88	2.40	10.44	21.92	Vertical	Pass
16QAM	1	0	Lowest	12.16	2.37	10.40	20.19	Horizontal	Pass
	1	0	Middle	12.21	2.39	10.42	20.24	Horizontal	Pass
	1	0	Highest	12.23	2.40	10.44	20.27	Horizontal	Pass
	1	0	Lowest	13.48	2.37	10.40	21.51	Vertical	Pass
	1	0	Middle	13.64	2.39	10.42	21.67	Vertical	Pass
	1	0	Highest	13.54	2.40	10.44	21.58	Vertical	Pass
Limit	EIRP<2W=33dBm								



Radiated Power (EIRP) for LTE Band 4 / 1.4M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.86	2.35	10.13	20.64	Horizontal	Pass
	1	0	Middle	12.95	2.36	10.16	20.75	Horizontal	Pass
	1	0	Highest	12.78	2.37	10.22	20.63	Horizontal	Pass
	1	0	Lowest	14.3	2.35	10.13	22.08	Vertical	Pass
	1	0	Middle	14.35	2.36	10.16	22.15	Vertical	Pass
	1	0	Highest	14.23	2.37	10.22	22.08	Vertical	Pass
16QAM	1	0	Lowest	12.8	2.35	10.13	20.58	Horizontal	Pass
	1	0	Middle	12.61	2.36	10.16	20.41	Horizontal	Pass
	1	0	Highest	12.58	2.37	10.22	20.43	Horizontal	Pass
	1	0	Lowest	14.12	2.35	10.13	21.90	Vertical	Pass
	1	0	Middle	14.06	2.36	10.16	21.86	Vertical	Pass
	1	0	Highest	13.97	2.37	10.22	21.82	Vertical	Pass
Limit	EIRP<1W=30dBm								

Radiated Power (EIRP) for LTE Band 4 / 3M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.87	2.35	10.13	20.65	Horizontal	Pass
	1	0	Middle	13.05	2.36	10.16	20.85	Horizontal	Pass
	1	0	Highest	13.01	2.37	10.22	20.86	Horizontal	Pass
	1	0	Lowest	14.32	2.35	10.13	22.10	Vertical	Pass
	1	0	Middle	14.51	2.36	10.16	22.31	Vertical	Pass
	1	0	Highest	14.4	2.37	10.22	22.25	Vertical	Pass
16QAM	1	0	Lowest	12.62	2.35	10.13	20.40	Horizontal	Pass
	1	0	Middle	12.85	2.36	10.16	20.65	Horizontal	Pass
	1	0	Highest	12.74	2.37	10.22	20.59	Horizontal	Pass
	1	0	Lowest	14.02	2.35	10.13	21.80	Vertical	Pass
	1	0	Middle	14.25	2.36	10.16	22.05	Vertical	Pass
	1	0	Highest	14.06	2.37	10.22	21.91	Vertical	Pass
Limit	EIRP<1W=30dBm								



Radiated Power (EIRP) for LTE Band 4 / 5M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.96	2.35	10.13	20.74	Horizontal	Pass
	1	0	Middle	12.89	2.36	10.16	20.69	Horizontal	Pass
	1	0	Highest	12.79	2.37	10.22	20.64	Horizontal	Pass
	1	0	Lowest	14.29	2.35	10.13	22.07	Vertical	Pass
	1	0	Middle	14.3	2.36	10.16	22.10	Vertical	Pass
	1	0	Highest	14.17	2.37	10.22	22.02	Vertical	Pass
16QAM	1	0	Lowest	12.7	2.35	10.13	20.48	Horizontal	Pass
	1	0	Middle	12.7	2.36	10.16	20.50	Horizontal	Pass
	1	0	Highest	12.64	2.37	10.22	20.49	Horizontal	Pass
	1	0	Lowest	14.01	2.35	10.13	21.79	Vertical	Pass
	1	0	Middle	14.1	2.36	10.16	21.90	Vertical	Pass
	1	0	Highest	14.05	2.37	10.22	21.90	Vertical	Pass
Limit	EIRP<1W=30dBm								

Radiated Power (EIRP) for LTE Band 4 / 10M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.94	2.35	10.13	20.72	Horizontal	Pass
	1	0	Middle	13.11	2.36	10.16	20.91	Horizontal	Pass
	1	0	Highest	12.83	2.37	10.22	20.68	Horizontal	Pass
	1	0	Lowest	14.42	2.35	10.13	22.20	Vertical	Pass
	1	0	Middle	14.42	2.36	10.16	22.22	Vertical	Pass
	1	0	Highest	14.24	2.37	10.22	22.09	Vertical	Pass
16QAM	1	0	Lowest	12.72	2.35	10.13	20.50	Horizontal	Pass
	1	0	Middle	12.73	2.36	10.16	20.53	Horizontal	Pass
	1	0	Highest	12.53	2.37	10.22	20.38	Horizontal	Pass
	1	0	Lowest	14.17	2.35	10.13	21.95	Vertical	Pass
	1	0	Middle	14.04	2.36	10.16	21.84	Vertical	Pass
	1	0	Highest	13.98	2.37	10.22	21.83	Vertical	Pass
Limit	EIRP<1W=30dBm								



Radiated Power (EIRP) for LTE Band 4 / 15M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.91	2.35	10.13	20.69	Horizontal	Pass
	1	0	Middle	12.79	2.36	10.16	20.59	Horizontal	Pass
	1	0	Highest	12.89	2.37	10.22	20.74	Horizontal	Pass
	1	0	Lowest	14.4	2.35	10.13	22.18	Vertical	Pass
	1	0	Middle	14.1	2.36	10.16	21.90	Vertical	Pass
	1	0	Highest	14.28	2.37	10.22	22.13	Vertical	Pass
16QAM	1	0	Lowest	12.62	2.35	10.13	20.40	Horizontal	Pass
	1	0	Middle	12.42	2.36	10.16	20.22	Horizontal	Pass
	1	0	Highest	12.71	2.37	10.22	20.56	Horizontal	Pass
	1	0	Lowest	14.1	2.35	10.13	21.88	Vertical	Pass
	1	0	Middle	13.85	2.36	10.16	21.65	Vertical	Pass
	1	0	Highest	14.07	2.37	10.22	21.92	Vertical	Pass
Limit	EIRP<1W=30dBm								

Radiated Power (EIRP) for LTE Band 4 / 20M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	13.07	2.35	10.13	20.85	Horizontal	Pass
	1	0	Middle	13.05	2.36	10.16	20.85	Horizontal	Pass
	1	0	Highest	13.04	2.37	10.22	20.89	Horizontal	Pass
	1	0	Lowest	14.47	2.35	10.13	22.25	Vertical	Pass
	1	0	Middle	14.54	2.36	10.16	22.34	Vertical	Pass
	1	0	Highest	14.45	2.37	10.22	22.30	Vertical	Pass
16QAM	1	0	Lowest	12.85	2.35	10.13	20.63	Horizontal	Pass
	1	0	Middle	12.89	2.36	10.16	20.69	Horizontal	Pass
	1	0	Highest	13	2.37	10.22	20.85	Horizontal	Pass
	1	0	Lowest	14.22	2.35	10.13	22.00	Vertical	Pass
	1	0	Middle	14.33	2.36	10.16	22.13	Vertical	Pass
	1	0	Highest	14.3	2.37	10.22	22.15	Vertical	Pass
Limit	EIRP<1W=30dBm								



Radiated Power (ERP) for LTE Band 5 / 1.4M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	18.88	1.27	6.70	2.15	22.16	Horizontal	Pass
	1	0	Middle	18.98	1.28	6.70	2.15	22.25	Horizontal	Pass
	1	0	Highest	19.05	1.29	6.70	2.15	22.31	Horizontal	Pass
	1	0	Lowest	20.25	1.27	6.70	2.15	23.53	Vertical	Pass
	1	0	Middle	20.38	1.28	6.70	2.15	23.65	Vertical	Pass
	1	0	Highest	20.44	1.29	6.70	2.15	23.70	Vertical	Pass
16QAM	1	0	Lowest	18.72	1.27	6.70	2.15	22.00	Horizontal	Pass
	1	0	Middle	18.82	1.28	6.70	2.15	22.09	Horizontal	Pass
	1	0	Highest	18.71	1.29	6.70	2.15	21.97	Horizontal	Pass
	1	0	Lowest	20.22	1.27	6.70	2.15	23.50	Vertical	Pass
	1	0	Middle	20.15	1.28	6.70	2.15	23.42	Vertical	Pass
	1	0	Highest	20.2	1.29	6.70	2.15	23.46	Vertical	Pass
Limit	ERP<7W=38.45dBm									

Radiated Power (ERP) for LTE Band 5 / 3M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	18.82	1.27	6.70	2.15	22.10	Horizontal	Pass
	1	0	Middle	19.13	1.28	6.70	2.15	22.40	Horizontal	Pass
	1	0	Highest	19.2	1.29	6.70	2.15	22.46	Horizontal	Pass
	1	0	Lowest	20.24	1.27	6.70	2.15	23.52	Vertical	Pass
	1	0	Middle	20.53	1.28	6.70	2.15	23.80	Vertical	Pass
	1	0	Highest	20.54	1.29	6.70	2.15	23.80	Vertical	Pass
16QAM	1	0	Lowest	18.52	1.27	6.70	2.15	21.80	Horizontal	Pass
	1	0	Middle	18.74	1.28	6.70	2.15	22.01	Horizontal	Pass
	1	0	Highest	18.84	1.29	6.70	2.15	22.10	Horizontal	Pass
	1	0	Lowest	19.89	1.27	6.70	2.15	23.17	Vertical	Pass
	1	0	Middle	20.18	1.28	6.70	2.15	23.45	Vertical	Pass
	1	0	Highest	20.17	1.29	6.70	2.15	23.43	Vertical	Pass
Limit	ERP<7W=38.45dBm									



Radiated Power (ERP) for LTE Band 5 / 5M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	19.04	1.27	6.70	2.15	22.32	Horizontal	Pass
	1	0	Middle	19.08	1.28	6.70	2.15	22.35	Horizontal	Pass
	1	0	Highest	19.4	1.29	6.70	2.15	22.66	Horizontal	Pass
	1	0	Lowest	20.39	1.27	6.70	2.15	23.67	Vertical	Pass
	1	0	Middle	20.52	1.28	6.70	2.15	23.79	Vertical	Pass
	1	0	Highest	20.7	1.29	6.70	2.15	23.96	Vertical	Pass
16QAM	1	0	Lowest	18.76	1.27	6.70	2.15	22.04	Horizontal	Pass
	1	0	Middle	18.8	1.28	6.70	2.15	22.07	Horizontal	Pass
	1	0	Highest	19.18	1.29	6.70	2.15	22.44	Horizontal	Pass
	1	0	Lowest	20.13	1.27	6.70	2.15	23.41	Vertical	Pass
	1	0	Middle	20.17	1.28	6.70	2.15	23.44	Vertical	Pass
	1	0	Highest	20.5	1.29	6.70	2.15	23.76	Vertical	Pass
Limit	ERP<7W=38.45dBm									

Radiated Power (ERP) for LTE Band 5 / 10M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	19.36	1.27	6.70	2.15	22.64	Horizontal	Pass
	1	0	Middle	19.41	1.28	6.70	2.15	22.68	Horizontal	Pass
	1	0	Highest	19.37	1.29	6.70	2.15	22.63	Horizontal	Pass
	1	0	Lowest	20.7	1.27	6.70	2.15	23.98	Vertical	Pass
	1	0	Middle	20.71	1.28	6.70	2.15	23.98	Vertical	Pass
	1	0	Highest	20.78	1.29	6.70	2.15	24.04	Vertical	Pass
16QAM	1	0	Lowest	19.07	1.27	6.70	2.15	22.35	Horizontal	Pass
	1	0	Middle	19.12	1.28	6.70	2.15	22.39	Horizontal	Pass
	1	0	Highest	19.04	1.29	6.70	2.15	22.30	Horizontal	Pass
	1	0	Lowest	20.48	1.27	6.70	2.15	23.76	Vertical	Pass
	1	0	Middle	20.49	1.28	6.70	2.15	23.76	Vertical	Pass
	1	0	Highest	20.46	1.29	6.70	2.15	23.72	Vertical	Pass
Limit	ERP<7W=38.45dBm									



Radiated Power (ERP) for LTE Band 12 / 1.4M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	18.25	1.21	6.40	2.15	21.29	Horizontal	Pass
	1	0	Middle	18.35	1.22	6.40	2.15	21.38	Horizontal	Pass
	1	0	Highest	18.29	1.23	6.40	2.15	21.31	Horizontal	Pass
	1	0	Lowest	19.73	1.21	6.40	2.15	22.77	Vertical	Pass
	1	0	Middle	19.84	1.22	6.40	2.15	22.87	Vertical	Pass
	1	0	Highest	19.75	1.23	6.40	2.15	22.77	Vertical	Pass
16QAM	1	0	Lowest	18.1	1.21	6.40	2.15	21.14	Horizontal	Pass
	1	0	Middle	18.38	1.22	6.40	2.15	21.41	Horizontal	Pass
	1	0	Highest	18.06	1.23	6.40	2.15	21.08	Horizontal	Pass
	1	0	Lowest	19.5	1.21	6.40	2.15	22.54	Vertical	Pass
	1	0	Middle	19.74	1.22	6.40	2.15	22.77	Vertical	Pass
	1	0	Highest	19.5	1.23	6.40	2.15	22.52	Vertical	Pass
Limit	ERP<3W=34.77dBm									

Radiated Power (ERP) for LTE Band 12 / 3M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	18	1.21	6.40	2.15	21.04	Horizontal	Pass
	1	0	Middle	18.15	1.22	6.40	2.15	21.18	Horizontal	Pass
	1	0	Highest	18.12	1.23	6.40	2.15	21.14	Horizontal	Pass
	1	0	Lowest	19.42	1.21	6.40	2.15	22.46	Vertical	Pass
	1	0	Middle	19.53	1.22	6.40	2.15	22.56	Vertical	Pass
	1	0	Highest	19.62	1.23	6.40	2.15	22.64	Vertical	Pass
16QAM	1	0	Lowest	17.99	1.21	6.40	2.15	21.03	Horizontal	Pass
	1	0	Middle	17.95	1.22	6.40	2.15	20.98	Horizontal	Pass
	1	0	Highest	18.02	1.23	6.40	2.15	21.04	Horizontal	Pass
	1	0	Lowest	19.32	1.21	6.40	2.15	22.36	Vertical	Pass
	1	0	Middle	19.37	1.22	6.40	2.15	22.40	Vertical	Pass
	1	0	Highest	19.38	1.23	6.40	2.15	22.40	Vertical	Pass
Limit	ERP<3W=34.77dBm									



Radiated Power (ERP) for LTE Band 12 / 5M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	18.53	1.21	6.40	2.15	21.57	Horizontal	Pass
	1	0	Middle	18.27	1.22	6.40	2.15	21.30	Horizontal	Pass
	1	0	Highest	18.22	1.23	6.40	2.15	21.24	Horizontal	Pass
	1	0	Lowest	19.86	1.21	6.40	2.15	22.90	Vertical	Pass
	1	0	Middle	19.62	1.22	6.40	2.15	22.65	Vertical	Pass
	1	0	Highest	19.56	1.23	6.40	2.15	22.58	Vertical	Pass
16QAM	1	0	Lowest	18.23	1.21	6.40	2.15	21.27	Horizontal	Pass
	1	0	Middle	18.07	1.22	6.40	2.15	21.10	Horizontal	Pass
	1	0	Highest	17.99	1.23	6.40	2.15	21.01	Horizontal	Pass
	1	0	Lowest	19.63	1.21	6.40	2.15	22.67	Vertical	Pass
	1	0	Middle	19.55	1.22	6.40	2.15	22.58	Vertical	Pass
	1	0	Highest	19.36	1.23	6.40	2.15	22.38	Vertical	Pass
Limit	ERP<3W=34.77dBm									

Radiated Power (ERP) for LTE Band 12 / 10M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	18.68	1.21	6.40	2.15	21.72	Horizontal	Pass
	1	0	Middle	18.58	1.22	6.40	2.15	21.61	Horizontal	Pass
	1	0	Highest	18.63	1.23	6.40	2.15	21.65	Horizontal	Pass
	1	0	Lowest	19.99	1.21	6.40	2.15	23.03	Vertical	Pass
	1	0	Middle	19.94	1.22	6.40	2.15	22.97	Vertical	Pass
	1	0	Highest	20.08	1.23	6.40	2.15	23.10	Vertical	Pass
16QAM	1	0	Lowest	18.32	1.21	6.40	2.15	21.36	Horizontal	Pass
	1	0	Middle	18.35	1.22	6.40	2.15	21.38	Horizontal	Pass
	1	0	Highest	18.4	1.23	6.40	2.15	21.42	Horizontal	Pass
	1	0	Lowest	19.73	1.21	6.40	2.15	22.77	Vertical	Pass
	1	0	Middle	19.68	1.22	6.40	2.15	22.71	Vertical	Pass
	1	0	Highest	19.78	1.23	6.40	2.15	22.80	Vertical	Pass
Limit	ERP<3W=34.77dBm									



Radiated Power (ERP) for LTE Band 13 / 5M										
Modulation	RB		Channel	Result						Conclusion
				S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P.(dBm)	Polarization	
	Size	Offset							Of Max. ERP	
QPSK	1	0	Lowest	15.56	1.21	6.40	2.15	18.60	Horizontal	Pass
	1	0	Middle	15.74	1.22	6.40	2.15	18.77	Horizontal	Pass
	1	0	Highest	15.68	1.23	6.40	2.15	18.70	Horizontal	Pass
	1	0	Lowest	16.99	1.21	6.40	2.15	20.03	Vertical	Pass
	1	0	Middle	17.07	1.22	6.40	2.15	20.10	Vertical	Pass
	1	0	Highest	17.08	1.23	6.40	2.15	20.10	Vertical	Pass
16QAM	1	0	Lowest	15.46	1.21	6.40	2.15	18.50	Horizontal	Pass
	1	0	Middle	15.3	1.22	6.40	2.15	18.33	Horizontal	Pass
	1	0	Highest	15.42	1.23	6.40	2.15	18.44	Horizontal	Pass
	1	0	Lowest	16.79	1.21	6.40	2.15	19.83	Vertical	Pass
	1	0	Middle	16.76	1.22	6.40	2.15	19.79	Vertical	Pass
	1	0	Highest	16.85	1.23	6.40	2.15	19.87	Vertical	Pass
Limit	ERP<3W=34.77dBm									

Radiated Power (ERP) for LTE Band 13 / 10M										
Modulation	RB		Channel	Result						Conclusion
				S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P.(dBm)	Polarization	
	Size	Offset							Of Max. ERP	
QPSK	1	0	Middle	16.29	1.22	6.40	2.15	19.32	Horizontal	Pass
	1	0	Middle	17.7	1.22	6.40	2.15	20.73	Vertical	Pass
16QAM	1	0	Middle	16.19	1.22	6.40	2.15	19.22	Horizontal	Pass
	1	0	Middle	17.62	1.22	6.40	2.15	20.65	Vertical	Pass
Limit	ERP<3W=34.77dBm									



Radiated Power (EIRP) for LTE Band 25 / 1.4M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I. R.P(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.49	2.37	10.40	20.52	Horizontal	Pass
	1	0	Middle	12.34	2.39	10.42	20.37	Horizontal	Pass
	1	0	Highest	12.46	2.40	10.44	20.50	Horizontal	Pass
	1	0	Lowest	13.86	2.37	10.40	21.89	Vertical	Pass
	1	0	Middle	13.68	2.39	10.42	21.71	Vertical	Pass
	1	0	Highest	13.92	2.40	10.44	21.96	Vertical	Pass
16QAM	1	0	Lowest	12.25	2.37	10.40	20.28	Horizontal	Pass
	1	0	Middle	12.2	2.39	10.42	20.23	Horizontal	Pass
	1	0	Highest	12.12	2.40	10.44	20.16	Horizontal	Pass
	1	0	Lowest	13.6	2.37	10.40	21.63	Vertical	Pass
	1	0	Middle	13.51	2.39	10.42	21.54	Vertical	Pass
	1	0	Highest	13.55	2.40	10.44	21.59	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 25 / 3M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I. R.P(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.23	2.37	10.40	20.26	Horizontal	Pass
	1	0	Middle	12.03	2.39	10.42	20.06	Horizontal	Pass
	1	0	Highest	12.32	2.40	10.44	20.36	Horizontal	Pass
	1	0	Lowest	13.56	2.37	10.40	21.59	Vertical	Pass
	1	0	Middle	13.53	2.39	10.42	21.56	Vertical	Pass
	1	0	Highest	13.73	2.40	10.44	21.77	Vertical	Pass
16QAM	1	0	Lowest	11.93	2.37	10.40	19.96	Horizontal	Pass
	1	0	Middle	12.08	2.39	10.42	20.11	Horizontal	Pass
	1	0	Highest	12.11	2.40	10.44	20.15	Horizontal	Pass
	1	0	Lowest	13.25	2.37	10.40	21.28	Vertical	Pass
	1	0	Middle	13.4	2.39	10.42	21.43	Vertical	Pass
	1	0	Highest	13.49	2.40	10.44	21.53	Vertical	Pass
Limit	EIRP<2W=33dBm								



Radiated Power (EIRP) for LTE Band 25 / 5M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I. R.P(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	11.95	2.37	10.40	19.98	Horizontal	Pass
	1	0	Middle	12.1	2.39	10.42	20.13	Horizontal	Pass
	1	0	Highest	12.13	2.40	10.44	20.17	Horizontal	Pass
	1	0	Lowest	13.44	2.37	10.40	21.47	Vertical	Pass
	1	0	Middle	13.53	2.39	10.42	21.56	Vertical	Pass
	1	0	Highest	13.5	2.40	10.44	21.54	Vertical	Pass
16QAM	1	0	Lowest	11.81	2.37	10.40	19.84	Horizontal	Pass
	1	0	Middle	11.81	2.39	10.42	19.84	Horizontal	Pass
	1	0	Highest	11.79	2.40	10.44	19.83	Horizontal	Pass
	1	0	Lowest	13.13	2.37	10.40	21.16	Vertical	Pass
	1	0	Middle	13.31	2.39	10.42	21.34	Vertical	Pass
	1	0	Highest	13.25	2.40	10.44	21.29	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 25 / 10M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I. R.P(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.63	2.37	10.40	20.66	Horizontal	Pass
	1	0	Middle	12.28	2.39	10.42	20.31	Horizontal	Pass
	1	0	Highest	12.44	2.40	10.44	20.48	Horizontal	Pass
	1	0	Lowest	13.93	2.37	10.40	21.96	Vertical	Pass
	1	0	Middle	13.67	2.39	10.42	21.70	Vertical	Pass
	1	0	Highest	13.88	2.40	10.44	21.92	Vertical	Pass
16QAM	1	0	Lowest	12.24	2.37	10.40	20.27	Horizontal	Pass
	1	0	Middle	11.98	2.39	10.42	20.01	Horizontal	Pass
	1	0	Highest	12.24	2.40	10.44	20.28	Horizontal	Pass
	1	0	Lowest	13.64	2.37	10.40	21.67	Vertical	Pass
	1	0	Middle	13.43	2.39	10.42	21.46	Vertical	Pass
	1	0	Highest	13.69	2.40	10.44	21.73	Vertical	Pass
Limit	EIRP<2W=33dBm								



Radiated Power (EIRP) for LTE Band 25 / 15M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I. R.P(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.46	2.37	10.40	20.49	Horizontal	Pass
	1	0	Middle	12.41	2.39	10.42	20.44	Horizontal	Pass
	1	0	Highest	12.48	2.40	10.44	20.52	Horizontal	Pass
	1	0	Lowest	13.8	2.37	10.40	21.83	Vertical	Pass
	1	0	Middle	13.75	2.39	10.42	21.78	Vertical	Pass
	1	0	Highest	13.94	2.40	10.44	21.98	Vertical	Pass
16QAM	1	0	Lowest	11.98	2.37	10.40	20.01	Horizontal	Pass
	1	0	Middle	12.29	2.39	10.42	20.32	Horizontal	Pass
	1	0	Highest	12.34	2.40	10.44	20.38	Horizontal	Pass
	1	0	Lowest	13.42	2.37	10.40	21.45	Vertical	Pass
	1	0	Middle	13.6	2.39	10.42	21.63	Vertical	Pass
	1	0	Highest	13.7	2.40	10.44	21.74	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 25 / 20M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I. R.P(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.54	2.37	10.40	20.57	Horizontal	Pass
	1	0	Middle	12.69	2.39	10.42	20.72	Horizontal	Pass
	1	0	Highest	12.74	2.40	10.44	20.78	Horizontal	Pass
	1	0	Lowest	13.99	2.37	10.40	22.02	Vertical	Pass
	1	0	Middle	14.16	2.39	10.42	22.19	Vertical	Pass
	1	0	Highest	14.13	2.40	10.44	22.17	Vertical	Pass
16QAM	1	0	Lowest	12.39	2.37	10.40	20.42	Horizontal	Pass
	1	0	Middle	12.59	2.39	10.42	20.62	Horizontal	Pass
	1	0	Highest	12.47	2.40	10.44	20.51	Horizontal	Pass
	1	0	Lowest	13.74	2.37	10.40	21.77	Vertical	Pass
	1	0	Middle	13.93	2.39	10.42	21.96	Vertical	Pass
	1	0	Highest	13.82	2.40	10.44	21.86	Vertical	Pass
Limit	EIRP<2W=33dBm								



Radiated Power (ERP) for LTE Band 26(Part 22) / 1.4M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15.53	2.35	10.13	2.15	21.16	Horizontal	Pass
	1	0	Middle	15.3	2.36	10.16	2.15	20.95	Horizontal	Pass
	1	0	Highest	15.44	2.37	10.22	2.15	21.14	Horizontal	Pass
	1	0	Lowest	16.9	2.35	10.13	2.15	22.53	Vertical	Pass
	1	0	Middle	16.72	2.36	10.16	2.15	22.37	Vertical	Pass
	1	0	Highest	16.83	2.37	10.22	2.15	22.53	Vertical	Pass
16QAM	1	0	Lowest	15.2	2.35	10.13	2.15	20.83	Horizontal	Pass
	1	0	Middle	15.11	2.36	10.16	2.15	20.76	Horizontal	Pass
	1	0	Highest	15.14	2.37	10.22	2.15	20.84	Horizontal	Pass
	1	0	Lowest	16.56	2.35	10.13	2.15	22.19	Vertical	Pass
	1	0	Middle	16.53	2.36	10.16	2.15	22.18	Vertical	Pass
	1	0	Highest	16.5	2.37	10.22	2.15	22.20	Vertical	Pass
Limit	ERP<7W=38.45dBm									

Radiated Power (ERP) for LTE Band 26(Part 22) / 3M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15	2.35	10.13	2.15	20.63	Horizontal	Pass
	1	0	Middle	15.07	2.36	10.16	2.15	20.72	Horizontal	Pass
	1	0	Highest	15.28	2.37	10.22	2.15	20.98	Horizontal	Pass
	1	0	Lowest	16.44	2.35	10.13	2.15	22.07	Vertical	Pass
	1	0	Middle	16.55	2.36	10.16	2.15	22.20	Vertical	Pass
	1	0	Highest	16.61	2.37	10.22	2.15	22.31	Vertical	Pass
16QAM	1	0	Lowest	14.81	2.35	10.13	2.15	20.44	Horizontal	Pass
	1	0	Middle	14.82	2.36	10.16	2.15	20.47	Horizontal	Pass
	1	0	Highest	14.91	2.37	10.22	2.15	20.61	Horizontal	Pass
	1	0	Lowest	16.19	2.35	10.13	2.15	21.82	Vertical	Pass
	1	0	Middle	16.26	2.36	10.16	2.15	21.91	Vertical	Pass
	1	0	Highest	16.38	2.37	10.22	2.15	22.08	Vertical	Pass
Limit	ERP<7W=38.45dBm									



Radiated Power (ERP) for LTE Band 26(Part 22) / 5M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15.27	2.35	10.13	2.15	20.90	Horizontal	Pass
	1	0	Middle	15.4	2.36	10.16	2.15	21.05	Horizontal	Pass
	1	0	Highest	15.4	2.37	10.22	2.15	21.10	Horizontal	Pass
	1	0	Lowest	16.59	2.35	10.13	2.15	22.22	Vertical	Pass
	1	0	Middle	16.72	2.36	10.16	2.15	22.37	Vertical	Pass
	1	0	Highest	16.72	2.37	10.22	2.15	22.42	Vertical	Pass
16QAM	1	0	Lowest	14.82	2.35	10.13	2.15	20.45	Horizontal	Pass
	1	0	Middle	15.05	2.36	10.16	2.15	20.70	Horizontal	Pass
	1	0	Highest	15.01	2.37	10.22	2.15	20.71	Horizontal	Pass
	1	0	Lowest	16.31	2.35	10.13	2.15	21.94	Vertical	Pass
	1	0	Middle	16.45	2.36	10.16	2.15	22.10	Vertical	Pass
	1	0	Highest	16.44	2.37	10.22	2.15	22.14	Vertical	Pass
Limit	ERP<7W=38.45dBm									

Radiated Power (ERP) for LTE Band 26(Part 22) / 10M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15	2.35	10.13	2.15	20.63	Horizontal	Pass
	1	0	Middle	15.13	2.36	10.16	2.15	20.78	Horizontal	Pass
	1	0	Highest	14.61	2.37	10.22	2.15	20.31	Horizontal	Pass
	1	0	Lowest	16.48	2.35	10.13	2.15	22.11	Vertical	Pass
	1	0	Middle	16.44	2.36	10.16	2.15	22.09	Vertical	Pass
	1	0	Highest	16.03	2.37	10.22	2.15	21.73	Vertical	Pass
16QAM	1	0	Lowest	14.82	2.35	10.13	2.15	20.45	Horizontal	Pass
	1	0	Middle	14.87	2.36	10.16	2.15	20.52	Horizontal	Pass
	1	0	Highest	14.3	2.37	10.22	2.15	20.00	Horizontal	Pass
	1	0	Lowest	16.18	2.35	10.13	2.15	21.81	Vertical	Pass
	1	0	Middle	16.22	2.36	10.16	2.15	21.87	Vertical	Pass
	1	0	Highest	15.78	2.37	10.22	2.15	21.48	Vertical	Pass
Limit	ERP<7W=38.45dBm									



Radiated Power (ERP) for LTE Band 26(Part 22) / 15M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15.59	2.35	10.13	2.15	21.22	Horizontal	Pass
	1	0	Middle	15.39	2.36	10.16	2.15	21.04	Horizontal	Pass
	1	0	Highest	15.41	2.37	10.22	2.15	21.11	Horizontal	Pass
	1	0	Lowest	16.94	2.35	10.13	2.15	22.57	Vertical	Pass
	1	0	Middle	16.83	2.36	10.16	2.15	22.48	Vertical	Pass
	1	0	Highest	16.87	2.37	10.22	2.15	22.57	Vertical	Pass
16QAM	1	0	Lowest	15.13	2.35	10.13	2.15	20.76	Horizontal	Pass
	1	0	Middle	15.19	2.36	10.16	2.15	20.84	Horizontal	Pass
	1	0	Highest	15.14	2.37	10.22	2.15	20.84	Horizontal	Pass
	1	0	Lowest	16.57	2.35	10.13	2.15	22.20	Vertical	Pass
	1	0	Middle	16.62	2.36	10.16	2.15	22.27	Vertical	Pass
	1	0	Highest	16.61	2.37	10.22	2.15	22.31	Vertical	Pass
Limit	ERP<7W=38.45dBm									



Radiated Power (ERP) for LTE Band 26(Part 90) / 1.4M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15.63	2.35	10.13	2.15	21.26	Horizontal	Pass
	1	0	Middle	15.48	2.36	10.16	2.15	21.13	Horizontal	Pass
	1	0	Highest	15.52	2.37	10.22	2.15	21.22	Horizontal	Pass
	1	0	Lowest	16.99	2.35	10.13	2.15	22.62	Vertical	Pass
	1	0	Middle	16.88	2.36	10.16	2.15	22.53	Vertical	Pass
	1	0	Highest	16.92	2.37	10.22	2.15	22.62	Vertical	Pass
16QAM	1	0	Lowest	15.25	2.35	10.13	2.15	20.88	Horizontal	Pass
	1	0	Middle	15.26	2.36	10.16	2.15	20.91	Horizontal	Pass
	1	0	Highest	15.24	2.37	10.22	2.15	20.94	Horizontal	Pass
	1	0	Lowest	16.69	2.35	10.13	2.15	22.32	Vertical	Pass
	1	0	Middle	16.57	2.36	10.16	2.15	22.22	Vertical	Pass
	1	0	Highest	16.64	2.37	10.22	2.15	22.34	Vertical	Pass
Limit	ERP<100W=50dBm									

Radiated Power (ERP) for LTE Band 26(Part 90) / 3M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15.73	2.35	10.13	2.15	21.36	Horizontal	Pass
	1	0	Middle	15.52	2.36	10.16	2.15	21.17	Horizontal	Pass
	1	0	Highest	15.59	2.37	10.22	2.15	21.29	Horizontal	Pass
	1	0	Lowest	17.04	2.35	10.13	2.15	22.67	Vertical	Pass
	1	0	Middle	16.98	2.36	10.16	2.15	22.63	Vertical	Pass
	1	0	Highest	16.89	2.37	10.22	2.15	22.59	Vertical	Pass
16QAM	1	0	Lowest	15.44	2.35	10.13	2.15	21.07	Horizontal	Pass
	1	0	Middle	15.25	2.36	10.16	2.15	20.90	Horizontal	Pass
	1	0	Highest	15.25	2.37	10.22	2.15	20.95	Horizontal	Pass
	1	0	Lowest	16.86	2.35	10.13	2.15	22.49	Vertical	Pass
	1	0	Middle	16.72	2.36	10.16	2.15	22.37	Vertical	Pass
	1	0	Highest	16.7	2.37	10.22	2.15	22.40	Vertical	Pass
Limit	ERP<100W=50dBm									



Radiated Power (ERP) for LTE Band 26(Part 90) / 5M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Lowest	15.84	2.35	10.13	2.15	21.47	Horizontal	Pass
	1	0	Middle	15.67	2.36	10.16	2.15	21.32	Horizontal	Pass
	1	0	Highest	15.56	2.37	10.22	2.15	21.26	Horizontal	Pass
	1	0	Lowest	17.15	2.35	10.13	2.15	22.78	Vertical	Pass
	1	0	Middle	16.99	2.36	10.16	2.15	22.64	Vertical	Pass
	1	0	Highest	17.05	2.37	10.22	2.15	22.75	Vertical	Pass
16QAM	1	0	Lowest	15.52	2.35	10.13	2.15	21.15	Horizontal	Pass
	1	0	Middle	15.4	2.36	10.16	2.15	21.05	Horizontal	Pass
	1	0	Highest	15.44	2.37	10.22	2.15	21.14	Horizontal	Pass
	1	0	Lowest	16.88	2.35	10.13	2.15	22.51	Vertical	Pass
	1	0	Middle	16.85	2.36	10.16	2.15	22.50	Vertical	Pass
	1	0	Highest	16.74	2.37	10.22	2.15	22.44	Vertical	Pass
Limit	ERP<100W=50dBm									

Radiated Power (ERP) for LTE Band 26(Part 90) / 10M										
Modulation	RB		Channel	Result						Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	correction factor(dB)	PMeas E.R.P(dBm)	Polarization Of Max. ERP	
QPSK	1	0	Middle	15.97	2.36	10.16	2.15	21.62	Horizontal	Pass
	1	0	Middle	17.21	2.36	10.16	2.15	22.86	Vertical	Pass
16QAM	1	0	Middle	15.61	2.36	10.16	2.15	21.26	Horizontal	Pass
	1	0	Middle	16.83	2.36	10.16	2.15	22.48	Vertical	Pass
Limit	ERP<100W=50dBm									



Radiated Power (EIRP) for LTE Band 41 / 15M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.14	2.56	10.60	20.18	Horizontal	Pass
	1	0	Middle	11.97	2.67	10.65	19.95	Horizontal	Pass
	1	0	Highest	12.23	2.72	10.70	20.21	Horizontal	Pass
	1	0	Lowest	13.51	2.56	10.60	21.55	Vertical	Pass
	1	0	Middle	13.45	2.67	10.65	21.43	Vertical	Pass
	1	0	Highest	13.59	2.72	10.70	21.57	Vertical	Pass
16QAM	1	0	Lowest	11.81	2.56	10.60	19.85	Horizontal	Pass
	1	0	Middle	11.71	2.67	10.65	19.69	Horizontal	Pass
	1	0	Highest	12.1	2.72	10.70	20.08	Horizontal	Pass
	1	0	Lowest	13.16	2.56	10.60	21.20	Vertical	Pass
	1	0	Middle	13.2	2.67	10.65	21.18	Vertical	Pass
	1	0	Highest	13.45	2.72	10.70	21.43	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 41 / 20M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.28	2.56	10.60	20.32	Horizontal	Pass
	1	0	Middle	12.58	2.67	10.65	20.56	Horizontal	Pass
	1	0	Highest	12.56	2.72	10.70	20.54	Horizontal	Pass
	1	0	Lowest	13.72	2.56	10.60	21.76	Vertical	Pass
	1	0	Middle	13.96	2.67	10.65	21.94	Vertical	Pass
	1	0	Highest	13.88	2.72	10.70	21.86	Vertical	Pass
16QAM	1	0	Lowest	11.96	2.56	10.60	20.00	Horizontal	Pass
	1	0	Middle	12.29	2.67	10.65	20.27	Horizontal	Pass
	1	0	Highest	12.18	2.72	10.70	20.16	Horizontal	Pass
	1	0	Lowest	13.31	2.56	10.60	21.35	Vertical	Pass
	1	0	Middle	13.65	2.67	10.65	21.63	Vertical	Pass
	1	0	Highest	13.55	2.72	10.70	21.53	Vertical	Pass
Limit	EIRP<2W=33dBm								

Radiated Power (EIRP) for LTE Band 66 / 1.4M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.42	2.35	10.13	20.20	Horizontal	Pass
	1	0	Middle	12.3	2.36	10.16	20.10	Horizontal	Pass
	1	0	Highest	12.2	2.37	10.22	20.05	Horizontal	Pass
	1	0	Lowest	13.8	2.35	10.13	21.58	Vertical	Pass
	1	0	Middle	13.76	2.36	10.16	21.56	Vertical	Pass
	1	0	Highest	13.66	2.37	10.22	21.51	Vertical	Pass
16QAM	1	0	Lowest	12.09	2.35	10.13	19.87	Horizontal	Pass
	1	0	Middle	12.09	2.36	10.16	19.89	Horizontal	Pass
	1	0	Highest	12.03	2.37	10.22	19.88	Horizontal	Pass
	1	0	Lowest	13.47	2.35	10.13	21.25	Vertical	Pass
	1	0	Middle	13.49	2.36	10.16	21.29	Vertical	Pass
	1	0	Highest	13.44	2.37	10.22	21.29	Vertical	Pass
Limit	EIRP<1W=30dBm								



Radiated Power (EIRP) for LTE Band 66 / 3M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.06	2.35	10.13	19.84	Horizontal	Pass
	1	0	Middle	12.2	2.36	10.16	20.00	Horizontal	Pass
	1	0	Highest	12.13	2.37	10.22	19.98	Horizontal	Pass
	1	0	Lowest	13.48	2.35	10.13	21.26	Vertical	Pass
	1	0	Middle	13.66	2.36	10.16	21.46	Vertical	Pass
	1	0	Highest	13.55	2.37	10.22	21.40	Vertical	Pass
16QAM	1	0	Lowest	11.94	2.35	10.13	19.72	Horizontal	Pass
	1	0	Middle	11.91	2.36	10.16	19.71	Horizontal	Pass
	1	0	Highest	11.8	2.37	10.22	19.65	Horizontal	Pass
	1	0	Lowest	13.32	2.35	10.13	21.10	Vertical	Pass
	1	0	Middle	13.4	2.36	10.16	21.20	Vertical	Pass
	1	0	Highest	13.23	2.37	10.22	21.08	Vertical	Pass
Limit	EIRP<1W=30dBm								

Radiated Power (EIRP) for LTE Band 66 / 5M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.16	2.35	10.13	19.94	Horizontal	Pass
	1	0	Middle	12.23	2.36	10.16	20.03	Horizontal	Pass
	1	0	Highest	12.14	2.37	10.22	19.99	Horizontal	Pass
	1	0	Lowest	13.62	2.35	10.13	21.40	Vertical	Pass
	1	0	Middle	13.56	2.36	10.16	21.36	Vertical	Pass
	1	0	Highest	13.46	2.37	10.22	21.31	Vertical	Pass
16QAM	1	0	Lowest	11.83	2.35	10.13	19.61	Horizontal	Pass
	1	0	Middle	11.86	2.36	10.16	19.66	Horizontal	Pass
	1	0	Highest	11.86	2.37	10.22	19.71	Horizontal	Pass
	1	0	Lowest	13.32	2.35	10.13	21.10	Vertical	Pass
	1	0	Middle	13.33	2.36	10.16	21.13	Vertical	Pass
	1	0	Highest	13.25	2.37	10.22	21.10	Vertical	Pass
Limit	EIRP<1W=30dBm								

Radiated Power (EIRP) for LTE Band 66 / 10M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.06	2.35	10.13	19.84	Horizontal	Pass
	1	0	Middle	11.85	2.36	10.16	19.65	Horizontal	Pass
	1	0	Highest	11.8	2.37	10.22	19.65	Horizontal	Pass
	1	0	Lowest	13.48	2.35	10.13	21.26	Vertical	Pass
	1	0	Middle	13.28	2.36	10.16	21.08	Vertical	Pass
	1	0	Highest	13.27	2.37	10.22	21.12	Vertical	Pass
16QAM	1	0	Lowest	11.77	2.35	10.13	19.55	Horizontal	Pass
	1	0	Middle	11.6	2.36	10.16	19.40	Horizontal	Pass
	1	0	Highest	11.68	2.37	10.22	19.53	Horizontal	Pass
	1	0	Lowest	13.17	2.35	10.13	20.95	Vertical	Pass
	1	0	Middle	13.02	2.36	10.16	20.82	Vertical	Pass
	1	0	Highest	13.16	2.37	10.22	21.01	Vertical	Pass
Limit	EIRP<1W=30dBm								



Radiated Power (EIRP) for LTE Band 66 / 15M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.06	2.35	10.13	19.84	Horizontal	Pass
	1	0	Middle	12.13	2.36	10.16	19.93	Horizontal	Pass
	1	0	Highest	12.25	2.37	10.22	20.10	Horizontal	Pass
	1	0	Lowest	13.53	2.35	10.13	21.31	Vertical	Pass
	1	0	Middle	13.56	2.36	10.16	21.36	Vertical	Pass
	1	0	Highest	13.7	2.37	10.22	21.55	Vertical	Pass
16QAM	1	0	Lowest	12.05	2.35	10.13	19.83	Horizontal	Pass
	1	0	Middle	11.9	2.36	10.16	19.70	Horizontal	Pass
	1	0	Highest	11.84	2.37	10.22	19.69	Horizontal	Pass
	1	0	Lowest	13.37	2.35	10.13	21.15	Vertical	Pass
	1	0	Middle	13.37	2.36	10.16	21.17	Vertical	Pass
	1	0	Highest	13.33	2.37	10.22	21.18	Vertical	Pass
Limit	EIRP<1W=30dBm								

Radiated Power (EIRP) for LTE Band 66 / 20M									
Modulation	RB		Channel	Result					Conclusion
	Size	Offset		S G.Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max. EIRP	
QPSK	1	0	Lowest	12.57	2.35	10.13	20.35	Horizontal	Pass
	1	0	Middle	12.56	2.36	10.16	20.36	Horizontal	Pass
	1	0	Highest	12.36	2.37	10.22	20.21	Horizontal	Pass
	1	0	Lowest	13.92	2.35	10.13	21.70	Vertical	Pass
	1	0	Middle	13.91	2.36	10.16	21.71	Vertical	Pass
	1	0	Highest	13.85	2.37	10.22	21.70	Vertical	Pass
16QAM	1	0	Lowest	12.31	2.35	10.13	20.09	Horizontal	Pass
	1	0	Middle	12.24	2.36	10.16	20.04	Horizontal	Pass
	1	0	Highest	12.07	2.37	10.22	19.92	Horizontal	Pass
	1	0	Lowest	13.76	2.35	10.13	21.54	Vertical	Pass
	1	0	Middle	13.69	2.36	10.16	21.49	Vertical	Pass
	1	0	Highest	13.49	2.37	10.22	21.34	Vertical	Pass
Limit	EIRP<1W=30dBm								

6. OCCUPIED BANDWIDTH


6.1 DESCRIPTION OF OCCUPIED BANDWIDTH MEASUREMENT

6.1.1 MEASUREMENT METHOD

1.The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

2.The 26 db emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 db below the maximum in-band spectral density of the modulated signal. spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

6.1.2 TEST SETUP



6.1.3 TEST PROCEDURES

1. The testing follows FCC KDB 971168 D01 v03r01 Section 4.2 and 4.3.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Set the test probe and measure the Occupied Bandwidth of the spectrum analyzer.
5. Measure and record the Occupied Bandwidth from the Spectrum Analyzer.

	LTE					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	30kHz	100kHz	100kHz	300kHz	300kHz
VBW	100kHz	100kHz	300kHz	300kHz	1000kHz	1000kHz
Detector	PK	PK	PK	PK	PK	PK
Trace	Max	Max	Max	Max	Max	Max
Sweep Count	Auto	Auto	Auto	Auto	Auto	Auto



6.1.4 MEASUREMENT RESULT

LTE Band 2 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.0969	1.311	1.1048	1.287	1.0952	1.303
1.4	16-QAM	1.102	1.31	1.093	1.277	1.097	1.301
3	QPSK	2.689	2.921	2.683	2.925	2.683	2.925
3	16-QAM	2.682	2.953	2.6812	2.929	2.679	2.932
5	QPSK	4.505	5.027	4.502	4.991	4.518	5.006
5	16-QAM	4.5	5.024	4.533	5.044	4.5084	5.039
10	QPSK	8.912	9.626	8.93	9.732	8.907	9.626
10	16-QAM	8.912	9.61	8.927	9.637	8.9	9.61
15	QPSK	13.367	14.54	13.431	14.66	13.446	14.65
15	16-QAM	13.422	14.58	13.438	14.58	13.44	14.63
20	QPSK	17.832	19.12	17.875	19.35	17.883	19.24
20	16-QAM	17.875	19.22	17.858	19.29	17.899	19.3

LTE Band 4 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.1	1.321	1.1046	1.284	1.096	1.305
1.4	16-QAM	1.0991	1.312	1.094	1.272	1.095	1.32
3	QPSK	2.686	2.92	2.683	2.938	2.6831	2.926
3	16-QAM	2.683	2.942	2.682	2.934	2.68	2.923
5	QPSK	4.508	5.025	4.5	4.991	4.517	5.019
5	16-QAM	4.504	5.013	4.526	5.023	4.5198	5.033
10	QPSK	8.915	9.641	8.93	9.649	8.934	9.75
10	16-QAM	8.92	9.584	8.926	9.667	8.926	9.634
15	QPSK	13.378	14.57	13.436	14.77	13.447	14.83
15	16-QAM	13.43	14.59	13.458	14.65	13.444	14.75
20	QPSK	17.815	19.11	17.898	19.41	17.865	19.115
20	16-QAM	17.877	19.21	17.891	19.35	17.861	19.27

LTE Band 5 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.0989	1.304	1.108	1.292	1.098	1.327
1.4	16-QAM	1.099	1.307	1.094	1.285	1.099	1.291
3	QPSK	2.6833	2.914	2.69	2.942	2.684	2.932
3	16-QAM	2.681	2.926	2.681	2.942	2.6776	2.925
5	QPSK	4.507	5.023	4.498	5.025	4.504	4.981
5	16-QAM	4.502	5.01	4.526	4.988	4.501	4.99
10	QPSK	8.914	9.609	8.907	9.611	8.902	9.636
10	16-QAM	8.916	9.547	8.914	9.591	8.899	9.608



LTE Band 12 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.0986	1.313	1.106	1.286	1.0971	1.307
1.4	16-QAM	1.098	1.304	1.094	1.276	1.0969	1.296
3	QPSK	2.68	2.916	2.6892	2.921	2.684	2.938
3	16-QAM	2.679	2.927	2.682	2.95	2.683	2.924
5	QPSK	4.498	4.988	4.505	5.002	4.521	5.019
5	16-QAM	4.493	4.97	4.534	5.038	4.514	5.028
10	QPSK	8.914	9.609	8.947	9.738	8.908	9.676
10	16-QAM	8.918	9.611	8.94	9.665	8.901	9.595
LTE Band 13 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
5	QPSK	4.531	5.032	4.516	5.02	4.5	4.984
5	16-QAM	4.531	5.065	4.5099	5.014	4.521	5.038
10	QPSK	N/A	N/A	8.966	9.758	N/A	N/A
10	16-QAM	N/A	N/A	8.946	9.758	N/A	N/A
LTE Band 25 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.101	1.316	1.104	1.281	1.0967	1.296
1.4	16-QAM	1.0926	1.278	1.0966	1.303	1.03	1.325
3	QPSK	2.689	2.924	2.684	2.927	2.686	2.93
3	16-QAM	2.6833	2.936	2.6814	2.928	2.685	2.923
5	QPSK	4.506	5.005	4.495	4.997	4.531	5.01
5	16-QAM	4.525	5.01	4.524	5.058	4.5122	5.019
10	QPSK	8.912	9.721	8.905	9.669	8.903	9.628
10	16-QAM	8.903	9.565	8.922	9.651	8.895	9.593
15	QPSK	13.368	14.53	13.422	14.67	13.371	14.63
15	16-QAM	13.406	14.55	13.408	14.68	13.369	14.52
20	QPSK	17.803	19.13	17.845	19.31	17.798	18.95
20	16-QAM	17.838	19.17	17.808	19.17	17.832	19.04
LTE Band 26(Part 22) Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.096	1.311	1.0985	1.341	1.108	1.288
1.4	16-QAM	1.1	1.308	1.095	1.29	1.1	1.32
3	QPSK	2.683	2.922	2.684	2.945	2.682	2.933
3	16-QAM	2.681	2.913	2.681	2.939	2.68	2.914
5	QPSK	4.509	5.008	4.499	5.014	4.5	4.977
5	16-QAM	4.504	5.008	4.53	5.021	4.509	5
10	QPSK	8.916	9.608	8.904	9.601	8.918	9.7
10	16-QAM	8.905	9.533	8.918	9.583	8.903	9.6
15	QPSK	13.364	14.55	13.426	14.64	13.443	14.67
15	16-QAM	13.378	14.56	13.445	14.59	13.48	14.67



LTE Band 26(Part 90) Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.096	1.312	1.104	1.293	1.0968	1.325
1.4	16-QAM	1.094	1.293	1.097	1.311	1.0992	1.305
3	QPSK	2.687	2.914	2.681	2.946	2.683	2.931
3	16-QAM	2.68	2.939	2.68	2.927	2.6791	2.939
5	QPSK	4.501	5.005	4.502	5.019	4.527	5.017
5	4.5084	4.5084	5.008	4.5259	5.027	4.506	5.017
10	QPSK	N/A	N/A	8.923	9.747	N/A	N/A
10	16-QAM	N/A	N/A	8.9253	11.77	N/A	N/A
LTE Band 41 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
5	QPSK	4.52	4.996	4.502	5	4.501	5.021
5	16-QAM	4.505	5.096	4.511	5.06	4.5019	4.958
10	QPSK	8.932	10.05	8.9352	9.759	8.924	9.664
10	16-QAM	8.939	9.598	8.924	9.507	8.91	9.623
15	QPSK	13.439	14.63	13.439	16.39	13.472	15.35
15	16-QAM	13.49	15.24	13.482	14.79	13.45	14.66
20	QPSK	17.876	19.32	17.865	19.82	17.899	19.08
20	16-QAM	17.873	20.24	17.85	19.93	17.864	19.22
LTE Band 66 Bandwidth [MHz]							
BW [MHz]	Mode	Lowest		Middle		Highest	
		99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
1.4	QPSK	1.106	1.285	1.0948	1.295	1.1005	1.325
1.4	16-QAM	1.093	1.315	1.093	1.275	1.098	1.327
3	QPSK	2.689	2.926	2.684	2.941	2.6833	2.918
3	16-QAM	2.6812	2.948	2.6812	2.917	2.68	2.946
5	QPSK	4.504	4.988	4.501	4.996	4.524	5.02
5	16-QAM	4.5	5.009	4.527	5.034	4.531	5.039
10	QPSK	8.912	9.612	8.93	9.678	8.933	9.771
10	16-QAM	8.911	9.666	8.918	9.633	8.93	9.666
15	QPSK	13.378	14.54	13.422	14.77	13.437	14.76
15	16-QAM	13.416	14.65	13.442	14.67	13.43	14.72
20	QPSK	17.824	19.17	17.889	19.46	17.835	19.14
20	16-QAM	17.87	19.3	17.877	19.37	17.807	19.21

Note: Test chart See Appendix A



7. CONDUCTED BAND EDGE

7.1 DESCRIPTION OF CONDUCTED BAND EDGE MEASUREMENT

7.1.1 MEASUREMENT METHOD

1. §22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

2. §24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed

3. §27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4. §27.53(m)(4)

For operations in the 2496 MHz ~ 2690 MHz band this section, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.


5. §27.53 (g)

For operations in the 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

6. §90.691 (a)

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

7.1.2 TEST SETUP



7.1.3 TEST PROCEDURES

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0 and ANSI C63.26 2015 Section 5.7.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Set spectrum analyzer with RMS/AVG detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.

	LTE					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	12MHz	13MHz	15MHz	20MHz	25MHz	30MHz
RBW	30kHz	30kHz	100kHz	100kHz	300kHz	300kHz
VBW	100kHz	100kHz	300kHz	300kHz	1000kHz	1000kHz
Detector	RMS	RMS	RMS	RMS	RMS	RMS
Trace	Max	Max	Max	Max	Max	Max
Sweep Count	Auto	Auto	Auto	Auto	Auto	Auto

7.1.4 MEASUREMENT RESULT

Note: Test chart See Appendix B

8. CONDUCTED SPURIOUS EMISSION


8.1 DESCRIPTION OF CONDUCTED SPURIOUS EMISSION MEASUREMENT

8.1.1 MEASUREMENT METHOD

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

8.1.2 TEST SETUP



8.1.3 TEST PROCEDURES

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0 and ANSI C63.26 2015 Section 5.7.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)} = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

	LTE					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	Auto	Auto	Auto	Auto	Auto	Auto
RBW	1000kHz	1000kHz	1000kHz	1000kHz	1000kHz	1000kHz
VBW	3000kHz	3000kHz	3000kHz	3000kHz	3000kHz	3000kHz
Detector	PK	PK	PK	PK	PK	PK
Trace	Max	Max	Max	Max	Max	Max

8.1.4 TEST RESULTS

Note: Test chart See Appendix C

9. RADIATED SPURIOUS EMISSION

9.1 DESCRIPTION OF RADIATED SPURIOUS EMISSION

9.1.1 MEASUREMENT METHOD

The radiated spurious emission was measured by substitution method according to ANSI C63.26 2015. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

9.1.2 TEST SETUP

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, $RSE = Rx \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + Gain \text{ (dBi)} - 107 \text{ (dBuV to dBm)}$ The SA is calibrated using following setup.


b) EUT was placed on 1.5 m non-conductive stand at a 3 m test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 m from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic measured with peak detector and 1MHz bandwidth.

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.


The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below:

Power=PMea+ARpl

For radiated test from 30MHz to 1GHz



For radiated test from above 1GHz



9.1.3 TEST PROCEDURES

1. The testing FCC KDB 971168 D01 Section 7 and ANSI C63.26 2015 Section 5.5.
2. The EUT was placed on a rotatable wooden table with 1.5 meter above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)\text{dB}$ below the transmitter power $P(\text{Watts})$

$$= P(\text{W}) - [43 + 10\log(P)] (\text{dB})$$

$$= [30 + 10\log(P)] (\text{dBm}) - [43 + 10\log(P)] (\text{dB})$$

$$= -13\text{dBm}$$



9.1.4 TEST RESULTS

LTE Band 2 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3703.88	-33.77	12.60	12.93	-34.10	-13.00	-21.10	H
5557.27	-34.92	13.10	17.11	-38.93	-13.00	-25.93	H
7409.51	-32.88	11.50	22.20	-43.58	-13.00	-30.58	H
3703.88	-34.98	12.60	12.93	-35.31	-13.00	-22.31	V
5557.27	-34.30	13.10	17.11	-38.31	-13.00	-25.31	V
7409.51	-32.41	11.50	22.20	-43.11	-13.00	-30.11	V
LTE Band 2 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.52	-34.39	12.60	12.93	-34.72	-13.00	-21.72	H
5639.51	-34.82	13.10	17.11	-38.83	-13.00	-25.83	H
7520.10	-33.15	11.50	22.20	-43.85	-13.00	-30.85	H
3759.52	-35.08	12.60	12.93	-35.41	-13.00	-22.41	V
5639.51	-34.21	13.10	17.11	-38.22	-13.00	-25.22	V
7520.10	-33.04	11.50	22.20	-43.74	-13.00	-30.74	V
LTE Band 2 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3817.92	-33.92	12.60	12.93	-34.25	-13.00	-21.25	H
5727.36	-35.46	13.10	17.11	-39.47	-13.00	-26.47	H
7636.56	-33.37	11.50	22.20	-44.07	-13.00	-31.07	H
3817.92	-34.82	12.60	12.93	-35.15	-13.00	-22.15	V
5727.36	-34.56	13.10	17.11	-38.57	-13.00	-25.57	V
7636.56	-32.71	11.50	22.20	-43.41	-13.00	-30.41	V



LTE Band 2 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3703.66	-34.89	12.60	12.93	-35.22	-13.00	-22.22	H
5557.33	-34.55	13.10	17.11	-38.56	-13.00	-25.56	H
7409.77	-33.27	11.50	22.20	-43.97	-13.00	-30.97	H
3703.66	-35.41	12.60	12.93	-35.74	-13.00	-22.74	V
5557.33	-35.00	13.10	17.11	-39.01	-13.00	-26.01	V
7409.77	-32.41	11.50	22.20	-43.11	-13.00	-30.11	V
LTE Band 2 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.58	-34.57	12.60	12.93	-34.90	-13.00	-21.90	H
5639.41	-34.93	13.10	17.11	-38.94	-13.00	-25.94	H
7520.16	-32.18	11.50	22.20	-42.88	-13.00	-29.88	H
3759.58	-34.93	12.60	12.93	-35.26	-13.00	-22.26	V
5639.41	-34.65	13.10	17.11	-38.66	-13.00	-25.66	V
7520.16	-32.93	11.50	22.20	-43.63	-13.00	-30.63	V
LTE Band 2 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3818.27	-34.06	12.60	12.93	-34.39	-13.00	-21.39	H
5727.50	-35.10	13.10	17.11	-39.11	-13.00	-26.11	H
7636.61	-33.33	11.50	22.20	-44.03	-13.00	-31.03	H
3818.27	-35.92	12.60	12.93	-36.25	-13.00	-23.25	V
5727.50	-33.81	13.10	17.11	-37.82	-13.00	-24.82	V
7636.61	-31.75	11.50	22.20	-42.45	-13.00	-29.45	V



LTE Band 2 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3704.95	-34.67	12.60	12.93	-35.00	-13.00	-22.00	H
5557.78	-34.75	13.10	17.11	-38.76	-13.00	-25.76	H
7410.23	-32.41	11.50	22.20	-43.11	-13.00	-30.11	H
3704.95	-34.55	12.60	12.93	-34.88	-13.00	-21.88	V
5557.78	-33.79	13.10	17.11	-37.80	-13.00	-24.80	V
7410.23	-32.01	11.50	22.20	-42.71	-13.00	-29.71	V
LTE Band 2 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.84	-34.50	12.60	12.93	-34.83	-13.00	-21.83	H
5639.63	-34.45	13.10	17.11	-38.46	-13.00	-25.46	H
7519.96	-33.65	11.50	22.20	-44.35	-13.00	-31.35	H
3759.84	-34.85	12.60	12.93	-35.18	-13.00	-22.18	V
5639.63	-34.30	13.10	17.11	-38.31	-13.00	-25.31	V
7519.96	-32.01	11.50	22.20	-42.71	-13.00	-29.71	V
LTE Band 2 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3813.97	-34.87	12.60	12.93	-35.20	-13.00	-22.20	H
5721.34	-34.54	13.10	17.11	-38.55	-13.00	-25.55	H
7628.78	-32.56	11.50	22.20	-43.26	-13.00	-30.26	H
3813.97	-35.81	12.60	12.93	-36.14	-13.00	-23.14	V
5721.34	-34.30	13.10	17.11	-38.31	-13.00	-25.31	V
7628.78	-33.14	11.50	22.20	-43.84	-13.00	-30.84	V



LTE Band 2 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3710.21	-34.91	12.60	12.93	-35.24	-13.00	-22.24	H
5565.73	-34.15	13.10	17.11	-38.16	-13.00	-25.16	H
7420.98	-32.67	11.50	22.20	-43.37	-13.00	-30.37	H
3710.21	-35.00	12.60	12.93	-35.33	-13.00	-22.33	V
5565.73	-33.95	13.10	17.11	-37.96	-13.00	-24.96	V
7420.98	-32.67	11.50	22.20	-43.37	-13.00	-30.37	V
LTE Band 2 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.89	-33.67	12.60	12.93	-34.00	-13.00	-21.00	H
5639.61	-34.79	13.10	17.11	-38.80	-13.00	-25.80	H
7519.98	-32.30	11.50	22.20	-43.00	-13.00	-30.00	H
3759.89	-34.63	12.60	12.93	-34.96	-13.00	-21.96	V
5639.61	-34.66	13.10	17.11	-38.67	-13.00	-25.67	V
7519.98	-33.18	11.50	22.20	-43.88	-13.00	-30.88	V
LTE Band 2 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3809.02	-33.89	12.60	12.93	-34.22	-13.00	-21.22	H
5713.58	-34.54	13.10	17.11	-38.55	-13.00	-25.55	H
7617.67	-33.63	11.50	22.20	-44.33	-13.00	-31.33	H
3809.02	-35.30	12.60	12.93	-35.63	-13.00	-22.63	V
5713.58	-34.64	13.10	17.11	-38.65	-13.00	-25.65	V
7617.67	-32.48	11.50	22.20	-43.18	-13.00	-30.18	V



LTE Band 2 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3715.93	-34.05	12.60	12.93	-34.38	-13.00	-21.38	H
5574.17	-35.43	13.10	17.11	-39.44	-13.00	-26.44	H
7618.23	-32.93	11.50	22.20	-43.63	-13.00	-30.63	H
3715.93	-35.65	12.60	12.93	-35.98	-13.00	-22.98	V
5574.17	-34.73	13.10	17.11	-38.74	-13.00	-25.74	V
7618.23	-33.00	11.50	22.20	-43.70	-13.00	-30.70	V
LTE Band 2 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.78	-34.55	12.60	12.93	-34.88	-13.00	-21.88	H
5639.57	-34.96	13.10	17.11	-38.97	-13.00	-25.97	H
7520.05	-32.63	11.50	22.20	-43.33	-13.00	-30.33	H
3759.78	-34.63	12.60	12.93	-34.96	-13.00	-21.96	V
5639.57	-34.54	13.10	17.11	-38.55	-13.00	-25.55	V
7520.05	-32.47	11.50	22.20	-43.17	-13.00	-30.17	V
LTE Band 2 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3803.28	-34.38	12.60	12.93	-34.71	-13.00	-21.71	H
5705.14	-34.87	13.10	17.11	-38.88	-13.00	-25.88	H
7606.90	-32.74	11.50	22.20	-43.44	-13.00	-30.44	H
3803.28	-34.55	12.60	12.93	-34.88	-13.00	-21.88	V
5705.14	-34.53	13.10	17.11	-38.54	-13.00	-25.54	V
7606.90	-32.73	11.50	22.20	-43.43	-13.00	-30.43	V



LTE Band 2 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3721.24	-34.33	12.60	12.93	-34.66	-13.00	-21.66	H
5580.99	-34.80	13.10	17.11	-38.81	-13.00	-25.81	H
7441.86	-33.09	11.50	22.20	-43.79	-13.00	-30.79	H
3721.24	-35.65	12.60	12.93	-35.98	-13.00	-22.98	V
5580.99	-34.06	13.10	17.11	-38.07	-13.00	-25.07	V
7441.86	-32.51	11.50	22.20	-43.21	-13.00	-30.21	V
LTE Band 2 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.59	-34.87	12.60	12.93	-35.20	-13.00	-22.20	H
5639.64	-34.20	13.10	17.11	-38.21	-13.00	-25.21	H
7519.82	-33.10	11.50	22.20	-43.80	-13.00	-30.80	H
3759.59	-34.62	12.60	12.93	-34.95	-13.00	-21.95	V
5639.64	-33.84	13.10	17.11	-37.85	-13.00	-24.85	V
7519.82	-32.17	11.50	22.20	-42.87	-13.00	-29.87	V
LTE Band 2 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3798.35	-34.80	12.60	12.93	-35.13	-13.00	-22.13	H
5697.48	-34.67	13.10	17.11	-38.68	-13.00	-25.68	H
7596.88	-32.16	11.50	22.20	-42.86	-13.00	-29.86	H
3798.35	-35.91	12.60	12.93	-36.24	-13.00	-23.24	V
5697.48	-33.90	13.10	17.11	-37.91	-13.00	-24.91	V
7596.88	-33.05	11.50	22.20	-43.75	-13.00	-30.75	V



LTE Band 4 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3421.24	-33.64	12.90	12.56	-33.30	-13.00	-20.30	H
5132.13	-35.45	13.10	16.32	-38.67	-13.00	-25.67	H
6842.54	-32.68	12.33	21.13	-41.48	-13.00	-28.48	H
3421.24	-35.19	12.90	12.56	-34.85	-13.00	-21.85	V
5132.13	-34.79	13.10	16.32	-38.01	-13.00	-25.01	V
6842.54	-32.39	12.33	21.13	-41.19	-13.00	-28.19	V
LTE Band 4 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3464.70	-34.26	12.90	12.56	-33.92	-13.00	-20.92	H
5196.72	-34.05	13.10	16.32	-37.27	-13.00	-24.27	H
6930.24	-32.66	12.33	21.13	-41.46	-13.00	-28.46	H
3464.70	-35.95	12.90	12.56	-35.61	-13.00	-22.61	V
5196.72	-34.34	13.10	16.32	-37.56	-13.00	-24.56	V
6930.24	-32.10	12.33	21.13	-40.90	-13.00	-27.90	V
LTE Band 4 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3508.41	-34.63	12.90	12.56	-34.29	-13.00	-21.29	H
5262.32	-34.06	13.10	16.32	-37.28	-13.00	-24.28	H
7015.55	-33.42	12.33	21.13	-42.22	-13.00	-29.22	H
3508.41	-35.83	12.90	12.56	-35.49	-13.00	-22.49	V
5262.32	-34.02	13.10	16.32	-37.24	-13.00	-24.24	V
7015.55	-32.74	12.33	21.13	-41.54	-13.00	-28.54	V



LTE Band 4 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3423.79	-33.78	12.90	12.56	-33.44	-13.00	-20.44	H
5135.88	-34.27	13.10	16.32	-37.49	-13.00	-24.49	H
6848.45	-32.49	12.33	21.13	-41.29	-13.00	-28.29	H
3423.79	-35.65	12.90	12.56	-35.31	-13.00	-22.31	V
5135.88	-34.95	13.10	16.32	-38.17	-13.00	-25.17	V
6848.45	-32.12	12.33	21.13	-40.92	-13.00	-27.92	V
LTE Band 4 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3464.51	-33.81	12.90	12.56	-33.47	-13.00	-20.47	H
5196.93	-34.30	13.10	16.32	-37.52	-13.00	-24.52	H
6929.71	-33.41	12.33	21.13	-42.21	-13.00	-29.21	H
3464.51	-35.79	12.90	12.56	-35.45	-13.00	-22.45	V
5196.93	-34.16	13.10	16.32	-37.38	-13.00	-24.38	V
6929.71	-33.12	12.33	21.13	-41.92	-13.00	-28.92	V
LTE Band 4 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3506.10	-33.69	12.90	12.56	-33.35	-13.00	-20.35	H
5261.95	-34.56	13.10	16.32	-37.78	-13.00	-24.78	H
7012.56	-32.49	12.33	21.13	-41.29	-13.00	-28.29	H
3506.10	-34.78	12.90	12.56	-34.44	-13.00	-21.44	V
5261.95	-35.13	13.10	16.32	-38.35	-13.00	-25.35	V
7012.56	-32.78	12.33	21.13	-41.58	-13.00	-28.58	V



LTE Band 4 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3424.66	-34.57	12.90	12.56	-34.23	-13.00	-21.23	H
5137.00	-34.65	13.10	16.32	-37.87	-13.00	-24.87	H
6849.69	-32.45	12.33	21.13	-41.25	-13.00	-28.25	H
3424.66	-35.64	12.90	12.56	-35.30	-13.00	-22.30	V
5137.00	-34.65	13.10	16.32	-37.87	-13.00	-24.87	V
6849.69	-32.27	12.33	21.13	-41.07	-13.00	-28.07	V
LTE Band 4 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3464.62	-33.84	12.90	12.56	-33.50	-13.00	-20.50	H
5196.59	-34.64	13.10	16.32	-37.86	-13.00	-24.86	H
6929.98	-33.61	12.33	21.13	-42.41	-13.00	-29.41	H
3464.62	-34.89	12.90	12.56	-34.55	-13.00	-21.55	V
5196.59	-35.05	13.10	16.32	-38.27	-13.00	-25.27	V
6929.98	-32.73	12.33	21.13	-41.53	-13.00	-28.53	V
LTE Band 4 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3505.18	-34.69	12.90	12.56	-34.35	-13.00	-21.35	H
5256.76	-34.29	13.10	16.32	-37.51	-13.00	-24.51	H
7009.81	-32.82	12.33	21.13	-41.62	-13.00	-28.62	H
3505.18	-35.45	12.90	12.56	-35.11	-13.00	-22.11	V
5256.76	-34.14	13.10	16.32	-37.36	-13.00	-24.36	V
7009.81	-32.27	12.33	21.13	-41.07	-13.00	-28.07	V



LTE Band 4 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3430.07	-33.49	12.90	12.56	-33.15	-13.00	-20.15	H
5145.40	-34.33	13.10	16.32	-37.55	-13.00	-24.55	H
6860.36	-32.91	12.33	21.13	-41.71	-13.00	-28.71	H
3430.07	-35.39	12.90	12.56	-35.05	-13.00	-22.05	V
5145.40	-34.05	13.10	16.32	-37.27	-13.00	-24.27	V
6860.36	-32.42	12.33	21.13	-41.22	-13.00	-28.22	V
LTE Band 4 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3464.37	-33.67	12.90	12.56	-33.33	-13.00	-20.33	H
5196.63	-35.12	13.10	16.32	-38.34	-13.00	-25.34	H
6929.52	-33.55	12.33	21.13	-42.35	-13.00	-29.35	H
3464.37	-34.88	12.90	12.56	-34.54	-13.00	-21.54	V
5196.63	-34.83	13.10	16.32	-38.05	-13.00	-25.05	V
6929.52	-32.06	12.33	21.13	-40.86	-13.00	-27.86	V
LTE Band 4 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3500.24	-33.59	12.90	12.56	-33.25	-13.00	-20.25	H
5250.13	-34.49	13.10	16.32	-37.71	-13.00	-24.71	H
6999.81	-32.76	12.33	21.13	-41.56	-13.00	-28.56	H
3500.24	-34.70	12.90	12.56	-34.36	-13.00	-21.36	V
5250.13	-33.87	13.10	16.32	-37.09	-13.00	-24.09	V
6999.81	-33.04	12.33	21.13	-41.84	-13.00	-28.84	V



LTE Band 4 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3434.69	-34.26	12.90	12.56	-33.92	-13.00	-20.92	H
5152.31	-34.27	13.10	16.32	-37.49	-13.00	-24.49	H
6870.64	-32.77	12.33	21.13	-41.57	-13.00	-28.57	H
3434.69	-34.94	12.90	12.56	-34.60	-13.00	-21.60	V
5152.31	-33.97	13.10	16.32	-37.19	-13.00	-24.19	V
6870.64	-32.69	12.33	21.13	-41.49	-13.00	-28.49	V
LTE Band 4 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3464.88	-33.68	12.90	12.56	-33.34	-13.00	-20.34	H
5196.68	-34.40	13.10	16.32	-37.62	-13.00	-24.62	H
6929.85	-33.52	12.33	21.13	-42.32	-13.00	-29.32	H
3464.88	-34.94	12.90	12.56	-34.60	-13.00	-21.60	V
5196.68	-33.75	13.10	16.32	-36.97	-13.00	-23.97	V
6929.85	-32.29	12.33	21.13	-41.09	-13.00	-28.09	V
LTE Band 4 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3495.49	-34.48	12.90	12.56	-34.14	-13.00	-21.14	H
5242.33	-34.60	13.10	16.32	-37.82	-13.00	-24.82	H
6990.29	-32.84	12.33	21.13	-41.64	-13.00	-28.64	H
3495.49	-35.04	12.90	12.56	-34.70	-13.00	-21.70	V
5242.33	-34.13	13.10	16.32	-37.35	-13.00	-24.35	V
6990.29	-32.82	12.33	21.13	-41.62	-13.00	-28.62	V



LTE Band 4 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3440.37	-34.09	12.90	12.56	-33.75	-13.00	-20.75	H
5160.04	-35.37	13.10	16.32	-38.59	-13.00	-25.59	H
6880.40	-32.77	12.33	21.13	-41.57	-13.00	-28.57	H
3440.37	-35.22	12.90	12.56	-34.88	-13.00	-21.88	V
5160.04	-34.26	13.10	16.32	-37.48	-13.00	-24.48	V
6880.40	-31.96	12.33	21.13	-40.76	-13.00	-27.76	V
LTE Band 4 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3464.71	-34.14	12.90	12.56	-33.80	-13.00	-20.80	H
5196.51	-34.60	13.10	16.32	-37.82	-13.00	-24.82	H
6929.69	-32.66	12.33	21.13	-41.46	-13.00	-28.46	H
3464.71	-35.00	12.90	12.56	-34.66	-13.00	-21.66	V
5196.51	-34.75	13.10	16.32	-37.97	-13.00	-24.97	V
6929.69	-32.97	12.33	21.13	-41.77	-13.00	-28.77	V
LTE Band 4 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3490.50	-34.47	12.90	12.56	-34.13	-13.00	-21.13	H
5235.15	-34.41	13.10	16.32	-37.63	-13.00	-24.63	H
6979.36	-33.20	12.33	21.13	-42.00	-13.00	-29.00	H
3490.50	-35.93	12.90	12.56	-35.59	-13.00	-22.59	V
5235.15	-33.85	13.10	16.32	-37.07	-13.00	-24.07	V
6979.36	-31.73	12.33	21.13	-40.53	-13.00	-27.53	V



LTE Band 5 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1648.72	-33.92	9.56	9.72	-34.08	-13.00	-21.08	H
2473.59	-35.37	10.50	10.86	-35.73	-13.00	-22.73	H
3298.69	-32.81	12.78	11.57	-31.60	-13.00	-18.60	H
1648.72	-34.53	9.56	9.72	-34.69	-13.00	-21.69	V
2473.59	-33.76	10.50	10.86	-34.12	-13.00	-21.12	V
3298.69	-32.95	12.78	11.57	-31.74	-13.00	-18.74	V
LTE Band 5 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.80	-34.80	9.56	9.72	-34.96	-13.00	-21.96	H
2509.17	-34.66	10.50	10.86	-35.02	-13.00	-22.02	H
3345.53	-32.58	12.78	11.57	-31.37	-13.00	-18.37	H
1672.80	-35.79	9.56	9.72	-35.95	-13.00	-22.95	V
2509.17	-33.94	10.50	10.86	-34.30	-13.00	-21.30	V
3345.53	-33.20	12.78	11.57	-31.99	-13.00	-18.99	V
LTE Band 5 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1696.25	-34.93	9.56	9.72	-35.09	-13.00	-22.09	H
2544.34	-34.71	10.50	10.86	-35.07	-13.00	-22.07	H
3393.00	-32.65	12.78	11.57	-31.44	-13.00	-18.44	H
1696.25	-35.23	9.56	9.72	-35.39	-13.00	-22.39	V
2544.34	-34.24	10.50	10.86	-34.60	-13.00	-21.60	V
3393.00	-32.69	12.78	11.57	-31.48	-13.00	-18.48	V



LTE Band 5 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1650.33	-34.01	9.56	9.72	-34.17	-13.00	-21.17	H
2475.92	-35.32	10.50	10.86	-35.68	-13.00	-22.68	H
3301.25	-33.54	12.78	11.57	-32.33	-13.00	-19.33	H
1650.33	-35.68	9.56	9.72	-35.84	-13.00	-22.84	V
2475.92	-35.15	10.50	10.86	-35.51	-13.00	-22.51	V
3301.25	-32.17	12.78	11.57	-30.96	-13.00	-17.96	V
LTE Band 5 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.40	-33.80	9.56	9.72	-33.96	-13.00	-20.96	H
2508.75	-34.35	10.50	10.86	-34.71	-13.00	-21.71	H
3345.68	-32.46	12.78	11.57	-31.25	-13.00	-18.25	N/A
1672.40	-35.10	9.56	9.72	-35.26	-13.00	-22.26	V
2508.75	-35.13	10.50	10.86	-35.49	-13.00	-22.49	V
3345.68	-32.88	12.78	11.57	-31.67	-13.00	-18.67	V
LTE Band 5 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1694.29	-34.56	9.56	9.72	-34.72	-13.00	-21.72	H
2542.09	-34.87	10.50	10.86	-35.23	-13.00	-22.23	H
3389.34	-32.96	12.78	11.57	-31.75	-13.00	-18.75	H
1694.29	-35.89	9.56	9.72	-36.05	-13.00	-23.05	V
2542.09	-35.00	10.50	10.86	-35.36	-13.00	-22.36	V
3389.34	-32.07	12.78	11.57	-30.86	-13.00	-17.86	V



LTE Band 5 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.64	-34.94	9.56	9.72	-35.10	-13.00	-22.10	H
2478.70	-35.33	10.50	10.86	-35.69	-13.00	-22.69	H
3305.65	-32.22	12.78	11.57	-31.01	-13.00	-18.01	H
1652.64	-34.55	9.56	9.72	-34.71	-13.00	-21.71	V
2478.70	-34.11	10.50	10.86	-34.47	-13.00	-21.47	V
3305.65	-32.57	12.78	11.57	-31.36	-13.00	-18.36	V
LTE Band 5 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.43	-34.07	9.56	9.72	-34.23	-13.00	-21.23	H
2508.87	-35.20	10.50	10.86	-35.56	-13.00	-22.56	H
3345.49	-32.87	12.78	11.57	-31.66	-13.00	-18.66	H
1672.43	-35.26	9.56	9.72	-35.42	-13.00	-22.42	V
2508.87	-35.16	10.50	10.86	-35.52	-13.00	-22.52	V
3345.49	-31.78	12.78	11.57	-30.57	-13.00	-17.57	V
LTE Band 5 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1692.57	-33.45	9.56	9.72	-33.61	-13.00	-20.61	H
2538.84	-34.31	10.50	10.86	-34.67	-13.00	-21.67	H
3385.73	-32.83	12.78	11.57	-31.62	-13.00	-18.62	H
1692.57	-35.88	9.56	9.72	-36.04	-13.00	-23.04	V
2538.84	-34.47	10.50	10.86	-34.83	-13.00	-21.83	V
3385.73	-32.65	12.78	11.57	-31.44	-13.00	-18.44	V



LTE Band 5 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1657.91	-33.84	9.56	9.72	-34.00	-13.00	-21.00	H
2486.09	-34.88	10.50	10.86	-35.24	-13.00	-22.24	H
3315.20	-33.58	12.78	11.57	-32.37	-13.00	-19.37	H
1657.91	-35.36	9.56	9.72	-35.52	-13.00	-22.52	V
2486.09	-34.36	10.50	10.86	-34.72	-13.00	-21.72	V
3315.20	-32.12	12.78	11.57	-30.91	-13.00	-17.91	V
LTE Band 5 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.41	-34.86	9.56	9.72	-35.02	-13.00	-22.02	H
2508.98	-35.15	10.50	10.86	-35.51	-13.00	-22.51	H
3345.24	-33.14	12.78	11.57	-31.93	-13.00	-18.93	H
1672.41	-35.06	9.56	9.72	-35.22	-13.00	-22.22	V
2508.98	-34.82	10.50	10.86	-35.18	-13.00	-22.18	V
3345.24	-32.37	12.78	11.57	-31.16	-13.00	-18.16	V
LTE Band 5 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1687.53	-34.52	9.56	9.72	-34.68	-13.00	-21.68	H
2531.60	-35.40	10.50	10.86	-35.76	-13.00	-22.76	H
3375.89	-32.16	12.78	11.57	-30.95	-13.00	-17.95	H
1687.53	-35.31	9.56	9.72	-35.47	-13.00	-22.47	V
2531.60	-34.79	10.50	10.86	-35.15	-13.00	-22.15	V
3375.89	-31.91	12.78	11.57	-30.70	-13.00	-17.70	V



LTE Band 12 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1399.28	-33.66	8.17	9.34	-34.83	-13.00	-21.83	H
2098.81	-34.44	9.53	10.42	-35.33	-13.00	-22.33	H
2798.64	-32.93	11.27	11.12	-32.78	-13.00	-19.78	H
1399.28	-34.69	8.17	9.34	-35.86	-13.00	-22.86	V
2098.81	-34.54	9.53	10.42	-35.43	-13.00	-22.43	V
2798.64	-33.16	11.27	11.12	-33.01	-13.00	-20.01	V
LTE Band 12 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1414.71	-33.96	8.17	9.34	-35.13	-13.00	-22.13	H
2122.46	-34.13	9.53	10.42	-35.02	-13.00	-22.02	H
2829.88	-32.46	11.27	11.12	-32.31	-13.00	-19.31	H
1414.71	-35.67	8.17	9.34	-36.84	-13.00	-23.84	V
2122.46	-34.54	9.53	10.42	-35.43	-13.00	-22.43	V
2829.88	-32.59	11.27	11.12	-32.44	-13.00	-19.44	V
LTE Band 12 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1430.46	-33.53	8.17	9.34	-34.70	-13.00	-21.70	H
2145.75	-35.42	9.53	10.42	-36.31	-13.00	-23.31	H
2860.94	-32.94	11.27	11.12	-32.79	-13.00	-19.79	H
1430.46	-34.95	8.17	9.34	-36.12	-13.00	-23.12	V
2145.75	-34.92	9.53	10.42	-35.81	-13.00	-22.81	V
2860.94	-32.42	11.27	11.12	-32.27	-13.00	-19.27	V



LTE Band 12 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1400.88	-34.51	8.17	9.34	-35.68	-13.00	-22.68	H
2101.26	-34.41	9.53	10.42	-35.30	-13.00	-22.30	H
2801.68	-32.53	11.27	11.12	-32.38	-13.00	-19.38	H
1400.88	-35.96	8.17	9.34	-37.13	-13.00	-24.13	V
2101.26	-34.30	9.53	10.42	-35.19	-13.00	-22.19	V
2801.68	-32.58	11.27	11.12	-32.43	-13.00	-19.43	V
LTE Band 12 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1414.82	-33.75	8.17	9.34	-34.92	-13.00	-21.92	H
2122.21	-35.45	9.53	10.42	-36.34	-13.00	-23.34	H
2829.54	-32.70	11.27	11.12	-32.55	-13.00	-19.55	H
1414.82	-35.61	8.17	9.34	-36.78	-13.00	-23.78	V
2122.21	-34.32	9.53	10.42	-35.21	-13.00	-22.21	V
2829.54	-32.34	11.27	11.12	-32.19	-13.00	-19.19	V
LTE Band 12 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1428.57	-34.22	8.17	9.34	-35.39	-13.00	-22.39	H
2143.46	-34.97	9.53	10.42	-35.86	-13.00	-22.86	H
2857.63	-32.59	11.27	11.12	-32.44	-13.00	-19.44	H
1428.57	-34.68	8.17	9.34	-35.85	-13.00	-22.85	V
2143.46	-34.03	9.53	10.42	-34.92	-13.00	-21.92	V
2857.63	-32.22	11.27	11.12	-32.07	-13.00	-19.07	V



LTE Band 12 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1402.58	-33.58	8.17	9.34	-34.75	-13.00	-21.75	H
2104.23	-35.16	9.53	10.42	-36.05	-13.00	-23.05	H
2805.71	-32.99	11.27	11.12	-32.84	-13.00	-19.84	H
1402.58	-34.72	8.17	9.34	-35.89	-13.00	-22.89	V
2104.23	-33.77	9.53	10.42	-34.66	-13.00	-21.66	V
2805.71	-32.06	11.27	11.12	-31.91	-13.00	-18.91	V
LTE Band 12 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1414.67	-34.17	8.17	9.34	-35.34	-13.00	-22.34	H
2122.24	-34.84	9.53	10.42	-35.73	-13.00	-22.73	H
2829.62	-32.54	11.27	11.12	-32.39	-13.00	-19.39	H
1414.67	-36.01	8.17	9.34	-37.18	-13.00	-24.18	V
2122.24	-34.37	9.53	10.42	-35.26	-13.00	-22.26	V
2829.62	-32.11	11.27	11.12	-31.96	-13.00	-18.96	V
LTE Band 12 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1426.74	-33.63	8.17	9.34	-34.80	-13.00	-21.80	H
2140.47	-35.35	9.53	10.42	-36.24	-13.00	-23.24	H
2853.80	-33.64	11.27	11.12	-33.49	-13.00	-20.49	H
1426.74	-34.68	8.17	9.34	-35.85	-13.00	-22.85	V
2140.47	-34.40	9.53	10.42	-35.29	-13.00	-22.29	V
2853.80	-32.01	11.27	11.12	-31.86	-13.00	-18.86	V



LTE Band 12 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1407.63	-33.77	8.17	9.34	-34.94	-13.00	-21.94	H
2111.79	-35.22	9.53	10.42	-36.11	-13.00	-23.11	H
2815.83	-33.27	11.27	11.12	-33.12	-13.00	-20.12	H
1407.63	-34.81	8.17	9.34	-35.98	-13.00	-22.98	V
2111.79	-35.18	9.53	10.42	-36.07	-13.00	-23.07	V
2815.83	-33.00	11.27	11.12	-32.85	-13.00	-19.85	V
LTE Band 12 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1414.98	-33.99	8.17	9.34	-35.16	-13.00	-22.16	H
2122.35	-34.54	9.53	10.42	-35.43	-13.00	-22.43	H
2829.96	-32.84	11.27	11.12	-32.69	-13.00	-19.69	H
1414.98	-35.17	8.17	9.34	-36.34	-13.00	-23.34	V
2122.35	-34.17	9.53	10.42	-35.06	-13.00	-22.06	V
2829.96	-32.85	11.27	11.12	-32.70	-13.00	-19.70	V
LTE Band 12 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1421.59	-33.63	8.17	9.34	-34.80	-13.00	-21.80	H
2132.54	-35.35	9.53	10.42	-36.24	-13.00	-23.24	H
2843.66	-32.50	11.27	11.12	-32.35	-13.00	-19.35	H
1421.59	-35.24	8.17	9.34	-36.41	-13.00	-23.41	V
2132.54	-34.93	9.53	10.42	-35.82	-13.00	-22.82	V
2843.66	-31.99	11.27	11.12	-31.84	-13.00	-18.84	V



LTE Band 13 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1559.14	-33.74	9.56	9.72	-33.90	-13.00	-20.90	H
2338.24	-35.48	10.50	10.86	-35.84	-13.00	-22.84	H
3118.21	-33.04	12.78	11.57	-31.83	-13.00	-18.83	H
1559.14	-34.95	9.56	9.72	-35.11	-13.00	-22.11	V
2338.24	-34.77	10.50	10.86	-35.13	-13.00	-22.13	V
3118.21	-32.30	12.78	11.57	-31.09	-13.00	-18.09	V
LTE Band 13 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1563.96	-33.60	9.56	9.72	-33.76	-13.00	-20.76	H
2345.84	-34.33	10.50	10.86	-34.69	-13.00	-21.69	H
3128.01	-33.56	12.78	11.57	-32.35	-13.00	-19.35	H
1563.96	-35.82	9.56	9.72	-35.98	-13.00	-22.98	V
2345.84	-34.70	10.50	10.86	-35.06	-13.00	-22.06	V
3128.01	-32.72	12.78	11.57	-31.51	-13.00	-18.51	V
LTE Band 13 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1568.98	-34.71	9.56	9.72	-34.87	-13.00	-21.87	H
2353.20	-34.34	10.50	10.86	-34.70	-13.00	-21.70	H
3138.10	-32.18	12.78	11.57	-30.97	-13.00	-17.97	H
1568.98	-34.62	9.56	9.72	-34.78	-13.00	-21.78	V
2353.20	-35.02	10.50	10.86	-35.38	-13.00	-22.38	V
3138.10	-32.60	12.78	11.57	-31.39	-13.00	-18.39	V
LTE Band 13 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1564.05	-33.51	9.56	9.72	-33.67	-13.00	-20.67	H
2346.18	-35.22	10.50	10.86	-35.58	-13.00	-22.58	H
3127.73	-32.92	12.78	11.57	-31.71	-13.00	-18.71	H
1564.05	-34.79	9.56	9.72	-34.95	-13.00	-21.95	V
2346.18	-33.79	10.50	10.86	-34.15	-13.00	-21.15	V
3127.73	-33.12	12.78	11.57	-31.91	-13.00	-18.91	V



LTE Band 25 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3701.34	-34.26	12.60	12.93	-34.59	-13.00	-21.59	H
5551.68	-34.25	13.10	17.11	-38.26	-13.00	-25.26	H
7402.49	-33.28	11.50	22.20	-43.98	-13.00	-30.98	H
3701.34	-35.18	12.60	12.93	-35.51	-13.00	-22.51	V
5551.68	-35.17	13.10	17.11	-39.18	-13.00	-26.18	V
7402.49	-32.73	11.50	22.20	-43.43	-13.00	-30.43	V
LTE Band 25 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3764.82	-34.29	12.60	12.93	-34.62	-13.00	-21.62	H
5646.96	-35.42	13.10	17.11	-39.43	-13.00	-26.43	H
7530.03	-32.41	11.50	22.20	-43.11	-13.00	-30.11	H
3764.82	-35.78	12.60	12.93	-36.11	-13.00	-23.11	V
5646.96	-34.21	13.10	17.11	-38.22	-13.00	-25.22	V
7530.03	-31.91	11.50	22.20	-42.61	-13.00	-29.61	V
LTE Band 25 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3828.29	-34.23	12.60	12.93	-34.56	-13.00	-21.56	H
5727.48	-35.05	13.10	17.11	-39.06	-13.00	-26.06	H
7657.09	-32.72	11.50	22.20	-43.42	-13.00	-30.42	H
3828.29	-35.13	12.60	12.93	-35.46	-13.00	-22.46	V
5727.48	-35.13	13.10	17.11	-39.14	-13.00	-26.14	V
7657.09	-32.17	11.50	22.20	-42.87	-13.00	-29.87	V



LTE Band 25 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3702.97	-33.61	12.60	12.93	-33.94	-13.00	-20.94	H
5554.10	-35.20	13.10	17.11	-39.21	-13.00	-26.21	H
7405.83	-33.36	11.50	22.20	-44.06	-13.00	-31.06	H
3702.97	-34.72	12.60	12.93	-35.05	-13.00	-22.05	V
5554.10	-33.81	13.10	17.11	-37.82	-13.00	-24.82	V
7405.83	-32.55	11.50	22.20	-43.25	-13.00	-30.25	V
LTE Band 25 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3764.81	-34.51	12.60	12.93	-34.84	-13.00	-21.84	H
5646.85	-34.68	13.10	17.11	-38.69	-13.00	-25.69	H
7529.82	-32.61	11.50	22.20	-43.31	-13.00	-30.31	H
3764.81	-36.00	12.60	12.93	-36.33	-13.00	-23.33	V
5646.85	-34.90	13.10	17.11	-38.91	-13.00	-25.91	V
7529.82	-32.04	11.50	22.20	-42.74	-13.00	-29.74	V
LTE Band 25 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3826.87	-34.03	12.60	12.93	-34.36	-13.00	-21.36	H
5739.99	-34.56	13.10	17.11	-38.57	-13.00	-25.57	H
7654.35	-33.17	11.50	22.20	-43.87	-13.00	-30.87	H
3826.87	-35.14	12.60	12.93	-35.47	-13.00	-22.47	V
5739.99	-34.25	13.10	17.11	-38.26	-13.00	-25.26	V
7654.35	-32.16	11.50	22.20	-42.86	-13.00	-29.86	V



LTE Band 25 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3705.33	-33.50	12.60	12.93	-33.83	-13.00	-20.83	H
5557.28	-35.47	13.10	17.11	-39.48	-13.00	-26.48	H
7409.88	-32.28	11.50	22.20	-42.98	-13.00	-29.98	H
3705.33	-35.52	12.60	12.93	-35.85	-13.00	-22.85	V
5557.28	-35.01	13.10	17.11	-39.02	-13.00	-26.02	V
7409.88	-32.79	11.50	22.20	-43.49	-13.00	-30.49	V
LTE Band 25 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3764.87	-34.77	12.60	12.93	-35.10	-13.00	-22.10	H
5647.03	-35.05	13.10	17.11	-39.06	-13.00	-26.06	H
7530.10	-33.27	11.50	22.20	-43.97	-13.00	-30.97	H
3764.87	-35.29	12.60	12.93	-35.62	-13.00	-22.62	V
5647.03	-33.96	13.10	17.11	-37.97	-13.00	-24.97	V
7530.10	-32.96	11.50	22.20	-43.66	-13.00	-30.66	V
LTE Band 25 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3825.20	-33.60	12.60	12.93	-33.93	-13.00	-20.93	H
5737.15	-34.86	13.10	17.11	-38.87	-13.00	-25.87	H
7650.55	-32.23	11.50	22.20	-42.93	-13.00	-29.93	H
3825.20	-34.53	12.60	12.93	-34.86	-13.00	-21.86	V
5737.15	-35.09	13.10	17.11	-39.10	-13.00	-26.10	V
7650.55	-33.04	11.50	22.20	-43.74	-13.00	-30.74	V



LTE Band 25 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3710.12	-33.57	12.60	12.93	-33.90	-13.00	-20.90	H
5565.41	-34.27	13.10	17.11	-38.28	-13.00	-25.28	H
7420.23	-33.32	11.50	22.20	-44.02	-13.00	-31.02	H
3710.12	-34.52	12.60	12.93	-34.85	-13.00	-21.85	V
5565.41	-34.65	13.10	17.11	-38.66	-13.00	-25.66	V
7420.23	-32.38	11.50	22.20	-43.08	-13.00	-30.08	V
LTE Band 25 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3764.86	-34.51	12.60	12.93	-34.84	-13.00	-21.84	H
5647.46	-34.26	13.10	17.11	-38.27	-13.00	-25.27	H
7529.92	-32.82	11.50	22.20	-43.52	-13.00	-30.52	H
3764.86	-35.02	12.60	12.93	-35.35	-13.00	-22.35	V
5647.46	-33.99	13.10	17.11	-38.00	-13.00	-25.00	V
7529.92	-32.30	11.50	22.20	-43.00	-13.00	-30.00	V
LTE Band 25 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3820.20	-34.12	12.60	12.93	-34.45	-13.00	-21.45	H
5729.85	-34.11	13.10	17.11	-38.12	-13.00	-25.12	H
7640.05	-32.26	11.50	22.20	-42.96	-13.00	-29.96	H
3820.20	-34.57	12.60	12.93	-34.90	-13.00	-21.90	V
5729.85	-33.77	13.10	17.11	-37.78	-13.00	-24.78	V
7640.05	-32.94	11.50	22.20	-43.64	-13.00	-30.64	V



LTE Band 25 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3715.21	-34.66	12.60	12.93	-34.99	-13.00	-21.99	H
5572.30	-34.21	13.10	17.11	-38.22	-13.00	-25.22	H
7430.75	-32.70	11.50	22.20	-43.40	-13.00	-30.40	H
3715.21	-35.24	12.60	12.93	-35.57	-13.00	-22.57	V
5572.30	-33.92	13.10	17.11	-37.93	-13.00	-24.93	V
7430.75	-32.89	11.50	22.20	-43.59	-13.00	-30.59	V
LTE Band 25 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3765.13	-33.90	12.60	12.93	-34.23	-13.00	-21.23	H
5647.11	-34.72	13.10	17.11	-38.73	-13.00	-25.73	H
7429.83	-32.87	11.50	22.20	-43.57	-13.00	-30.57	H
3765.13	-34.54	12.60	12.93	-34.87	-13.00	-21.87	V
5647.11	-34.21	13.10	17.11	-38.22	-13.00	-25.22	V
7429.83	-31.80	11.50	22.20	-42.50	-13.00	-29.50	V
LTE Band 25 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.35	-33.70	12.60	12.93	-34.03	-13.00	-21.03	H
5722.24	-34.45	13.10	17.11	-38.46	-13.00	-25.46	H
7630.14	-32.33	11.50	22.20	-43.03	-13.00	-30.03	H
3815.35	-35.26	12.60	12.93	-35.59	-13.00	-22.59	V
5722.24	-34.51	13.10	17.11	-38.52	-13.00	-25.52	V
7630.14	-32.19	11.50	22.20	-42.89	-13.00	-29.89	V



LTE Band 25 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3720.08	-34.66	12.60	12.93	-34.99	-13.00	-21.99	H
5580.33	-35.37	13.10	17.11	-39.38	-13.00	-26.38	H
7440.12	-33.08	11.50	22.20	-43.78	-13.00	-30.78	H
3720.08	-35.63	12.60	12.93	-35.96	-13.00	-22.96	V
5580.33	-34.31	13.10	17.11	-38.32	-13.00	-25.32	V
7440.12	-32.16	11.50	22.20	-42.86	-13.00	-29.86	V
LTE Band 25 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3765.16	-34.76	12.60	12.93	-35.09	-13.00	-22.09	H
5647.10	-34.87	13.10	17.11	-38.88	-13.00	-25.88	H
7529.97	-32.96	11.50	22.20	-43.66	-13.00	-30.66	H
3765.16	-34.89	12.60	12.93	-35.22	-13.00	-22.22	V
5647.10	-35.20	13.10	17.11	-39.21	-13.00	-26.21	V
7529.97	-31.92	11.50	22.20	-42.62	-13.00	-29.62	V
LTE Band 25 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3810.18	-34.27	12.60	12.93	-34.60	-13.00	-21.60	H
5715.35	-34.92	13.10	17.11	-38.93	-13.00	-25.93	H
7620.15	-33.43	11.50	22.20	-44.13	-13.00	-31.13	H
3810.18	-35.13	12.60	12.93	-35.46	-13.00	-22.46	V
5715.35	-34.46	13.10	17.11	-38.47	-13.00	-25.47	V
7620.15	-32.35	11.50	22.20	-43.05	-13.00	-30.05	V



LTE Band 26(Part 22) / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1649.19	-33.78	9.56	9.72	-33.94	-13.00	-20.94	H
2473.56	-34.28	10.50	10.86	-34.64	-13.00	-21.64	H
3298.83	-32.27	12.78	11.57	-31.06	-13.00	-18.06	H
1649.19	-35.53	9.56	9.72	-35.69	-13.00	-22.69	V
2473.56	-34.07	10.50	10.86	-34.43	-13.00	-21.43	V
3298.83	-32.68	12.78	11.57	-31.47	-13.00	-18.47	V
LTE Band 26(Part 22) / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.83	-34.59	9.56	9.72	-34.75	-13.00	-21.75	H
2508.93	-34.93	10.50	10.86	-35.29	-13.00	-22.29	H
3345.90	-33.52	12.78	11.57	-32.31	-13.00	-19.31	H
1672.83	-35.05	9.56	9.72	-35.21	-13.00	-22.21	V
2508.93	-34.74	10.50	10.86	-35.10	-13.00	-22.10	V
3345.90	-31.77	12.78	11.57	-30.56	-13.00	-17.56	V
LTE Band 26(Part 22) / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1696.26	-34.11	9.56	9.72	-34.27	-13.00	-21.27	H
2544.56	-34.36	10.50	10.86	-34.72	-13.00	-21.72	H
3392.91	-32.40	12.78	11.57	-31.19	-13.00	-18.19	H
1696.26	-35.13	9.56	9.72	-35.29	-13.00	-22.29	V
2544.56	-34.32	10.50	10.86	-34.68	-13.00	-21.68	V
3392.91	-33.01	12.78	11.57	-31.80	-13.00	-18.80	V



LTE Band 26(Part 22) / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1651.20	-34.71	9.56	9.72	-34.87	-13.00	-21.87	H
2476.45	-34.27	10.50	10.86	-34.63	-13.00	-21.63	H
3301.95	-32.44	12.78	11.57	-31.23	-13.00	-18.23	H
1651.20	-35.42	9.56	9.72	-35.58	-13.00	-22.58	V
2476.45	-34.75	10.50	10.86	-35.11	-13.00	-22.11	V
3301.95	-32.10	12.78	11.57	-30.89	-13.00	-17.89	V
LTE Band 26(Part 22) / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1673.26	-34.30	9.56	9.72	-34.46	-13.00	-21.46	H
2508.83	-34.04	10.50	10.86	-34.40	-13.00	-21.40	H
3346.00	-33.19	12.78	11.57	-31.98	-13.00	-18.98	H
1673.26	-35.59	9.56	9.72	-35.75	-13.00	-22.75	V
2508.83	-34.29	10.50	10.86	-34.65	-13.00	-21.65	V
3346.00	-32.29	12.78	11.57	-31.08	-13.00	-18.08	V
LTE Band 26(Part 22) / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1695.42	-34.37	9.56	9.72	-34.53	-13.00	-21.53	H
2542.10	-35.01	10.50	10.86	-35.37	-13.00	-22.37	H
3389.96	-33.12	12.78	11.57	-31.91	-13.00	-18.91	H
1695.42	-35.08	9.56	9.72	-35.24	-13.00	-22.24	V
2542.10	-34.96	10.50	10.86	-35.32	-13.00	-22.32	V
3389.96	-31.92	12.78	11.57	-30.71	-13.00	-17.71	V



LTE Band 26(Part 22) / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.84	-34.93	9.56	9.72	-35.09	-13.00	-22.09	H
2479.48	-35.43	10.50	10.86	-35.79	-13.00	-22.79	H
3306.83	-32.45	12.78	11.57	-31.24	-13.00	-18.24	H
1652.84	-35.20	9.56	9.72	-35.36	-13.00	-22.36	V
2479.48	-34.82	10.50	10.86	-35.18	-13.00	-22.18	V
3306.83	-32.82	12.78	11.57	-31.61	-13.00	-18.61	V
LTE Band 26(Part 22) / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.92	-34.19	9.56	9.72	-34.35	-13.00	-21.35	H
2509.26	-34.06	10.50	10.86	-34.42	-13.00	-21.42	H
3345.80	-32.35	12.78	11.57	-31.14	-13.00	-18.14	H
1672.92	-34.95	9.56	9.72	-35.11	-13.00	-22.11	V
2509.26	-34.59	10.50	10.86	-34.95	-13.00	-21.95	V
3345.80	-31.90	12.78	11.57	-30.69	-13.00	-17.69	V
LTE Band 26(Part 22) / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.34	-33.81	9.56	9.72	-33.97	-13.00	-20.97	H
2539.34	-34.84	10.50	10.86	-35.20	-13.00	-22.20	H
3385.95	-33.07	12.78	11.57	-31.86	-13.00	-18.86	H
1693.34	-34.92	9.56	9.72	-35.08	-13.00	-22.08	V
2539.34	-34.61	10.50	10.86	-34.97	-13.00	-21.97	V
3385.95	-32.07	12.78	11.57	-30.86	-13.00	-17.86	V



LTE Band 26(Part 22) / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1657.91	-33.80	9.56	9.72	-33.96	-13.00	-20.96	H
2486.67	-35.27	10.50	10.86	-35.63	-13.00	-22.63	H
3315.65	-32.65	12.78	11.57	-31.44	-13.00	-18.44	H
1657.91	-34.97	9.56	9.72	-35.13	-13.00	-22.13	V
2486.67	-34.57	10.50	10.86	-34.93	-13.00	-21.93	V
3315.65	-32.43	12.78	11.57	-31.22	-13.00	-18.22	V
LTE Band 26(Part 22) / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.77	-34.73	9.56	9.72	-34.89	-13.00	-21.89	H
2508.94	-35.15	10.50	10.86	-35.51	-13.00	-22.51	H
3346.04	-32.65	12.78	11.57	-31.44	-13.00	-18.44	H
1672.77	-35.05	9.56	9.72	-35.21	-13.00	-22.21	V
2508.94	-34.79	10.50	10.86	-35.15	-13.00	-22.15	V
3346.04	-31.71	12.78	11.57	-30.50	-13.00	-17.50	V
LTE Band 26(Part 22) / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1688.71	-34.89	9.56	9.72	-35.05	-13.00	-22.05	H
2532.11	-34.51	10.50	10.86	-34.87	-13.00	-21.87	H
3375.84	-33.31	12.78	11.57	-32.10	-13.00	-19.10	H
1688.71	-36.01	9.56	9.72	-36.17	-13.00	-23.17	V
2532.11	-35.00	10.50	10.86	-35.36	-13.00	-22.36	V
3375.84	-32.24	12.78	11.57	-31.03	-13.00	-18.03	V



LTE Band 26(Part 22) / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1663.15	-34.16	9.56	9.72	-34.32	-13.00	-21.32	H
2494.39	-34.89	10.50	10.86	-35.25	-13.00	-22.25	H
3325.91	-32.54	12.78	11.57	-31.33	-13.00	-18.33	H
1663.15	-35.54	9.56	9.72	-35.70	-13.00	-22.70	V
2494.39	-34.67	10.50	10.86	-35.03	-13.00	-22.03	V
3325.91	-33.06	12.78	11.57	-31.85	-13.00	-18.85	V
LTE Band 26(Part 22) / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.77	-34.69	9.56	9.72	-34.85	-13.00	-21.85	H
2509.25	-35.08	10.50	10.86	-35.44	-13.00	-22.44	H
3346.18	-33.46	12.78	11.57	-32.25	-13.00	-19.25	H
1672.77	-35.45	9.56	9.72	-35.61	-13.00	-22.61	V
2509.25	-34.45	10.50	10.86	-34.81	-13.00	-21.81	V
3346.18	-32.57	12.78	11.57	-31.36	-13.00	-18.36	V
LTE Band 26(Part 22) / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1683.54	-33.72	9.56	9.72	-33.88	-13.00	-20.88	H
2524.48	-34.53	10.50	10.86	-34.89	-13.00	-21.89	H
3366.66	-32.75	12.78	11.57	-31.54	-13.00	-18.54	H
1683.54	-35.18	9.56	9.72	-35.34	-13.00	-22.34	V
2524.48	-34.52	10.50	10.86	-34.88	-13.00	-21.88	V
3366.66	-31.80	12.78	11.57	-30.59	-13.00	-17.59	V



LTE Band 26(Part 90) / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1629.06	-34.85	9.56	9.72	-35.01	-13.00	-22.01	H
2444.17	-34.68	10.50	10.86	-35.04	-13.00	-22.04	H
3258.65	-32.59	12.78	11.57	-31.38	-13.00	-18.38	H
1629.06	-34.87	9.56	9.72	-35.03	-13.00	-22.03	V
2444.17	-35.08	10.50	10.86	-35.44	-13.00	-22.44	V
3258.65	-32.43	12.78	11.57	-31.22	-13.00	-18.22	V
LTE Band 26(Part 90) / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1637.88	-34.48	9.56	9.72	-34.64	-13.00	-21.64	H
2457.28	-35.05	10.50	10.86	-35.41	-13.00	-22.41	H
3276.06	-32.90	12.78	11.57	-31.69	-13.00	-18.69	H
1637.88	-35.03	9.56	9.72	-35.19	-13.00	-22.19	V
2457.28	-34.70	10.50	10.86	-35.06	-13.00	-22.06	V
3276.06	-32.29	12.78	11.57	-31.08	-13.00	-18.08	V
LTE Band 26(Part 90) / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1646.60	-34.87	9.56	9.72	-35.03	-13.00	-22.03	H
2456.95	-34.42	10.50	10.86	-34.78	-13.00	-21.78	H
3257.99	-32.78	12.78	11.57	-31.57	-13.00	-18.57	H
1646.60	-35.98	9.56	9.72	-36.14	-13.00	-23.14	V
2456.95	-34.09	10.50	10.86	-34.45	-13.00	-21.45	V
3257.99	-31.90	12.78	11.57	-30.69	-13.00	-17.69	V



LTE Band 26(Part 90) / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1631.20	-33.63	9.56	9.72	-33.79	-13.00	-20.79	H
2446.21	-34.12	10.50	10.86	-34.48	-13.00	-21.48	H
3261.48	-33.27	12.78	11.57	-32.06	-13.00	-19.06	H
1631.20	-34.92	9.56	9.72	-35.08	-13.00	-22.08	V
2446.21	-34.84	10.50	10.86	-35.20	-13.00	-22.20	V
3261.48	-31.71	12.78	11.57	-30.50	-13.00	-17.50	V
LTE Band 26(Part 90) / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1637.88	-33.81	9.56	9.72	-33.97	-13.00	-20.97	H
2457.19	-34.33	10.50	10.86	-34.69	-13.00	-21.69	H
3276.29	-33.28	12.78	11.57	-32.07	-13.00	-19.07	H
1637.88	-35.38	9.56	9.72	-35.54	-13.00	-22.54	V
2457.19	-34.50	10.50	10.86	-34.86	-13.00	-21.86	V
3276.29	-31.73	12.78	11.57	-30.52	-13.00	-17.52	V
LTE Band 26(Part 90) / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1644.70	-34.17	9.56	9.72	-34.33	-13.00	-21.33	H
2467.17	-34.28	10.50	10.86	-34.64	-13.00	-21.64	H
3276.08	-32.24	12.78	11.57	-31.03	-13.00	-18.03	H
1644.70	-35.10	9.56	9.72	-35.26	-13.00	-22.26	V
2467.17	-33.87	10.50	10.86	-34.23	-13.00	-21.23	V
3276.08	-32.42	12.78	11.57	-31.21	-13.00	-18.21	V



LTE Band 26(Part 90) / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1632.86	-34.79	9.56	9.72	-34.95	-13.00	-21.95	H
2449.37	-33.99	10.50	10.86	-34.35	-13.00	-21.35	H
3266.61	-32.84	12.78	11.57	-31.63	-13.00	-18.63	H
1632.86	-36.01	9.56	9.72	-36.17	-13.00	-23.17	V
2449.37	-34.28	10.50	10.86	-34.64	-13.00	-21.64	V
3266.61	-32.31	12.78	11.57	-31.10	-13.00	-18.10	V

LTE Band 26(Part 90) / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1638.11	-34.24	9.56	9.72	-34.40	-13.00	-21.40	H
2457.06	-34.48	10.50	10.86	-34.84	-13.00	-21.84	H
3276.29	-33.49	12.78	11.57	-32.28	-13.00	-19.28	H
1638.11	-34.70	9.56	9.72	-34.86	-13.00	-21.86	V
2457.06	-34.00	10.50	10.86	-34.36	-13.00	-21.36	V
3276.29	-31.82	12.78	11.57	-30.61	-13.00	-17.61	V

LTE Band 26(Part 90) / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1643.17	-33.72	9.56	9.72	-33.88	-13.00	-20.88	H
2464.10	-35.02	10.50	10.86	-35.38	-13.00	-22.38	H
3286.12	-33.08	12.78	11.57	-31.87	-13.00	-18.87	H
1643.17	-35.44	9.56	9.72	-35.60	-13.00	-22.60	V
2464.10	-34.94	10.50	10.86	-35.30	-13.00	-22.30	V
3286.12	-32.45	12.78	11.57	-31.24	-13.00	-18.24	V

LTE Band 26(Part 90) / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1638.00	-33.77	9.56	9.72	-33.93	-13.00	-20.93	H
2457.14	-35.12	10.50	10.86	-35.48	-13.00	-22.48	H
3275.85	-32.36	12.78	11.57	-31.15	-13.00	-18.15	H
1638.00	-35.73	9.56	9.72	-35.89	-13.00	-22.89	V
2457.14	-34.70	10.50	10.86	-35.06	-13.00	-22.06	V
3275.85	-32.25	12.78	11.57	-31.04	-13.00	-18.04	V



LTE Band 41 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
4996.89	-33.60	12.66	15.86	-36.80	-25.00	-11.80	H
7495.71	-35.28	11.46	19.28	-43.10	-25.00	-18.10	H
9994.12	-33.53	12.79	23.19	-43.93	-25.00	-18.93	H
4997.17	-35.02	12.66	15.86	-38.22	-25.00	-13.22	V
7495.85	-34.96	11.46	19.28	-42.78	-25.00	-17.78	V
9994.13	-32.04	12.79	23.19	-42.44	-25.00	-17.44	V
LTE Band 41 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5186.02	-34.88	12.72	15.86	-38.02	-25.00	-13.02	H
7779.37	-34.32	11.46	19.28	-42.14	-25.00	-17.14	H
10371.99	-33.25	12.09	23.19	-44.35	-25.00	-19.35	H
5186.02	-34.70	12.72	15.86	-37.84	-25.00	-12.84	V
7779.37	-35.04	11.46	19.28	-42.86	-25.00	-17.86	V
10371.99	-32.99	12.09	23.19	-44.09	-25.00	-19.09	V
LTE Band 41 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5374.77	-34.38	12.76	15.86	-37.48	-25.00	-12.48	H
8062.45	-35.13	11.45	19.28	-42.96	-25.00	-17.96	H
10749.99	-32.63	12.28	23.19	-43.54	-25.00	-18.54	H
5374.77	-35.44	12.76	15.86	-38.54	-25.00	-13.54	V
8062.45	-33.85	11.45	19.28	-41.68	-25.00	-16.68	V
10749.99	-32.12	12.28	23.19	-43.03	-25.00	-18.03	V



LTE Band 41 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5002.14	-34.80	12.66	15.86	-38.00	-25.00	-13.00	H
7503.14	-34.14	11.46	19.28	-41.96	-25.00	-16.96	H
10004.47	-32.49	12.79	23.19	-42.89	-25.00	-17.89	H
5002.14	-34.54	12.66	15.86	-37.74	-25.00	-12.74	V
7503.14	-34.26	11.46	19.28	-42.08	-25.00	-17.08	V
10004.47	-31.78	12.79	23.19	-42.18	-25.00	-17.18	V
LTE Band 41 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5186.63	-34.24	12.72	15.86	-37.38	-25.00	-12.38	H
7779.63	-34.08	11.46	19.28	-41.90	-25.00	-16.90	H
10371.30	-32.76	12.09	23.19	-43.86	-25.00	-18.86	H
5186.63	-35.54	12.72	15.86	-38.68	-25.00	-13.68	V
7779.63	-35.10	11.46	19.28	-42.92	-25.00	-17.92	V
10371.30	-32.93	12.09	23.19	-44.03	-25.00	-19.03	V
LTE Band 41 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5370.36	-34.24	12.76	15.86	-37.34	-25.00	-12.34	H
8055.55	-35.41	11.45	19.28	-43.24	-25.00	-18.24	H
10740.21	-33.13	12.28	23.19	-44.04	-25.00	-19.04	H
5370.36	-35.48	12.76	15.86	-38.58	-25.00	-13.58	V
8055.55	-33.78	11.45	19.28	-41.61	-25.00	-16.61	V
10740.21	-32.72	12.28	23.19	-43.63	-25.00	-18.63	V



LTE Band 41 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5007.01	-34.61	12.66	15.86	-37.81	-25.00	-12.81	H
7510.31	-34.53	11.46	19.28	-42.35	-25.00	-17.35	H
10014.68	-33.32	12.79	23.19	-43.72	-25.00	-18.72	H
5007.01	-35.67	12.66	15.86	-38.87	-25.00	-13.87	V
7510.31	-34.02	11.46	19.28	-41.84	-25.00	-16.84	V
10014.68	-31.79	12.79	23.19	-42.19	-25.00	-17.19	V
LTE Band 41 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5185.92	-33.60	12.72	15.86	-36.74	-25.00	-11.74	H
7779.11	-35.02	11.46	19.28	-42.84	-25.00	-17.84	H
10372.34	-33.45	12.09	23.19	-44.55	-25.00	-19.55	H
5185.92	-35.75	12.72	15.86	-38.89	-25.00	-13.89	V
7779.11	-34.37	11.46	19.28	-42.19	-25.00	-17.19	V
10372.34	-31.89	12.09	23.19	-42.99	-25.00	-17.99	V
LTE Band 41 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5365.75	-33.70	12.76	15.86	-36.80	-25.00	-11.80	H
8047.07	-35.27	11.45	19.28	-43.10	-25.00	-18.10	H
10730.19	-33.28	12.28	23.19	-44.19	-25.00	-19.19	H
5365.75	-35.24	12.76	15.86	-38.34	-25.00	-13.34	V
8047.07	-34.34	11.45	19.28	-42.17	-25.00	-17.17	V
10730.19	-32.34	12.28	23.19	-43.25	-25.00	-18.25	V



LTE Band 41 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5012.02	-33.65	12.66	15.86	-36.85	-25.00	-11.85	H
7518.37	-34.87	11.46	19.28	-42.69	-25.00	-17.69	H
10024.27	-32.46	12.79	23.19	-42.86	-25.00	-17.86	H
5012.02	-34.84	12.66	15.86	-38.04	-25.00	-13.04	V
7518.37	-34.67	11.46	19.28	-42.49	-25.00	-17.49	V
10024.27	-32.72	12.79	23.19	-43.12	-25.00	-18.12	V
LTE Band 41 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5185.88	-34.82	12.72	15.86	-37.96	-25.00	-12.96	H
7779.20	-35.40	11.46	19.28	-43.22	-25.00	-18.22	H
10371.94	-32.86	12.09	23.19	-43.96	-25.00	-18.96	H
5185.88	-35.08	12.72	15.86	-38.22	-25.00	-13.22	V
7779.20	-34.59	11.46	19.28	-42.41	-25.00	-17.41	V
10371.94	-32.33	12.09	23.19	-43.43	-25.00	-18.43	V
LTE Band 41 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5360.10	-34.10	12.76	15.86	-37.20	-25.00	-12.20	H
8040.51	-35.36	11.45	19.28	-43.19	-25.00	-18.19	H
10720.25	-33.42	12.28	23.19	-44.33	-25.00	-19.33	H
5360.10	-34.88	12.76	15.86	-37.98	-25.00	-12.98	V
8040.51	-33.99	11.45	19.28	-41.82	-25.00	-16.82	V
10720.25	-32.01	12.28	23.19	-42.92	-25.00	-17.92	V



LTE Band 66 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3421.27	-34.16	12.90	12.56	-33.82	-13.00	-20.82	H
5132.06	-35.46	13.10	16.32	-38.68	-13.00	-25.68	H
6842.40	-32.50	12.33	21.13	-41.30	-13.00	-28.30	H
3421.27	-35.03	12.90	12.56	-34.69	-13.00	-21.69	V
5132.06	-35.14	13.10	16.32	-38.36	-13.00	-25.36	V
6842.40	-32.84	12.33	21.13	-41.64	-13.00	-28.64	V
LTE Band 66 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3490.11	-33.94	12.90	12.56	-33.60	-13.00	-20.60	H
5235.03	-34.78	13.10	16.32	-38.00	-13.00	-25.00	H
6979.96	-33.41	12.33	21.13	-42.21	-13.00	-29.21	H
3490.11	-34.59	12.90	12.56	-34.25	-13.00	-21.25	V
5235.03	-34.00	13.10	16.32	-37.22	-13.00	-24.22	V
6979.96	-32.73	12.33	21.13	-41.53	-13.00	-28.53	V
LTE Band 66 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3558.19	-34.25	12.90	12.56	-33.91	-13.00	-20.91	H
5336.93	-35.14	13.10	16.32	-38.36	-13.00	-25.36	H
7116.73	-32.33	12.33	21.13	-41.13	-13.00	-28.13	H
3558.19	-34.58	12.90	12.56	-34.24	-13.00	-21.24	V
5336.93	-33.81	13.10	16.32	-37.03	-13.00	-24.03	V
7116.73	-31.74	12.33	21.13	-40.54	-13.00	-27.54	V



LTE Band 66 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3423.04	-34.81	12.90	12.56	-34.47	-13.00	-21.47	H
5134.47	-35.37	13.10	16.32	-38.59	-13.00	-25.59	H
6846.01	-33.11	12.33	21.13	-41.91	-13.00	-28.91	H
3423.04	-35.41	12.90	12.56	-35.07	-13.00	-22.07	V
5134.47	-34.35	13.10	16.32	-37.57	-13.00	-24.57	V
6846.01	-31.81	12.33	21.13	-40.61	-13.00	-27.61	V
LTE Band 66 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3490.12	-34.14	12.90	12.56	-33.80	-13.00	-20.80	H
5235.11	-35.47	13.10	16.32	-38.69	-13.00	-25.69	H
6980.01	-32.54	12.33	21.13	-41.34	-13.00	-28.34	H
3490.12	-36.01	12.90	12.56	-35.67	-13.00	-22.67	V
5235.11	-33.89	13.10	16.32	-37.11	-13.00	-24.11	V
6980.01	-33.17	12.33	21.13	-41.97	-13.00	-28.97	V
LTE Band 66 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3556.80	-34.05	12.90	12.56	-33.71	-13.00	-20.71	H
5262.07	-34.30	13.10	16.32	-37.52	-13.00	-24.52	H
7114.14	-32.60	12.33	21.13	-41.40	-13.00	-28.40	H
3556.80	-35.60	12.90	12.56	-35.26	-13.00	-22.26	V
5262.07	-33.80	13.10	16.32	-37.02	-13.00	-24.02	V
7114.14	-32.28	12.33	21.13	-41.08	-13.00	-28.08	V



LTE Band 66 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3425.00	-34.08	12.90	12.56	-33.74	-13.00	-20.74	H
5137.08	-34.36	13.10	16.32	-37.58	-13.00	-24.58	H
6850.37	-33.59	12.33	21.13	-42.39	-13.00	-29.39	H
3425.00	-35.38	12.90	12.56	-35.04	-13.00	-22.04	V
5137.08	-34.53	13.10	16.32	-37.75	-13.00	-24.75	V
6850.37	-32.19	12.33	21.13	-40.99	-13.00	-27.99	V
LTE Band 66 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3489.89	-34.70	12.90	12.56	-34.36	-13.00	-21.36	H
5234.84	-34.95	13.10	16.32	-38.17	-13.00	-25.17	H
6980.01	-33.46	12.33	21.13	-42.26	-13.00	-29.26	H
3489.89	-34.76	12.90	12.56	-34.42	-13.00	-21.42	V
5234.84	-34.87	13.10	16.32	-38.09	-13.00	-25.09	V
6980.01	-31.88	12.33	21.13	-40.68	-13.00	-27.68	V
LTE Band 66 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3558.06	-34.52	12.90	12.56	-34.18	-13.00	-21.18	H
52354.02	-35.40	13.10	16.32	-38.62	-13.00	-25.62	H
7110.18	-33.09	12.33	21.13	-41.89	-13.00	-28.89	H
3558.06	-34.68	12.90	12.56	-34.34	-13.00	-21.34	V
52354.02	-34.05	13.10	16.32	-37.27	-13.00	-24.27	V
7110.18	-32.08	12.33	21.13	-40.88	-13.00	-27.88	V



LTE Band 66 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3430.14	-34.05	12.90	12.56	-33.71	-13.00	-20.71	H
5145.22	-35.07	13.10	16.32	-38.29	-13.00	-25.29	H
6880.05	-32.46	12.33	21.13	-41.26	-13.00	-28.26	H
3430.14	-34.76	12.90	12.56	-34.42	-13.00	-21.42	V
5145.22	-34.55	13.10	16.32	-37.77	-13.00	-24.77	V
6880.05	-33.17	12.33	21.13	-41.97	-13.00	-28.97	V
LTE Band 66 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3489.91	-34.84	12.90	12.56	-34.50	-13.00	-21.50	H
5234.97	-35.48	13.10	16.32	-38.70	-13.00	-25.70	H
6979.95	-33.17	12.33	21.13	-41.97	-13.00	-28.97	H
3489.91	-35.05	12.90	12.56	-34.71	-13.00	-21.71	V
5234.97	-34.69	13.10	16.32	-37.91	-13.00	-24.91	V
6979.95	-32.68	12.33	21.13	-41.48	-13.00	-28.48	V
LTE Band 66 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3550.55	-34.49	12.90	12.56	-34.15	-13.00	-21.15	H
5235.18	-35.01	13.10	16.32	-38.23	-13.00	-25.23	H
7099.95	-33.20	12.33	21.13	-42.00	-13.00	-29.00	H
3550.55	-35.66	12.90	12.56	-35.32	-13.00	-22.32	V
5235.18	-34.79	13.10	16.32	-38.01	-13.00	-25.01	V
7099.95	-32.02	12.33	21.13	-40.82	-13.00	-27.82	V



LTE Band 66 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3435.18	-34.17	12.90	12.56	-33.83	-13.00	-20.83	H
5152.36	-34.75	13.10	16.32	-37.97	-13.00	-24.97	H
6870.01	-33.49	12.33	21.13	-42.29	-13.00	-29.29	H
3435.18	-35.99	12.90	12.56	-35.65	-13.00	-22.65	V
5152.36	-34.07	13.10	16.32	-37.29	-13.00	-24.29	V
6870.01	-31.92	12.33	21.13	-40.72	-13.00	-27.72	V
LTE Band 66 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3489.87	-33.53	12.90	12.56	-33.19	-13.00	-20.19	H
5235.14	-34.13	13.10	16.32	-37.35	-13.00	-24.35	H
6980.14	-32.47	12.33	21.13	-41.27	-13.00	-28.27	H
3489.87	-35.58	12.90	12.56	-35.24	-13.00	-22.24	V
5235.14	-34.44	13.10	16.32	-37.66	-13.00	-24.66	V
6980.14	-32.84	12.33	21.13	-41.64	-13.00	-28.64	V
LTE Band 66 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3545.13	-33.55	12.90	12.56	-33.21	-13.00	-20.21	H
5332.27	-34.43	13.10	16.32	-37.65	-13.00	-24.65	H
7089.78	-32.70	12.33	21.13	-41.50	-13.00	-28.50	H
3545.13	-35.39	12.90	12.56	-35.05	-13.00	-22.05	V
5332.27	-34.38	13.10	16.32	-37.60	-13.00	-24.60	V
7089.78	-31.83	12.33	21.13	-40.63	-13.00	-27.63	V



LTE Band 66 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3440.19	-34.82	12.90	12.56	-34.48	-13.00	-21.48	H
5159.88	-34.89	13.10	16.32	-38.11	-13.00	-25.11	H
6879.91	-33.32	12.33	21.13	-42.12	-13.00	-29.12	H
3440.19	-34.52	12.90	12.56	-34.18	-13.00	-21.18	V
5159.88	-34.79	13.10	16.32	-38.01	-13.00	-25.01	V
6879.91	-32.28	12.33	21.13	-41.08	-13.00	-28.08	V
LTE Band 66 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3490.22	-34.91	12.90	12.56	-34.57	-13.00	-21.57	H
5235.14	-35.16	13.10	16.32	-38.38	-13.00	-25.38	H
6979.81	-32.96	12.33	21.13	-41.76	-13.00	-28.76	H
3490.22	-34.91	12.90	12.56	-34.57	-13.00	-21.57	V
5235.14	-35.17	13.10	16.32	-38.39	-13.00	-25.39	V
6979.81	-33.20	12.33	21.13	-42.00	-13.00	-29.00	V
LTE Band 66 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3540.02	-33.90	12.90	12.56	-33.56	-13.00	-20.56	H
5309.85	-34.96	13.10	16.32	-38.18	-13.00	-25.18	H
7080.73	-32.94	12.33	21.13	-41.74	-13.00	-28.74	H
3540.02	-35.86	12.90	12.56	-35.52	-13.00	-22.52	V
5309.85	-35.09	13.10	16.32	-38.31	-13.00	-25.31	V
7080.73	-32.27	12.33	21.13	-41.07	-13.00	-28.07	V


10. FREQUENCY STABILITY

10.1 DESCRIPTION OF FREQUENCY STABILITY MEASUREMENT

10.1.1 MEASUREMENT METHOD

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

10.1.2 TEST SETUP



10.1.3 TEST PROCEDURES FOR TEMPERATURE VARIATION

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

10.1.4 TEST PROCEDURES FOR VOLTAGE VARIATION

1. The testing follows FCC KDB 971168 D01v01r03 Section 9.
2. The EUT was placed in a temperature chamber at $25 \pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.



10.1.5 TEST RESULTS

LTE Band 2 (QPSK) / 1880MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	19.28	0.010	2.5ppm	PASS
40		35.96	0.019		
30		31.04	0.017		
20		30.07	0.016		
10		30.83	0.016		
0		24.22	0.013		
-10		27.52	0.015		
-20		25.30	0.013		
-30		23.92	0.013		
25	Maximum Voltage	21.72	0.012		
25	BEP	18.84	0.010		

LTE Band 2 (QPSK) / 1880MHz / BW20M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	13.88	0.007	2.5ppm	PASS
40		33.89	0.018		
30		19.98	0.011		
20		13.07	0.007		
10		17.78	0.009		
0		21.88	0.012		
-10		34.37	0.018		
-20		25.24	0.013		
-30		23.01	0.012		
25	Maximum Voltage	16.09	0.009		
25	BEP	25.69	0.014		



LTE Band 4 (QPSK) / 1733MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	27.66	0.016	2.5ppm	PASS
40		27.95	0.016		
30		33.85	0.020		
20		20.91	0.012		
10		16.99	0.010		
0		16.98	0.010		
-10		32.31	0.019		
-20		33.59	0.019		
-30		12.13	0.007		
25	Maximum Voltage	29.94	0.017		
25	BEP	24.84	0.014		

LTE Band 4 (QPSK) / 1733MHz / BW20M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	33.42	0.019	2.5ppm	PASS
40		13.56	0.008		
30		36.42	0.021		
20		36.12	0.021		
10		35.84	0.021		
0		22.81	0.013		
-10		30.60	0.018		
-20		33.32	0.019		
-30		22.82	0.013		
25	Maximum Voltage	32.56	0.019		
25	BEP	29.26	0.017		



LTE Band 5 (QPSK) / 836.5MHz / BW5M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	32.13	0.045	2.5ppm	PASS
40		13.83	0.019		
30		26.71	0.038		
20		29.59	0.042		
10		36.05	0.051		
0		26.92	0.038		
-10		35.22	0.005		
-20		29.74	0.042		
-30		20.49	0.029		
25	Maximum Voltage	26.34	0.037		
25	BEP	22.70	0.032		

LTE Band 5 (QPSK) / 836.5MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	33.21	0.047	2.5ppm	PASS
40		17.07	0.024		
30		35.02	0.049		
20		21.37	0.030		
10		26.46	0.037		
0		17.81	0.025		
-10		22.87	0.003		
-20		26.16	0.037		
-30		20.95	0.030		
25	Maximum Voltage	13.12	0.018		
25	BEP	25.38	0.036		



LTE Band 12 (QPSK) / 707.5MHz / BW5M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	14.58	0.021	2.5ppm	PASS
40		28.88	0.041		
30		34.36	0.048		
20		26.43	0.037		
10		12.97	0.018		
0		35.03	0.049		
-10		18.22	0.003		
-20		30.66	0.043		
-30		32.21	0.045		
25	Maximum Voltage	25.76	0.036		
25	BEP	16.43	0.023		

LTE Band 12 (QPSK) / 707.5MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	27.34	0.039	2.5ppm	PASS
40		32.76	0.046		
30		20.06	0.028		
20		26.68	0.038		
10		18.22	0.026		
0		34.46	0.049		
-10		36.24	0.005		
-20		21.32	0.030		
-30		28.67	0.040		
25	Maximum Voltage	22.44	0.032		
25	BEP	30.17	0.042		



LTE Band 13 (QPSK) / 782MHz / BW5M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	16.25	0.023	2.5ppm	PASS
40		30.19	0.043		
30		11.82	0.017		
20		19.07	0.027		
10		32.98	0.046		
0		19.99	0.028		
-10		17.15	0.002		
-20		20.68	0.029		
-30		16.05	0.023		
25	Maximum Voltage	33.12	0.047		
25	BEP	29.37	0.041		

LTE Band 13 (QPSK) / 782MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	29.43	0.041	2.5ppm	PASS
40		29.71	0.042		
30		14.08	0.020		
20		23.18	0.033		
10		21.81	0.031		
0		35.58	0.050		
-10		26.84	0.004		
-20		28.57	0.040		
-30		27.45	0.039		
25	Maximum Voltage	30.63	0.043		
25	BEP	12.48	0.018		



LTE Band 25 (QPSK) / 1880MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	29.45	0.016	2.5ppm	PASS
40		13.34	0.007		
30		12.45	0.007		
20		21.77	0.012		
10		14.08	0.007		
0		20.30	0.011		
-10		33.04	0.018		
-20		35.72	0.019		
-30		26.32	0.014		
25	Maximum Voltage	23.97	0.013		
25	BEP	20.04	0.011		

LTE Band 25 (QPSK) / 1880MHz / BW20M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	24.54	0.013	2.5ppm	PASS
40		29.54	0.016		
30		22.61	0.012		
20		14.06	0.007		
10		22.79	0.012		
0		30.60	0.016		
-10		17.54	0.009		
-20		36.21	0.019		
-30		12.64	0.007		
25	Maximum Voltage	17.85	0.009		
25	BEP	14.13	0.008		



LTE Band 26(Part 22) (QPSK) / 836.5MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	24.23	0.014	2.5ppm	PASS
40		27.02	0.016		
30		21.85	0.013		
20		25.84	0.015		
10		25.17	0.015		
0		18.79	0.011		
-10		21.37	0.012		
-20		11.97	0.007		
-30		26.64	0.015		
25	Maximum Voltage	28.94	0.017		
25	BEP	26.39	0.015		

LTE Band 26(Part 22) (QPSK) / 836.5MHz / BW20M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	36.20	0.021	2.5ppm	PASS
40		36.49	0.021		
30		19.01	0.011		
20		18.59	0.011		
10		29.99	0.017		
0		32.27	0.019		
-10		13.76	0.008		
-20		18.59	0.011		
-30		18.86	0.011		
25	Maximum Voltage	24.91	0.014		
25	BEP	13.93	0.008		



LTE Band 26(Part 90) (QPSK) / 819MHz / BW5M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	31.93	0.018	2.5ppm	PASS
40		36.05	0.021		
30		19.19	0.011		
20		13.94	0.008		
10		31.40	0.018		
0		30.05	0.017		
-10		13.45	0.008		
-20		11.62	0.007		
-30		31.71	0.018		
25	Maximum Voltage	28.70	0.017		
25	BEP	33.29	0.019		

LTE Band 26(Part 90) (QPSK) / 819MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	14.20	0.008	2.5ppm	PASS
40		12.16	0.007		
30		13.44	0.008		
20		23.10	0.013		
10		34.03	0.020		
0		29.96	0.017		
-10		19.13	0.011		
-20		16.68	0.010		
-30		27.21	0.016		
25	Maximum Voltage	14.32	0.008		
25	BEP	28.89	0.017		



LTE Band 41 (QPSK) / 2593MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	13.93	0.005	2.5ppm	PASS
40		13.77	0.005		
30		29.65	0.012		
20		12.31	0.005		
10		22.86	0.009		
0		33.19	0.013		
-10		30.78	0.012		
-20		31.58	0.012		
-30		23.25	0.009		
25	Maximum Voltage	32.73	0.013		
25	BEP	32.68	0.013		

LTE Band 41 (QPSK) / 2593MHz / BW20M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	19.70	0.008	2.5ppm	PASS
40		34.11	0.013		
30		29.51	0.012		
20		22.92	0.009		
10		26.71	0.011		
0		21.42	0.008		
-10		27.05	0.011		
-20		20.72	0.008		
-30		19.88	0.008		
25	Maximum Voltage	13.54	0.005		
25	BEP	25.63	0.010		



LTE Band 66 (QPSK) / 1745MHz / BW10M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	11.94	0.007	2.5ppm	PASS
40		18.73	0.011		
30		26.66	0.015		
20		21.20	0.012		
10		29.38	0.017		
0		14.71	0.008		
-10		14.67	0.008		
-20		27.24	0.016		
-30		12.65	0.007		
25	Maximum Voltage	33.57	0.019		
25	BEP	20.14	0.012		

LTE Band 66 (QPSK) / 1745MHz / BW20M					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	20.77	0.012	2.5ppm	PASS
40		28.72	0.017		
30		34.18	0.020		
20		29.35	0.017		
10		31.11	0.018		
0		35.27	0.020		
-10		24.82	0.014		
-20		21.33	0.012		
-30		35.84	0.021		
25	Maximum Voltage	20.91	0.012		
25	BEP	15.31	0.009		



APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※

