

FCC Part 22H & 27

Measurement and Test Report

For

HONGKONG UCLOUDLINK NETWORK TECHNOLOGY LIMITED

Unit D. 16F, Chenknang plaza 250 Hennessy Road, wanchai HongKong

FCC ID: 2AC88-G2

FCC Rules: FCC Part 22H, FCC Part 27

Product Description: 4G Free Roaming Hotspot

Tested Model: G2

Report No.: STRD1506066I-1

Tested Date: 2015-06-12 to 2015-07-25

Issued Date: 2015-07-31

Tested By: Silin Chen / Engineer

Silin chen

Reviewed By: Lahm Peng / EMC Manager

Lahm peng

Approved & Authorized By: Jandy So / PSQ Manager

Jandyso

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 TEST EQUIPMENT LIST AND DETAILS.....	7
2. SUMMARY OF TEST RESULTS.....	8
3. RF EXPOSURE.....	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. RF OUTPUT POWER.....	10
4.1 STANDARD APPLICABLE.....	10
4.2 TEST PROCEDURE.....	10
4.3 ENVIRONMENTAL CONDITIONS.....	10
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	11
5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER.....	15
5.1 STANDARD APPLICABLE.....	15
5.2 TEST PROCEDURE.....	15
5.3 ENVIRONMENTAL CONDITIONS.....	15
5.4 SUMMARY OF TEST RESULTS.....	15
6. EMISSION BANDWIDTH.....	16
6.1 STANDARD APPLICABLE.....	16
6.2 TEST PROCEDURE.....	16
6.3 ENVIRONMENTAL CONDITIONS.....	16
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	16
7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....	17
7.1 STANDARD APPLICABLE.....	17
7.2 TEST PROCEDURE.....	17
7.3 ENVIRONMENTAL CONDITIONS.....	17
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
8. SPURIOUS RADIATED EMISSIONS.....	18
8.1 MEASUREMENT UNCERTAINTY.....	18
8.2 STANDARD APPLICABLE.....	18
8.3 TEST PROCEDURE.....	18
8.4 ENVIRONMENTAL CONDITIONS.....	18
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	18
9. FREQUENCY STABILITY.....	29
9.1 STANDARD APPLICABLE.....	29
9.2 TEST PROCEDURE.....	29
9.3 ENVIRONMENTAL CONDITIONS.....	30
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	30

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: HONGKONG UCLOUDLINK NETWORK TECHNOLOGY LIMITED

Address of applicant: Unit D. 16F, Chenknang plaza 250 Hennessy Road, wanchai HongKong

Manufacturer: Shenzhen Ukelink New Technology co., Ltd

Address of manufacturer: 3rd Floor, A Part of Building 1, Shenzhen Software Industry Base, Nanshan district xuefu Road, Shenzhen City, Guangdong Province, P.R. China

General Description of EUT:	
Product Name:	4G Free Roaming Hotspot
Brand Name:	GlocalMe
Model No.:	G2
Hardware version:	G2A_Main_Rev1.1
Software version:	G2_HTSV1.1.001.017.150804
Rated Voltage:	DC 3.7V Li-ion Battery
Battery:	6000mAh
Device Category:	Portable Device
Main board: <i>The EUT Main board support GSM850/900/DCS1800/PCS1900, WCDMA Band 1/2/5/8, LTE Band 1/3/5/7/8/17/20/39/40/41 function. It is intended for speech, Multimedia Message Service (MMS) transmission and 4G free roaming hotspot. It is equipped with GPRS/EDGE class 12 for GSM850/900/DCS1800/PCS1900, GPS, Bluetooth and Wi-Fi functions. For more information see the following datasheet</i>	
Vice board: <i>The EUT Vice board support GSM850/900/DCS1800/PCS1900, WCDMA Band 1/2/5/8. It is intended for system localization. It is equipped with GPRS/EDGE class 12 for GSM850/900/DCS1800/PCS1900 functions. For more information see the following datasheet</i>	
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT: Main board	
4G	
Support Networks:	FDD-LTE, TDD-LTE
Support Band:	FDD-LTE Band 5, 7, 17, TDD-LTE Band 41
Uplink Frequency:	FDD-LTE Band 5: Tx: 824-849MHz, FDD-LTE Band 7: Tx: 2500-2570MHz, FDD-LTE Band 17: Tx: 704-716MHz, TDD-LTE Band 41: Tx: 2496-2690MHz,
Downlink Frequency:	FDD-LTE Band 5: Rx: 869-894MHz, FDD-LTE Band 7: Rx: 2620-2690MHz, FDD-LTE Band 17: Rx: 734-746MHz, TDD-LTE Band 41: Rx: 2496-2690MHz,
RF Output Power:	FDD-LTE Band 5: 23.87dBm, FDD-LTE Band 7: 22.50dBm FDD-LTE Band 17: 24.42dBm TDD-LTE Band 41: 24.29dBm
Type of Emission:	FDD-LTE Band 5: 9M54G7D/9M53D7W FDD-LTE Band 7: 18M7G7D/18M6D7W FDD-LTE Band 17: 9M56G7D/9M53D7W TDD-LTE Band 41: 21M9G7D/18M7D7W
Type of Modulation:	QPSK, 16QAM
Antenna Type:	Integral Antenna
Antenna Gain:	FDD-LTE Band 5: -0.92dBi, FDD-LTE Band 7: -0.89dBi, FDD-LTE Band 17: -0.91dBi, TDD-LTE Band 41: -0.91dBi,

1.2 Test Standards

The following report is prepared on behalf of the HONGKONG U-CLOUDLINK NETWORK TECHNOLOGY LIMITED in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 27 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603-C: 2004 and ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	FDD-LTE Band 5	Low, Middle, High Channels
TM2	FDD-LTE Band 17	Low, Middle, High Channels
TM3	TDD-LTE Band 41	Low, Middle, High Channels

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	0.8	Unshielded	Without Ferrite
Earphone	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Test Equipment List and Details

Kind of Equipment	Manufacturer	Type	S/N	Cal Date	Due Date
Equipment list of < Shenzhen SEM.Test Technology Co., Ltd.>					
Test SIM card	-		-	N/A	
Communication Tester	Rohde & Schwarz	CMW500	148650	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	N9020A	US47140102	2015-06-17	2016-06-16
Signal Generator	Agilent	83752A	3610A01453	2015-06-17	2016-06-16
Vector Signal Generator	Agilent	N5182A	MY47070202	2015-06-17	2016-06-16
Power Divider	Weinschel	1506A	PM204	2015-06-17	2016-06-16
Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 27.50 (d)	RF Output Power	Compliant
§ 24.51	Peak-to-average Radio (PAR) of Transmitter	Compliant
§ 22.917 (b), § 27.53	Emission Bandwidth	Compliant
§ 22.917 (a), § 27.53	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 27.53	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 27.53	Out of Band Emissions	Compliant
§ 22.355, § 27.54	Frequency Stability	Compliant

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

4. RF Output Power


4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §27.50(d) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band are limited to 1 watt EIRP

4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2009 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

4.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.4 Summary of Test Results/Plots

Max. Radiated Power:

FDD-LTE Band 5

Channel Bandwidth: 1.4 MHz			
Modulation	Channel	E.r.p [dBm]	Verdict
QPSK	LCH	23.87	PASS
	MCH	23.47	PASS
	HCH	23.58	PASS
16QAM	LCH	22.75	PASS
	MCH	22.67	PASS
	HCH	22.70	PASS
Channel Bandwidth: 3 MHz			
Modulation	Channel	E.r.p [dBm]	Verdict
QPSK	LCH	23.45	PASS
	MCH	23.36	PASS
	HCH	23.31	PASS
16QAM	LCH	22.76	PASS
	MCH	22.64	PASS
	HCH	22.49	PASS
Channel Bandwidth: 5 MHz			
Modulation	Channel	E.r.p [dBm]	Verdict
QPSK	LCH	23.46	PASS
	MCH	23.23	PASS
	HCH	23.36	PASS
16QAM	LCH	22.69	PASS
	MCH	22.50	PASS
	HCH	22.51	PASS
Channel Bandwidth: 10 MHz			
Modulation	Channel	E.r.p [dBm]	Verdict
QPSK	LCH	23.38	PASS
	MCH	23.17	PASS
	HCH	23.23	PASS
16QAM	LCH	22.58	PASS
	MCH	22.52	PASS
	HCH	22.58	PASS

FDD-LTE Band 7

Channel Bandwidth: 5 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	21.63	PASS
	MCH	21.17	PASS
	HCH	21.35	PASS
16QAM	LCH	21.13	PASS
	MCH	20.86	PASS
	HCH	21.12	PASS
Channel Bandwidth: 10 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	21.25	PASS
	MCH	21.22	PASS
	HCH	20.78	PASS
16QAM	LCH	21.31	PASS
	MCH	21.33	PASS
	HCH	21.41	PASS
Channel Bandwidth: 15 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	21.35	PASS
	MCH	21.32	PASS
	HCH	21.41	PASS
16QAM	LCH	21.42	PASS
	MCH	21.00	PASS
	HCH	20.86	PASS
Channel Bandwidth: 20 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	21.19	PASS
	MCH	21.51	PASS
	HCH	21.28	PASS
16QAM	LCH	21.67	PASS
	MCH	21.53	PASS
	HCH	21.33	PASS

FDD-LTE Band 17

Channel Bandwidth: 5 MHz			
Modulation	Channel	E.r.p [dBm]	Verdict
QPSK	LCH	24.42	PASS
	MCH	24.26	PASS
	HCH	24.37	PASS
16QAM	LCH	23.74	PASS
	MCH	23.36	PASS
	HCH	22.88	PASS
Channel Bandwidth: 10 MHz			
Modulation	Channel	E.r.p [dBm]	Verdict
QPSK	LCH	24.23	PASS
	MCH	23.94	PASS
	HCH	24.18	PASS
16QAM	LCH	23.56	PASS
	MCH	23.28	PASS
	HCH	23.77	PASS

TDD-LTE Band 41

Channel Bandwidth: 5 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	22.46	PASS
	MCH	23.96	PASS
	HCH	23.73	PASS
16QAM	LCH	22.02	PASS
	MCH	22.68	PASS
	HCH	23.00	PASS
Channel Bandwidth: 10 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	22.61	PASS
	MCH	24.13	PASS
	HCH	23.76	PASS
16QAM	LCH	21.89	PASS
	MCH	23.41	PASS
	HCH	22.99	PASS

Channel Bandwidth: 15 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	22.60	PASS
	MCH	24.17	PASS
	HCH	23.72	PASS
16QAM	LCH	21.86	PASS
	MCH	23.42	PASS
	HCH	23.06	PASS
Channel Bandwidth: 20 MHz			
Modulation	Channel	E.i.r.p [dBm]	Verdict
QPSK	LCH	22.58	PASS
	MCH	24.17	PASS
	HCH	24.04	PASS
16QAM	LCH	21.80	PASS
	MCH	23.26	PASS
	HCH	22.96	PASS

Max. Conducted Output Power

Please refer to Appendix A: Average Power Output Data

Test result: Pass

5. Peak-to-average Radio (PAR) of Transmitter


5.1 Standard Applicable

Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results

Please refer to Appendix B: Peak-to-Average Ratio

Test result: Pass

6. Emission Bandwidth

6.1 Standard Applicable


According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.4 Summary of Test Results/Plots

Please refer to Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test result: Pass

7. Out of Band Emissions at Antenna Terminal

7.1 Standard Applicable


According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h) For operations in the 1710-1755 MHz and 2110-2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB

7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10^{th} harmonic.

Test Configuration for the out of band emissions testing:



7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

7.4 Summary of Test Results/Plots

Please refer to Appendix D: Band Edge

Test result: Pass

8. Spurious Radiated Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.20 dB.

8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h) For operations in the 1710-1755 MHz and 2110-2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB

8.3 Test Procedure

1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2009 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Spurious Emission From 30MHz to 1GHz


For FDD_LTE Band 5 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	49.5328	-69.71	4.35	-65.36	-13.00	-52.36	ERP
2	110.1816	-69.27	2.17	-67.10	-13.00	-54.10	ERP
3	968.9338	-68.86	18.01	-50.85	-13.00	-37.85	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	52.7600	-67.91	4.07	-63.84	-13.00	-50.84	ERP
2	96.4362	-67.90	1.81	-66.09	-13.00	-53.09	ERP
3	982.6200	-68.92	18.22	-50.70	-13.00	-37.70	ERP


For FDD_LTE Band 7Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.5030	-77.48	4.34	-73.14	-13.00	-60.14	EIRP
2	159.7844	-75.40	-0.55	-75.95	-13.00	-62.95	EIRP
3	1000.0000	-77.72	18.48	-59.24	-13.00	-46.24	EIRP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	48.6719	-77.72	4.35	-73.37	-13.00	-60.37	EIRP
2	159.7844	-74.16	-0.55	-74.71	-13.00	-61.71	EIRP
3	979.1804	-77.02	18.17	-58.85	-13.00	-45.85	EIRP


For FDD_LTE Band 17 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	44.7434	-68.86	4.28	-64.58	-13.00	-51.58	ERP
2	105.6415	-68.50	2.22	-66.28	-13.00	-53.28	ERP
3	929.0082	-67.31	17.50	-49.81	-13.00	-36.81	ERP


Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	46.3402	-69.04	4.34	-64.70	-13.00	-51.70	ERP
2	109.4116	-67.57	2.21	-65.36	-13.00	-52.36	ERP
3	989.5355	-68.85	18.32	-50.53	-13.00	-37.53	ERP


For TDD_LTE Band 41 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.5030	-69.18	4.34	-64.84	-13.00	-51.84	ERP
2	93.1132	-67.56	1.23	-66.33	-13.00	-53.33	ERP
3	929.0082	-67.31	17.50	-49.81	-13.00	-36.81	ERP

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	51.4807	-68.27	4.21	-64.06	-13.00	-51.06	ERP
2	109.4116	-67.57	2.21	-65.36	-13.00	-52.36	ERP
3	1000.0000	-68.87	18.48	-50.39	-13.00	-37.39	ERP

Note: Margin= (Reading+ Correct)- Limit

Spurious Emissions Above 1GHz
For FDD_LTE Band 5 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel						
1648.4	-55.26	4.94	-50.32	-13	-37.32	H
2472.6	-59.79	8.46	-51.33	-13	-38.33	H
1648.4	-53.25	4.94	-48.31	-13	-35.31	V
2472.6	-55.78	8.46	-47.32	-13	-34.32	V
Middle Channel						
1673.2	-56.42	5.11	-51.31	-13	-38.31	H
2509.8	-60.86	8.54	-52.32	-13	-39.32	H
1673.2	-54.22	5.11	-49.11	-13	-36.11	V
2509.8	-56.75	8.54	-48.21	-13	-35.21	V
High Channel						
1697.6	-53.51	5.29	-48.22	-13	-35.22	H
2546.4	-56.02	8.59	-47.43	-13	-34.43	H
1697.6	-51.13	5.29	-45.84	-13	-32.84	V
2546.4	-54.91	8.59	-46.32	-13	-33.32	V

For FDD_LTE Band 7 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel						
5005.0	-59.77	9.45	-50.32	-13	-37.32	H
7507.5	-62.88	11.55	-51.33	-13	-38.33	H
5005.0	-57.76	9.45	-48.31	-13	-35.31	V
7507.5	-58.87	11.55	-47.32	-13	-34.32	V
Middle Channel						
5070	-60.94	9.63	-51.31	-13	-38.31	H
7605	-64.26	11.94	-52.32	-13	-39.32	H
5070	-58.74	9.63	-49.11	-13	-36.11	V
7605	-60.15	11.94	-48.21	-13	-35.21	V
High Channel						
5135.0	-59.25	10.02	-49.23	-13	-36.23	H
7702.5	-62.34	12.11	-50.23	-13	-37.23	H
5135.0	-58.54	10.02	-48.52	-13	-35.52	V
7702.5	-63.54	12.11	-51.43	-13	-38.43	V

For FDD_LTE Band 17 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel						
1413.0	-53.22	3.85	-49.37	-13	-36.37	H
2119.5	-56.46	7.23	-49.23	-13	-36.23	H
1413.0	-50.08	3.85	-46.23	-13	-33.23	V
2119.5	-54.45	7.23	-47.22	-13	-34.22	V
Middle Channel						
1420.0	-55.36	3.93	-51.43	-13	-38.43	H
2130.0	-57.69	7.46	-50.23	-13	-37.23	H
1420.0	-49.16	3.93	-45.23	-13	-32.23	V
2130.0	-52.11	7.46	-44.65	-13	-31.65	V
High Channel						
1427.0	-53.66	4.17	-49.49	-13	-36.49	H
2140.5	-57.41	7.93	-49.48	-13	-36.48	H
1427.0	-50.40	4.17	-46.23	-13	-33.23	V
2140.5	-53.05	7.93	-45.12	-13	-32.12	V

For FDD_LTE Band 41 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel						
4997.0	-60.46	11.23	-49.23	-13	-36.23	H
7495.5	-63.35	15.23	-48.12	-13	-35.12	H
4997.0	-56.35	11.23	-45.12	-13	-32.12	V
7495.5	-59.35	15.23	-44.12	-13	-31.12	V
Middle Channel						
5186.0	-62.43	12.21	-50.22	-13	-37.22	H
7779.0	-65.57	16.34	-49.23	-13	-36.23	H
5186.0	-60.44	12.21	-48.23	-13	-35.23	V
7779.0	-65.57	16.34	-49.23	-13	-36.23	V
High Channel						
5375.0	-64.82	13.39	-51.43	-13	-38.43	H
8062.5	-67.21	17.22	-49.99	-13	-36.99	H
5375.0	-60.72	13.39	-47.33	-13	-34.33	V
8062.5	-63.45	17.22	-46.23	-13	-33.23	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the data is not display.

9. Frequency Stability

9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal

9.3 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

Please refer to Appendix F: Frequency Stability

Test result: Pass

***** END OF REPORT *****