



Calix GigaCenter™

1035 N McDowell Blvd., Petaluma, CA 94954

POWER: 12V = 4.1A

WARNING
AVERTISSEMENT

RISK OF ELECTRICAL SHOCK
RISQUE DE CHOC ÉLECTRIQUE

The device complies with Part 15 of FCC rules.
Operation is subject to the following two conditions:
• This device may not cause harmful interference.
• This device must accept any interference received,
including interference that may cause undesired operations.

This Class [B] digital apparatus complies with Canadian ICES-003.
Cet appareil numérique de la classe [B] est conforme à la norme
NMB-003 du Canada.

FCC ID 2ABLK-844FX-X
FC Tested to Comply
with FCC Standards
FOR HOME OR OFFICE USE

IC:4009A-844FX
MODEL 844F-1



RoHS
COMPLIANT



L.T.E
E207975
UL factory ID : 34

844F-1



100-Level No.: 100-04519 10
300-Level No.: 300-02551 10
Serial No.: 34YYMMXXXXXX
SSID: CXNKXXXXXXXXXX
WAN MAC: XXXXXXXXXXXXXX



MTA MAC: XXXXXXXXXXXXXX



Security Type: WPA2.AES
WPA Key: XXXXXXXXXXXXXXXXXXXX
IP Address: 192.168.1.1
User/Password: admin/XXXXXXX

US: I70DL01A844F-X
REN: 01A

This product meets the requirements of 47 CFR Part 68



Calix GigaCenter™

1035 N McDowell Blvd., Petaluma, CA 94954

POWER: 12V = 4.1A

WARNING
AVERTISSEMENT

RISK OF ELECTRICAL SHOCK
RISQUE DE CHOC ÉLECTRIQUE

The device complies with Part 15 of FCC rules.
Operation is subject to the following two conditions:
• This device may not cause harmful interference.
• This device must accept any interference received,
including interference that may cause undesired operations.

FCC ID 2ABLK-844FX-X
FC Tested to Comply
with FCC Standards
FOR HOME OR OFFICE USE

MODEL 844F-2

US: I70DL01A844F-X
REN: 01A

This product meets the requirements of 47 CFR Part 68

This Class [B] digital apparatus complies with Canadian ICES-003.
Cet appareil numérique de la classe [B] est conforme à la norme
NMB-003 du Canada.



RoHS
COMPLIANT



CERTIFIED



LISTED E207975
UL factory ID: 34

844F-2



100-Level No.: 100-04519 10
300-Level No.: 300-02551 10
Serial No.: 34YYMMXXXXXX
SSID: CXNKXXXXXXXXXX
WAN MAC: XXXXXXXXXXXXXX



MTA MAC: XXXXXXXXXXXXXX



Security Type: WPA2.AES
WPA Key: XXXXXXXXXXXXXXXXXXXX
IP Address: 192.168.1.1
User/Password: admin/XXXXXXX



Calix GigaCenter™

844FB-1

1035 N McDowell Blvd., Petaluma, CA 94954

POWER: 12V = 4.1A



100-Level No.: 100-04532 10
300-Level No.: 300-02550 10
Serial No.: 34YYMMXXXXXX
SSID: CXNKXXXXXXXXXX
WAN MAC: XXXXXXXXXXXXXX

WARNING
AVERTISSEMENT

RISK OF ELECTRICAL SHOCK
RISQUE DE CHOC ÉLECTRIQUE

The device complies with Part 15 of FCC rules.
Operation is subject to the following two conditions:
• This device may not cause harmful interference.
• This device must accept any interference received,
including interference that may cause undesired operations.

This Class [B] digital apparatus complies with Canadian ICES-003.
Cet appareil numérique de la classe [B] est conforme à la norme
NMB-003 du Canada.

FCC ID 2ABLK-844FX-X



Tested to Comply
with FCC Standards
FOR HOME OR OFFICE USE

IC:4009A-844FX
MODEL 844FB-1



RoHS
COMPLIANT



CERTIFIED



LISTED

L.T.E
E207975

UL factory ID : 34



MTA MAC: XXXXXXXXXXXXXX



Security Type: WPA2.AES
WPA Key: XXXXXXXXXXXXXXXXXXXX
IP Address: 192.168.1.1
User/Password: admin/XXXXXXX

US: I70DL01A844FB-X
REN: 01A

This product meets the requirements of 47 CFR Part 68



Calix GigaCenter™

1035 N McDowell Blvd., Petaluma, CA 94954

POWER: 12V = 4.1A

WARNING
AVERTISSEMENT

RISK OF ELECTRICAL SHOCK
RISQUE DE CHOC ÉLECTRIQUE

The device complies with Part 15 of FCC rules.
Operation is subject to the following two conditions:
• This device may not cause harmful interference.
• This device must accept any interference received,
including interference that may cause undesired operations.

FCC ID 2ABLK-844FX-X



Tested to Comply
with FCC Standards
FOR HOME OR OFFICE USE

MODEL 844FB-2



RoHS
COMPLIANT



CERTIFIED



LISTED E207975
UL factory ID : 34

844FB-2



100-Level No.: 100-04519 10
300-Level No.: 300-02551 10
Serial No.: 34YYMMXXXXXX
SSID: CXNKXXXXXXXXXX
WAN MAC: XXXXXXXXXXXXXX



MTA MAC: XXXXXXXXXXXXXX




Security Type: WPA2.AES
WPA Key: XXXXXXXXXXXXXXXXXXXX
IP Address: 192.168.1.1
User/Password: admin/XXXXXXX

US: I70DL01A844F-X

REN: 01A

This product meets the requirements of 47 CFR Part 68



Label location