

TEST REPORT

Applicant Name : Winner Wave Limited
Address : Unit 1615 Peninsula Tower, 538 Castle Peak Road, Lai Chi Kok
Kowloon, Hong Kong
Report Number : SZNS221025-49151E-RF-00
FCC ID: 2ADFS-T02PLUS

Test Standard (s)

FCC PART 15.407

Sample Description

Product Type: QuattroPod
Model No.: T02 PIUS
Multiple Model(s) No.: T03
Trade Mark: QuattroPod
Date Received: 2022/10/25
Report Date: 2022/12/01

Test Result:	Pass*
--------------	-------


* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Nick Fang
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §1.1307 (B) (3) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
FCC §15.203 – ANTENNA REQUIREMENT	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.407 (B) (6) §15.207 (A) – CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP	16
TEST PROCEDURE	16
TRANSF FACTOR & MARGIN CALCULATION	17
TEST DATA	17
§15.205 & §15.209 & §15.407(B)– UNDESIRABLE EMISSION	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
FACTOR & MARGIN CALCULATION	22
TEST DATA	22
FCC §15.407(A),(E) – 26 DB & 6DB EMISSION BANDWIDTH	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	34
FCC §15.407(A) – CONDUCTED TRANSMITTER OUTPUT POWER	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	36

FCC §15.407(A) - POWER SPECTRAL DENSITY37
 TEST PROCEDURE37
 TEST DATA38
APPENDIX39
 APPENDIX A1: EMISSION BANDWIDTH39
 APPENDIX A2: OCCUPIED CHANNEL BANDWIDTH45
 APPENDIX B: DUTY CYCLE51
 APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER57
 APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY58

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	QuattroPod
Tested Model	T02 PIUS
Multiple Models	T03 (model difference see product declaration letter of similarity)
Frequency Range	5G Wi-Fi: 5150-5250MHz
Mode	802.11a/n20/n40/ac20/ac40/ac80
Maximum Conducted Average Output Power	5150-5250 MHz: 17.55dBm
Modulation Technique	OFDM
Antenna Specification*	1.8dBi (provided by the applicant)
Voltage Range	DC 5V from USB port
Sample serial number	1NH0-8 (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The system supports 802.11a/n-HT20/n-HT 40/ac-VHT 20/ac-VHT 40/ac-VHT 80 modes.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a/n20/ac20 mode: channel 36, 40, 48 were tested;

For 802.11n40/ac40 mode: channel 38, 46 were tested;

For 802.11ac80 mode, channel 42 was tested.

EUT Exercise Software

“MP_Kit_RTL11ac_8821CU_USB_v1.23A_20170307(BETA)*” exercise software was used, the power level was provided by the manufacturer.

The worst case was performed under:

U-NII	Mode	Data rate	Power Level*		
			Low Channel	Middle Channel	High Channel
5150 – 5250MHz	802.11a	6Mbps	63	63	63
	802.11n-HT20	MCS0	63	63	63
	802.11n-HT40	MCS0	47	/	47
	802.11ac20	MCS0	57	57	57
	802.11ac40	MCS0	45	/	45
	802.11ac80	MCS0	/	42	/

The worse-case data rates are determined to be as follows for each mode based upon investigations by measuring the output power and PSD across all data rated bandwidths, and modulations.

The power level was provided by the applicant.

Duty cycle

Test Result: Pass. Please refer to the Appendix.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Infinix	Mobile Phone	X6515	221013V151
DELL	PC	Latitude E7280	9RVYFH2
Shi ying yuan	Adapter	ICP12-050-2000B	Unkown

External I/O Cable


Cable Description	Length (m)	From Port	To
Shielded detachable HDMI cable	0.2	PC	EUT
Un-shielded un-detachable USB cable	0.18	EUT	Adapter
Shielded detachable USB cable	1.0	EUT	Phone
Un-shielded un-detachable AC cable	1.2	Socket	Mains

Block Diagram of Test Setup


For conducted emission:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §1.1307 (b) (3) & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.407(b)(9)& §15.207(a)	Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Not Applicable

Not Applicable: the EUT not operating within frequency range of 5250-5350MHz&5470-5725MHz.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/10	2023/11/9
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
CD	Band Reject Filter	BRM-5.15/5.35g-45	075	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/01/19	2023/01/18
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) (3) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBm)	(dBi)	(dBd)	(dBm)	(W)		
5G Wi-Fi	5150-5250	18.0	1.8	-0.35	17.65	0.058	0.2	0.768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
3. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement for 5G Wi-Fi which were permanently attached. Please refer to the EUT photos.

Type	Antenna Gain	Impedance	Frequency Range
PCB	1.8dBi	50 Ω	5150-5850MHz


Result: Compliant.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$


Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa


The testing was performed by Lipa Li on 2022-11-16.

EUT operation mode: Transmitting (worst case is 802.11n20, 5240MHz)

AC 120V/60 Hz, Line:

Site : Shielding Room
 Condition: Line
 Job No. : SZNS221025-49151E-RF
 Mode : 5G WIFI
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.166	9.80	17.26	27.06	55.16	-28.10	Average
2	0.166	9.80	29.27	39.07	65.16	-26.09	QP
3	0.293	9.80	23.24	33.04	50.43	-17.39	Average
4	0.293	9.80	32.12	41.92	60.43	-18.51	QP
5	0.301	9.80	24.24	34.04	50.22	-16.18	Average
6	0.301	9.80	34.35	44.15	60.22	-16.07	QP
7	0.516	9.81	18.85	28.66	46.00	-17.34	Average
8	0.516	9.81	26.24	36.05	56.00	-19.95	QP
9	2.001	9.82	12.61	22.43	46.00	-23.57	Average
10	2.001	9.82	17.19	27.01	56.00	-28.99	QP
11	7.388	9.87	5.64	15.51	50.00	-34.49	Average
12	7.388	9.87	13.87	23.74	60.00	-36.26	QP

AC 120V/60 Hz, Neutral:

Site : Shielding Room
 Condition: Neutral
 Job No. : SZNS221025-49151E-RF
 Mode : 5G WIFI
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.177	9.80	21.90	31.70	54.64	-22.94	Average
2	0.177	9.80	26.32	36.12	64.64	-28.52	QP
3	0.292	9.80	27.76	37.56	50.48	-12.92	Average
4	0.292	9.80	33.35	43.15	60.48	-17.33	QP
5	0.434	9.80	28.49	38.29	47.18	-8.89	Average
6	0.434	9.80	33.36	43.16	57.18	-14.02	QP
7	0.500	9.80	21.01	30.81	46.00	-15.19	Average
8	0.500	9.80	28.54	38.34	56.00	-17.66	QP
9	2.692	9.83	18.56	28.39	46.00	-17.61	Average
10	2.692	9.83	23.55	33.38	56.00	-22.62	QP
11	8.940	9.99	13.80	23.79	50.00	-26.21	Average
12	8.940	9.99	20.00	29.99	60.00	-30.01	QP

§15.205 & §15.209 & §15.407(B)– UNDESIRABLE EMISSION

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

Below 1 GHz:



Above 1 GHz:

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure**Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dB μ V/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dB μ V/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB, for 18-40GHz range, the limit of 1m distance was added by 9.5dB from limit of 3m to compared with the result measurement at 1m distance.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level / Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	25~25.5 °C
Relative Humidity:	52~60%
ATM Pressure:	101.0 kPa


The testing was performed by Jimi on 2022-11-21 for below 1GHz and Jason Liu on 2022-11-25 for above 1GHz.

EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axes of orientation was recorded)

30 MHz – 1 GHz: (worst case is 802.11n20, 5240MHz)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : SZNS221025-49151E-RF
Test Mode: 5G WIFI

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	108.030	-11.99	38.97	26.98	43.50	-16.52	Peak
2	134.973	-15.02	41.93	26.91	43.50	-16.59	Peak
3	270.138	-10.22	54.10	43.88	46.00	-2.12	QP
4	334.126	-7.68	50.00	42.32	46.00	-3.68	QP
5	665.512	-1.66	43.10	41.44	46.00	-4.56	QP
6	990.403	2.83	35.89	38.72	54.00	-15.28	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS221025-49151E-RF
 Test Mode: 5G WIFI

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	52.783	-10.13	36.56	26.43	40.00	-13.57	Peak
2	99.006	-12.03	43.04	31.01	43.50	-12.49	Peak
3	193.858	-11.31	42.16	30.85	43.50	-12.65	Peak
4	288.243	-9.36	50.71	41.35	46.00	-4.65	QP
5	337.511	-7.52	49.10	41.58	46.00	-4.42	QP
6	662.892	-1.65	40.83	39.18	46.00	-6.82	Peak

Above 1GHz:**5150-5250 MHz:**

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11a									
5180 MHZ									
4500	65.86	PK	143	1.5	H	-4.72	61.14	74	-12.86
4500	51.63	AV	143	1.5	H	-4.72	46.91	54	-7.09
4500	66.34	PK	33	1.4	V	-4.72	61.62	74	-12.38
4500	52.22	AV	33	1.4	V	-4.72	47.50	54	-6.50
5150	69.86	PK	354	2.1	H	-2.73	67.13	74	-6.87
5150	54.25	AV	354	2.1	H	-2.73	51.52	54	-2.48
5150	67.35	PK	9	2.2	V	-2.73	64.62	74	-9.38
5150	52.70	AV	9	2.2	V	-2.73	49.97	54	-4.03
10360	52.38	PK	163	1.6	H	8.12	60.50	68.2	-7.70
10360	52.31	PK	18	1.6	V	8.12	60.43	68.2	-7.77
5200 MHZ									
10400	51.82	PK	133	1.6	H	8.24	60.06	68.2	-8.14
10400	51.91	PK	226	1.6	V	8.24	60.15	68.2	-8.05
5240 MHZ									
5350	62.17	PK	11	1.9	H	-2.33	59.84	74	-14.16
5350	48.84	AV	11	1.9	H	-2.33	46.51	54	-7.49
5350	62.18	PK	117	2	V	-2.33	59.85	74	-14.15
5350	48.98	AV	117	2	V	-2.33	46.65	54	-7.35
5460	61.81	PK	207	1.6	H	-2.26	59.55	74	-14.45
5460	47.65	AV	207	1.6	H	-2.26	45.39	54	-8.61
5460	61.91	PK	340	1.6	V	-2.26	59.65	74	-14.35
5460	47.68	AV	340	1.6	V	-2.26	45.42	54	-8.58
10480	51.90	PK	22	1.7	H	8.56	60.46	68.2	-7.74
10480	52.58	PK	316	1.7	V	8.56	61.14	68.2	-7.06

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n20									
5180 MHZ									
4500	66.56	PK	167	2.3	H	-4.72	61.84	74	-12.16
4500	52.23	AV	167	2.3	H	-4.72	47.51	54	-6.49
4500	66.18	PK	284	1.8	V	-4.72	61.46	74	-12.54
4500	52.18	AV	284	1.8	V	-4.72	47.46	54	-6.54
5150	72.73	PK	28	2.1	H	-2.73	70.00	74	-4.00
5150	54.47	AV	28	2.1	H	-2.73	51.74	54	-2.26
5150	71.67	PK	78	1.2	V	-2.73	68.94	74	-5.06
5150	53.19	AV	78	1.2	V	-2.73	50.46	54	-3.54
10360	52.83	PK	162	1.7	H	8.12	60.95	68.2	-7.25
10360	52.20	PK	45	1.7	V	8.12	60.32	68.2	-7.88
5200 MHZ									
10400	52.23	PK	288	1.4	H	8.24	60.47	68.2	-7.73
10400	52.04	PK	14	1.4	V	8.24	60.28	68.2	-7.92
5240 MHZ									
5350	62.85	PK	231	1.3	H	-2.33	60.52	74	-13.48
5350	49.13	AV	231	1.3	H	-2.33	46.80	54	-7.20
5350	62.71	PK	284	2	V	-2.33	60.38	74	-13.62
5350	49.41	AV	284	2	V	-2.33	47.08	54	-6.92
5460	61.10	PK	172	1.7	H	-2.26	58.84	74	-15.16
5460	48.95	AV	172	1.7	H	-2.26	46.69	54	-7.31
5460	61.98	PK	128	1.6	V	-2.26	59.72	74	-14.28
5460	48.88	AV	128	1.6	V	-2.26	46.62	54	-7.38
10480	52.77	PK	20	1.7	H	8.56	61.33	68.2	-6.87
10480	52.63	PK	91	1.7	V	8.56	61.19	68.2	-7.01

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11N40									
5190 MHZ									
4500	65.92	PK	356	1.6	H	-4.72	61.20	74	-12.80
4500	52.80	AV	356	1.6	H	-4.72	48.08	54	-5.92
4500	66.74	PK	319	2.4	V	-4.72	62.02	74	-11.98
4500	52.96	AV	319	2.4	V	-4.72	48.24	54	-5.76
5150	67.50	PK	69	1.6	H	-2.73	64.77	74	-9.23
5150	53.73	AV	69	1.6	H	-2.73	51.00	54	-3.00
5150	68.05	PK	346	1	V	-2.73	65.32	74	-8.68
5150	53.58	AV	346	1	V	-2.73	50.85	54	-3.15
10380	52.07	PK	103	1.1	H	8.18	60.25	68.2	-7.95
10380	52.20	PK	86	1.1	V	8.18	60.38	68.2	-7.82
5230 MHZ									
5350	61.71	PK	47	2.1	H	-2.33	59.38	74	-14.62
5350	49.42	AV	47	2.1	H	-2.33	47.09	54	-6.91
5350	61.86	PK	157	2.4	V	-2.33	59.53	74	-14.47
5350	49.18	AV	157	2.4	V	-2.33	46.85	54	-7.15
5460	61.96	PK	80	1.2	H	-2.26	59.70	74	-14.30
5460	48.82	AV	80	1.2	H	-2.26	46.56	54	-7.44
5460	61.55	PK	199	1.2	V	-2.26	59.29	74	-14.71
5460	49.07	AV	199	1.2	V	-2.26	46.81	54	-7.19
10460	52.60	PK	326	1.7	H	8.47	61.07	68.2	-7.13
10460	52.31	PK	11	1.7	V	8.47	60.78	68.2	-7.42

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11AC20									
5180 MHz									
4500	65.94	PK	192	1.5	H	-4.72	61.22	74	-12.78
4500	52.19	AV	192	1.5	H	-4.72	47.47	54	-6.53
4500	65.56	PK	349	1	V	-4.72	60.84	74	-13.16
4500	52.30	AV	349	1	V	-4.72	47.58	54	-6.42
5150	65.61	PK	27	1.4	H	-2.73	62.88	74	-11.12
5150	53.55	AV	27	1.4	H	-2.73	50.82	54	-3.18
5150	63.89	PK	151	1.2	V	-2.73	61.16	74	-12.84
5150	52.29	AV	151	1.2	V	-2.73	49.56	54	-4.44
10360	52.52	PK	110	1.2	H	8.12	60.64	68.2	-7.56
10360	51.96	PK	77	1.2	V	8.12	60.08	68.2	-8.12
5200 MHz									
10400	52.37	PK	5	1.5	H	8.24	60.61	68.2	-7.59
10400	52.18	PK	345	1.5	V	8.24	60.42	68.2	-7.78
5240 MHz									
5350	62.52	PK	220	1.8	H	-2.33	60.19	74	-13.81
5350	49.14	AV	220	1.8	H	-2.33	46.81	54	-7.19
5350	61.54	PK	207	2.1	V	-2.33	59.21	74	-14.79
5350	49.10	AV	207	2.1	V	-2.33	46.77	54	-7.23
5460	61.91	PK	347	2.2	H	-2.26	59.65	74	-14.35
5460	49.35	AV	347	2.2	H	-2.26	47.09	54	-6.91
5460	51.63	PK	88	1.8	V	-2.26	49.37	74	-24.63
5460	49.05	AV	88	1.8	V	-2.26	46.79	54	-7.21
10480	52.50	PK	136	1.7	H	8.56	61.06	68.2	-7.14
10480	52.00	PK	269	1.7	V	8.56	60.56	68.2	-7.64

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11AC40									
5190 MHz									
4500	65.74	PK	156	2.1	H	-4.72	61.02	74	-12.98
4500	52.94	AV	156	2.1	H	-4.72	48.22	54	-5.78
4500	65.50	PK	156	1.6	V	-4.72	60.78	74	-13.22
4500	52.26	AV	156	1.6	V	-4.72	47.54	54	-6.46
5150	69.03	PK	128	1.2	H	-2.73	66.30	74	-7.70
5150	53.47	AV	128	1.2	H	-2.73	50.74	54	-3.26
5150	66.97	PK	116	1.7	V	-2.73	64.24	74	-9.76
5150	51.84	AV	116	1.7	V	-2.73	49.11	54	-4.89
10380	51.98	PK	216	2.4	H	8.18	60.16	68.2	-8.04
10380	52.15	PK	235	2.4	V	8.18	60.33	68.2	-7.87
5230 MHz									
5350	65.08	PK	90	1.2	H	-2.33	62.75	74	-11.25
5350	49.34	AV	90	1.2	H	-2.33	47.01	54	-6.99
5350	63.43	PK	311	2.3	V	-2.33	61.10	74	-12.90
5350	48.96	AV	311	2.3	V	-2.33	46.63	54	-7.37
5460	64.72	PK	255	1.1	H	-2.26	62.46	74	-11.54
5460	48.93	AV	255	1.1	H	-2.26	46.67	54	-7.33
5460	63.27	PK	184	1.1	V	-2.26	61.01	74	-12.99
5460	48.80	AV	184	1.1	V	-2.26	46.54	54	-7.46
10460	52.31	PK	337	1.7	H	8.47	60.78	68.2	-7.42
10460	51.79	PK	49	1.7	V	8.47	60.26	68.2	-7.94

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11AC80									
5210MHz									
4500	66.19	PK	151	1.4	H	-4.72	61.47	74	-12.53
4500	53.53	AV	151	1.4	H	-4.72	48.81	54	-5.19
4500	65.77	PK	107	2.3	V	-4.72	61.05	74	-12.95
4500	53.84	AV	107	2.3	V	-4.72	49.12	54	-4.88
5150	66.96	PK	11	1.9	H	-2.73	64.23	74	-9.77
5150	53.45	AV	11	1.9	H	-2.73	50.72	54	-3.28
5150	64.99	PK	40	1.9	V	-2.73	62.26	74	-11.74
5150	53.61	AV	40	1.9	V	-2.73	50.88	54	-3.12
5350	62.59	PK	309	1.2	H	-2.33	60.26	74	-13.74
5350	50.50	AV	309	1.2	H	-2.33	48.17	54	-5.83
5350	62.59	PK	237	1.3	V	-2.33	60.26	74	-13.74
5350	50.29	AV	237	1.3	V	-2.33	47.96	54	-6.04
5460	61.46	PK	254	2.1	H	-2.26	59.20	74	-14.80
5460	49.28	AV	254	2.1	H	-2.26	47.02	54	-6.98
5460	61.45	PK	108	1.8	V	-2.26	59.19	74	-14.81
5460	49.27	AV	108	1.8	V	-2.26	47.01	54	-6.99
10420	51.91	PK	312	1.7	H	8.32	60.23	68.2	-7.97
10420	52.20	PK	345	1.7	V	8.32	60.52	68.2	-7.68

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.


1 GHz - 18 GHz: (Pre-Scan plots)

802.11 n20, 5240MHz

Horizontal




Vertical




18-40GHz: (Pre-Scan plots)

802.11 n20, 5240MHz

Horizontal



Vertical



FCC §15.407(a),(e) – 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2022-11-14 and 2022-11-15.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

FCC §15.407(a) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

- Place the EUT on a bench and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- Add a correction factor to the display.



Note: the RF Control Unit has a built-in power sensor.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2022-11-14 and 2022-11-15.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

FCC §15.407(a) - POWER SPECTRAL DENSITY

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth ($< 1 \text{ MHz}$, or $< 500 \text{ kHz}$) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.1.a).
- Set $\text{VBW} \geq 3 \text{ RBW}$.
- If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2022-11-14 and 2022-11-15.

EUT operation mode: Transmitting

Test Result: Pass


Please refer to the Appendix.


APPENDIX


Appendix A1: Emission Bandwidth Test Result


Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	22.12	5169.08	5191.20	---	---
		5200	22.36	5188.92	5211.28	---	---
		5240	22.36	5228.88	5251.24	---	---
11N20SISO	Ant1	5180	23.00	5168.72	5191.72	---	---
		5200	23.00	5188.72	5211.72	---	---
		5240	23.04	5228.68	5251.72	---	---
11N40SISO	Ant1	5190	44.64	5167.84	5212.48	---	---
		5230	44.48	5207.92	5252.40	---	---
11AC20SISO	Ant1	5180	22.80	5168.92	5191.72	---	---
		5200	22.96	5188.80	5211.76	---	---
		5240	22.96	5228.76	5251.72	---	---
11AC40SISO	Ant1	5190	44.16	5167.84	5212.00	---	---
		5230	44.08	5207.92	5252.00	---	---
11AC80SISO	Ant1	5210	84.32	5168.08	5252.40	---	---


Test Graphs













Appendix A2: Occupied channel bandwidth Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	17.782	5170.969	5188.751	---	---
		5200	17.942	5190.889	5208.831	---	---
		5240	17.862	5230.929	5248.791	---	---
11N20SISO	Ant1	5180	18.861	5170.529	5189.391	---	---
		5200	18.981	5190.490	5209.471	---	---
		5240	18.901	5230.529	5249.431	---	---
11N40SISO	Ant1	5190	37.642	5171.219	5208.861	---	---
		5230	37.562	5211.299	5248.861	---	---
11AC20SISO	Ant1	5180	18.501	5170.889	5189.391	---	---
		5200	18.621	5190.849	5209.471	---	---
		5240	18.541	5230.849	5249.391	---	---
11AC40SISO	Ant1	5190	37.642	5171.219	5208.861	---	---
		5230	37.562	5211.299	5248.861	---	---
11AC80SISO	Ant1	5210	76.723	5171.798	5248.521	---	---


Note: the device not operating with any part of OBW fall within 5250-5350MHz range


Test Graphs











**Appendix B: Duty Cycle
Test Result**


Test Mode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11A	Ant1	5180	30.00	30.00	100.00
		5200	30.00	30.00	100.00
		5240	30.00	30.00	100.00
11N20SISO	Ant1	5180	30.00	30.00	100.00
		5200	30.00	30.00	100.00
		5240	30.00	30.00	100.00
11N40SISO	Ant1	5190	30.00	30.00	100.00
		5230	30.00	30.00	100.00
11AC20SISO	Ant1	5180	30.00	30.00	100.00
		5200	30.00	30.00	100.00
		5240	30.00	30.00	100.00
11AC40SISO	Ant1	5190	30.00	30.00	100.00
		5230	30.00	30.00	100.00
11AC80SISO	Ant1	5210	30.00	30.00	100.00

Test Graphs







11N40SISO Ant1 5190




11N40SISO Ant1 5230




11AC20SISO Ant1 5180




11AC20SISO Ant1 5200




11AC20SISO Ant1 5240



11AC40SISO Ant1 5190






**Appendix C: Maximum conducted output power
Test Result Channel Power**


Test Mode	Antenna	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
11A	Ant1	5180	17.27	≤23.98	PASS
		5200	17.03	≤23.98	PASS
		5240	17.52	≤23.98	PASS
11N20SISO	Ant1	5180	17.48	≤23.98	PASS
		5200	17.12	≤23.98	PASS
		5240	17.55	≤23.98	PASS
11N40SISO	Ant1	5190	12.02	≤23.98	PASS
		5230	12.45	≤23.98	PASS
11AC20SISO	Ant1	5180	15.79	≤23.98	PASS
		5200	15.47	≤23.98	PASS
		5240	15.97	≤23.98	PASS
11AC40SISO	Ant1	5190	11.25	≤23.98	PASS
		5230	11.66	≤23.98	PASS
11AC80SISO	Ant1	5210	9.58	≤23.98	PASS


**Appendix D: Maximum power spectral density
Test Result**


Test Mode	Antenna	Frequency[MHz]	Result [dBm/MHz]	Limit[dBm/MHz]	Verdict
11A	Ant1	5180	6.09	≤11.00	PASS
		5200	5.79	≤11.00	PASS
		5240	6.29	≤11.00	PASS
11N20SISO	Ant1	5180	6.12	≤11.00	PASS
		5200	5.56	≤11.00	PASS
		5240	6.05	≤11.00	PASS
11N40SISO	Ant1	5190	-2.42	≤11.00	PASS
		5230	-1.96	≤11.00	PASS
11AC20SISO	Ant1	5180	4.3	≤11.00	PASS
		5200	4.12	≤11.00	PASS
		5240	4.52	≤11.00	PASS
11AC40SISO	Ant1	5190	-3.1	≤11.00	PASS
		5230	-2.75	≤11.00	PASS
11AC80SISO	Ant1	5210	-6.43	≤11.00	PASS


Test Graphs











***** END OF REPORT *****