

FCC Test Report (WLAN)

Report No.: RFBAOZ-WTW-P20080227-1

FCC ID: WT8DNWAP840

Test Model: AP840

Received Date: Aug. 12, 2020

Test Date: Aug. 21 to Sep. 16, 2020

Issued Date: Oct. 30, 2020

Applicant: Datto, Inc.

Address: 101 Merritt 7, Norwalk, CT 06851 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT (WLAN)	7
3.2 Description of Test Modes	10
3.2.1 Test Mode Applicability and Tested Channel Detail	11
3.3 Duty Cycle of Test Signal	14
3.4 Description of Support Units	15
3.4.1 Configuration of System under Test	16
3.5 General Description of Applied Standards and References	18
4 Test Types and Results	19
4.1 Radiated Emission and Bandedge Measurement.....	19
4.1.1 Limits of Radiated Emission and Bandedge Measurement	19
4.1.2 Test Instruments	20
4.1.3 Test Procedure	22
4.1.4 Deviation from Test Standard	23
4.1.5 Test Setup.....	23
4.1.6 EUT Operating Condition	24
4.1.7 Test Results	25
4.2 Conducted Emission Measurement	45
4.2.1 Limits of Conducted Emission Measurement	45
4.2.2 Test Instruments	45
4.2.3 Test Procedure	46
4.2.4 Deviation from Test Standard	46
4.2.5 Test Setup.....	46
4.2.6 EUT Operating Condition	46
4.2.7 Test Results	47
4.3 Transmit Power Measurement	49
4.3.1 Limits of Transmit Power Measurement	49
4.3.2 Test Setup.....	49
4.3.3 Test Instruments	49
4.3.4 Test Procedure	50
4.3.5 Deviation from Test Standard	50
4.3.6 EUT Operating Condition	50
4.3.7 Test Results	51
4.4 Occupied Bandwidth Measurement	57
4.4.1 Test Setup.....	57
4.4.2 Test Instruments	57
4.4.3 Test Procedure	57
4.4.4 Test Results	58
4.5 Peak Power Spectral Density Measurement	64
4.5.1 Limits of Peak Power Spectral Density Measurement	64
4.5.2 Test Setup.....	64
4.5.3 Test Instruments	64
4.5.4 Test Procedure	64
4.5.5 Deviation from Test Standard	65
4.5.6 EUT Operating Condition	65
4.5.7 Test Results	66
4.6 Frequency Stability Measurement.....	72
4.6.1 Limits of Frequency Stability Measurement	72

4.6.2	Test Setup.....	72
4.6.3	Test Instruments	72
4.6.4	Test Procedure	72
4.6.5	Deviation from Test Standard	72
4.6.6	EUT Operating Condition	72
4.6.7	Test Results	73
4.7	6dB Bandwidth Measurement	74
4.7.1	Limits of 6dB Bandwidth Measurement	74
4.7.2	Test Setup.....	74
4.7.3	Test Instruments	74
4.7.4	Test Procedure	74
4.7.5	Deviation from Test Standard	74
4.7.6	EUT Operating Condition	74
4.7.7	Test Results	75
5	Pictures of Test Arrangements.....	77
	Annex A - Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)	78
	Annex B - Band-Edge Measurement (For U-NII-1 band)	82
	Appendix – Information of the Testing Laboratories	86

Release Control Record

Issue No.	Description	Date Issued
RFBAOZ-WTW-P20080227-1	Original release.	Oct. 30, 2020

1 Certificate of Conformity

Product: WiFi6 indoor Access Point

Brand: datto

Test Model: AP840

Sample Status: ENGINEERING SAMPLE

Applicant: Datto, Inc.

Test Date: Aug. 21 to Sep. 16, 2020

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Oct. 30, 2020

Claire Kuan / Specialist

Approved by :



Date:

Oct. 30, 2020

Clark Lin / Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
FCC Clause	Test Item	Result	Remarks
15.407(b)(6)	AC Power Conducted Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -6.11 dB at 8.09375 MHz.
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement*	Pass	Meet the requirement of limit. Minimum passing margin is -0.1dB at 5134.59MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	-	Reference only.
15.407(a)(1/2/3)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6dB bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is i-pex(MHF) not a standard connector.

Note:

1. For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.
2. For U-NII-1 band compliance with rule 15.407(b) of the band-edge items, the test plots were recorded in Annex B. Test Procedures refer to report 4.1.3.
3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.4 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.0 dB
	18GHz ~ 40GHz	5.3 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (WLAN)

Product	WiFi6 indoor Access Point
Brand	datto
Test Model	AP840
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	48 Vdc / 0.625A from power adapter, 48-54 Vdc / 0.5A from POE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT (20/40) mode in 2.4GHz 1024QAM for OFDMA in 11ax HE mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11 Mbps 802.11a/g: up to 54 Mbps 802.11n: up to 600 Mbps 802.11ac: up to 1733.3 Mbps 802.11ax: up to 2402 Mbps
Operating Frequency	2.4GHz: 2.412 ~ 2.462 GHz 5GHz: 5.18~ 5.24 GHz, 5.745 ~ 5.825 GHz
Number of Channel	2.4GHz: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 5GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 9 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 4 802.11ac (VHT80), 802.11ax (HE80): 2
Output Power	CDD Mode: 2.412 ~ 2.462 GHz: 952.722 mW 5.18 ~ 5.24 GHz: 610.7 mW 5.745 ~ 5.825 GHz: 963.3 mW Beamforming Mode: 2.412 ~ 2.462 GHz: 427.044 mW 5.18 ~ 5.24 GHz: 293.152 mW 5.745 ~ 5.825 GHz: 293.193 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. The EUT has below radios as following table:

Radio 1	Radio 2	Radio 3	Radio 4
WLAN 2.4GHz	WLAN 5GHz	Bluetooth	2.4GHz /5GHz Background Scanning (RX only)

2. Simultaneously transmission condition.

Condition	Technology		
1	WLAN (2.4GHz)	WLAN (5GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The antenna provided to the EUT, please refer to the following table:

Antenna No.	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
1	290-20458	3.97	2.4~2.4835	PIFA	i-pex(MHF)	210
2	290-20458	3.4	2.4~2.4835	PIFA	i-pex(MHF)	45
3	290-20458	3.79	2.4~2.4835	PIFA	i-pex(MHF)	130
4	290-20458	3.01	2.4~2.4835	PIFA	i-pex(MHF)	225
5	290-20458	5.22	5.15~5.85	PIFA	i-pex(MHF)	250
6	290-20458	5.71	5.15~5.85	PIFA	i-pex(MHF)	150
7	290-20458	5.45	5.15~5.85	PIFA	i-pex(MHF)	60
8	290-20458	4.69	5.15~5.85	PIFA	i-pex(MHF)	200
9 (Background Ant._ RX only)	290-20458	6.45 4.5	2.4~2.4835 5.15~5.85	PIFA	i-pex(MHF)	140
10 (BT Ant.)	-	3.28	2.4~2.4835	PCB	i-pex(MHF)	None

4. The EUT was pre-tested under the following modes:

Test Mode	Description
Mode A	With adapter mode
Mode B	With POE mode

Note: From the above modes, radiated emission the worst case was found in **Mode A**. Therefore only the test data of the mode was recorded in this report.

5. The EUT incorporates a MIMO function.

2.4GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	4TX	4RX
802.11g	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
VHT20	4TX	4RX
VHT40	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
5GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11a	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
802.11ac (VHT20)	4TX	4RX
802.11ac (VHT40)	4TX	4RX
802.11ac (VHT80)	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11ax (HE80)	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz), 802.11ac mode for 20MHz (40MHz, 80MHz) and 802.11ax mode for 20MHz (40MHz, 80MHz), therefore the manufacturer will control the power for 802.11n/ac mode is the same as the 802.11ax mode or more lower than it and investigated worst case to representative mode in test report. (Final test mode refer to section 3.2.1)
6. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
7. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
42	5210 MHz

FOR 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
151	5755 MHz	159	5795 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
155	5775 MHz

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of laying-flat and wall-mount. The worst case was found when positioned of on laying-flat.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter
802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6Mb/s
802.11ax (HE20)		36 to 48	36, 40, 48	OFDMA	BPSK	MCS0
802.11ax (HE40)		38 to 46	38, 46	OFDMA	BPSK	MCS0
802.11ax (HE80)		42	42	OFDMA	BPSK	MCS0
802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6Mb/s
802.11ax (HE20)		149 to 165	149, 157, 165	OFDMA	BPSK	MCS0
802.11ax (HE40)		151 to 159	151, 159	OFDMA	BPSK	MCS0
802.11ax (HE80)		155	155	OFDMA	BPSK	MCS0

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter
802.11ax (HE40)	5180-5240 5745-5825	38 to 46 151 to 159	159	OFDMA	BPSK	MCS0

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11ax (HE40)	5180-5240 5745-5825	38 to 46 151 to 159	159	OFDMA	BPSK	MCS0

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter
802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6Mb/s
802.11ac (VHT20) (output power only)		36 to 48	36, 40, 48	OFDM	BPSK	MCS0
802.11ac (VHT40) (output power only)		38 to 46	38, 46	OFDM	BPSK	MCS0
802.11ac (VHT80) (output power only)		42	42	OFDM	BPSK	MCS0
802.11ax (HE20)		36 to 48	36, 40, 48	OFDMA	BPSK	MCS0
802.11ax (HE40)		38 to 46	38, 46	OFDMA	BPSK	MCS0
802.11ax (HE80)		42	42	OFDMA	BPSK	MCS0
802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6Mb/s
802.11ac (VHT20) (output power only)		149 to 165	149, 157, 165	OFDM	BPSK	MCS0
802.11ac (VHT40) (output power only)		151 to 159	151, 159	OFDM	BPSK	MCS0
802.11ac (VHT80) (output power only)		155	155	OFDM	BPSK	MCS0
802.11ax (HE20)		149 to 165	149, 157, 165	OFDMA	BPSK	MCS0
802.11ax (HE40)		151 to 159	151, 159	OFDMA	BPSK	MCS0
802.11ax (HE80)		155	155	OFDMA	BPSK	MCS0

Beamforming Mode (output power only)						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate Parameter
802.11ac (VHT20)	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	MCS0
802.11ac (VHT40)		38 to 46	38, 46	OFDM	BPSK	MCS0
802.11ac (VHT80)		42	42	OFDM	BPSK	MCS0
802.11ax (HE20)		36 to 48	36, 40, 48	OFDMA	BPSK	MCS0
802.11ax (HE40)		38 to 46	38, 46	OFDMA	BPSK	MCS0
802.11ax (HE80)		42	42	OFDMA	BPSK	MCS0
802.11ac (VHT20)	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	MCS0
802.11ac (VHT40)		151 to 159	151, 159	OFDM	BPSK	MCS0
802.11ac (VHT80)		155	155	OFDM	BPSK	MCS0
802.11ax (HE20)		149 to 165	149, 157, 165	OFDMA	BPSK	MCS0
802.11ax (HE40)		151 to 159	151, 159	OFDMA	BPSK	MCS0
802.11ax (HE80)		155	155	OFDMA	BPSK	MCS0

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested By
RE _≥ 1G	25deg. C, 74%RH	DC 48V	Eric Peng
RE _{<} 1G	25deg. C, 64%RH	DC 48V	Eric Peng
PLC	25deg. C, 75%RH	DC 48V	Sampson Chen
APCM	25deg. C, 60%RH	DC 48V	Kevin Ko

3.3 Duty Cycle of Test Signal


Duty cycle of test signal is < 98%, duty factor shall be considered.

802.11a: Duty cycle = 1.973 ms/2.118 ms = 0.932, Duty factor = $10 * \log (1/\text{Duty cycle}) = 0.31 \text{ dB}$

802.11ax (HE20): Duty cycle = 5.44 ms/5.713 ms = 0.952, Duty factor = $10 * \log (1/\text{Duty cycle}) = 0.21 \text{ dB}$

802.11ax (HE40): Duty cycle = 5.435 ms/5.735 ms = 0.948, Duty factor = $10 * \log (1/\text{Duty cycle}) = 0.23 \text{ dB}$

802.11ax (HE80): Duty cycle = 5.442 ms/6.462 ms = 0.842, Duty factor = $10 * \log (1/\text{Duty cycle}) = 0.75 \text{ dB}$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
B.	Laptop	DELL	E6420	B92T3R1	FCC DoC	Provided by Lab
C.	iPod	Apple	MD778TA/A	CC4JMH7LF4T1	NA	Provided by Lab
D.	Adapter	Channel well	KPS-030S-VI	NA	NA	Supplied by client

Note:


1. All power cords of the above support units are non-shielded (1.5m).

ID	Descriptions (Cables)	Qty	Length (m)	Shielding (Yes/No)	Cores (Number)	Remarks
1	RJ-45 Cable	1	10	No	0	Provided by Lab
2	DC Cable	1	1	No	1	Supplied by client
3	RJ-45 Cable	1	10	No	0	Provided by Lab
4	AC Cable	1	0.8	No	0	Supplied by client
5	USB Cable	1	0.1	Yes	0	Provided by Lab


Note: The core(s) is(are) originally attached to the cable(s).

3.4.1 Configuration of System under Test

For conducted test:



For other test items:



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart E (15.407)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To		Limit	
789033 D02 General UNII Test Procedure New Rules v02r01		Field Strength at 3m	
		PK:74 (dBuV/m)	AV:54 (dBuV/m)
Frequency Band	Applicable To	EIRP Limit	Equivalent Field Strength at 3m
5150~5250 MHz	15.407(b)(1)	PK:-27 (dBm/MHz)	PK:68.2(dBuV/m)
5250~5350 MHz	15.407(b)(2)		
5470~5725 MHz	15.407(b)(3)		
5725~5850 MHz	15.407(b)(4)(i)	PK:-27 (dBm/MHz) ^{*1} PK:10 (dBm/MHz) ^{*2} PK:15.6 (dBm/MHz) ^{*3} PK:27 (dBm/MHz) ^{*4}	PK: 68.2(dBuV/m) ^{*1} PK:105.2 (dBuV/m) ^{*2} PK: 110.8(dBuV/m) ^{*3} PK:122.2 (dBuV/m) ^{*4}
^{*1} beyond 75 MHz or more above of the band edge. ^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. ^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. ^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.			

Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.2 Test Instruments

For radiated emission & BandEdge & OOB test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 06, 2020	July 05, 2021
Pre-Amplifier EMCi	EMC001340	980142	May 25, 2020	May 24, 2021
Loop Antenna Electro-Metrics	EM-6879	264	Feb. 18, 2020	Feb. 17, 2021
RF Cable	NA	LOOPCAB-001	Jan. 08, 2020	Jan. 07, 2021
RF Cable	NA	LOOPCAB-002	Jan. 08, 2020	Jan. 07, 2021
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	Apr. 28, 2020	Apr. 27, 2021
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 11, 2019	Nov. 10, 2020
RF Cable	8D	966-3-1	Mar. 17, 2020	Mar. 16, 2021
RF Cable	8D	966-3-2	Mar. 17, 2020	Mar. 16, 2021
RF Cable	8D	966-3-3	Mar. 17, 2020	Mar. 16, 2021
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Sep. 26, 2019	Sep. 25, 2020
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 24, 2019	Nov. 23, 2020
Pre-Amplifier EMCi	EMC12630SE	980384	Jan. 15, 2020	Jan. 14, 2021
RF Cable	EMC104-SM-SM-1200	160922	Jan. 15, 2020	Jan. 14, 2021
RF Cable	EMC104-SM-SM-2000	180601	June 09, 2020	June 08, 2021
RF Cable	EMC104-SM-SM-6000	180602	June 09, 2020	June 08, 2021
Spectrum Analyzer Keysight	N9030A	MY54490679	July 13, 2020	July 12, 2021
Pre-Amplifier EMCi	EMC184045SE	980387	Jan. 15, 2020	Jan. 14, 2021
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 24, 2019	Nov. 23, 2020
RF Cable	EMC102-KM-KM-1200	160924	Jan. 15, 2020	Jan. 14, 2021
RF Cable	EMC-KM-KM-4000	200214	Mar. 11, 2020	Mar. 10, 2021
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Tested Date: Aug. 21 to Sep. 12, 2020

For other test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	100964	May 29, 2020	May 28, 2021
Power meter Anritsu	ML2495A	1529002	July 22, 2020	July 21, 2021
Power sensor Anritsu	MA2411B	1339443	July 22, 2020	July 21, 2021
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 14, 2020	Apr. 13, 2021
AC Power Source Extech Electronics	6205	1440452	NA	NA
Temperature & Humidity Chamber Giant Force	GTH-150-40-SP-AR	MAA0812-008	Jan. 16, 2020	Jan. 15, 2021
True RMS Clamp Meter FLUKE	325	31130711WS	June 06, 2020	June 05, 2021
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Sep. 16, 2020

4.1.3 Test Procedure

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Condition

- Placed the EUT on the testing table.
- Controlling software (QDART_4.0.00156.0) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

CDD Mode

Above 1GHz Data:

802.11a

Channel	TX Channel 36	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	64.1 PK	74.0	-9.9	2.65 H	178	60.4	3.7
2	5150.00	53.8 AV	54.0	-0.2	2.65 H	178	50.1	3.7
3	*5180.00	116.5 PK			2.65 H	178	112.9	3.6
4	*5180.00	108.6 AV			2.65 H	178	105.0	3.6
5	#10360.00	47.8 PK	68.2	-20.4	1.85 H	80	35.1	12.7
6	15540.00	45.6 PK	74.0	-28.4	1.66 H	63	32.4	13.2
7	15540.00	35.5 AV	54.0	-18.5	1.66 H	63	22.3	13.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	57.9 PK	74.0	-16.1	3.07 V	194	54.2	3.7
2	5150.00	48.8 AV	54.0	-5.2	3.07 V	194	45.1	3.7
3	*5180.00	115.4 PK			3.07 V	194	111.8	3.6
4	*5180.00	108.1 AV			3.07 V	194	104.5	3.6
5	#10360.00	46.6 PK	68.2	-21.6	1.55 V	58	33.9	12.7
6	15540.00	45.8 PK	74.0	-28.2	1.45 V	44	32.6	13.2
7	15540.00	34.7 AV	54.0	-19.3	1.45 V	44	21.5	13.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 40	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	121.6 PK			1.54 H	75	118.1	3.5
2	*5200.00	112.3 AV			1.54 H	75	108.8	3.5
3	#10400.00	48.9 PK	68.2	-19.3	1.55 H	73	36.1	12.8
4	15600.00	46.0 PK	74.0	-28.0	1.60 H	65	32.5	13.5
5	15600.00	34.5 AV	54.0	-19.5	1.60 H	65	21.0	13.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	119.6 PK			3.03 V	200	116.1	3.5
2	*5200.00	110.8 AV			3.03 V	200	107.3	3.5
3	#10400.00	47.8 PK	68.2	-20.4	1.50 V	52	35.0	12.8
4	15600.00	46.4 PK	74.0	-27.6	1.49 V	41	32.9	13.5
5	15600.00	36.5 AV	54.0	-17.5	1.49 V	41	23.0	13.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 48	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	118.9 PK			1.54 H	74	115.4	3.5
2	*5240.00	111.1 AV			1.54 H	74	107.6	3.5
3	5350.00	55.4 PK	74.0	-18.6	1.54 H	74	52.0	3.4
4	5350.00	44.3 AV	54.0	-9.7	1.54 H	74	40.9	3.4
5	#10480.00	47.6 PK	68.2	-20.6	1.56 H	73	34.5	13.1
6	15720.00	46.5 PK	74.0	-27.5	1.63 H	84	32.7	13.8
7	15720.00	35.8 AV	54.0	-18.2	1.63 H	84	22.0	13.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	116.7 PK			2.89 V	200	113.2	3.5
2	*5240.00	108.9 AV			2.89 V	200	105.4	3.5
3	5350.00	55.0 PK	74.0	-19.0	2.89 V	200	51.6	3.4
4	5350.00	43.9 AV	54.0	-10.1	2.89 V	200	40.5	3.4
5	#10480.00	47.3 PK	68.2	-20.9	1.58 V	62	34.2	13.1
6	15720.00	46.1 PK	74.0	-27.9	1.43 V	44	32.3	13.8
7	15720.00	35.2 AV	54.0	-18.8	1.43 V	44	21.4	13.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 149	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5592.62	51.6 PK	68.2	-16.6	1.42 H	307	47.3	4.3
2	*5745.00	121.3 PK			1.42 H	307	117.3	4.0
3	*5745.00	113.5 AV			1.42 H	307	109.5	4.0
4	#5947.04	50.5 PK	68.2	-17.7	1.42 H	307	45.6	4.9
5	11490.00	52.6 PK	74.0	-21.4	1.55 H	31	39.3	13.3
6	11490.00	42.7 AV	54.0	-11.3	1.55 H	31	29.4	13.3
7	#17235.00	48.3 PK	68.2	-19.9	1.68 H	38	30.7	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.79	56.4 PK	68.2	-11.8	1.00 V	19	52.0	4.4
2	*5745.00	120.9 PK			1.00 V	19	116.9	4.0
3	*5745.00	112.2 AV			1.00 V	19	108.2	4.0
4	#5927.92	53.4 PK	68.2	-14.8	1.00 V	19	48.5	4.9
5	11490.00	51.2 PK	74.0	-22.8	1.05 V	238	37.9	13.3
6	11490.00	47.1 AV	54.0	-6.9	1.05 V	238	33.8	13.3
7	#17235.00	46.8 PK	68.2	-21.4	1.50 V	255	29.2	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 157	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5594.44	52.3 PK	68.2	-15.9	1.42 H	307	48.0	4.3
2	*5785.00	121.3 PK			1.42 H	307	117.2	4.1
3	*5785.00	113.3 AV			1.42 H	307	109.2	4.1
4	#5972.80	50.8 PK	68.2	-17.4	1.42 H	307	45.9	4.9
5	11570.00	53.1 PK	74.0	-20.9	2.60 H	255	39.9	13.2
6	11570.00	46.4 AV	54.0	-7.6	2.60 H	255	33.2	13.2
7	#17355.00	50.6 PK	68.2	-17.6	1.52 H	245	33.0	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5641.75	55.2 PK	68.2	-13.0	1.00 V	19	50.9	4.3
2	*5785.00	120.2 PK			1.00 V	19	116.1	4.1
3	*5785.00	111.4 AV			1.00 V	19	107.3	4.1
4	#5925.27	54.3 PK	68.2	-13.9	1.00 V	19	49.4	4.9
5	11570.00	55.6 PK	74.0	-18.4	1.00 V	219	42.4	13.2
6	11570.00	48.6 AV	54.0	-5.4	1.00 V	219	35.4	13.2
7	#17355.00	51.5 PK	68.2	-16.7	1.12 V	215	33.9	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 165	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5630.73	51.9 PK	68.2	-16.3	1.42 H	307	47.6	4.3
2	*5825.00	120.5 PK			1.41 H	307	116.2	4.3
3	*5825.00	112.1 AV			1.41 H	307	107.8	4.3
4	#5924.64	51.8 PK	68.5	-16.7	1.42 H	307	46.9	4.9
5	11650.00	54.2 PK	74.0	-19.8	2.61 H	256	40.9	13.3
6	11650.00	46.9 AV	54.0	-7.1	2.61 H	256	33.6	13.3
7	#17475.00	50.1 PK	68.2	-18.1	1.53 H	249	32.2	17.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5637.83	54.2 PK	68.2	-14.0	1.00 V	19	49.9	4.3
2	*5825.00	120.2 PK			1.00 V	19	115.9	4.3
3	*5825.00	111.1 AV			1.00 V	19	106.8	4.3
4	#5928.02	52.3 PK	68.2	-15.9	1.00 V	19	47.4	4.9
5	11650.00	55.2 PK	74.0	-18.8	1.02 V	221	41.9	13.3
6	11650.00	48.3 AV	54.0	-5.7	1.02 V	221	35.0	13.3
7	#17475.00	50.7 PK	68.2	-17.5	1.14 V	236	32.8	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE20)

Channel	TX Channel 36	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5149.03	62.5 PK	74.0	-11.5	2.73 H	155	58.8	3.7
2	5149.03	53.8 AV	54.0	-0.2	2.73 H	155	50.1	3.7
3	*5180.00	123.8 PK			2.73 H	155	120.2	3.6
4	*5180.00	114.2 AV			2.73 H	155	110.6	3.6
5	#10360.00	47.5 PK	68.2	-20.7	1.56 H	4	34.8	12.7
6	15540.00	45.3 PK	74.0	-28.7	1.44 H	69	32.1	13.2
7	15540.00	33.7 AV	54.0	-20.3	1.44 H	69	20.5	13.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.9 PK	74.0	-15.1	2.46 V	187	55.2	3.7
2	5150.00	50.1 AV	54.0	-3.9	2.46 V	187	46.4	3.7
3	*5180.00	122.3 PK			2.46 V	187	118.7	3.6
4	*5180.00	111.4 AV			2.46 V	187	107.8	3.6
5	#10360.00	45.3 PK	68.2	-22.9	1.48 V	288	32.6	12.7
6	15540.00	46.0 PK	74.0	-28.0	1.60 V	301	32.8	13.2
7	15540.00	33.8 AV	54.0	-20.2	1.60 V	301	20.6	13.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 40	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	123.4 PK			1.00 H	76	119.9	3.5
2	*5200.00	110.2 AV			1.00 H	76	106.7	3.5
3	#10400.00	47.7 PK	68.2	-20.5	1.54 H	360	34.9	12.8
4	15600.00	45.8 PK	74.0	-28.2	1.43 H	69	32.3	13.5
5	15600.00	33.9 AV	54.0	-20.1	1.43 H	69	20.4	13.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	122.8 PK			2.47 V	185	119.3	3.5
2	*5200.00	109.1 AV			2.47 V	185	105.6	3.5
3	#10400.00	46.0 PK	68.2	-22.2	1.47 V	284	33.2	12.8
4	15600.00	45.8 PK	74.0	-28.2	1.60 V	300	32.3	13.5
5	15600.00	33.7 AV	54.0	-20.3	1.60 V	300	20.2	13.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 48	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	124.5 PK			1.00 H	76	121.0	3.5
2	*5240.00	113.0 AV			1.00 H	76	109.5	3.5
3	5350.00	55.5 PK	74.0	-18.5	1.00 H	76	52.1	3.4
4	5350.00	42.5 AV	54.0	-11.5	1.00 H	76	39.1	3.4
5	#10480.00	48.3 PK	68.2	-19.9	1.55 H	9	35.2	13.1
6	15720.00	46.6 PK	74.0	-27.4	1.43 H	70	32.8	13.8
7	15720.00	34.8 AV	54.0	-19.2	1.43 H	70	21.0	13.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	122.3 PK			2.50 V	170	118.8	3.5
2	*5240.00	111.7 AV			2.50 V	170	108.2	3.5
3	5350.00	54.6 PK	74.0	-19.4	2.50 V	170	51.2	3.4
4	5350.00	41.7 AV	54.0	-12.3	2.50 V	170	38.3	3.4
5	#10480.00	47.3 PK	68.2	-20.9	1.50 V	285	34.2	13.1
6	15720.00	46.2 PK	74.0	-27.8	1.66 V	301	32.4	13.8
7	15720.00	34.5 AV	54.0	-19.5	1.66 V	301	20.7	13.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 149	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5556.82	52.4 PK	68.2	-15.8	1.42 H	308	48.2	4.2
2	*5745.00	123.4 PK			1.42 H	308	119.4	4.0
3	*5745.00	112.1 AV			1.42 H	308	108.1	4.0
4	#5935.05	52.6 PK	68.2	-15.6	1.42 H	308	47.7	4.9
5	11490.00	50.3 PK	74.0	-23.7	2.94 H	331	37.0	13.3
6	11490.00	43.5 AV	54.0	-10.5	2.94 H	331	30.2	13.3
7	#17235.00	51.8 PK	68.2	-16.4	1.60 H	280	34.2	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5644.25	54.8 PK	68.2	-13.4	1.00 V	19	50.5	4.3
2	*5745.00	120.9 PK			1.00 V	19	116.9	4.0
3	*5745.00	110.8 AV			1.00 V	19	106.8	4.0
4	#5936.48	49.5 PK	68.2	-18.7	1.00 V	19	44.5	5.0
5	11490.00	51.0 PK	74.0	-23.0	2.58 V	209	37.7	13.3
6	11490.00	44.2 AV	54.0	-9.8	2.58 V	209	30.9	13.3
7	#17235.00	51.6 PK	68.2	-16.6	1.50 V	324	34.0	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 157	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5589.97	51.9 PK	68.2	-16.3	1.42 H	308	47.6	4.3
2	*5785.00	124.1 PK			1.42 H	308	120.0	4.1
3	*5785.00	112.6 AV			1.42 H	308	108.5	4.1
4	#6007.97	50.8 PK	68.2	-17.4	1.42 H	308	45.7	5.1
5	11570.00	49.5 PK	74.0	-24.5	2.92 H	331	36.3	13.2
6	11570.00	43.0 AV	54.0	-11.0	2.92 H	331	29.8	13.2
7	#17355.00	50.9 PK	68.2	-17.3	1.58 H	298	33.3	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5595.71	54.3 PK	68.2	-13.9	1.00 V	19	50.0	4.3
2	*5785.00	123.3 PK			1.00 V	19	119.2	4.1
3	*5785.00	112.1 AV			1.00 V	19	108.0	4.1
4	#5937.78	48.6 PK	68.2	-19.6	1.00 V	19	43.6	5.0
5	11570.00	51.1 PK	74.0	-22.9	2.59 V	211	37.9	13.2
6	11570.00	46.3 AV	54.0	-7.7	2.59 V	211	33.1	13.2
7	#17355.00	51.7 PK	68.2	-16.5	1.49 V	320	34.1	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 165	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5634.53	50.4 PK	68.2	-17.8	1.00 H	290	46.1	4.3
2	*5825.00	123.5 PK			1.00 H	290	119.2	4.3
3	*5825.00	111.4 AV			1.00 H	290	107.1	4.3
4	#6008.97	51.5 PK	68.2	-16.7	1.00 H	290	46.4	5.1
5	11650.00	50.3 PK	74.0	-23.7	3.00 H	331	37.0	13.3
6	11650.00	43.3 AV	54.0	-10.7	3.00 H	331	30.0	13.3
7	#17475.00	51.1 PK	68.2	-17.1	1.60 H	280	33.2	17.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5636.19	54.7 PK	68.2	-13.5	1.00 V	19	50.4	4.3
2	*5825.00	122.8 PK			1.00 V	19	118.5	4.3
3	*5825.00	111.1 AV			1.00 V	19	106.8	4.3
4	#5926.34	48.8 PK	68.2	-19.4	1.00 V	19	43.9	4.9
5	11650.00	50.8 PK	74.0	-23.2	2.55 V	211	37.5	13.3
6	11650.00	43.7 AV	54.0	-10.3	2.55 V	211	30.4	13.3
7	#17475.00	50.2 PK	68.2	-18.0	1.48 V	322	32.3	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE40)

Channel	TX Channel 38	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5134.59	63.0 PK	74.0	-11.0	2.58 H	188	59.3	3.7
2	5134.59	53.9 AV	54.0	-0.1	2.58 H	188	50.2	3.7
3	*5190.00	118.2 PK			2.58 H	188	114.6	3.6
4	*5190.00	108.8 AV			2.58 H	188	105.2	3.6
5	#10380.00	49.6 PK	68.2	-18.6	2.39 H	310	36.9	12.7
6	15570.00	51.2 PK	74.0	-22.8	1.48 H	246	37.8	13.4
7	15570.00	43.6 AV	54.0	-10.4	1.48 H	246	30.2	13.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.4 PK	74.0	-11.6	2.77 V	187	58.7	3.7
2	5150.00	53.2 AV	54.0	-0.8	2.77 V	187	49.5	3.7
3	*5190.00	116.8 PK			2.77 V	187	113.2	3.6
4	*5190.00	106.9 AV			2.77 V	187	103.3	3.6
5	#10380.00	48.7 PK	68.2	-19.5	2.15 V	201	36.0	12.7
6	15570.00	50.5 PK	74.0	-23.5	1.65 V	182	37.1	13.4
7	15570.00	42.3 AV	54.0	-11.7	1.65 V	182	28.9	13.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 46	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	122.8 PK			1.00 H	79	119.3	3.5
2	*5230.00	110.4 AV			1.00 H	79	106.9	3.5
3	5350.00	58.7 PK	74.0	-15.3	1.00 H	79	55.3	3.4
4	5350.00	45.8 AV	54.0	-8.2	1.00 H	79	42.4	3.4
5	#10460.00	51.1 PK	68.2	-17.1	2.48 H	309	38.1	13.0
6	15690.00	52.3 PK	74.0	-21.7	1.45 H	254	38.4	13.9
7	15690.00	44.6 AV	54.0	-9.4	1.45 H	254	30.7	13.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	121.3 PK			2.77 V	196	117.8	3.5
2	*5230.00	108.6 AV			2.77 V	196	105.1	3.5
3	5350.00	56.8 PK	74.0	-17.2	2.77 V	196	53.4	3.4
4	5350.00	44.7 AV	54.0	-9.3	2.77 V	196	41.3	3.4
5	#10460.00	50.1 PK	68.2	-18.1	2.21 V	202	37.1	13.0
6	15690.00	51.3 PK	74.0	-22.7	1.67 V	185	37.4	13.9
7	15690.00	43.2 AV	54.0	-10.8	1.67 V	185	29.3	13.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 151	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.99	58.3 PK	68.2	-9.9	1.42 H	315	53.9	4.4
2	*5755.00	120.9 PK			1.42 H	315	116.9	4.0
3	*5755.00	109.1 AV			1.42 H	315	105.1	4.0
4	#6013.69	51.0 PK	68.2	-17.2	1.42 H	315	45.9	5.1
5	11510.00	54.6 PK	74.0	-19.4	2.36 H	335	41.3	13.3
6	11510.00	47.1 AV	54.0	-6.9	2.36 H	335	33.8	13.3
7	#17265.00	51.3 PK	68.2	-16.9	1.60 H	239	33.8	17.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.05	60.5 PK	68.2	-7.7	1.00 V	19	56.1	4.4
2	*5755.00	119.7 PK			1.00 V	19	115.7	4.0
3	*5755.00	107.6 AV			1.00 V	19	103.6	4.0
4	#5923.71	51.7 PK	69.2	-17.5	1.00 V	19	46.8	4.9
5	11510.00	52.4 PK	74.0	-21.6	2.17 V	304	39.1	13.3
6	11510.00	45.0 AV	54.0	-9.0	2.17 V	304	31.7	13.3
7	#17265.00	50.7 PK	68.2	-17.5	1.68 V	188	33.2	17.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 159	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.79	52.8 PK	68.2	-15.4	1.42 H	315	48.4	4.4
2	*5795.00	121.8 PK			1.42 H	315	117.6	4.2
3	*5795.00	110.3 AV			1.42 H	315	106.1	4.2
4	#5930.80	59.5 PK	68.2	-8.7	1.42 H	315	54.6	4.9
5	11590.00	53.5 PK	74.0	-20.5	2.36 H	338	40.2	13.3
6	11590.00	46.5 AV	54.0	-7.5	2.36 H	338	33.2	13.3
7	#17385.00	50.7 PK	68.2	-17.5	1.60 H	240	33.0	17.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5641.01	55.8 PK	68.2	-12.4	1.00 V	19	51.5	4.3
2	*5795.00	120.3 PK			1.00 V	19	116.1	4.2
3	*5795.00	108.5 AV			1.00 V	19	104.3	4.2
4	#5924.70	51.7 PK	68.4	-16.7	1.00 V	19	46.8	4.9
5	11590.00	51.8 PK	74.0	-22.2	2.20 V	318	38.5	13.3
6	11590.00	44.7 AV	54.0	-9.3	2.20 V	318	31.4	13.3
7	#17385.00	49.6 PK	68.2	-18.6	1.69 V	190	31.9	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE80)

Channel	TX Channel 42	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5135.10	63.5 PK	74.0	-10.5	2.66 H	179	59.8	3.7
2	5135.10	53.8 AV	54.0	-0.2	2.66 H	179	50.1	3.7
3	*5210.00	110.0 PK			2.66 H	179	106.4	3.6
4	*5210.00	101.5 AV			2.66 H	179	97.9	3.6
5	5350.00	52.4 PK	74.0	-21.6	2.66 H	179	49.0	3.4
6	5350.00	40.5 AV	54.0	-13.5	2.66 H	179	37.1	3.4
7	#10420.00	51.1 PK	68.2	-17.1	2.38 H	265	38.3	12.8
8	15630.00	48.9 PK	74.0	-25.1	1.93 H	69	35.2	13.7
9	15630.00	40.7 AV	54.0	-13.3	1.93 H	69	27.0	13.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.0 PK	74.0	-12.0	2.80 V	182	58.3	3.7
2	5150.00	52.9 AV	54.0	-1.1	2.80 V	182	49.2	3.7
3	*5210.00	110.0 PK			2.80 V	182	106.4	3.6
4	*5210.00	99.6 AV			2.80 V	182	96.0	3.6
5	5350.00	51.7 PK	74.0	-22.3	2.80 V	182	48.3	3.4
6	5350.00	41.5 AV	54.0	-12.5	2.80 V	182	38.1	3.4
7	#10420.00	50.6 PK	68.2	-17.6	2.52 V	315	37.8	12.8
8	15630.00	48.3 PK	74.0	-25.7	1.74 V	201	34.6	13.7
9	15630.00	40.1 AV	54.0	-13.9	1.74 V	201	26.4	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 155	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.70	66.7 PK	68.2	-1.5	1.41 H	316	62.3	4.4
2	*5775.00	116.3 PK			1.41 H	316	112.2	4.1
3	*5775.00	104.2 AV			1.41 H	316	100.1	4.1
4	#5930.77	56.0 PK	68.2	-12.2	1.41 H	316	51.1	4.9
5	11550.00	50.6 PK	74.0	-23.4	2.66 H	305	37.4	13.2
6	11550.00	41.3 AV	54.0	-12.7	2.66 H	305	28.1	13.2
7	#17325.00	48.1 PK	68.2	-20.1	1.75 H	75	30.5	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5642.67	62.8 PK	68.2	-5.4	1.00 V	18	58.5	4.3
2	*5775.00	115.5 PK			1.00 V	18	111.4	4.1
3	*5775.00	103.6 AV			1.00 V	18	99.5	4.1
4	#5925.20	55.1 PK	68.2	-13.1	1.00 V	18	50.2	4.9
5	11550.00	49.8 PK	74.0	-24.2	2.14 V	302	36.6	13.2
6	11550.00	40.7 AV	54.0	-13.3	2.14 V	302	27.5	13.2
7	#17325.00	47.6 PK	68.2	-20.6	1.71 V	160	30.0	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Below 1GHz Data:


802.11ax (HE40)

CHANNEL	TX Channel 159	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	34.75	31.2 QP	40.0	-8.8	2.50 H	138	39.8	-8.6
2	115.12	29.4 QP	43.5	-14.1	1.50 H	93	38.9	-9.5
3	186.17	30.1 QP	43.5	-13.4	1.50 H	265	39.1	-9.0
4	250.02	31.1 QP	46.0	-14.9	1.00 H	310	39.1	-8.0
5	454.37	29.8 QP	46.0	-16.2	2.00 H	0	31.1	-1.3
6	622.99	31.8 QP	46.0	-14.2	1.50 H	43	29.1	2.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 159	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.95	34.0 QP	40.0	-6.0	1.00 V	360	42.2	-8.2
2	114.17	29.0 QP	43.5	-14.5	1.00 V	270	38.6	-9.6
3	250.02	28.3 QP	46.0	-17.7	1.00 V	72	36.3	-8.0
4	322.24	28.0 QP	46.0	-18.0	1.00 V	54	33.0	-5.0
5	432.55	31.3 QP	46.0	-14.7	1.00 V	315	33.1	-1.8
6	650.02	32.5 QP	46.0	-13.5	1.00 V	130	29.4	3.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 19, 2020	Mar. 18, 2021
50 ohms Terminator	50	3	Oct. 23, 2019	Oct. 22, 2020
RF Cable	5D-FB	COCCAB-001	Sep. 27, 2019	Sep. 26, 2020
Fixed attenuator EMCI	STI02-2200-10	003	Aug. 29, 2020	Aug. 28, 2021
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: Sep. 14, 2020

4.2.3 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	9.91	34.66	20.64	44.57	30.55	65.58	55.58	-21.01	-25.03
2	0.34922	9.94	37.32	31.22	47.26	41.16	58.98	48.98	-11.72	-7.82
3	7.83984	10.32	33.45	33.21	43.77	43.53	60.00	50.00	-16.23	-6.47
4	8.09375	10.34	33.66	33.55	44.00	43.89	60.00	50.00	-16.00	-6.11
5	18.96875	10.95	24.78	24.04	35.73	34.99	60.00	50.00	-24.27	-15.01
6	29.33984	11.26	21.25	21.19	32.51	32.45	60.00	50.00	-27.49	-17.55

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.91	33.52	19.10	43.43	29.01	65.79	55.79	-22.36	-26.78
2	0.16562	9.92	31.52	17.67	41.44	27.59	65.18	55.18	-23.74	-27.59
3	0.34531	9.94	36.36	30.70	46.30	40.64	59.07	49.07	-12.77	-8.43
4	7.33594	10.24	30.05	30.00	40.29	40.24	60.00	50.00	-19.71	-9.76
5	7.83984	10.26	33.27	32.93	43.53	43.19	60.00	50.00	-16.47	-6.81
6	8.09375	10.27	32.80	32.65	43.07	42.92	60.00	50.00	-16.93	-7.08

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 Transmit Power Measurement

4.3.1 Limits of Transmit Power Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
	√	Indoor Access Point	1 Watt (30 dBm)
		Client device	250mW (24 dBm)
U-NII-2A			250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C			250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3		√	1 Watt (30 dBm)

*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;


Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.


For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.3.2 Test Setup

FOR POWER OUTPUT MEASUREMENT



FOR 26dB OCCUPIED BANDWIDTH



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

FOR POWER OUTPUT MEASUREMENT

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

FOR 26dB OCCUPIED BANDWIDTH

1. Set RBW = approximately 1% of the emission bandwidth.
2. Set the VBW > RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Results

For U-NII-1 Band & simultaneous transmission in non-adjacent channels

CDD Mode

802.11a

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	18.44	18.55	18.69	18.72	289.871	24.62	30.00	Pass
40	5200	18.59	18.61	18.74	18.75	294.694	24.69	30.00	Pass
48	5240	18.45	18.65	18.54	18.58	286.827	24.58	30.00	Pass

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	18.43	18.36	18.65	18.62	284.272	24.54	30.00	Pass
40	5200	18.74	18.60	18.64	18.62	293.152	24.67	30.00	Pass
48	5240	18.65	18.53	18.82	18.56	292.555	24.66	30.00	Pass

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	21.48	21.22	21.68	21.33	556.102	27.45	30.00	Pass
46	5230	21.53	21.39	21.79	21.56	574.181	27.59	30.00	Pass

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	17.96	17.69	17.71	17.66	238.631	23.78	30.00	Pass

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	18.70	18.62	18.85	18.90	301.27	24.79	30.00	Pass
40	5200	19.01	18.86	18.93	18.82	310.9	24.93	30.00	Pass
48	5240	18.92	18.76	19.08	18.76	309.217	24.90	30.00	Pass

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	21.52	21.30	21.85	21.58	573.791	27.59	30.00	Pass
46	5230	21.78	21.65	22.07	21.84	610.7	27.86	30.00	Pass

802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	18.04	17.79	17.92	17.87	246.976	23.93	30.00	Pass

Beamforming Mode

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	18.44	18.20	18.31	18.48	274.126	24.38	24.70	Pass
40	5200	18.69	18.47	18.50	18.54	286.512	24.57	24.70	Pass
48	5240	17.98	18.31	18.14	18.49	266.365	24.25	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	18.27	18.04	18.34	18.67	272.677	24.36	24.70	Pass
46	5230	18.60	18.88	18.71	18.35	292.405	24.66	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	17.96	17.69	17.71	17.66	238.631	23.78	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	18.43	18.36	18.65	18.62	284.272	24.54	24.70	Pass
40	5200	18.74	18.60	18.64	18.62	293.152	24.67	24.70	Pass
48	5240	18.65	18.53	18.82	18.56	292.555	24.66	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	18.23	18.40	18.48	18.38	275.045	24.39	24.70	Pass
46	5230	18.77	18.20	18.93	18.66	293.019	24.67	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.

802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	18.04	17.79	17.92	17.87	246.976	23.93	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.

U-NII-3 Band

CDD Mode

802.11a

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
149	5745	23.24	23.26	23.61	23.33	867.592	29.38	30.00	Pass
157	5785	23.23	23.19	23.65	23.36	867.337	29.38	30.00	Pass
165	5825	23.31	23.22	23.58	23.37	869.487	29.39	30.00	Pass

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
149	5745	23.01	23.11	23.19	23.42	832.866	29.21	30.00	Pass
157	5785	23.06	23.15	23.41	23.67	860.93	29.35	30.00	Pass
165	5825	23.13	23.06	23.35	23.48	847.006	29.28	30.00	Pass

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
151	5755	23.45	23.38	23.63	23.37	887.025	29.48	30.00	Pass
159	5795	23.51	23.44	23.84	23.49	910.649	29.59	30.00	Pass

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
155	5775	21.21	21.24	21.38	21.06	530.223	27.24	30.00	Pass

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
149	5745	23.24	23.37	23.49	23.66	883.764	29.46	30.00	Pass
157	5785	23.31	23.35	23.61	23.84	902.279	29.55	30.00	Pass
165	5825	23.34	23.26	23.55	23.69	887.959	29.48	30.00	Pass

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
151	5755	23.66	23.65	23.93	23.67	943.995	29.75	30.00	Pass
159	5795	23.71	23.74	24.04	23.77	963.3	29.84	30.00	Pass

802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
155	5775	21.41	21.45	21.68	21.29	559.811	27.48	30.00	Pass

Beamforming Mode

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
149	5745	17.94	18.05	18.20	18.81	268.158	24.28	24.70	Pass
157	5785	17.90	18.51	18.28	18.85	276.651	24.42	24.70	Pass
165	5825	18.49	18.14	18.10	18.55	271.974	24.35	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 11.3 dBi > 6 dBi, so the power limit shall be reduced to 30-(11.3-6) = 24.70 dBm.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
151	5755	18.41	18.24	18.91	18.26	280.815	24.48	24.70	Pass
159	5795	18.72	18.48	18.57	18.32	284.808	24.55	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 11.3 dBi > 6 dBi, so the power limit shall be reduced to 30-(11.3-6) = 24.70 dBm.

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
155	5775	18.40	18.68	18.75	18.36	286.512	24.57	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 11.3 dBi > 6 dBi, so the power limit shall be reduced to 30-(11.3-6) = 24.70 dBm.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
149	5745	18.25	18.45	18.69	19.16	293.193	24.67	24.70	Pass
157	5785	17.88	18.25	18.69	19.36	288.469	24.60	24.70	Pass
165	5825	18.67	18.19	18.81	18.88	292.839	24.67	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 11.3 dBi > 6 dBi, so the power limit shall be reduced to 30-(11.3-6) = 24.70 dBm.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
151	5755	18.60	18.46	18.43	18.53	283.537	24.53	24.70	Pass
159	5795	18.13	18.64	19.09	18.22	285.597	24.56	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 11.3 dBi > 6 dBi, so the power limit shall be reduced to 30-(11.3-6) = 24.70 dBm.


802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
155	5775	18.36	18.87	18.56	18.63	290.364	24.63	24.70	Pass

Note: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4]$ = 11.3 dBi > 6 dBi, so the power limit shall be reduced to 30-(11.3-6) = 24.70 dBm.

4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to SAMPLE. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

4.4.4 Test Results

CDD Mode

802.11a

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
36	5180	16.44	16.44	16.44	16.56
40	5200	16.44	16.32	16.44	16.56
48	5240	16.56	16.56	16.44	16.56
149	5745	16.56	16.56	16.44	16.68
157	5785	16.44	16.68	17.16	16.56
165	5825	16.44	16.44	16.68	16.68

802.11ax (HE20)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
36	5180	18.96	18.96	19.08	18.96
40	5200	18.96	18.96	18.96	18.96
48	5240	19.08	18.96	19.08	19.08
149	5745	19.08	18.96	18.96	18.96
157	5785	19.08	19.08	19.2	19.08
165	5825	19.08	19.08	19.08	18.96

802.11ax (HE40)


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
38	5190	38.16	38.16	38.16	38.16
46	5230	38.16	37.68	38.16	38.16
151	5755	38.16	38.16	38.16	38.16
159	5795	38.16	38.64	38.4	38.16

802.11ax (HE80)


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
42	5210	76.8	77.28	77.76	77.28
155	5775	77.76	77.28	76.8	77.28

Spectrum Plot of Max. Value


802.11a Chain 3 / CH157




802.11ax (HE20) Chain 2 / CH157



802.11ax (HE40) Chain 1 / CH159




802.11ax (HE80) Chain 2 / CH42




Spectrum Plot for near by DFS band
(DFS is required, if 99% OCP straddle into U-NII-2A band)


802.11a_Chain 0 / CH48




802.11a_Chain 1 / CH48




802.11a_Chain 2 / CH48




802.11a_Chain 3 / CH48




802.11ax (HE20)_Chain 0 / CH48




802.11ax (HE20)_Chain 1 / CH48



802.11ax (HE20)_Chain 2 / CH48




802.11ax (HE20)_Chain 3 / CH48




Spectrum Plot for near by DFS band
(DFS is required, if 99% OCP straddle into U-NII-2A band)


802.11ax (HE40)_Chain 0 / CH46




802.11ax (HE40)_Chain 1 / CH46




802.11ax (HE40)_Chain 2 / CH46




802.11ax (HE40)_Chain 3 / CH46




802.11ax (HE80)_Chain 0 / CH42




802.11ax (HE80)_Chain 1 / CH42



802.11ax (HE80)_Chain 2 / CH42




802.11ax (HE80)_Chain 3 / CH42




Spectrum Plot for near by DFS band
(DFS is required, if 99% OCP straddle into U-NII-2C band)


802.11a Chain 0 / CH149




802.11a Chain 1 / CH149




802.11a Chain 2 / CH149




802.11a Chain 3 / CH149




802.11ax (HE20) Chain 0 / CH149




802.11ax (HE20) Chain 1 / CH149



802.11ax (HE20) Chain 2 / CH149




802.11ax (HE20) Chain 3 / CH149




Spectrum Plot for near by DFS band
(DFS is required, if 99% OCP straddle into U-NII-2C band)


802.11ax (HE40)_Chain 0 / CH151




802.11ax (HE40)_Chain 1 / CH151




802.11ax (HE40)_Chain 2 / CH151




802.11ax (HE40)_Chain 3 / CH151




802.11ax (HE80)_Chain 0 / CH155




802.11ax (HE80)_Chain 1 / CH155



802.11ax (HE80)_Chain 2 / CH155



802.11ax (HE80)_Chain 3 / CH155




4.5 Peak Power Spectral Density Measurement

4.5.1 Limits of Peak Power Spectral Density Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
	√	Indoor Access Point	
		Client device	11dBm/ MHz
U-NII-2A			11dBm/ MHz
U-NII-2C			11dBm/ MHz
U-NII-3	√		30dBm/ 500kHz

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

For U-NII-1 band:

Using method SA-2

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to “free run”.
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value and add 10 log (1/duty cycle)

For U-NII-3 band:

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 300 kHz, Set VBW ≥ 1 MHz, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent value in 500 kHz by adjusting (increasing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500\text{kHz}/300\text{kHz})$
5. Sweep time = auto, trigger set to “free run”.
6. Trace average at least 100 traces in power averaging mode.
7. Record the max value and add 10 log (1/duty cycle)

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6.

4.5.7 Test Results

For U-NII-1 Band

CDD Mode

802.11a

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)				Duty Factor (dB)	Total PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	5.00	4.48	4.41	4.91	0.31	11.04	11.70	Pass
40	5200	5.69	4.71	6.19	4.37	0.31	11.63	11.70	Pass
48	5240	5.35	5.31	3.74	4.67	0.31	11.14	11.70	Pass

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $17 - (11.3 - 6) = 11.7 \text{ dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)				Duty Factor (dB)	Total PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	5.95	4.20	4.91	5.59	0.21	11.45	11.70	Pass
40	5200	4.16	5.78	5.73	4.81	0.21	11.40	11.70	Pass
48	5240	4.93	4.95	5.12	5.24	0.21	11.30	11.70	Pass

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $17 - (11.3 - 6) = 11.7 \text{ dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)				Duty Factor (dB)	Total PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	-7.83	-8.19	-6.75	-7.73	0.23	-1.34	11.70	Pass
46	5230	4.81	4.66	4.70	4.82	0.23	11.00	11.70	Pass

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $17 - (11.3 - 6) = 11.7 \text{ dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.


802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)				Duty Factor (dB)	Total PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	-2.88	-3.22	-3.02	-2.64	0.75	3.83	11.70	Pass


- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $17 - (11.3 - 6) = 11.7 \text{ dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11a_Chain 2 / CH40




802.11ax (HE20)_Chain 0 / CH36



802.11ax (HE40)_Chain 3 / CH46



802.11ax (HE80)_Chain 3 / CH42



For U-NII-3 Band

CDD Mode

802.11a

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)				Duty Factor (dB)	Total PSD (dBm/300 kHz)	Total PSD (dBm/500 kHz)	PSD Limit (dBm/500 kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3					
149	5745	2.57	2.72	1.19	2.73	0.31	8.68	10.90	24.70	Pass
157	5785	2.00	1.63	1.02	1.59	0.31	7.90	10.12	24.70	Pass
165	5825	0.98	1.08	1.28	1.19	0.31	7.46	9.68	24.70	Pass

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.
 3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)				Duty Factor (dB)	Total PSD (dBm/300 kHz)	Total PSD (dBm/500 kHz)	PSD Limit (dBm/500 kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3					
149	5745	1.20	1.23	0.90	1.11	0.21	7.34	9.56	24.70	Pass
157	5785	0.92	0.60	0.62	1.09	0.21	7.05	9.27	24.70	Pass
165	5825	0.62	0.26	0.48	0.28	0.21	6.65	8.87	24.70	Pass

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.
 3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)				Duty Factor (dB)	Total PSD (dBm/300 kHz)	Total PSD (dBm/500 kHz)	PSD Limit (dBm/500 kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3					
151	5755	-1.10	-0.38	-1.32	-1.05	0.23	5.31	7.53	24.70	Pass
159	5795	-1.31	-1.28	-0.93	-1.17	0.23	5.08	7.30	24.70	Pass

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.
 3. Refer to section 3.3 for duty cycle spectrum plot.


802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)				Duty Factor (dB)	Total PSD (dBm/300 kHz)	Total PSD (dBm/500 kHz)	PSD Limit (dBm/500 kHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3					
155	5775	-6.40	-6.10	-6.86	-7.02	0.75	0.19	2.41	24.70	Pass


- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 4] = 11.3 \text{ dBi} > 6 \text{ dBi}$, so the power density limit shall be reduced to $30 - (11.3 - 6) = 24.70 \text{ dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11a_Chain 3 / CH149




802.11ax (HE20)_Chain 1 / CH149



802.11ax (HE40)_Chain 1 / CH151



802.11ax (HE80)_Chain 1 / CH155




4.6 Frequency Stability Measurement

4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

4.6.7 Test Results

Frequency Stability Versus Temp.									
Operating Frequency: 5180 MHz									
TEMP. (°C)	Power Supply (Vac)	0 Minute		2 Minutes		5 Minutes		10 Minutes	
		Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail
40	120	5179.9808	Pass	5179.9786	Pass	5179.98	Pass	5179.9799	Pass
30	120	5179.9802	Pass	5179.9785	Pass	5179.978	Pass	5179.9805	Pass
20	120	5180.0108	Pass	5180.0092	Pass	5180.0108	Pass	5180.0112	Pass
10	120	5180.0176	Pass	5180.019	Pass	5180.0204	Pass	5180.0173	Pass
0	120	5179.9844	Pass	5179.9861	Pass	5179.9837	Pass	5179.9812	Pass


Frequency Stability Versus Voltage									
Operating Frequency: 5180 MHz									
TEMP. (°C)	Power Supply (Vac)	0 Minute		2 Minutes		5 Minutes		10 Minutes	
		Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail
20	138	5180.0099	Pass	5180.0093	Pass	5180.0118	Pass	5180.0106	Pass
	120	5180.0108	Pass	5180.0092	Pass	5180.0108	Pass	5180.0112	Pass
	102	5180.0105	Pass	5180.0088	Pass	5180.0103	Pass	5180.0116	Pass

4.7 6dB Bandwidth Measurement

4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

CDD Mode

802.11a

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
149	5745	15.49	15.6	15.91	15.69	0.5	Pass
157	5785	15.3	15.7	15.71	15.61	0.5	Pass
165	5825	15.2	15.22	15.76	15.68	0.5	Pass

802.11ax (HE20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
149	5745	18.42	17.73	17.71	18.56	0.5	Pass
157	5785	18.48	18.75	18.51	18.47	0.5	Pass
165	5825	17.11	18.57	18.29	16.13	0.5	Pass

802.11ax (HE40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
151	5755	37.18	37.33	37.82	37.96	0.5	Pass
159	5795	37.6	36.02	37.54	37.14	0.5	Pass

802.11ax (HE80)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
155	5775	72.29	73.09	74.34	72.58	0.5	Pass

Spectrum Plot of Worst Value


802.11a_Chain 0 / CH165




802.11ax (HE20)_Chain 3 / CH165



802.11ax (HE40)_Chain 1 / CH159



802.11ax (HE80)_Chain 0 / CH155



5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

Annex A - Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)


802.11a

CH 149 5745 MHz

Horizontal




Vertical




CH 157 5785 MHz

Horizontal




Vertical




CH 165 5825 MHz

Horizontal




Vertical




802.11ax (HE20)

CH 149 5745 MHz

Horizontal




Vertical




CH 157 5785 MHz

Horizontal




Vertical




CH 165 5825 MHz

Horizontal




Vertical




802.11ax (HE40)

CH 151 5755 MHz

Horizontal




Vertical




CH 159 5795 MHz

Horizontal




Vertical




802.11ax (HE80)

CH 155 5775 MHz

Horizontal




Vertical




Annex B - Band-Edge Measurement (For U-NII-1 band)


802.11a




802.11ax (HE20)



802.11ax (HE40)



802.11ax (HE80)



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---