



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Phone
BRAND NAME : Motorola
MODEL NAME : XT2433-2, XT2433-1
FCC ID : IHDT56AS4
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Apr. 26, 2024 ~ Jun. 26, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (ShenZhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	7
1.9 Specification of Accessory.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	16
3.6 AC Conducted Emission Measurement.....	20
3.7 Antenna Requirements.....	22
4 LIST OF MEASURING EQUIPMENT.....	23
5 MEASUREMENT UNCERTAINTY	24
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR422904B	Rev. 01	Initial issue of report	Jul. 26, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.55 dB at 2483.520 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.10 dB at 0.197 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago, IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago, IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Motorola
Model Name	XT2433-2, XT2433-1
FCC ID	IHDT56AS4
IMEI Code	Conducted: 356304130012194/356304130012202 Conduction: 356304130012830/356304130012848 Radiation: 356304130083377/356304130123181
HW Version	DVT2
SW Version	UOA34.101
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. The two models are only different for market segment, all the others are same.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 1Mbps: 11.99 dBm (0.0158 W) BLE 2Mbps: 11.89 dBm (0.0155 W)
99% Occupied Bandwidth	BLE 1Mbps: 1.007 MHz BLE 2Mbps: 2.022 MHz
Antenna Type / Gain	IFA Antenna with gain -3.2 dBi
Type of Modulation	Bluetooth LE : GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS TH01-KS	CN1257	314309

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-SZ	CN1256	421272

Test data subcontracted: Radiated Spurious Emission test case in section 3.5 of this report

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	CO01-KS	AUDIX	E3	6.2009-8-24
3.	03CH04-SZ	AUDIX	E3	6.2009-8-24



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(AOHAI)	Model Name	MC-201L
AC Adapter 1(EU)	Brand Name	Motorola(AOHAI)	Model Name	MC-202L
AC Adapter 1(UK)	Brand Name	Motorola(AOHAI)	Model Name	MC-203L
AC Adapter 1(IN)	Brand Name	Motorola(AOHAI)	Model Name	MC-204
AC Adapter 1(AU)	Brand Name	Motorola(AOHAI)	Model Name	MC-205L
AC Adapter 1(AR)	Brand Name	Motorola(AOHAI)	Model Name	MC-206L
AC Adapter 2(US)	Brand Name	Motorola(Salcomp)	Model Name	MC-201L
AC Adapter 2(EU)	Brand Name	Motorola(Salcomp)	Model Name	MC-202L
AC Adapter 2(UK)	Brand Name	Motorola(Salcomp)	Model Name	MC-203L
AC Adapter 2(AU)	Brand Name	Motorola(Salcomp)	Model Name	MC-205L
AC Adapter 2(AR)	Brand Name	Motorola(Salcomp)	Model Name	MC-206L
AC Adapter 2(BR)	Brand Name	Motorola(Salcomp)	Model Name	MC-207L
AC Adapter 2(Chile)	Brand Name	Motorola(Salcomp)	Model Name	MC-209L
AC Adapter 3(US)	Brand Name	Motorola(Chenyang)	Model Name	MC-201L
AC Adapter 3(EU)	Brand Name	Motorola(Chenyang)	Model Name	MC-202L
AC Adapter 3(AR)	Brand Name	Motorola(Chenyang)	Model Name	MC-206L
AC Adapter 3(BR)	Brand Name	Motorola(Chenyang)	Model Name	MC-207L
AC Adapter 4(BR)	Brand Name	Motorola(Cliptech)	Model Name	MC-207L
AC Adapter 5(IN)	Brand Name	Motorola(XIHI)	Model Name	MC-204
Battery 1	Brand Name	Motorola(ATL)	Model Name	QG50
Battery 2	Brand Name	Motorola(Sunwoda)	Model Name	QG50
Battery 3	Brand Name	Motorola(JIADE)	Model Name	QG50
USB Cable 1	Brand Name	Saibao	Model Name	SZN-A026A
USB Cable 2	Brand Name	Juwei	Model Name	JWUB1606-ZN01H



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 2(Charging from Adapter 4) + Earphone
Remark: Radiated Test Cases were performance with Adapter, Earphone and USB Cable.	

2.3 Connection Diagram of Test System

Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	Lenovo	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	Earphone	Apple	DZAY1V-A9007ZJ W3-000	Fcc DoC	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.86 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 1.86 + 10 = 11.86 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density(100kHz)

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Apr. 26, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Apr. 26, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Apr. 26, 2024	Jan. 01, 2025	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 18, 2023	Jun. 21, 2024~ Jun. 26, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2023	Jun. 21, 2024~ Jun. 26, 2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Jun. 21, 2024~ Jun. 26, 2024	Jun. 27, 2024	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May 09, 2024	Jun. 21, 2024~ Jun. 26, 2024	May 08, 2025	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Jul. 07, 2023	Jun. 21, 2024~ Jun. 26, 2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 08, 2023	Jun. 21, 2024~ Jun. 26, 2024	Jul. 07, 2024	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz~3000MHz	Oct. 18, 2023	Jun. 21, 2024~ Jun. 26, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 18, 2023	Jun. 21, 2024~ Jun. 26, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 07, 2023	Jun. 21, 2024~ Jun. 26, 2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY57280136	500MHz~26.5GHz	Aug. 21, 2023	Jun. 21, 2024~ Jun. 26, 2024	Aug. 20, 2024	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F119050019	N/A	Oct. 18, 2023	Jun. 21, 2024~ Jun. 26, 2024	Oct. 17, 2024	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 21, 2024~ Jun. 26, 2024	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 21, 2024~ Jun. 26, 2024	NCR	Radiation (03CH04-SZ)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 18, 2024	Jun. 02, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Jun. 02, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr. 18, 2024	Jun. 02, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Jun. 02, 2024	Oct. 10, 2024	Conduction (CO01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.04ppm

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2024.4.26

Test Engineer: Jiang Jun


DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	6dB BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant6	2402	0.67	2401.66	2402.33	0.5	PASS
		2440	0.67	2439.66	2440.33	0.5	PASS
		2480	0.67	2479.66	2480.33	0.5	PASS
BLE_2M	Ant6	2402	1.14	2401.42	2402.55	0.5	PASS
		2440	1.14	2439.42	2440.55	0.5	PASS
		2480	1.13	2479.42	2480.55	0.5	PASS




Test Graphs






BLE_1M_2480



Date: 26.APR.2024 12:39:40


BLE_2M_2402



Date: 26.APR.2024 12:42:11




BLE_2M_2440



Date: 26.APR.2024 12:46:43

BLE_2M_2480



Date: 26.APR.2024 12:49:22




Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
BLE_1M	Ant6	2402	1.007	2401.5005	2402.5075
		2440	1.007	2439.5005	2440.5075
		2480	0.999	2479.5045	2480.5035
BLE_2M	Ant6	2402	2.022	2401.0050	2403.0270
		2440	2.014	2439.0090	2441.0230
		2480	2.014	2479.0050	2481.0190




Test Graphs






BLE_1M_2480



Date: 26.APR.2024 12:39:45


BLE_2M_2402



Date: 26.APR.2024 12:42:18




BLE_2M_2440



Date: 26.APR.2024 12:46:49

BLE_2M_2480



Date: 26.APR.2024 12:49:29

Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail
BLE1M	Ant6	0	11.34	30.00	-3.2	8.14	36.00	Pass
		19	11.99	30.00	-3.2	8.79	36.00	Pass
		39	11.92	30.00	-3.2	8.72	36.00	Pass
BLE2M	Ant6	0	11.22	30.00	-3.2	8.02	36.00	Pass
		19	11.87	30.00	-3.2	8.67	36.00	Pass
		39	11.89	30.00	-3.2	8.69	36.00	Pass

Test Result Average (Reference Only)

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)
BLE1M	Ant6	0	4.99	11.32
		19	4.99	11.97
		39	4.99	11.88
BLE2M	Ant6	0	4.83	11.14
		19	4.83	11.84
		39	4.83	11.85




Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant6	2402	-5.01	≤8.00	PASS
		2440	-4.37	≤8.00	PASS
		2480	-4.11	≤8.00	PASS
BLE_2M	Ant6	2402	-7.64	≤8.00	PASS
		2440	-6.92	≤8.00	PASS
		2480	-6.6	≤8.00	PASS




Test Graphs






BLE_1M_Ant6_2480



Date: 26.APR.2024 12:39:56


BLE_2M_Ant6_2402



Date: 26.APR.2024 12:42:28




BLE_2M_Ant6_2440



Date: 26.APR.2024 12:47:00

BLE_2M_Ant6_2480



Date: 26.APR.2024 12:49:40




Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant6	2402	2401.75	9.94
		2440	2439.75	10.56
		2480	2479.75	10.93
BLE_2M	Ant6	2402	2401.50	9.48
		2440	2439.50	10.09
		2480	2479.50	10.47




Test Graphs






BLE_1M_Ant6_2480



Date: 26.APR.2024 12:40:04


BLE_2M_Ant6_2402



Date: 26.APR.2024 12:42:36




BLE_2M_Ant6_2440



Date: 26.APR.2024 12:47:07

BLE_2M_Ant6_2480



Date: 26.APR.2024 12:49:47




Band edge measurements

Test Result


TestMode	Antenna	ChName	Freq (MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm /100KHz]	Verdict
BLE_1M	Ant6	Low	2402	9.94	-45.64	≤-10.06	PASS
		High	2480	10.93	-46.1	≤-9.07	PASS
BLE_2M	Ant6	Low	2402	9.48	-31.55	≤-10.52	PASS
		High	2480	10.47	-45.9	≤-9.53	PASS



Test Graphs




BLE_2M_Ant6_Low_2402



Date: 26.APR.2024 12:42:50

BLE_2M_Ant6_High_2480



Date: 26.APR.2024 12:50:02




Conducted Spurious Emission

Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	Ant6	2402	30~1000	9.94	-50.39	≤-10.06	PASS
			1000~26500	9.94	-44.83	≤-10.06	PASS
		2440	30~1000	10.56	-50.21	≤-9.44	PASS
			1000~26500	10.56	-44.8	≤-9.44	PASS
		2480	30~1000	10.93	-50.53	≤-9.07	PASS
			1000~26500	10.93	-43.96	≤-9.07	PASS
BLE_2M	Ant6	2402	30~1000	9.48	-49.69	≤-10.52	PASS
			1000~26500	9.48	-44.33	≤-10.52	PASS
		2440	30~1000	10.09	-50.47	≤-9.91	PASS
			1000~26500	10.09	-45.45	≤-9.91	PASS
		2480	30~1000	10.47	-50.71	≤-9.53	PASS
			1000~26500	10.47	-44.33	≤-9.53	PASS




Test Graphs



BLE_1M_Ant6_2440_30~1000




BLE_1M_Ant6_2440_1000~26500






BLE_1M_Ant6_2480_30~1000




Date: 26.APR.2024 12:40:26

BLE_1M_Ant6_2480_1000~26500




Date: 26.APR.2024 12:40:42

BLE_2M_Ant6_2402_30~1000



Date: 26.APR.2024 12:42:58


BLE_2M_Ant6_2402_1000~26500



Date: 26.APR.2024 12:43:14




BLE_2M_Ant6_2440_30~1000



Date: 26.APR.2024 12:47:13


BLE_2M_Ant6_2440_1000~26500




Date: 26.APR.2024 12:47:29



BLE_2M_Ant6_2480_30~1000




BLE_2M_Ant6_2480_1000~26500



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 2023 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.181	43.05	-21.41	64.46	32.60	0.04	10.41	QP
2	0.181	26.25	-28.21	54.46	15.80	0.04	10.41	Average
3 *	0.474	41.21	-15.24	56.45	31.00	-0.02	10.23	QP
4	0.474	29.11	-17.34	46.45	18.90	-0.02	10.23	Average
5	0.546	38.66	-17.34	56.00	28.50	-0.04	10.20	QP
6	0.546	28.36	-17.64	46.00	18.20	-0.04	10.20	Average
7	0.679	39.68	-16.32	56.00	29.60	-0.07	10.15	QP
8	0.679	27.68	-18.32	46.00	17.60	-0.07	10.15	Average
9	1.021	40.59	-15.41	56.00	30.60	-0.10	10.09	QP
10	1.021	28.19	-17.81	46.00	18.20	-0.10	10.09	Average
11	14.288	43.24	-16.76	60.00	32.20	-0.12	11.16	QP
12	14.288	33.14	-16.86	50.00	22.10	-0.12	11.16	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 2023 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1 *	0.197	49.66	-14.10	63.76	39.20	0.05	10.41	QP
2	0.197	33.66	-20.10	53.76	23.20	0.05	10.41	Average
3	0.246	42.97	-18.94	61.91	32.60	0.00	10.37	QP
4	0.246	26.27	-25.64	51.91	15.90	0.00	10.37	Average
5	0.469	38.77	-17.77	56.54	28.60	-0.07	10.24	QP
6	0.469	29.77	-16.77	46.54	19.60	-0.07	10.24	Average
7	0.544	40.33	-15.67	56.00	30.20	-0.07	10.20	QP
8	0.544	30.73	-15.27	46.00	20.60	-0.07	10.20	Average
9	2.422	38.45	-17.55	56.00	28.50	-0.12	10.07	QP
10	2.422	28.15	-17.85	46.00	18.20	-0.12	10.07	Average
11	14.907	40.70	-19.30	60.00	29.60	-0.10	11.20	QP
12	14.907	32.40	-17.60	50.00	21.30	-0.10	11.20	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Wenbo Xiao	Relative Humidity :	50%
		Temperature :	20°C~22°C

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 5	2400-2483.5	6	Bluetooth-LE_GSFK	00	2402	1Mbps	-	-
Mode 6	2400-2483.5	6	Bluetooth-LE_GSFK	19	2440	1Mbps	-	-
Mode 7	2400-2483.5	6	Bluetooth-LE_GSFK	39	2480	1Mbps	-	-
Mode 8	2400-2483.5	6	Bluetooth-LE_GSFK	00	2402	2Mbps	-	-
Mode 9	2400-2483.5	6	Bluetooth-LE_GSFK	19	2440	2Mbps	-	-
Mode 10	2400-2483.5	6	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-
Mode 11	2400-2483.5	6	Bluetooth-LE_GSFK-LF	39	2480	2Mbps	-	LF





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
5	Bluetooth-LE_GSFK	00	2367.33	34.86	54.00	-19.14	H	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	00	4804.00	40.36	54.00	-13.64	V	Average	Pass	Harmonic
6	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	4880.00	45.31	54.00	-8.69	V	Average	Pass	Harmonic
7	Bluetooth-LE_GSFK	39	2483.72	39.32	54.00	-14.68	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	39	4960.00	45.13	54.00	-8.87	V	Average	Pass	Harmonic
8	Bluetooth-LE_GSFK	00	2389.17	36.83	54.00	-17.17	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	00	4804.00	40.52	54.00	-13.48	V	Average	Pass	Harmonic
9	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	4880.00	45.29	54.00	-8.71	V	Average	Pass	Harmonic
10	Bluetooth-LE_GSFK	39	2483.52	45.45	54.00	-8.55	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	39	4960.00	45.35	54.00	-8.65	V	Average	Pass	Harmonic
11	Bluetooth-LE_GSFK-LF	39	41.64	28.90	40.00	-11.10	V	Peak	PASS	LF



Mode	5																																																																																											
	Band Edge																																																																																											
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																											
ANT	6																																																																																											
Pol.	Horizontal						Fundamental																																																																																					
Peak	Level (dBuV/m) Date: 2024-06-21 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2383.61</td><td>44.94</td><td>74.00</td><td>-29.06</td><td>42.40</td><td>30.72</td><td>5.35</td><td>33.53</td><td>200</td><td>141</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2383.61	44.94	74.00	-29.06	42.40	30.72	5.35	33.53	200	141	PEAK	Level (dBuV/m) Date: 2024-06-21 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>85.72</td><td>-----</td><td>-----</td><td>83.17</td><td>30.72</td><td>5.37</td><td>33.54</td><td>200</td><td>141</td><td>PEAK_74</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	85.72	-----	-----	83.17	30.72	5.37	33.54	200	141	PEAK_74
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2383.61	44.94	74.00	-29.06	42.40	30.72	5.35	33.53	200	141	PEAK																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2402.00	85.72	-----	-----	83.17	30.72	5.37	33.54	200	141	PEAK_74																																																																																	
Avg	Level (dBuV/m) Date: 2024-06-21 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2367.33</td><td>34.86</td><td>54.00</td><td>-19.14</td><td>32.31</td><td>30.73</td><td>5.34</td><td>33.52</td><td>200</td><td>141</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2367.33	34.86	54.00	-19.14	32.31	30.73	5.34	33.52	200	141	AVERAGE	Level (dBuV/m) Date: 2024-06-21 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>85.16</td><td>-----</td><td>-----</td><td>82.61</td><td>30.72</td><td>5.37</td><td>33.54</td><td>200</td><td>141</td><td>AVG_54</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	85.16	-----	-----	82.61	30.72	5.37	33.54	200	141	AVG_54
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2367.33	34.86	54.00	-19.14	32.31	30.73	5.34	33.52	200	141	AVERAGE																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2402.00	85.16	-----	-----	82.61	30.72	5.37	33.54	200	141	AVG_54																																																																																	





Mode	5																																																																																															
	Band Edge																																																																																															
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																															
ANT	6																																																																																															
Pol.	Vertical						Fundamental																																																																																									
Peak	 Date: 2024-06-21 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.70</td><td>45.01</td><td>74.00</td><td>-28.99</td><td>42.46</td><td>30.72</td><td>5.36</td><td>33.53</td><td>100</td><td>302</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2389.70	45.01	74.00	-28.99	42.46	30.72	5.36	33.53	100	302	PEAK	 Date: 2024-06-21 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>100.59</td><td>-----</td><td>-----</td><td>98.04</td><td>30.72</td><td>5.37</td><td>33.54</td><td>100</td><td>302</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2402.00	100.59	-----	-----	98.04	30.72	5.37	33.54	100	302	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2389.70	45.01	74.00	-28.99	42.46	30.72	5.36	33.53	100	302	PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2402.00	100.59	-----	-----	98.04	30.72	5.37	33.54	100	302	PEAK																																																																																					
Avg	 Date: 2024-06-21 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2388.54</td><td>34.83</td><td>54.00</td><td>-19.17</td><td>32.28</td><td>30.72</td><td>5.36</td><td>33.53</td><td>100</td><td>302</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2388.54	34.83	54.00	-19.17	32.28	30.72	5.36	33.53	100	302	AVERAGE	 Date: 2024-06-21 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>100.04</td><td>-----</td><td>-----</td><td>97.49</td><td>30.72</td><td>5.37</td><td>33.54</td><td>100</td><td>302</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2402.00	100.04	-----	-----	97.49	30.72	5.37	33.54	100	302	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2388.54	34.83	54.00	-19.17	32.28	30.72	5.36	33.53	100	302	AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2402.00	100.04	-----	-----	97.49	30.72	5.37	33.54	100	302	AVERAGE																																																																																					



Mode	5																																																																																																											
	Harmonic																																																																																																											
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																											
ANT	6																																																																																																											
Pol.	Horizontal						Vertical																																																																																																					
Peak Avg	Level (dBuV/m) Date: 2024-06-22 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>43.52</td><td>74.00</td><td>-30.48</td><td>63.69</td><td>35.73</td><td>8.94</td><td>64.84</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4804.00	43.52	74.00	-30.48	63.69	35.73	8.94	64.84	---	---	Peak	Level (dBuV/m) Date: 2024-06-22 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>44.30</td><td>74.00</td><td>-29.70</td><td>64.47</td><td>35.73</td><td>8.94</td><td>64.84</td><td>246</td><td>8</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>40.36</td><td>54.00</td><td>-13.64</td><td>60.53</td><td>35.73</td><td>8.94</td><td>64.84</td><td>246</td><td>8</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4804.00	44.30	74.00	-29.70	64.47	35.73	8.94	64.84	246	8	Peak	2	4804.00	40.36	54.00	-13.64	60.53	35.73	8.94	64.84	246	8	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																		
1	4804.00	43.52	74.00	-30.48	63.69	35.73	8.94	64.84	---	---	Peak																																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																		
1	4804.00	44.30	74.00	-29.70	64.47	35.73	8.94	64.84	246	8	Peak																																																																																																	
2	4804.00	40.36	54.00	-13.64	60.53	35.73	8.94	64.84	246	8	Average																																																																																																	



Mode	6																																																																																																							
	Harmonic																																																																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																							
ANT	6																																																																																																							
Pol.	Horizontal								Vertical																																																																																															
Peak Avg	Level (dBuV/m) Date: 2024-06-22  300060009000120001500018000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>4880.00</td><td>44.12</td><td>74.00</td><td>-29.88</td><td>64.37</td><td>35.91</td><td>8.71</td></tr><tr><td>2</td><td>7320.00</td><td>45.36</td><td>74.00</td><td>-28.64</td><td>63.17</td><td>36.87</td><td>10.18</td></tr></table>									Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	4880.00	44.12	74.00	-29.88	64.37	35.91	8.71	2	7320.00	45.36	74.00	-28.64	63.17	36.87	10.18	Level (dBuV/m) Date: 2024-06-22  300060009000120001500018000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>4880.00</td><td>49.30</td><td>74.00</td><td>-24.70</td><td>69.55</td><td>35.91</td><td>8.71</td></tr><tr><td>2</td><td>4880.00</td><td>45.31</td><td>54.00</td><td>-8.69</td><td>65.56</td><td>35.91</td><td>8.71</td></tr><tr><td>3</td><td>7320.00</td><td>46.11</td><td>74.00</td><td>-27.89</td><td>63.92</td><td>36.87</td><td>10.18</td></tr></table>									Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	4880.00	49.30	74.00	-24.70	69.55	35.91	8.71	2	4880.00	45.31	54.00	-8.69	65.56	35.91	8.71	3	7320.00	46.11	74.00	-27.89	63.92	36.87	10.18
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																	
1	4880.00	44.12	74.00	-29.88	64.37	35.91	8.71																																																																																																	
2	7320.00	45.36	74.00	-28.64	63.17	36.87	10.18																																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																	
1	4880.00	49.30	74.00	-24.70	69.55	35.91	8.71																																																																																																	
2	4880.00	45.31	54.00	-8.69	65.56	35.91	8.71																																																																																																	
3	7320.00	46.11	74.00	-27.89	63.92	36.87	10.18																																																																																																	



Mode	7																																																																																	
	Band Edge																																																																																	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																	
ANT	6																																																																																	
Pol.	Horizontal					Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2480 2484 2488 2492 2496 2500 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2483.60</td><td>54.30</td><td>74.00</td><td>-19.70</td><td>51.73</td><td>30.70</td><td>5.46</td><td>33.59</td><td>397 360 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2483.60	54.30	74.00	-19.70	51.73	30.70	5.46	33.59	397 360 PEAK	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2480.00</td><td>100.60</td><td>-----</td><td>-----</td><td>98.03</td><td>30.70</td><td>5.46</td><td>33.59</td><td>397 360 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2480.00	100.60	-----	-----	98.03	30.70	5.46	33.59	397 360 PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2483.60	54.30	74.00	-19.70	51.73	30.70	5.46	33.59	397 360 PEAK																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2480.00	100.60	-----	-----	98.03	30.70	5.46	33.59	397 360 PEAK																																																																										
Avg	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2480 2484 2488 2492 2496 2500 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2483.72</td><td>37.48</td><td>54.00</td><td>-16.52</td><td>34.91</td><td>30.70</td><td>5.46</td><td>33.59</td><td>397 360 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2483.72	37.48	54.00	-16.52	34.91	30.70	5.46	33.59	397 360 AVERAGE	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2480.00</td><td>100.09</td><td>-----</td><td>-----</td><td>97.52</td><td>30.70</td><td>5.46</td><td>33.59</td><td>397 360 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2480.00	100.09	-----	-----	97.52	30.70	5.46	33.59	397 360 AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2483.72	37.48	54.00	-16.52	34.91	30.70	5.46	33.59	397 360 AVERAGE																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2480.00	100.09	-----	-----	97.52	30.70	5.46	33.59	397 360 AVERAGE																																																																										







Mode	7	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	Level (dBuV/m) Date: 2024-06-21 1 2483.70 56.44 74.00 -17.56 53.87 30.70 5.46 33.59 256 255 PEAK	Level (dBuV/m) Date: 2024-06-21 1 2480.00 103.94 ----- 101.37 30.70 5.46 33.59 256 255 PEAK
	Level (dBuV/m) Date: 2024-06-21 1 2483.72 39.32 54.00 -14.68 36.75 30.70 5.46 33.59 256 255 AVERAGE	Level (dBuV/m) Date: 2024-06-21 1 2480.00 103.43 ----- 100.86 30.70 5.46 33.59 256 255 AVERAGE



Mode	7																																																																																																																											
	Harmonic																																																																																																																											
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																																											
ANT	6																																																																																																																											
Pol.	Horizontal						Vertical																																																																																																																					
Peak Avg	Level (dBuV/m) Date: 2024-06-22 Frequency (MHz)						Level (dBuV/m) Date: 2024-06-22 Frequency (MHz)																																																																																																																					
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>43.43</td><td>74.00</td><td>-30.57</td><td>63.77</td><td>36.10</td><td>8.46</td><td>64.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7440.00</td><td>44.74</td><td>74.00</td><td>-29.26</td><td>62.61</td><td>36.82</td><td>10.17</td><td>64.86</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4960.00	43.43	74.00	-30.57	63.77	36.10	8.46	64.90	---	---	Peak	2	7440.00	44.74	74.00	-29.26	62.61	36.82	10.17	64.86	---	---	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>49.50</td><td>74.00</td><td>-24.50</td><td>69.84</td><td>36.10</td><td>8.46</td><td>64.90</td><td>253</td><td>7</td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>45.13</td><td>54.00</td><td>-8.87</td><td>65.47</td><td>36.10</td><td>8.46</td><td>64.90</td><td>253</td><td>7</td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>44.49</td><td>74.00</td><td>-29.51</td><td>62.36</td><td>36.82</td><td>10.17</td><td>64.86</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4960.00	49.50	74.00	-24.50	69.84	36.10	8.46	64.90	253	7	Peak	2	4960.00	45.13	54.00	-8.87	65.47	36.10	8.46	64.90	253	7	Average	3	7440.00	44.49	74.00	-29.51	62.36	36.82	10.17	64.86	---	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																			
1	4960.00	43.43	74.00	-30.57	63.77	36.10	8.46	64.90	---	---	Peak																																																																																																																	
2	7440.00	44.74	74.00	-29.26	62.61	36.82	10.17	64.86	---	---	Peak																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																			
1	4960.00	49.50	74.00	-24.50	69.84	36.10	8.46	64.90	253	7	Peak																																																																																																																	
2	4960.00	45.13	54.00	-8.87	65.47	36.10	8.46	64.90	253	7	Average																																																																																																																	
3	7440.00	44.49	74.00	-29.51	62.36	36.82	10.17	64.86	---	---	Peak																																																																																																																	



		8																																																																																																	
Mode		Band Edge																																																																																																	
		2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																	
ANT		6																																																																																																	
Pol.		Horizontal					Fundamental																																																																																												
Peak	 Level (dBuV/m) vs Frequency (MHz). Date: 2024-06-21. Peak at 2386.86 MHz.					 Level (dBuV/m) vs Frequency (MHz). Date: 2024-06-21. Peak at 2402.00 MHz.																																																																																													
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2325.44</td><td>44.37</td><td>74.00</td><td>-29.63</td><td>41.83</td><td>30.73</td><td>5.31</td><td>33.50</td><td>105</td><td>0 PEAK</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2325.44	44.37	74.00	-29.63	41.83	30.73	5.31	33.50	105	0 PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>94.42</td><td>-----</td><td>-----</td><td>91.87</td><td>30.72</td><td>5.37</td><td>33.54</td><td>105</td><td>0 PEAK</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2402.00	94.42	-----	-----	91.87	30.72	5.37	33.54	105
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2325.44	44.37	74.00	-29.63	41.83	30.73	5.31	33.50	105	0 PEAK																																																																																									
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	94.42	-----	-----	91.87	30.72	5.37	33.54	105	0 PEAK																																																																																									
Avg	 Level (dBuV/m) vs Frequency (MHz). Date: 2024-06-21. Peak at 2386.86 MHz.					 Level (dBuV/m) vs Frequency (MHz). Date: 2024-06-21. Peak at 2402.00 MHz.																																																																																													
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2386.86</td><td>36.41</td><td>54.00</td><td>-17.59</td><td>33.86</td><td>30.72</td><td>5.36</td><td>33.53</td><td>105</td><td>0 AVERAGE</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2386.86	36.41	54.00	-17.59	33.86	30.72	5.36	33.53	105	0 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>93.98</td><td>-----</td><td>-----</td><td>91.43</td><td>30.72</td><td>5.37</td><td>33.54</td><td>105</td><td>0 AVERAGE</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2402.00	93.98	-----	-----	91.43	30.72	5.37	33.54	105
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2386.86	36.41	54.00	-17.59	33.86	30.72	5.36	33.53	105	0 AVERAGE																																																																																									
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	93.98	-----	-----	91.43	30.72	5.37	33.54	105	0 AVERAGE																																																																																									



Mode	8																																																			
	Band Edge																																																			
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																			
ANT	6																																																			
Pol.	Vertical																																																			
Peak	Fundamental																																																			
	Date: 2024-06-21																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.91</td><td>46.41</td><td>74.00</td><td>-27.59</td><td>43.86</td><td>30.72</td><td>5.36</td><td>33.53</td><td>212</td><td>243</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2389.91	46.41	74.00	-27.59	43.86	30.72	5.36	33.53	212	243	PEAK
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																										
1	2389.91	46.41	74.00	-27.59	43.86	30.72	5.36	33.53	212	243	PEAK																																									
Avg	Date: 2024-06-21																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2389.17</td><td>36.83</td><td>54.00</td><td>-17.17</td><td>34.28</td><td>30.72</td><td>5.36</td><td>33.53</td><td>212</td><td>243</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	2389.17	36.83	54.00	-17.17	34.28	30.72	5.36	33.53	212	243
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																										
1	2389.17	36.83	54.00	-17.17	34.28	30.72	5.36	33.53	212	243	AVERAGE																																									



Mode	8																																																																																																							
	Harmonic																																																																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH00_2402MHz																																																																																																							
ANT	6																																																																																																							
Pol.	Horizontal						Vertical																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2024-06-22 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>42.75</td><td>74.00</td><td>-31.25</td><td>62.92</td><td>35.73</td><td>8.94</td><td>64.84</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	42.75	74.00	-31.25	62.92	35.73	8.94	64.84	---	---	Peak	Level (dBuV/m) Date: 2024-06-22 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>46.08</td><td>74.00</td><td>-27.92</td><td>66.25</td><td>35.73</td><td>8.94</td><td>64.84</td><td>278</td><td>6</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>40.52</td><td>54.00</td><td>-13.48</td><td>60.69</td><td>35.73</td><td>8.94</td><td>64.84</td><td>278</td><td>6</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	46.08	74.00	-27.92	66.25	35.73	8.94	64.84	278	6	Peak	2	4804.00	40.52	54.00	-13.48	60.69	35.73	8.94	64.84	278	6	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	4804.00	42.75	74.00	-31.25	62.92	35.73	8.94	64.84	---	---	Peak																																																																																													
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	4804.00	46.08	74.00	-27.92	66.25	35.73	8.94	64.84	278	6	Peak																																																																																													
2	4804.00	40.52	54.00	-13.48	60.69	35.73	8.94	64.84	278	6	Average																																																																																													



Mode	9																																																																																																																					
	Harmonic																																																																																																																					
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																																					
ANT	6																																																																																																																					
Pol.	Horizontal					Vertical																																																																																																																
Peak Avg	Level (dBuV/m) Date: 2024-06-22 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 3000 6000 9000 12000 15000 18000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>44.64</td><td>74.00</td><td>-29.36</td><td>64.89</td><td>35.91</td><td>8.71</td><td>64.87</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7320.00</td><td>45.61</td><td>74.00</td><td>-28.39</td><td>63.42</td><td>36.87</td><td>10.18</td><td>64.86</td><td>---</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4880.00	44.64	74.00	-29.36	64.89	35.91	8.71	64.87	---	Peak	2	7320.00	45.61	74.00	-28.39	63.42	36.87	10.18	64.86	---	Peak	Level (dBuV/m) Date: 2024-06-22 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 3000 6000 9000 12000 15000 18000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>47.95</td><td>74.00</td><td>-26.05</td><td>68.20</td><td>35.91</td><td>8.71</td><td>64.87</td><td>290</td><td>6 Peak</td></tr><tr><td>2</td><td>4880.00</td><td>45.29</td><td>54.00</td><td>-8.71</td><td>65.54</td><td>35.91</td><td>8.71</td><td>64.87</td><td>290</td><td>6 Average</td></tr><tr><td>3</td><td>7320.00</td><td>45.24</td><td>74.00</td><td>-28.76</td><td>63.05</td><td>36.87</td><td>10.18</td><td>64.86</td><td>---</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	47.95	74.00	-26.05	68.20	35.91	8.71	64.87	290	6 Peak	2	4880.00	45.29	54.00	-8.71	65.54	35.91	8.71	64.87	290	6 Average	3	7320.00	45.24	74.00	-28.76	63.05	36.87	10.18	64.86	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																													
1	4880.00	44.64	74.00	-29.36	64.89	35.91	8.71	64.87	---	Peak																																																																																																												
2	7320.00	45.61	74.00	-28.39	63.42	36.87	10.18	64.86	---	Peak																																																																																																												
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																												
1	4880.00	47.95	74.00	-26.05	68.20	35.91	8.71	64.87	290	6 Peak																																																																																																												
2	4880.00	45.29	54.00	-8.71	65.54	35.91	8.71	64.87	290	6 Average																																																																																																												
3	7320.00	45.24	74.00	-28.76	63.05	36.87	10.18	64.86	---	Peak																																																																																																												



Mode	10																																																																																	
	Band Edge																																																																																	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																	
ANT	6																																																																																	
Pol.	Horizontal					Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2480 2484 2488 2492 2496 2500 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2483.76</td><td>54.26</td><td>74.00</td><td>-19.74</td><td>51.69</td><td>30.70</td><td>5.46</td><td>33.59</td><td>400 307 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2483.76	54.26	74.00	-19.74	51.69	30.70	5.46	33.59	400 307 PEAK	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2480.00</td><td>101.28</td><td>-----</td><td>-----</td><td>98.71</td><td>30.70</td><td>5.46</td><td>33.59</td><td>400 307 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2480.00	101.28	-----	-----	98.71	30.70	5.46	33.59	400 307 PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2483.76	54.26	74.00	-19.74	51.69	30.70	5.46	33.59	400 307 PEAK																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2480.00	101.28	-----	-----	98.71	30.70	5.46	33.59	400 307 PEAK																																																																										
Avg	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2480 2484 2488 2492 2496 2500 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2483.52</td><td>42.81</td><td>54.00</td><td>-11.19</td><td>40.24</td><td>30.70</td><td>5.46</td><td>33.59</td><td>400 307 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2483.52	42.81	54.00	-11.19	40.24	30.70	5.46	33.59	400 307 AVERAGE	Level (dBuV/m) Date: 2024-06-21 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2480.00</td><td>100.87</td><td>-----</td><td>-----</td><td>98.30</td><td>30.70</td><td>5.46</td><td>33.59</td><td>400 307 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1 2480.00	100.87	-----	-----	98.30	30.70	5.46	33.59	400 307 AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2483.52	42.81	54.00	-11.19	40.24	30.70	5.46	33.59	400 307 AVERAGE																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																										
1 2480.00	100.87	-----	-----	98.30	30.70	5.46	33.59	400 307 AVERAGE																																																																										





Mode	10																																																																																							
	Band Edge																																																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																							
ANT	6																																																																																							
Pol.	Vertical					Fundamental																																																																																		
Peak	Level (dBuV/m) Date: 2024-06-21 PEAK_BE_74 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.94</td><td>57.25</td><td>74.00</td><td>-16.75</td><td>54.68</td><td>30.70</td><td>5.46</td><td>33.59</td><td>249</td><td>256 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2483.94	57.25	74.00	-16.75	54.68	30.70	5.46	33.59	249	256 PEAK	Level (dBuV/m) Date: 2024-06-21 PEAK_74 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>104.05</td><td>-----</td><td>-----</td><td>101.48</td><td>30.70</td><td>5.46</td><td>33.59</td><td>249</td><td>256 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2480.00	104.05	-----	-----	101.48	30.70	5.46	33.59	249	256 PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2483.94	57.25	74.00	-16.75	54.68	30.70	5.46	33.59	249	256 PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2480.00	104.05	-----	-----	101.48	30.70	5.46	33.59	249	256 PEAK																																																																														
Avg	Level (dBuV/m) Date: 2024-06-21 AVG_BE_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.52</td><td>45.45</td><td>54.00</td><td>-8.55</td><td>42.88</td><td>30.70</td><td>5.46</td><td>33.59</td><td>249</td><td>256 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2483.52	45.45	54.00	-8.55	42.88	30.70	5.46	33.59	249	256 AVERAGE	Level (dBuV/m) Date: 2024-06-21 AVG_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>103.58</td><td>-----</td><td>-----</td><td>101.01</td><td>30.70</td><td>5.46</td><td>33.59</td><td>249</td><td>256 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2480.00	103.58	-----	-----	101.01	30.70	5.46	33.59	249	256 AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2483.52	45.45	54.00	-8.55	42.88	30.70	5.46	33.59	249	256 AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2480.00	103.58	-----	-----	101.01	30.70	5.46	33.59	249	256 AVERAGE																																																																														



Mode	10																																																																																																																							
	Harmonic																																																																																																																							
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																																							
ANT	6																																																																																																																							
Pol.	Horizontal					Vertical																																																																																																																		
Peak Avg	Data: 1 Level (dBuV/m) Date: 2024-06-26 Horizontal Polarization Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red limit line at 74.00 dBuV/m, and a red average line at 54.00 dBuV/m. Two peaks are marked with blue vertical lines and labeled 1 and 2.					Data: 2 Level (dBuV/m) Date: 2024-06-26 Vertical Polarization Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red limit line at 74.00 dBuV/m, and a red average line at 54.00 dBuV/m. Two peaks are marked with blue vertical lines and labeled 1 and 2.																																																																																																																		
	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Level</th><th>Loss</th><th>Factor</th><th></th><th></th><th>Remark</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4960.00</td><td>43.70</td><td>-30.30</td><td>74.00</td><td>64.09</td><td>36.10</td><td>8.41</td><td>64.90</td><td>Peak</td></tr><tr><td>2</td><td>7440.00</td><td>44.93</td><td>-29.07</td><td>74.00</td><td>62.80</td><td>36.82</td><td>10.17</td><td>64.86</td><td>Peak</td></tr></table>						Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos			Freq	Level	Limit	Level	Loss	Factor			Remark		MHz	dBuV/m	dB	dBuV	dB/m	dB	cm	deg			1	4960.00	43.70	-30.30	74.00	64.09	36.10	8.41	64.90	Peak	2	7440.00	44.93	-29.07	74.00	62.80	36.82	10.17	64.86	Peak	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Level</th><th>Loss</th><th>Factor</th><th></th><th></th><th>Remark</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>* 4960.00</td><td>47.96</td><td>-26.04</td><td>74.00</td><td>68.35</td><td>36.10</td><td>8.41</td><td>64.90</td><td>284 9 Peak</td></tr><tr><td>2</td><td>4960.00</td><td>45.35</td><td>-8.65</td><td>54.00</td><td>65.74</td><td>36.10</td><td>8.41</td><td>64.90</td><td>284 9 Average</td></tr><tr><td>3</td><td>7440.00</td><td>45.40</td><td>-28.60</td><td>74.00</td><td>63.27</td><td>36.82</td><td>10.17</td><td>64.86</td><td>Peak</td></tr></table>						Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos			Freq	Level	Limit	Level	Loss	Factor			Remark		MHz	dBuV/m	dB	dBuV	dB/m	dB	cm	deg			1	* 4960.00	47.96	-26.04	74.00	68.35	36.10	8.41	64.90	284 9 Peak	2	4960.00	45.35	-8.65	54.00	65.74	36.10	8.41	64.90	284 9 Average	3	7440.00	45.40	-28.60	74.00	63.27	36.82	10.17	64.86	Peak
		Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos																																																																																																																
Freq	Level	Limit	Level	Loss	Factor			Remark																																																																																																																
MHz	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																	
1	4960.00	43.70	-30.30	74.00	64.09	36.10	8.41	64.90	Peak																																																																																																															
2	7440.00	44.93	-29.07	74.00	62.80	36.82	10.17	64.86	Peak																																																																																																															
	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos																																																																																																																	
Freq	Level	Limit	Level	Loss	Factor			Remark																																																																																																																
MHz	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																																																	
1	* 4960.00	47.96	-26.04	74.00	68.35	36.10	8.41	64.90	284 9 Peak																																																																																																															
2	4960.00	45.35	-8.65	54.00	65.74	36.10	8.41	64.90	284 9 Average																																																																																																															
3	7440.00	45.40	-28.60	74.00	63.27	36.82	10.17	64.86	Peak																																																																																																															




Mode	11																																																																																																																																																																																																																			
	LF																																																																																																																																																																																																																			
	2400-2483.5_Bluetooth-LE_GSKF-LF_CH39_2480MHz																																																																																																																																																																																																																			
ANT	6																																																																																																																																																																																																																			
Pol.	Horizontal						Vertical																																																																																																																																																																																																													
QP/ Peak																																																																																																																																																																																																																				
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>30.00</td><td>23.27</td><td>40.00</td><td>-16.73</td><td>29.14</td><td>25.20</td><td>0.53</td><td>31.60</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>181.32</td><td>17.19</td><td>43.50</td><td>-26.31</td><td>32.46</td><td>15.00</td><td>1.37</td><td>31.64</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>316.15</td><td>23.88</td><td>46.00</td><td>-22.12</td><td>33.99</td><td>19.50</td><td>1.86</td><td>31.47</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>619.76</td><td>27.76</td><td>46.00</td><td>-18.24</td><td>30.60</td><td>25.70</td><td>2.60</td><td>31.14</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>766.23</td><td>31.00</td><td>46.00</td><td>-15.00</td><td>30.89</td><td>28.40</td><td>2.88</td><td>31.17</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>945.68</td><td>31.88</td><td>46.00</td><td>-14.12</td><td>28.83</td><td>30.64</td><td>3.22</td><td>30.81</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	30.00	23.27	40.00	-16.73	29.14	25.20	0.53	31.60	---	---	Peak	2	181.32	17.19	43.50	-26.31	32.46	15.00	1.37	31.64	---	---	Peak	3	316.15	23.88	46.00	-22.12	33.99	19.50	1.86	31.47	---	---	Peak	4	619.76	27.76	46.00	-18.24	30.60	25.70	2.60	31.14	---	---	Peak	5	766.23	31.00	46.00	-15.00	30.89	28.40	2.88	31.17	---	---	Peak	6	945.68	31.88	46.00	-14.12	28.83	30.64	3.22	30.81	---	---	Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>30.97</td><td>27.45</td><td>40.00</td><td>-12.55</td><td>33.83</td><td>24.70</td><td>0.54</td><td>31.62</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>41.64</td><td>28.90</td><td>40.00</td><td>-11.10</td><td>41.27</td><td>18.80</td><td>0.63</td><td>31.80</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>169.68</td><td>18.26</td><td>43.50</td><td>-25.24</td><td>32.89</td><td>15.70</td><td>1.33</td><td>31.66</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>566.41</td><td>27.37</td><td>46.00</td><td>-18.63</td><td>29.61</td><td>26.44</td><td>2.49</td><td>31.17</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>794.36</td><td>31.08</td><td>46.00</td><td>-14.92</td><td>30.94</td><td>28.32</td><td>2.93</td><td>31.11</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>931.13</td><td>32.92</td><td>46.00</td><td>-13.08</td><td>30.72</td><td>29.84</td><td>3.20</td><td>30.84</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	30.97	27.45	40.00	-12.55	33.83	24.70	0.54	31.62	---	---	Peak	2	41.64	28.90	40.00	-11.10	41.27	18.80	0.63	31.80	---	---	Peak	3	169.68	18.26	43.50	-25.24	32.89	15.70	1.33	31.66	---	---	Peak	4	566.41	27.37	46.00	-18.63	29.61	26.44	2.49	31.17	---	---	Peak	5	794.36	31.08	46.00	-14.92	30.94	28.32	2.93	31.11	---	---	Peak	6	931.13	32.92	46.00	-13.08	30.72	29.84	3.20	30.84	---	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																											
1	30.00	23.27	40.00	-16.73	29.14	25.20	0.53	31.60	---	---	Peak																																																																																																																																																																																																									
2	181.32	17.19	43.50	-26.31	32.46	15.00	1.37	31.64	---	---	Peak																																																																																																																																																																																																									
3	316.15	23.88	46.00	-22.12	33.99	19.50	1.86	31.47	---	---	Peak																																																																																																																																																																																																									
4	619.76	27.76	46.00	-18.24	30.60	25.70	2.60	31.14	---	---	Peak																																																																																																																																																																																																									
5	766.23	31.00	46.00	-15.00	30.89	28.40	2.88	31.17	---	---	Peak																																																																																																																																																																																																									
6	945.68	31.88	46.00	-14.12	28.83	30.64	3.22	30.81	---	---	Peak																																																																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																											
1	30.97	27.45	40.00	-12.55	33.83	24.70	0.54	31.62	---	---	Peak																																																																																																																																																																																																									
2	41.64	28.90	40.00	-11.10	41.27	18.80	0.63	31.80	---	---	Peak																																																																																																																																																																																																									
3	169.68	18.26	43.50	-25.24	32.89	15.70	1.33	31.66	---	---	Peak																																																																																																																																																																																																									
4	566.41	27.37	46.00	-18.63	29.61	26.44	2.49	31.17	---	---	Peak																																																																																																																																																																																																									
5	794.36	31.08	46.00	-14.92	30.94	28.32	2.93	31.11	---	---	Peak																																																																																																																																																																																																									
6	931.13	32.92	46.00	-13.08	30.72	29.84	3.20	30.84	---	---	Peak																																																																																																																																																																																																									

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth –LE 1Mbps	31.71	0.397	2.518	3kHz
Bluetooth –LE 2Mbps	32.87	0.206	4.859	10kHz

Bluetooth – LE 1Mbps





Bluetooth – LE 2Mbps

