



# M. Flom Associates, Inc.

## International Compliance Testing Laboratory

3356 N. San Marcos Place, Suite 107  
Chandler, AZ 85225

toll-free: (866) 311-3268  
fax: (480) 926-3598

<http://www.mflom.com>  
[info@mflom.com](mailto:info@mflom.com)



Date: December 3, 2004

Federal Communications Commission  
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: E. F. Johnson Company  
Equipment: 242-5337-211-AAAA  
FCC ID: ATH2425331  
FCC Rules: Radiofrequency Radiation Exposure Limits  
47 CFR 1.1310  
MPE - Mobiles X Fixed Based Station           

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

David E. Lee,  
Compliance Test Manager

enclosure(s)  
cc: Applicant  
DEL/del

M. Flom Associates, Inc.  
3356 N. San Marcos Place, Suite 107  
Chandler, Arizona 85225-7176  
(480) 926-3100 phone, fax (480) 926-3598

FCC ID: ATH2425331  
MFA p0490011, d04c00088

**Environmental Assessment**

for

**Mobiles/Fixed Base Station**

for

**FCC ID: ATH2425331**

Model:RS-5331

to

**Federal Communications Commission**

**47 CFR 1.1310 (MPE)**

Radiofrequency Radiation Exposure Limits

**Date Of Report:** December 3, 2004

**On the Behalf of the Applicant:**

E. F. Johnson Company

**At the Request of:**


P.O. 170502

E. F. Johnson Company,  
299 Johnson Ave.  
Waseca, MN 56093-0514

**Attention of:**

(507) 835-6579; FAX: -6666  
John Oblak, Director, Radio Products Development  
E-mail: [joblak@efjohnson.com](mailto:joblak@efjohnson.com)

**Supervised By:**



David E. Lee,  
Compliance Test Manager

## Table of Contents

Rule	Description	Page
2.1033(c)	General Information Required	3
	Standard Test Conditions and Engineering Practices	4
1.1310	Environmental Assessment	5

*Required information per ISO/IEC Guide 25-1990, paragraph 13.2:*

a) **Test Report (Supplemental)**

b) Laboratory: M. Flom Associates, Inc.  
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107  
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d04c0008

d) Client: E. F. Johnson Company,  
299 Johnson Ave.  
Waseca, MN 56093-0514

e) Identification: 242-5337-211-AAAA  
FCC ID: ATH2425331  
Description: UHF FM Mobile Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: December 3, 2004  
EUT Received: September 20, 2004

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



David E. Lee,  
Compliance Test Manager

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

### Identification of the Equipment Under Test (EUT)

**Name and Address of Applicant:**

E. F. Johnson Company  
299 Johnson Ave.  
Waseca, MN 56093-0514

**Manufacturer:**

EF Johnson Company  
Irving, Texas

**FCC ID:**

ATH2425331

**Model Number:**

242-5337-211-AAAA

**Description:**

UHF FM Mobile Transceiver

**Type of Emission:**

16K0F3E, 14K0F3E, 11K0F3E, 8K10F1E,  
8J10F1D

**Frequency Range, MHz:**

380 to 470

**Power Rating, Watts:**

\_\_\_\_\_ Switchable

\_\_\_\_\_ Variable

45

\_\_\_\_\_ N/A

**Modulation:**

\_\_\_\_\_ AMPS

\_\_\_\_\_ TDMA

\_\_\_\_\_ CDMA

  X   OTHER

**Antenna:**

\_\_\_\_\_ Helical

\_\_\_\_\_ Monopole

  X   Whip

\_\_\_\_\_ Other

**Note:** For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.



## A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 – 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: **2152-01**



## NIST

I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Agreement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at <http://ts.nist.gov/mra> under the 'Asia' category."

BSMI Number: **SL2-IN-E-041R**

## **Standard Test Conditions and Engineering Practices**

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2001, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

**Name of Test:** Environmental Assessment

**Specification:** FCC: 47 CFR 1.1310

**Measurement Guide:** ANSI/IEEE C95.1 1992

**Test Equipment:** Maximum Permissible Exposure (MPE) measurement system, consisting of:  
Amplifier Research FP6001 Field Test Kit (Cal June, 04)

**Measurement Procedure:**

1. The following measurements were performed with a field probe using ANSI/IEEE C95.1 as a guide.
2. Prior to making any measurements, the measurements system was calibrated in accordance with the manufacturer's procedures.
3. The EUT's radiating element (antenna) was placed on a 1 m tall table for ease of testing. For equipment normally operated on a metal surface, a ground plane was used.
4. The remaining equipment necessary to operate the EUT was maintained at a distance from the measurement arrangement suitable to minimize interference with the measurements.
5. The minimum safe distance was calculated from the formula Power Density =  $EIRP / 4\pi R^2$  (Peak Watts/m<sup>2</sup>). The calculation is shown with the measurement data.
6. With the EUT operating at maximum power, a search was initiated for worst-case emissions with the probe raised and lowered over a range of 0.2 to 2 meters in height and over a horizontal plane of 0° to 360°.
7. Average values were calculated for the whole body (0.2-2.0m), lower body (0.2-0.8m) and upper body (1.0-2.0m).

**Results:** Attached.



**Test Setup:** Maximum Permissible Exposure (MPE)



**Name of Test:** R.F. Radiation Exposure

FCC Rules: 1.1307, 1.1310, 1.1311, 2.1091

Description, EUT: See page 2 of Test Report

Limits: Uncontrolled Exposure	0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
47 CFR 1.1310	1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
Table 1, (B)	30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
	300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
	1500-100,000 MHz:	Limit [mW/cm <sup>2</sup> ] = 1.0

Test Frequencies, MHz	380.000	425.000	470.000
Power, Conducted, W	= 45		
Test Antenna Gain	-0.15dBd = 2dbi = Numeric Gain of 1.58		
Test Antenna Model	¼ wave monopole over ground plane (ASPA1415)		
PTT Factor	50% = 0.5		
Total Adjustment Factor	X 0.79		

Pre-test	Power <sub>[W EIRP]</sub> = P <sub>[conducted]</sub> x G <sub>[antenna]</sub>	=	45 X 0.79 = 36.66
Calculations	Limit <sub>[mW/cm<sup>2</sup>]</sub>	=	0.25 / 0.28 / 0.31
	Limit <sub>[W/m<sup>2</sup>]</sub> = 10 x Limit <sub>[mW/cm<sup>2</sup>]</sub>	=	2.50 / 2.80 / 3.10
	R <sub>[m]</sub> = [P <sub>[W EIRP]</sub> / (4π x Limit <sub>[W/m<sup>2</sup>]</sub> )] <sup>1/2</sup>	=	1.06 / 1.00 / 0.96

Results at tested distances	Probe Height, m	Power Density, mW/cm <sup>2</sup>		
		Freq. 380.000 MHz Distance 100 cm	Freq. 425.000MHz Distance 100 cm	Freq. 470.000MHz Distance 100 cm
	2.0	0.139	0.130	0.122
	1.8	0.173	0.165	0.158
	1.6	0.197	0.180	0.176
	1.4	0.223	0.205	0.192
	1.2	0.220	0.210	0.199
	1.0	0.201	0.197	0.203
	0.8	0.187	0.177	0.184
	0.6	0.162	0.167	0.163
	0.4	0.145	0.150	0.141
	0.2	0.111	0.125	0.129

Power Density Calculations: The measured power density readings were summed and the results divided by the number of readings to calculate the average.

	380 MHz	425 MHz	470 MHz
Whole body average (0.2 - 0.8 m, mW/cm <sup>2</sup> ) =	0.176	0.171	0.167
Lower body average (0.2 - 0.8 m, mW/cm <sup>2</sup> ) =	0.151	0.155	0.154
Upper body average (1.0 - 2.0 m, mW/cm <sup>2</sup> ) =	0.192	0.181	0.175



Performed By:  
END OF TEST REPORT

David E. Lee, Lab Manager

(The following will be placed in the Instruction Manual)

### **Mandatory Safety Instructions to Installers & Users**

Use only manufacturer or dealer supplied antenna.

**Antenna Minimum Safe Distance:** 100cm (1m).

Antenna Gain: 0dB referenced to a dipole (0dBd), 2.15dB referenced to isotropic (2.15dBi)

The Federal Communications Commission has adopted a safety standard for human exposure to RF (Radio Frequency) energy, which is below the OSHA (Occupational Safety and Health Act) limits.

**Antenna Mounting:** The antenna supplied by the manufacturer or radio dealer must not be mounted at a location such that during radio transmission, any person or persons can come closer than the above indicated minimum safe distance to the antenna i.e. **100cm (1m)**.

To comply with current FCC RF Exposure limits, the antenna must be installed at or exceeding the minimum safe distance shown above, and in accordance with the requirements of the antenna manufacturer or supplier.

**Base Station Installation:** The antenna should be fixed-mounted on an outdoor permanent structure. RF Exposure compliance must be addressed at the time of installation.

**Antenna Substitution:** Do not substitute any antenna for the one supplied or recommended by the manufacturer or radio dealer. You may be exposing person or persons to excess radio frequency radiation. You may contact your radio dealer or the manufacturer for further instructions.

**Warning:** Maintain a separation distance from the antenna to a person(s) of at least **100cm (1m)**.

You, as the qualified end-user of this radio device must control the exposure conditions of bystanders to ensure the minimum separation distance (above) is maintained between the antenna and nearby persons for satisfying RF Exposure compliance. The operation of this transmitter must satisfy the requirements of Occupational/Controlled Exposure Environment, for work-related use. Transmit only when person(s) are at least the minimum distance from the properly installed, externally mounted antenna.

**Testimonial  
and  
Statement of Certification**

**This is to certify that:**

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



David E. Lee,  
Compliance Test Manager