Notes:

- 1) Material: Black Text on White Polyester or equivalent with Permanent adhesive, must meet UL Rub test requirements
- 2)The serial number will be of the Format DDDY-XXXXXX-NNNN where:
- DDD = the Julian date of the day manufacture. Example January 1 is 001, Feb 1 is 032, December 31 = 365. Tolerance = +/- 3 days Y= the significant digit of the Year of manufacture. Example 2010 = 0, 2011=1, 2017=7.

XXXXXX= the exact Model Number of the Product. (MG8702)

= a sequential number from 0001 to 9999 that indicates the number of the unit produced of that type, on that day.

- 3) ZZZZZZZSSSS represents the MAC Address.
- 4) Default SSID to be "MOTOSSSS" where SSSS is the last 4 digits of the CM MAC.
- 5) Wireless Security Key/Password "Word1Word2nnn" is constructed as a randomly chosen word from the Zoom "Friendly Passphrase" file's adjective column (Word1), a randomly chosen word from the noun column (Word2), and a randomly selected 3-digit number "nnn" that cannot contain a 0 or a 1 (must use only digits 2,3,4,5,6,7,8,9). For example, "PlasticBarn352".
- 6) Add Code 128 barcodes to empty space shown in 4 locations: under WiFi Network SSID, WiFi Password, S/N, and CM MAC fields. The barcode content is to contain the same unique per-unit data as the field above it, not including "S/N:" or "CM MAC:".
- 7) All Code 128 barcodes should fit the available space, minimum height is 4 mm
- 8) Add QR code image in location as shown by example below, size 20mmx20mm. QR code content to be as follows:

WIFI:T:WPA2;S:MOTOSSSS;P:word1word2nnn;;DEVICE:M:ZZZZZZZZSSSS;S:DDDY-MG8702-####;T:MG8702;;

167mm

Where above text in red is static, always included exactly as shown.

The above text in blue is variable and shall be as described in the above notes 2, 3, 4 and 5.

9) Label Size is 167 mm x 67 mm, three 1mm radiused corners and one C2.2mm wedge-cut corner as shown



motorola

MTRLC LLC motorolanetwork.com



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not conditions: (1) I his device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: 2AF5PMG8702

DOCSIS 3.1 Cable Gateway

Default WiFi Settings

WiFi Network (SSID):

MOTO373A



WiFi Password:

GreenBird583



Model: MG8702

Power: +12VDC === 3.5A


Router Configuration IP Address: 192.168.0.1

User Name: admin Password: motorola

S/N: 2039-MG8702-2495



CM MAC: 0040364E373A





67mm

Made in China to MTRLC LLC's Specifications

C2.2 mm wedge cut

1mm radius 3 places

PROPRIETARY AND CONFIDENTIAL			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	7	Zoom Telephonics		
THE INFORMATION			DIMENSIONS ARE IN MM TOLERANCES:	DRAWN			99 High Street, Boston, MA 02110 USA			
CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ZOOM Telephonics, Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ZOOM Telephonics, Inc IS PROHIBITED.			FRACTIONAL +/-	CHECKED			TITLE:			
			ANGULAR: MACH +/- BEND +/- TWO PLACE DECIMAL	ENG APPR.			Labe	Label, MG8702 Compliar		
			+/-	MFG APPR.			Pre-Production Version			
			THREE PLACE DECIMAL +/-	Q.A.						
			INTERPRET GEOMETRIC	COMMENTS:			SIZE	DWG. NO.	REV	
			TOLERANCING PER: MATERIAL:				Α	364XX-1	-1 P0	
	NEXT ASSY	USED ON	FINISH:							
		-								

