

FCC

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Rugged Tablet PC

ISSUED TO
Winmate Communication INC.

9F, No. 111-6, Shing-De Rd., San-Chung Dist, New Taipei 24158,
Taiwan, R. O. C.



Tested by:

Gao Shaodong

(Engineer)


Date Jun. 17, 2016

Approved by:

Wei Yanguan

(Chief Engineer)

Date Jun. 17, 2016



Report No.: BL-SZ1640251-602

EUT Type: Rugged Tablet PC

Model Name: MMX-070, FlexCommand-7,
M700xxxxxxxxxx(The "X" can be 0-9,
A-Z, a-z , or blank for marketing purpose)

Brand Name: Winmate

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: PX9M700

Test conclusion: Pass

Test Date: Jun. 1, 2016 ~ Jun. 7, 2016

Date of Issue: Jun. 17, 2016

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Jun. 17, 2016	Initial Issue

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	6
1.1	Identification of the Testing Laboratory	6
1.2	Identification of the Responsible Testing Location	6
1.3	Laboratory Condition	6
1.4	Announce	6
2	PRODUCT INFORMATION	7
2.1	Applicant Information	7
2.2	Manufacturer Information	7
2.3	Factory Information	7
2.4	General Description for Equipment under Test (EUT)	7
2.5	Ancillary Equipment	7
2.6	Technical Information	8
2.7	Additional Instructions	8
3	SUMMARY OF TEST RESULTS	10
3.1	Test Standards	10
3.2	Verdict	10
4	GENERAL TEST CONFIGURATIONS	11
4.1	Test Environments	11
4.2	Test Equipment List	11
4.3	Description of Test Setup	12
4.3.1	For Antenna Port Test	12
4.3.2	For AC Power Supply Port Test	12
4.3.3	For Radiated Test (Below 30 MHz)	13
4.3.4	For Radiated Test (30 MHz-1 GHz)	13
4.3.5	For Radiated Test (Above 1 GHz)	14
4.4	Measurement Results Explanation Example	15

4.4.1	For conducted test items:	15
4.4.2	For radiated band edges and spurious emission test:.....	15
5	TEST ITEMS.....	16
5.1	Antenna Requirements.....	16
5.1.1	Standard Applicable	16
5.1.2	Antenna Anti-Replacement Construction	16
5.1.3	Antenna Gain	16
5.2	Number of Hopping Frequency	17
5.2.1	Limit.....	17
5.2.2	Test Setup	17
5.2.3	Test Procedure	17
5.2.4	Test Result	17
5.3	Peak Output Power	18
5.3.1	Test Limit.....	18
5.3.2	Test Setup	18
5.3.3	Test Procedure	18
5.3.4	Test Result	18
5.4	Occupied Bandwidth	19
5.4.1	Limit.....	19
5.4.2	Test Setup	19
5.4.3	Test Procedure	19
5.4.4	Test Result	19
5.5	Carrier Frequency Separation	20
5.5.1	Limit.....	20
5.5.2	Test Setup	20
5.5.3	Test Procedure	20
5.5.4	Test Result	20
5.6	Time of Occupancy (Dwell time)	21
5.6.1	Limit.....	21
5.6.2	Test Setup	21
5.6.3	Test Procedure	21
5.6.4	Test Result	21

5.7	Conducted Spurious Emission & Authorized-band band-edge	22
5.7.1	Limit.....	22
5.7.2	Test Setup	22
5.7.3	Test Procedure	22
5.7.4	Test Result	22
5.8	Conducted Emission	23
5.8.1	Limit.....	23
5.8.2	Test Setup	23
5.8.3	Test Procedure	23
5.8.4	Test Result	23
5.9	Radiated Spurious Emission	24
5.9.1	Limit.....	24
5.9.2	Test Setup	24
5.9.3	Test Procedure	24
5.9.4	Test Result	25
5.10	Band Edge (Restricted-band band-edge).....	26
5.10.1	Limit.....	26
5.10.2	Test Setup	26
5.10.3	Test Procedure	26
5.10.4	Test Result	26
ANNEX A	TEST RESULT	27
A.1	Number of Hopping Frequency	27
A.2	Peak Output Power	29
A.3	20 dB and 99% bandwidth	35
A.4	Hopping Frequency Separation.....	39
A.5	Average Time of Occupancy	41
A.6	Conducted Spurious Emissions & Authorized-band band-edge	45
A.7	Conducted Emissions.....	51
A.8	Radiated Emission	53
A.9	Band Edge (Restricted-band band-edge).....	62
ANNEX B	TEST SETUP PHOTOS	67
ANNEX C	EUT EXTERNAL PHOTOS	67

ANNEX D	EUT INTERNAL PHOTOS	67
---------	---------------------------	----

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v3.1.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Winmate Communication INC.
Address	9F, No. 111-6, Shing-De Rd., San-Chung Dist, New Taipei 24158, Taiwan, R. O. C.

2.2 Manufacturer Information

Manufacturer	Winmate Communication INC.
Address	9F, No. 111-6, Shing-De Rd., San-Chung Dist, New Taipei 24158, Taiwan, R. O. C.

2.3 Factory Information

Factory	Winmate Communication INC.
Address	9F, No. 111-6, Shing-De Rd., San-Chung Dist, New Taipei 24158, Taiwan, R. O. C.

2.4 General Description for Equipment under Test (EUT)

EUT Type	Rugged Tablet PC
Model Name Under Test	M700xxxxxxxxxxx
Series Model Name	MMX-070, FlexCommand-7, M700xxxxxxxxxxx(The "X" can be 0-9, A-Z, a-z, or blank for marketing purpose)
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name which for the different marketing sales area
Hardware Version	MK8-200
Software Version	151110
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Bluetooth 3.0, WIFI 802.11b, 802.11g and 802.11n (HT20/40), GPS

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	Winmate
	Model No.	M700DT4
	Serial No.	N/A
	Capacitance	5300 mAh
	Rated Voltage	3.7 V
	Limit Charge Voltage	4.2 V
Ancillary Equipment 2	Charger 1	
	Brand Name	ENG
	Model Name	3A-182WP05
	Rated Input	100-240 V ~, 50/60 Hz, 600 mA

	Rated Output	5 V $\pm$, 3000 mA
--	--------------	---------------------

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Transfer Rate	1 Mbps, 2 Mbps, 3 Mbps
Frequency Range	The frequency range used is 2402 MHz – 2480 MHz; The frequency block is 2400 MHz to 2483.5 MHz.
Number of channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz).
Antenna Type	PCB Antenna
Antenna Gain	1 dBi (All involve the antenna gain test item, has been included in the final results)
About the Product	The equipment is Rugged Tablet PC, it contains Bluetooth 3.0 at 2.4 GHz ISM band. Only the Bluetooth 3.0 was tested in this report.

2.7 Additional Instructions


EUT Software Settings:

Mode	☒ Bluetooth test mode loop back enabled. EUT is controlled over CBT / CMU.
------	---


Power level setup in software		
Test Software Version	Bluetooth Signaling – V3.5.20 – Base V3.5.11	
Mode	Channel	Soft Set
DH5	ALL	TX LEVEL is built-in set parameters and cannot be changed and selected.
2DH5	ALL	
3DH5	ALL	

Run Software:


DH5



2DH5



3DH5



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-14 Edition)	Miscellaneous Wireless Communications Services
2	FCC PUBLIC NOTICE DA 00-705 (Mar. 30, 2000)	Filling and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note 1}
2	Number of Hopping Frequency	15.247(a)	ANNEX A.1	Pass
3	Peak Output Power	15.247(b)	ANNEX A.2	Pass
4	Occupied Bandwidth	15.247(a)	ANNEX A.3	Pass
5	Carrier Frequency Separation	15.247(a)	ANNEX A.4	Pass
6	Time of Occupancy (Dwell time)	15.247(a)	ANNEX A.5	Pass
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	ANNEX A.6	Pass
8	Conducted Emission	15.207	ANNEX A.7	Pass
9	Radiated Spurious Emission	15.209 15.247(d)	ANNEX A.8	Pass
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	ANNEX A.9	Pass
Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.				
Note 2: GFSK, $\pi/4$ -DQPSK and 8-DPSK are tested, but only GFSK and 8-DPSK are shown in this report (except Peak Output Power).				

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:


Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	-20℃ to +60℃
Working Voltage of the EUT	NV (Normal Voltage)	3.7V from battery/ 5V from Adapter

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2015.07.16	2016.07.15
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2015.07.16	2016.07.15
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2015.07.01	2016.06.30
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2015.07.16	2016.07.15
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2015.10.15	2016.10.14
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2015.07.14	2016.07.13
LISN	SCHWARZBECK	NSLK 8127	8127-687	2015.07.14	2016.07.13
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2015.07.16	2016.07.15
Power Splitter	KMW	DCPD-LDC	1305003215	2015.07.01	2016.06.30
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2015.07.21	2016.07.20
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	18141664	2015.07.17	2016.07.16
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2015.08.07	2016.08.06
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2017.02.27
Shielded Enclosure	ChangNing	CN-130701	130703	--	--


4.3 Description of Test Setup

4.3.1 For Antenna Port Test




(Diagram 1)

4.3.2 For AC Power Supply Port Test




(Diagram 2)

4.3.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.3.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.3.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.4 Measurement Results Explanation Example

4.4.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.4.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) = $20 * \log (\text{Duty cycle})$.

Duty cycle = on time / 100 milliseconds

On time = dwell time * hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) = $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)
= $45.61 + (-21.21) = 24.4 \text{ (dBuV/m)}$

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.


If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	The antenna is welded on the mainboard, can't be replaced by the consumer

PCB Antenna

Reference Documents	Item
Photo	

RF Chip

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequency

5.2.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.2.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Peak Output Power

5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems that operates in the 2400 MHz to 2483.5 MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1 Watt.

5.3.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

5.4.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The average time of occupancy on any channel within the Period can be calculated with formulas:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.6.4 Test Result

Please refer to ANNEX A.5

5.7 Conducted Spurious Emission & Authorized-band band-edge

5.7.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.3.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V/m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V/m}@3\text{m}$ (PK).

5.9.2 Test Setup

See section 4.3.3 to 4.3.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Please refer to ANNEX A.8.

5.10 Band Edge (Restricted-band band-edge)

5.10.1 Limit

FCC §15.209&15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.10.2 Test Setup

See section 4.3.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak /AV

Trace = max hold

Allow the trace to stabilize.

$E \text{ [dB}\mu\text{V/m]} = UR + AT + A\text{Factor [dB]}; AT = LCable \text{ loss [dB]} - G\text{preamp [dB]}$

AT: Total correction Factor except Antenna

UR: Receiver Reading

Gpreamp: Preamplifier Gain

AFactor: Antenna Factor at 3m

5.10.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power

Test Data

GFSK Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	6.67	4.65	30	1000	Pass
Middle	5.76	3.77			Pass
High	5.15	3.28			Pass

π/4-DQPSK Mode:


Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	5.94	3.93	30	1000	Pass
Middle	5.16	3.28			Pass
High	4.57	2.86			Pass

8-DPSK Mode:


Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	6.07	4.05	30	1000	Pass
Middle	5.30	3.39			Pass
High	4.75	2.99			Pass

Test plots


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL




GFSK HIGH CHANNEL




1/4-DQPSK LOW CHANNEL




□/4-DQPSK MIDDLE CHANNEL




□/4-DQPSK HIGH CHANNEL




8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



A.3 20 dB and 99% bandwidth

Test Data

GFSK Mode:

Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.970	0.884
Middle	0.966	0.883
High	0.969	0.886

8-DPSK Mode:


Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.304	1.158
Middle	1.303	1.159
High	1.303	1.159

Test plots


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL




GFSK HIGH CHANNEL




8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL




A.4 Hopping Frequency Separation

Test Data


Note: The systems operate with an output power no greater than 125 mw, The data provided in the section A.2.

Mode	Frequency separation (MHz)	Max 20 dB Bandwidth (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Verdict
GFSK	1.000	0.970	0.647	Pass
8-DPSK	1.005	1.304	0.869	Pass

Test Plots



8-DPSK



A.5 Average Time of Occupancy

Test Data

GFSK Mode:


DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.360	115.204	0.4	Pass
DH 3	1.613	258.088	0.4	Pass
DH 5	2.847	303.689	0.4	Pass

8-DPSK Mode:


DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.370	118.404	0.4	Pass
DH 3	1.600	256.008	0.4	Pass
DH 5	2.867	305.823	0.4	Pass

Test Plots


GFSK DH1




GFSK DH3




GFSK DH5




8-DPSK DH1



8-DPSK DH3



8-DPSK DH5



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-47.45	6.5	-13.50	Pass
Middle	-47.52	5.44	-14.56	Pass
High	-49.24	4.67	-15.33	Pass

8-DPSK Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-48.27	4.86	-15.14	Pass
Middle	-48.31	4.05	-15.95	Pass
High	-48.53	3.53	-16.47	Pass

Hopping Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-48.12	7.41	-12.59	Pass
8-DPSK	-46.84	2.64	-17.36	Pass

Test Plots


GFSK LOW CHANNEL , BAND EDGE




GFSK LOW CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




GFSK High CHANNEL , BAND EDGE




GFSK High CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




GFSK High CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




8-DPSK LOW CHANNEL , BAND EDGE




8-DPSK LOW CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




8-DPSK LOW CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




8-DPSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




8-DPSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




8-DPSK High CHANNEL , BAND EDGE




8-DPSK High CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




8-DPSK High CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




GFSK Hopping BAND EDGE (LOW)




GFSK Hopping BAND EDGE (HIGH)




GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz




GFSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz




8-DPSK Hopping BAND EDGE (LOW)




8-DPSK Hopping BAND EDGE (HIGH)



8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz




A.7 Conducted Emissions

Note 1: The EUT is working in the Normal link mode.

Note 2: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.17	53.0	11.00	65.4	12.40	Peak	L Line	Pass
1**	0.17	39.0	11.00	55.4	16.40	AV	L Line	Pass
2	0.54	36.6	11.00	56.0	19.40	Peak	L Line	Pass
2**	0.54	27.6	11.00	46.0	18.40	AV	L Line	Pass
3	1.13	38.4	11.00	56.0	17.60	Peak	L Line	Pass
3**	1.13	27.2	11.00	46.0	18.80	AV	L Line	Pass
4	2.52	38.4	11.00	56.0	17.60	Peak	L Line	Pass
4**	2.52	28.1	11.00	46.0	17.90	AV	L Line	Pass
5	5.23	35.2	11.00	60.0	24.80	Peak	L Line	Pass
5**	5.23	24.3	11.00	50.0	25.70	AV	L Line	Pass
6	21.70	39.5	11.00	60.0	20.50	Peak	L Line	Pass
6**	21.70	28.1	11.00	50.0	21.90	AV	L Line	Pass

PHASE N




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.17	52.6	11.00	65.5	12.90	Peak	N Line	Pass
1**	0.17	42.5	11.00	55.5	13.00	AV	N Line	Pass
2	0.28	42.3	11.00	62.2	19.90	Peak	N Line	Pass
2**	0.28	33.2	11.00	52.2	19.00	AV	N Line	Pass
3	0.55	38.7	11.00	56.0	17.30	Peak	N Line	Pass
3**	0.55	26.3	11.00	46.0	19.70	AV	N Line	Pass
4	2.19	38.9	11.00	56.0	17.10	Peak	N Line	Pass
4**	2.19	28.5	11.00	46.0	17.50	AV	N Line	Pass
5	8.32	38.1	11.00	60.0	21.90	Peak	N Line	Pass
5**	8.32	26.1	11.00	50.0	23.90	AV	N Line	Pass
6	22.13	37.5	11.00	60.0	22.50	Peak	N Line	Pass
6**	22.13	26.1	11.00	50.0	23.90	AV	N Line	Pass


A.8 Radiated Emission

Duty cycle correction factor for average measurement.

DH5 on time/100 ms(One Pulses) Plot on Channel 39



DH5 on time/100 ms(Count Pulse) Plot on Channel 39



Note:

1. Duty cycle = on time/100 milliseconds = $3 \times 2.867 / 100 = 8.60 \%$
2. Duty cycle correction factor = $20 \times \log(\text{Duty cycle}) = -21.31 \text{ dB}$
3. DH5 has the highest duty cycle and is reported.

Note 1: The symbol of “--” in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The EUT is working in the Normal link mode below 1 GHz.

Test Data and Plots


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	56.18	31.41	-19.34	40.0	8.59	Peak	329.20	100	Vertical	N/A
1**	56.18	17.00	-19.34	40.0	23.00	QP	329.20	100	Vertical	Pass
2	90.37	30.04	-21.82	43.5	13.46	Peak	232.90	100	Vertical	N/A
2**	90.37	21.00	-21.82	43.5	22.50	QP	232.90	100	Vertical	Pass
3	150.49	35.86	-23.46	43.5	7.64	Peak	329.20	100	Vertical	N/A
3**	150.49	22.50	-23.46	43.5	21.00	QP	329.20	100	Vertical	Pass
4	259.83	31.41	-18.68	46.0	14.59	Peak	355.30	100	Vertical	N/A
4**	259.83	23.00	-18.68	46.0	23.00	QP	355.30	100	Vertical	Pass
5	519.97	34.29	-12.79	46.0	11.71	Peak	142.50	100	Vertical	N/A
5**	519.97	23.89	-12.79	46.0	22.11	QP	142.50	100	Vertical	Pass
6	909.81	40.01	-5.49	46.0	5.99	Peak	334.10	100	Vertical	N/A
6**	909.81	22.76	-5.49	46.0	23.24	QP	334.10	100	Vertical	Pass

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	91.82	39.15	-21.48	43.5	4.35	Peak	304.50	100	Horizontal	N/A
1**	91.82	22.76	-21.48	43.5	20.74	QP	304.50	100	Horizontal	Pass
2	129.89	33.68	-23.25	43.5	9.82	Peak	0.30	100	Horizontal	N/A
2**	129.89	21.15	-23.25	43.5	22.35	QP	0.30	100	Horizontal	Pass
3	194.86	32.85	-20.67	43.5	10.65	Peak	4.50	100	Horizontal	N/A
3**	194.86	20.99	-20.67	43.5	22.51	QP	4.50	100	Horizontal	Pass
4	324.81	34.56	-16.91	46.0	11.44	Peak	80.60	100	Horizontal	N/A
4**	324.81	23.09	-16.91	46.0	22.91	QP	80.60	100	Horizontal	Pass
5	455.00	36.00	-14.39	46.0	10.00	Peak	154.50	100	Horizontal	N/A
5**	455.00	22.69	-14.39	46.0	23.31	QP	154.50	100	Horizontal	Pass
6	909.81	41.50	-5.49	46.0	4.50	Peak	267.60	100	Horizontal	N/A
6**	909.81	22.95	-5.49	46.0	23.05	QP	267.60	100	Horizontal	Pass

Note: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Test Data and Plots (1 GHz ~ 10th Harmonic)

GFSK LOW CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2402.15	94.95	-0.34	74	-20.95	Peak	307.8	150	Vertical	N/A
1**	2402.15	73.64	-0.34	54	-19.64	AV	307.8	150	Vertical	Pass
2	2857.04	51.62	2.03	74	22.38	Peak	339.6	150	Vertical	Pass
3	5887.53	51.89	15.62	74	22.11	Peak	3	150	Vertical	Pass
4	7830.70	42.93	14.95	74	31.07	Peak	345.3	150	Vertical	Pass
5	16046.59	44.32	11.20	74	29.68	Peak	205.2	150	Vertical	Pass
6	19559.07	45.06	10.45	74	28.94	Peak	163.9	150	Vertical	Pass

GFSK LOW CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2402.15	104.04	-0.34	74	-30.04	Peak	14.8	150	Horizontal	N/A
1**	2402.15	82.73	-0.34	54	-28.73	AV	14.8	150	Horizontal	Pass
2	2710.07	50.78	1.51	74	23.23	Peak	134.7	150	Horizontal	Pass
3	5436.14	52.04	14.81	74	21.97	Peak	307.7	150	Horizontal	Pass
4	11402.25	44.94	16.70	74	29.06	Peak	302.3	150	Horizontal	Pass
5	17554.49	44.46	9.58	74	29.54	Peak	94.4	150	Horizontal	Pass
6	18074.46	46.49	8.93	74	27.51	Peak	196.3	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2441.14	96.45	-0.38	74	-22.45	Peak	232.5	150	Vertical	N/A
1**	2441.14	75.14	-0.38	54	-21.14	AV	232.5	150	Vertical	Pass
2	2861.04	50.71	1.97	74	23.29	Peak	43.8	150	Vertical	Pass
3	4784.55	52.38	13.65	74	21.62	Peak	58.8	150	Vertical	Pass
4	8830.28	46.50	20.08	74	27.50	Peak	49.8	150	Vertical	Pass
5	16940.93	45.97	11.59	74	28.03	Peak	124.7	150	Vertical	Pass
6	18698.42	49.88	10.69	74	24.12	Peak	144.8	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2441.14	103.96	-0.38	74	-29.96	Peak	146.5	150	Horizontal	N/A
1**	2441.14	82.65	-0.38	54	-28.65	AV	146.5	150	Horizontal	Pass
2	2838.04	50.61	1.83	74	23.39	Peak	176.4	150	Horizontal	Pass
3	5966.26	52.22	15.61	74	21.78	Peak	57.6	150	Horizontal	Pass
4	10638.52	44.43	15.07	74	29.57	Peak	270.5	150	Horizontal	Pass
5	14424.29	44.15	11.88	74	29.85	Peak	145.7	150	Horizontal	Pass
6	18833.61	45.96	9.70	74	28.04	Peak	52.7	150	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480.13	95.29	-0.60	74	-21.29	Peak	230.5	150	Vertical	N/A
1**	2480.13	73.98	-0.60	54	-19.98	AV	230.5	150	Vertical	Pass
2	2864.03	51.03	2.06	74	22.97	Peak	303.9	150	Vertical	Pass
3	5965.51	52.35	15.61	74	21.65	Peak	42.7	150	Vertical	Pass
4	10762.06	44.59	15.15	74	29.41	Peak	51	150	Vertical	Pass
5	17263.31	46.92	8.70	74	27.08	Peak	267.1	150	Vertical	Pass
6	24620.63	48.51	11.69	74	25.49	Peak	217	150	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480.13	104.40	-0.60	74	-30.40	Peak	117.9	150	Horizontal	N/A
1**	2480.13	83.09	-0.60	54	-29.09	AV	117.9	150	Horizontal	Pass
2	2761.56	51.41	1.91	74	22.59	Peak	228	150	Horizontal	Pass
3	4693.08	52.25	13.24	74	21.75	Peak	287.8	150	Horizontal	Pass
4	6213.39	46.80	14.95	74	27.20	Peak	81.2	150	Horizontal	Pass
5	15401.83	45.36	9.43	74	28.64	Peak	153.9	150	Horizontal	Pass
6	22504.16	43.49	11.39	74	30.51	Peak	138.9	150	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2402.15	93.48	-0.34	74	-19.48	Peak	121.5	150	Vertical	N/A
1**	2402.15	72.17	-0.34	54	-18.17	AV	121.5	150	Vertical	Pass
2	2730.57	50.65	1.82	74	23.36	Peak	14.4	150	Vertical	Pass
3	4711.82	52.36	13.40	74	21.64	Peak	317	150	Vertical	Pass
4	8392.26	46.03	20.00	74	27.97	Peak	313.3	150	Vertical	Pass
5	14767.47	49.31	20.72	74	24.69	Peak	261.2	150	Vertical	Pass
6	22963.39	47.51	11.27	74	26.49	Peak	129.1	150	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2401.65	102.42	-0.27	74	-28.42	Peak	182.2	150	Horizontal	N/A
1**	2401.65	81.11	-0.27	54	-27.11	AV	182.2	150	Horizontal	Pass
2	2899.03	50.64	2.61	74	23.36	Peak	250.5	150	Horizontal	Pass
3	5943.76	51.53	15.87	74	22.47	Peak	269.4	150	Horizontal	Pass
4	10604.83	47.22	18.29	74	26.78	Peak	167.3	150	Horizontal	Pass
5	12480.45	43.91	10.80	74	30.09	Peak	120.7	150	Horizontal	Pass
6	23712.15	46.76	10.96	74	27.24	Peak	208.8	150	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2441.14	94.89	-0.38	74	-20.89	Peak	256.1	150	Vertical	N/A
1**	2441.14	73.58	-0.38	54	-19.58	AV	256.1	150	Vertical	Pass
2	2755.06	51.19	1.76	74	22.81	Peak	294.6	150	Vertical	Pass
3	5961.01	52.21	15.71	74	21.79	Peak	114.3	150	Vertical	Pass
4	11099.00	41.93	17.01	74	32.07	Peak	246.9	150	Vertical	Pass
5	13145.18	45.46	11.62	74	28.54	Peak	296.2	150	Vertical	Pass
6	23951.75	44.69	11.19	74	29.31	Peak	162.7	150	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2441.14	102.89	-0.38	74	-28.89	Peak	40.1	150	Horizontal	N/A
1**	2441.14	81.58	-0.38	54	-27.58	AV	40.1	150	Horizontal	Pass
2	2795.05	51.62	1.75	74	22.38	Peak	220.3	150	Horizontal	Pass
3	5973.76	52.70	15.67	74	21.30	Peak	270.7	150	Horizontal	Pass
4	9953.41	43.69	16.75	74	30.31	Peak	211.3	150	Horizontal	Pass
5	17377.70	47.11	9.03	74	26.89	Peak	139.6	150	Horizontal	Pass
6	20257.90	48.39	13.64	74	25.61	Peak	336.3	150	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480.13	93.70	-0.60	74	-19.70	Peak	217.2	150	Vertical	N/A
1**	2480.13	72.39	-0.60	54	-18.39	AV	217.2	150	Vertical	Pass
2	2863.03	50.62	2.04	74	23.38	Peak	269.1	150	Vertical	Pass
3	5973.01	51.45	15.65	74	22.55	Peak	27.4	150	Vertical	Pass
4	11548.25	49.85	16.89	74	24.15	Peak	22.4	150	Vertical	Pass
5	16119.38	43.83	9.29	74	30.17	Peak	258.9	150	Vertical	Pass
6	21096.51	49.21	9.95	74	24.79	Peak	270.8	150	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480.13	102.96	-0.60	74	-28.96	Peak	87.8	150	Horizontal	N/A
1**	2480.13	81.65	-0.60	54	-27.65	AV	87.8	150	Horizontal	Pass
2	2823.54	50.83	2.07	74	23.17	Peak	347.3	150	Horizontal	Pass
3	4721.57	52.44	13.58	74	21.56	Peak	172.9	150	Horizontal	Pass
4	10997.92	42.89	17.40	74	31.11	Peak	313.4	150	Horizontal	Pass
5	16722.55	44.34	9.25	74	29.67	Peak	70.1	150	Horizontal	Pass
6	21575.71	45.11	13.42	74	28.89	Peak	243.8	150	Horizontal	Pass

Hopping Mode:

GFSK MODE 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2452.14	96.37	-0.50	74	-22.37	Peak	129.5	150	Vertical	N/A
1**	2452.14	75.06	-0.50	54	-21.06	AV	129.5	150	Vertical	Pass
2	2818.55	50.41	2.14	74	23.59	Peak	124.3	150	Vertical	Pass
3	5964.01	53.05	15.67	74	20.96	Peak	114.3	150	Vertical	N/A
3**	5964.01	31.74	15.67	54	22.26	AV	114.3	150	Vertical	Pass
4	6584.03	48.28	19.66	74	25.72	Peak	16.2	150	Vertical	Pass
5	12087.35	43.41	9.04	74	30.59	Peak	335.2	150	Vertical	Pass
6	24900.17	48.78	11.91	74	25.22	Peak	196.4	150	Vertical	Pass

GFSK MODE 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2480.13	104.26	-0.60	74	-30.26	Peak	249.7	150	Horizontal	N/A
1**	2480.13	82.95	-0.60	54	-28.95	AV	249.7	150	Horizontal	Pass
2	2794.55	50.91	1.78	74	23.09	Peak	60.9	150	Horizontal	Pass
3	4864.03	52.12	13.57	74	21.88	Peak	148.3	150	Horizontal	Pass
4	10514.98	45.96	15.10	74	28.04	Peak	13.5	150	Horizontal	Pass
5	12671.38	43.48	9.62	74	30.52	Peak	38.3	150	Horizontal	Pass
6	19209.65	45.99	13.25	74	28.01	Peak	177.8	150	Horizontal	Pass

8-DPSK MODE 1 GHz to 25 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2450.14	95.10	-0.45	74	-21.10	Peak	341.3	150	Vertical	N/A
1**	2450.14	73.79	-0.45	54	-19.79	AV	341.3	150	Vertical	Pass
2	2754.06	50.54	1.82	74	23.46	Peak	356.6	150	Vertical	Pass
3	5994.00	51.95	15.77	74	22.05	Peak	197.7	150	Vertical	Pass
4	8156.41	42.49	14.76	74	31.51	Peak	274	150	Vertical	Pass
5	15474.63	49.89	9.04	74	24.11	Peak	12	150	Vertical	Pass
6	22004.99	46.56	11.67	74	27.44	Peak	265.2	150	Vertical	Pass

8-DPSK MODE 1 GHz to 25 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2422.14	102.50	-0.21	74	-28.50	Peak	49	150	Horizontal	N/A
1**	2422.14	81.19	-0.21	54	-27.19	AV	49	150	Horizontal	Pass
2	2802.55	50.66	1.63	74	23.34	Peak	228.9	150	Horizontal	Pass
3	5982.00	52.14	15.82	74	21.86	Peak	82.4	150	Horizontal	Pass
4	11301.17	47.36	14.24	74	26.64	Peak	78.8	150	Horizontal	Pass
5	16514.56	45.01	11.44	74	28.99	Peak	55.1	150	Horizontal	Pass
6	19289.52	46.18	9.50	74	27.82	Peak	213.9	150	Horizontal	Pass

A.9 Band Edge (Restricted-band band-edge)

Test Data

Note 1: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note 2: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note 3: The average levels were calculated from the peak level corrected with duty cycle correction factor (21.31 dB) derived from $20\log(\text{dwell time}/100 \text{ ms})$.

For example: Average level = 57.08 dBuV/m – 21.31(dB) = 35.77dBuV/m.


Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390	57.08	74	16.92	PEAK	Pass
		2390	35.77	54	18.23	AVERAGE	Pass
GFSK	HIGH	2483.5	64.16	74	9.84	PEAK	Pass
		2483.5	42.85	54	11.15	AVERAGE	Pass
8-DPSK	Low	2390	57.14	74	16.86	PEAK	Pass
		2390	35.83	54	18.17	AVERAGE	Pass
8-DPSK	HIGH	2483.5	58.80	74	15.20	PEAK	Pass
		2483.5	37.49	54	16.51	AVERAGE	Pass
GFSK(Hopping)	Low	2390	57.00	74	17.00	PEAK	Pass
		2390	35.69	54	18.31	AVERAGE	Pass
GFSK(Hopping)	HIGH	2483.5	58.18	74	15.82	PEAK	Pass
		2483.5	36.87	54	17.13	AVERAGE	Pass
8-DPSK (Hopping)	Low	2390	57.11	74	16.89	PEAK	Pass
		2390	35.80	54	18.20	AVERAGE	Pass
8-DPSK (Hopping)	HIGH	2483.5	57.44	74	16.56	PEAK	Pass
		2483.5	36.13	54	17.87	AVERAGE	Pass

Test Plots


GFSK LOW CHANNEL , PEAK




GFSK HIGH CHANNEL , PEAK



8-DPSK LOW CHANNEL , PEAK




8-DPSK HIGH CHANNEL , PEAK




Hopping Mode:


GFSK LOW FREQUENCY BAND, PEAK




GFSK HIGH FREQUENCY BAND, PEAK



8-DPSK LOW FREQUENCY BAND, PEAK



8-DPSK HIGH FREQUENCY BAND, PEAK



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ1640251-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ1640251-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ1640251-AI.PDF”.

--END OF REPORT--