

NR Band n66

40 MHz QPSK ANT B	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 4791547073									
	Date: 2024-11-29									
	Test Engineer: 26087									
	Configuration: EUT / AC Adapter, X-Position									
	Location: Chamber 1									
	Mode: 5G NR_QPSK NR n66 Harmonics, 40MHz Bandwidth									
	Test Votage: AC 120 V, 60 Hz									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 1730MHz									
	3460.00	-8.6	V	3.0	44.0	1.0	-51.5	-13.0	-38.5	
	5190.00	-7.4	V	3.0	44.6	1.0	-51.0	-13.0	-38.0	
	6920.00	-4.3	V	3.0	45.1	1.0	-48.3	-13.0	-35.3	
	3460.00	-8.6	H	3.0	44.0	1.0	-51.5	-13.0	-38.5	
	5190.00	-7.5	H	3.0	44.6	1.0	-51.1	-13.0	-38.1	
	6920.00	-4.3	H	3.0	45.1	1.0	-48.4	-13.0	-35.4	
	Mid Ch, 1745MHz									
	3490.00	-8.4	V	3.0	44.0	1.0	-51.4	-13.0	-38.4	
	5235.00	-7.2	V	3.0	44.6	1.0	-50.8	-13.0	-37.8	
	6980.00	-4.1	V	3.0	45.1	1.0	-48.2	-13.0	-35.2	
3490.00	-8.4	H	3.0	44.0	1.0	-51.4	-13.0	-38.4		
5235.00	-7.2	H	3.0	44.6	1.0	-50.8	-13.0	-37.8		
6980.00	-4.2	H	3.0	45.1	1.0	-48.3	-13.0	-35.3		
High Ch, 1760MHz										
3520.00	-8.1	V	3.0	44.0	1.0	-51.1	-13.0	-38.1		
5280.00	-6.1	V	3.0	44.6	1.0	-49.7	-13.0	-36.7		
7040.00	-3.8	V	3.0	45.1	1.0	-47.9	-13.0	-34.9		
3520.00	-8.1	H	3.0	44.0	1.0	-51.2	-13.0	-38.2		
5280.00	-7.1	H	3.0	44.6	1.0	-50.7	-13.0	-37.7		
7040.00	-3.8	H	3.0	45.1	1.0	-47.9	-13.0	-34.9		
40 MHz QPSK ANT D	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 4791547073									
	Date: 2024-11-20									
	Test Engineer: 24542									
	Configuration: EUT / X-Position									
	Location: Chamber 2									
	Mode: 5G NR_QPSK NR n66 Harmonics, 40MHz Bandwidth									
	Test Votage: AC 120 V, 60 Hz									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 1730MHz									
	3460.00	-8.6	V	3.0	43.0	1.0	-50.5	-13.0	-37.5	
	5190.00	-7.8	V	3.0	43.3	1.0	-50.2	-13.0	-37.2	
	6920.00	-3.2	V	3.0	43.3	1.0	-45.5	-13.0	-32.5	
	3460.00	-8.0	H	3.0	43.0	1.0	-50.0	-13.0	-37.0	
	5190.00	-7.6	H	3.0	43.3	1.0	-49.9	-13.0	-36.9	
	6920.00	-4.6	H	3.0	43.3	1.0	-46.9	-13.0	-33.9	
	Mid Ch, 1745MHz									
	3490.00	-7.4	V	3.0	43.0	1.0	-49.4	-13.0	-36.4	
	5235.00	-7.6	V	3.0	43.3	1.0	-50.0	-13.0	-37.0	
	6980.00	-3.7	V	3.0	43.3	1.0	-46.0	-13.0	-33.0	
3490.00	-8.3	H	3.0	43.0	1.0	-50.2	-13.0	-37.2		
5235.00	-7.5	H	3.0	43.3	1.0	-49.8	-13.0	-36.8		
6980.00	-4.8	H	3.0	43.3	1.0	-47.1	-13.0	-34.1		
High Ch, 1760MHz										
3520.00	-7.8	V	3.0	43.0	1.0	-49.8	-13.0	-36.8		
5280.00	-7.8	V	3.0	43.3	1.0	-50.1	-13.0	-37.1		
7040.00	-4.1	V	3.0	43.3	1.0	-46.4	-13.0	-33.4		
3520.00	-7.7	H	3.0	43.0	1.0	-49.7	-13.0	-36.7		
5280.00	-7.6	H	3.0	43.3	1.0	-49.9	-13.0	-36.9		
7040.00	-4.7	H	3.0	43.3	1.0	-47.0	-13.0	-34.0		

NR Band n77 (3450-3550 MHz)

		UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4791547073 Date: 2024-12-11 Test Engineer: 26087 Configuration: EUT / AC Adapter, X-Position Location: Chamber 2 Mode: 5G NR_QPSK NR n77 LO Harmonics, 90MHz Bandwidth Test Voltage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
90Hz QPSK ANT E		Low Ch, 3495MHz									
		6990.00	-1.1	V	3.0	43.3	1.0	-43.4	-13.0	-30.4	
		10485.00	5.5	V	3.0	41.2	1.0	-34.6	-13.0	-21.6	
		13980.00	8.0	V	3.0	40.0	1.0	-31.1	-13.0	-18.1	
		17475.00	14.5	V	3.0	40.6	1.0	-25.0	-13.0	-12.0	
		6990.00	-2.6	H	3.0	43.3	1.0	-44.9	-13.0	-31.9	
		10485.00	4.3	H	3.0	41.2	1.0	-35.8	-13.0	-22.8	
		13980.00	7.7	H	3.0	40.0	1.0	-31.3	-13.0	-18.3	
		17475.00	14.6	H	3.0	40.6	1.0	-25.0	-13.0	-12.0	
		Mid Ch, 3499.98MHz									
		6999.96	-1.5	V	3.0	43.3	1.0	-43.8	-13.0	-30.8	
		10499.94	5.8	V	3.0	41.1	1.0	-34.4	-13.0	-21.4	
		13999.92	7.9	V	3.0	40.0	1.0	-31.1	-13.0	-18.1	
		17499.90	16.6	V	3.0	40.6	1.0	-23.0	-13.0	-10.0	
		6999.96	-2.9	H	3.0	43.3	1.0	-45.2	-13.0	-32.2	
		10499.94	3.9	H	3.0	41.1	1.0	-36.2	-13.0	-23.2	
		13999.92	8.0	H	3.0	40.0	1.0	-31.1	-13.0	-18.1	
		17499.90	16.4	H	3.0	40.6	1.0	-23.2	-13.0	-10.2	
		High Ch, 3504MHz									
		7008.00	0.0	V	3.0	43.3	1.0	-42.3	-13.0	-29.3	
		10512.00	4.8	V	3.0	41.1	1.0	-35.4	-13.0	-22.4	
		14016.00	10.0	V	3.0	40.0	1.0	-29.1	-13.0	-16.1	
		17520.00	16.0	V	3.0	40.6	1.0	-23.6	-13.0	-10.6	
		7008.00	-0.5	H	3.0	43.3	1.0	-42.8	-13.0	-29.8	
		10512.00	4.6	H	3.0	41.1	1.0	-35.5	-13.0	-22.5	
		14016.00	9.9	H	3.0	40.0	1.0	-29.2	-13.0	-16.2	
		17520.00	15.8	H	3.0	40.6	1.0	-23.8	-13.0	-10.8	
10 MHz QPSK ANT B SRS1		UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4791547073 Date: 2024-12-27 Test Engineer: 24542 Configuration: EUT / AC Adapter, X-Position Location: Chamber 2 Mode: 5G NR n77 LQ(SRS) Harmonics, 10MHz Bandwidth Test Voltage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Ch, 3455MHz									
		6910.00	-5.0	V	3.0	43.3	1.0	-47.3	-13.0	-34.3	
		10365.00	0.5	V	3.0	41.3	1.0	-39.8	-13.0	-26.8	
		13820.00	6.9	V	3.0	40.0	1.0	-32.1	-13.0	-19.1	
		6910.00	-5.1	H	3.0	43.3	1.0	-47.4	-13.0	-34.4	
		10365.00	0.6	H	3.0	41.3	1.0	-39.6	-13.0	-26.6	
		13820.00	7.0	H	3.0	40.0	1.0	-32.0	-13.0	-19.0	
		Mid Ch, 3499.98MHz									
		6999.96	-4.7	V	3.0	43.3	1.0	-47.0	-13.0	-34.0	
		10499.94	0.9	V	3.0	41.1	1.0	-39.2	-13.0	-26.2	
		13999.92	8.3	V	3.0	40.0	1.0	-30.7	-13.0	-17.7	
		6999.96	-4.6	H	3.0	43.3	1.0	-46.8	-13.0	-33.8	
		10499.94	0.9	H	3.0	41.1	1.0	-39.2	-13.0	-26.2	
		13999.92	7.3	H	3.0	40.0	1.0	-31.7	-13.0	-18.7	
		High Ch, 3544MHz									
		7088.00	-4.8	V	3.0	43.2	1.0	-47.0	-13.0	-34.0	
		10632.00	1.1	V	3.0	41.0	1.0	-38.9	-13.0	-25.9	
		14176.00	7.5	V	3.0	40.1	1.0	-31.5	-13.0	-18.5	
		7088.00	-4.8	H	3.0	43.2	1.0	-47.0	-13.0	-34.0	
		10632.00	1.1	H	3.0	41.0	1.0	-38.9	-13.0	-25.9	
		14176.00	7.6	H	3.0	40.1	1.0	-31.4	-13.0	-18.4	

10 MHz QPSK ANT G SRS2	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 4791547073									
	Date: 2024-12-27									
	Test Engineer: 24542									
	Configuration: EUT / AC Adapter, X-Position									
	Location: Chamber 2									
	Mode: 5G NR n77 LO(SRS) Harmonics, 10MHz Bandwidth									
	Test Votage: AC 120 V, 60 Hz									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 3455MHz									
	6910.00	-5.0	V	3.0	43.3	1.0	-47.3	-13.0	-34.3	
	10365.00	0.5	V	3.0	41.3	1.0	-39.8	-13.0	-26.8	
	13820.00	7.0	V	3.0	40.0	1.0	-32.0	-13.0	-19.0	
	6910.00	-5.1	H	3.0	43.3	1.0	-47.4	-13.0	-34.4	
	10365.00	0.5	H	3.0	41.3	1.0	-39.7	-13.0	-26.7	
	13820.00	7.0	H	3.0	40.0	1.0	-32.0	-13.0	-19.0	
	Mid Ch, 3499.98MHz									
	6999.96	-4.6	V	3.0	43.3	1.0	-46.9	-13.0	-33.9	
	10499.94	1.1	V	3.0	41.1	1.0	-39.0	-13.0	-26.0	
	13999.92	7.6	V	3.0	40.0	1.0	-31.4	-13.0	-18.4	
	6999.96	-4.9	H	3.0	43.3	1.0	-47.2	-13.0	-34.2	
	10499.94	1.2	H	3.0	41.1	1.0	-39.0	-13.0	-26.0	
	13999.92	7.6	H	3.0	40.0	1.0	-31.4	-13.0	-18.4	
	High Ch, 3544MHz									
7088.00	-4.5	V	3.0	43.2	1.0	-46.7	-13.0	-33.7		
10632.00	1.2	V	3.0	41.0	1.0	-38.8	-13.0	-25.8		
14176.00	7.9	V	3.0	40.1	1.0	-31.2	-13.0	-18.2		
7088.00	-5.0	H	3.0	43.2	1.0	-47.2	-13.0	-34.2		
10632.00	1.3	H	3.0	41.0	1.0	-38.7	-13.0	-25.7		
14176.00	7.7	H	3.0	40.1	1.0	-31.4	-13.0	-18.4		
20 MHz QPSK ANT H SRS3	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
	Company: Samsung									
	Project #: 4791547073									
	Date: 2024-12-27									
	Test Engineer: 24542									
	Configuration: EUT / AC Adapter, X-Position									
	Location: Chamber 2									
	Mode: 5G NR n77 LO(SRS) Harmonics, 20MHz Bandwidth									
	Test Votage: AC 120 V, 60 Hz									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 3460MHz									
	6920.00	-5.1	V	3.0	43.3	1.0	-47.4	-13.0	-34.4	
	10380.00	0.5	V	3.0	41.2	1.0	-39.7	-13.0	-26.7	
	13840.00	7.2	V	3.0	40.0	1.0	-31.9	-13.0	-18.9	
	6920.00	-5.0	H	3.0	43.3	1.0	-47.3	-13.0	-34.3	
	10380.00	0.6	H	3.0	41.2	1.0	-39.7	-13.0	-26.7	
	13840.00	7.0	H	3.0	40.0	1.0	-32.0	-13.0	-19.0	
	Mid Ch, 3499.98MHz									
	6999.96	-4.9	V	3.0	43.3	1.0	-47.2	-13.0	-34.2	
	10499.94	1.2	V	3.0	41.1	1.0	-39.0	-13.0	-26.0	
	13999.92	7.5	V	3.0	40.0	1.0	-31.5	-13.0	-18.5	
	6999.96	-4.9	H	3.0	43.3	1.0	-47.1	-13.0	-34.1	
	10499.94	1.0	H	3.0	41.1	1.0	-39.2	-13.0	-26.2	
	13999.92	7.4	H	3.0	40.0	1.0	-31.6	-13.0	-18.6	
	High Ch, 3539MHz									
7078.00	-4.7	V	3.0	43.2	1.0	-47.0	-13.0	-34.0		
10617.00	1.0	V	3.0	41.0	1.0	-39.0	-13.0	-26.0		
14156.00	7.4	V	3.0	40.0	1.0	-31.6	-13.0	-18.6		
7078.00	-4.8	H	3.0	43.2	1.0	-47.0	-13.0	-34.0		
10617.00	1.2	H	3.0	41.0	1.0	-38.8	-13.0	-25.8		
14156.00	7.4	H	3.0	40.0	1.0	-31.6	-13.0	-18.6		

NR Band n77(3700-3980 MHz)

40 MHz QPSK ANT E	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
	Company:		Samsung							
	Project #:		4791547073							
	Date:		2024-12-27							
	Test Engineer:		24542							
	Configuration:		EUT / AC Adapter, Z-Position							
	Location:		Chamber 2							
	Mode:		5G NR_QPSK NR n77 UP Harmonics, 40MHz Bandwidth							
	Test Votage:		AC 120 V, 60 Hz							
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 3720MHz									
	7440.00	3.8	V	3.0	43.0	1.0	-38.2	-13.0	-25.2	
	11160.00	5.4	V	3.0	40.6	1.0	-34.1	-13.0	-21.1	
	14880.00	11.5	V	3.0	40.1	1.0	-27.6	-13.0	-14.6	
	7440.00	2.6	H	3.0	43.0	1.0	-39.4	-13.0	-26.4	
	11160.00	6.9	H	3.0	40.6	1.0	-32.7	-13.0	-19.7	
	14880.00	11.6	H	3.0	40.1	1.0	-27.5	-13.0	-14.5	
	Mid Ch, 3840MHz									
7680.00	5.3	V	3.0	42.8	1.0	-36.6	-13.0	-23.6		
11520.00	8.4	V	3.0	40.3	1.0	-30.9	-13.0	-17.9		
15360.00	12.8	V	3.0	40.2	1.0	-26.3	-13.0	-13.3		
7680.00	3.3	H	3.0	42.8	1.0	-38.5	-13.0	-25.5		
11520.00	6.6	H	3.0	40.3	1.0	-32.7	-13.0	-19.7		
15360.00	12.9	H	3.0	40.2	1.0	-26.3	-13.0	-13.3		
High Ch, 3960MHz										
7920.00	3.6	V	3.0	42.7	1.0	-38.0	-13.0	-25.0		
11880.00	6.8	V	3.0	40.0	1.0	-32.2	-13.0	-19.2		
15840.00	12.8	V	3.0	40.3	1.0	-26.4	-13.0	-13.4		
7920.00	3.0	H	3.0	42.7	1.0	-38.6	-13.0	-25.6		
11880.00	6.7	H	3.0	40.0	1.0	-32.3	-13.0	-19.3		
15840.00	12.6	H	3.0	40.3	1.0	-26.7	-13.0	-13.7		
20 MHz QPSK ANT B SRS1	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
	Company:		Samsung							
	Project #:		4791547073							
	Date:		2024-12-28							
	Test Engineer:		24542							
	Configuration:		EUT / X-Position							
	Location:		Chamber 2							
	Mode:		5G NR n77 UP(SRS) Harmonics, 20MHz Bandwidth							
	Test Votage:		AC 120 V, 60 Hz							
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 3710MHz									
	7420.00	-3.9	V	3.0	43.0	1.0	-45.9	-13.0	-32.9	
	11130.00	2.1	V	3.0	40.6	1.0	-37.5	-13.0	-24.5	
	14840.00	9.3	V	3.0	40.1	1.0	-29.8	-13.0	-16.8	
	7420.00	-4.2	H	3.0	43.0	1.0	-46.2	-13.0	-33.2	
	11130.00	2.6	H	3.0	40.6	1.0	-37.0	-13.0	-24.0	
	14840.00	9.4	H	3.0	40.1	1.0	-29.7	-13.0	-16.7	
	Mid Ch, 3840MHz									
	7680.00	-4.4	V	3.0	42.8	1.0	-46.2	-13.0	-33.2	
	11520.00	3.5	V	3.0	40.3	1.0	-35.7	-13.0	-22.7	
	15360.00	9.4	V	3.0	40.2	1.0	-29.7	-13.0	-16.7	
	7680.00	-4.8	H	3.0	42.8	1.0	-46.7	-13.0	-33.7	
	11520.00	3.7	H	3.0	40.3	1.0	-35.6	-13.0	-22.6	
	15360.00	9.4	H	3.0	40.2	1.0	-29.8	-13.0	-16.8	
	High Ch, 3970MHz									
	7940.00	-4.1	V	3.0	42.7	1.0	-45.8	-13.0	-32.8	
	11910.00	3.6	V	3.0	39.9	1.0	-35.3	-13.0	-22.3	
	15880.00	10.9	V	3.0	40.3	1.0	-28.3	-13.0	-15.3	
7940.00	-4.6	H	3.0	42.7	1.0	-46.2	-13.0	-33.2		
11910.00	3.7	H	3.0	39.9	1.0	-35.3	-13.0	-22.3		
15880.00	10.9	H	3.0	40.3	1.0	-28.4	-13.0	-15.4		

70 MHz	QPSK ANT G SRS2	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4791547073 Date: 2024-12-28 Test Engineer: 26087 Configuration: EUT / Z-Position Location: Chamber 1 Mode: 5G NR n77 UP(SRS) Harmonics, 70MHz Bandwidth Test Votage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Ch, 3735MHz									
		7470.00	-3.9	V	3.0	44.8	1.0	-47.7	-13.0	-34.7	
		11205.00	1.1	V	3.0	42.9	1.0	-40.8	-13.0	-27.8	
		14940.00	5.1	V	3.0	44.4	1.0	-38.3	-13.0	-25.3	
		7470.00	-3.8	H	3.0	44.8	1.0	-47.6	-13.0	-34.6	
		11205.00	1.3	H	3.0	42.9	1.0	-40.6	-13.0	-27.6	
		14940.00	5.1	H	3.0	44.4	1.0	-38.3	-13.0	-25.3	
		Mid Ch, 3840MHz									
		7680.00	-3.6	V	3.0	44.6	1.0	-47.2	-13.0	-34.2	
		11520.00	1.9	V	3.0	42.9	1.0	-40.0	-13.0	-27.0	
		15360.00	5.4	V	3.0	44.5	1.0	-38.1	-13.0	-25.1	
		7680.00	-3.6	H	3.0	44.6	1.0	-47.3	-13.0	-34.3	
		11520.00	2.1	H	3.0	42.9	1.0	-39.8	-13.0	-26.8	
		15360.00	5.3	H	3.0	44.5	1.0	-38.1	-13.0	-25.1	
		High Ch, 3945MHz									
		7890.00	-3.2	V	3.0	44.5	1.0	-46.7	-13.0	-33.7	
		11835.00	1.8	V	3.0	42.9	1.0	-40.1	-13.0	-27.1	
		15780.00	6.1	V	3.0	44.5	1.0	-37.4	-13.0	-24.4	
		7890.00	-3.6	H	3.0	44.5	1.0	-47.0	-13.0	-34.0	
		11835.00	1.8	H	3.0	42.9	1.0	-40.1	-13.0	-27.1	
15780.00	6.1	H	3.0	44.5	1.0	-37.5	-13.0	-24.5			
100 MHz	QPSK ANT H SRS3	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4791547073 Date: 2024-12-28 Test Engineer: 26087 Configuration: EUT / AC Adapter, Y-Position Location: Chamber 1 Mode: 5G NR n77 UP(SRS) Harmonics, 100MHz Bandwidth Test Votage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Ch, 3750MHz									
		7500.00	-4.0	V	3.0	44.7	1.0	-47.8	-13.0	-34.8	
		11250.00	1.1	V	3.0	42.9	1.0	-40.8	-13.0	-27.8	
		15000.00	5.1	V	3.0	44.4	1.0	-38.3	-13.0	-25.3	
		7500.00	-3.9	H	3.0	44.7	1.0	-47.6	-13.0	-34.6	
		11250.00	1.1	H	3.0	42.9	1.0	-40.8	-13.0	-27.8	
		15000.00	5.1	H	3.0	44.4	1.0	-38.3	-13.0	-25.3	
		Mid Ch, 3840MHz									
		7680.00	-3.2	V	3.0	44.6	1.0	-46.8	-13.0	-33.8	
		11520.00	2.0	V	3.0	42.9	1.0	-39.8	-13.0	-26.8	
		15360.00	5.1	V	3.0	44.5	1.0	-38.3	-13.0	-25.3	
		7680.00	-3.2	H	3.0	44.6	1.0	-46.8	-13.0	-33.8	
		11520.00	2.0	H	3.0	42.9	1.0	-39.9	-13.0	-26.9	
		15360.00	5.2	H	3.0	44.5	1.0	-38.3	-13.0	-25.3	
		High Ch, 3930MHz									
		7860.00	-3.3	V	3.0	44.5	1.0	-46.8	-13.0	-33.8	
		11790.00	1.5	V	3.0	42.9	1.0	-40.4	-13.0	-27.4	
		15720.00	6.1	V	3.0	44.5	1.0	-37.5	-13.0	-24.5	
		7860.00	-2.9	H	3.0	44.5	1.0	-46.4	-13.0	-33.4	
		11790.00	1.6	H	3.0	42.9	1.0	-40.3	-13.0	-27.3	
15720.00	5.9	H	3.0	44.5	1.0	-37.6	-13.0	-24.6			

END OF REPORT