

May 25, 2023

Robert Bosch Tool Corporation 1800 W. Central Rd. Mount Prospect, IL 60056 www.bosch.us

FCC ID: TXTPTM20R

To the certification reviewer:

We are hereby applying for [full] modular approval of the above-referenced FCC ID, based on compliance with [all] of the criteria as detailed below.

Sincerely,

[Signature] Josh MACY

Regulatory and Agency Approvals Manager (PT/ESS2-NA) Robert Bosch Tool Corporation

Part 15 Unlicensed Single Modular Transmitter Approval Justification per 15.212

| | Requirement per 15.212 | reference |
|-------|---|--|
| (i) | The radio elements of the modular transmitter must have their own RF shielding. | The module has RF shield and shielding is provided by a ground plane on the printed wiring board. |
| (ii) | The modular transmitter must have buffered modulation/data inputs (if such inputs are provided. | All modulation and data inputs are buffered by circuitry on the RF transmitter chip. |
| (iii) | The modular transmitter must have its own power supply regulation. | The module RF transmitter chip has integrated voltage regulation over the range of 1.8V to 3.8V. Further power supply regulation is provided by external circuitry of the host equipment over the range of 2.7 to 3.6 volts. |



May 25, 2023 Page 2 of 2

| (iv) | The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c). | The module has an integrated permanently attached non-replaceable PCB antenna. |
|--------|--|--|
| (v) | The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with Part 15 parameters. | Testing was performed with the module extended outside of the host on a special extender board, as shown in the test setup photos. |
| (vi) | The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. If the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. | A sample of the host label is provided as an exhibit, showing the FCC identifier of the module. |
| (vii) | The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. | The module complies fully with the operating requirements of Part 15 section [247] as demonstrated in the test report exhibit. |
| (viii) | The modular transmitter must comply with any applicable RF exposure requirements in its final | This module operates under Part 15 section [247], which is exempt from RF exposure evaluation owing to the very low |
| | configuration. | operating power. |